

Ultra-low-power consumption with the MSP430FR57xx family featuring FRAM



MSP430™ MCUs with Ferroelectric Random Access Memory (FRAM) offer even lower power consumption. With an active power mode of 100µA/MHz, these microcontrollers are truly industry leading. For applications that require continuous data logging, the low power consumption of these devices is unbeatable at 200 to 250 times less than typical flash memory based microcontrollers. While writing to memory, the MSP430FR57xx only needs 2.0V of current with no charge pump or boost whereas most Flash memory MCUs will need 12V to 15V of current to write.

FRAM microcontrollers

Performance and capabilities of today's embedded controllers are limited by the type of memory technology used. The MSP430FR57xx family with FRAM introduces the market to a new generation of superior non-volatile memory devices. This unified memory makes the MSP430FR57xx microcontroller very flexible. For example, you can dynamically partition the device memory into code space or data space, as needed. Again, this brings incredible flexibility to software designers, product manufacturers and

others offering a lower cost of ownership. FRAM is at the forefront of these 'next generation' memory technologies; it is the most proven and mature, having been used for the past several years in diverse applications from EEPROM or battery backed SRAM replacement devices to automotive applications. Texas Instruments is continuing our tradition of innovation by delivering embedded FRAM products that bring real, tangible value to our customers and partners.

Key features

- Non-volatile memory – data state is retained even when power is turned off
- Fast write speeds – current implementations are at less than 50ns – up to 100x faster than Flash or EEPROM technologies
- High endurance – over 100 trillion write cycles
- Very low memory access power requirements – 2.0v read/write compared to >10-14v write for Flash and EEPROM
- Enhanced data reliability – inherent write guarantee during a write cycle even in case of power loss
- Resistant to gamma radiation

MSP430FR57xx Microcontroller Comparison

	MSP430FR57xx	Flash microcontroller
Max. data write throughput (kBps)	1,400	13
Power consumption at max. throughput (µA)	720	2,200
Power consumption at 13 kBps throughput (µA)	9	2,200
Write endurance cycles	>100 trillion	100 to 100,000

For more information, visit ti.com/fram

Device	FRAM (KB)	SRAM (KB)	System Clock (MHz)	ADC10_B	Comp_D	Timer_A (1)	Timer_B (2)	eUSCI		Package Type			
								Channel A: UART/IrD A/SP	Channel B: SPI/I ² C	24 QFN	38 TSSOP	40 QFN	28 TSSOP
MSP430FR5739	16	1	24	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5738	16	1	24	y	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5737	16	1	24	-	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5736	16	1	24	-	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5735	8	1	24	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5734	8	1	24	y	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5733	8	1	24	-	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5732	8	1	24	-	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5731	4	0.512	24	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5730	4	0.512	24	y	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5729	16	1	8	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5728	16	1	8	y	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5727	16	1	8	-	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5726	16	1	8	-	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5725	8	1	8	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5724	8	1	8	y	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5723	8	1	8	-	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5722	8	1	8	-	10 ch.	3, 3	3	1	1	RGE			PW
MSP430FR5721	4	0.512	8	y	16 ch.	3, 3	3, 3, 3	2	1		DA	RHA	
MSP430FR5720	4	0.512	8	y	10 ch.	3, 3	3	1	1	RGE			PW

MSP430FR57xx Microcontroller

16-bit RISC MCU up to 24 MHz	Memory 16KB/8KB/4KB FRAM (with segment protections for code/data)	Power and clocking – Power on reset – Brownout reset – Low power Vreg (1.5V) – XT1, VLO – DCO – Realtime clock
	Debug Real-time JTAG Embedded emulation Boot strap loader	
	Peripherals 32 x 32 multiplier DMA (3ch) CRC16 Serial interface Unlimited serial comm. interface – 2 UARTS or SPI – 1 I ² C or SPI Analog Comparator/REF ADC10 (up to 12ch)	

Tools and support

Get started enjoying the benefits of the new MSP430FR57xx microcontrollers with these easy to use tools:

Software:

CCS v4.2.3

IAR-EW430 v5.20.x

Hardware:

MSP-EXP430FR5739 experimenters board

MSP-TS430RHA40A socketed target board

www.ti.com/fram

Important Notice: The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

July 2019

A122010

The platform bar and MSP430 are trademarks of Texas Instruments. All other trademarks are the property of their respective owners.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated