# <sup>10/20/09</sup> PMP4679 Rev. A - Test Results




1	Pictures of the Converter	.1
2	Main waveforms	.2
3	Efficiency	.4
4	loop measurements	.6
5	Step-Load Variations	.7
	Thermal Pictures	
	Warning	
	5	-

## 1 Pictures of the Converter

Board has been assembled accordingly with SCH and BOM PMP4679 Rev.A, which is indeed a copy of PR668 Rev.A.

Supply to the converter in all measurements is provided through AUX Power connector. All the measurements at  $T_{amb}=25^{\circ}C$ .



<sup>10/20/09</sup> PMP4679 Rev. A - Test Results



#### 2 Main waveforms




Fig.1 START-UP C1: Vout, C2: V\_aux\_power (scope probe on J1-, no GND)





Fig.2 C1:Vds\_Q1 @ Vin=57V, lout=1A













Fig.4 C1: Vds\_Q1, C2: V\_in ripple (scope probe on Aux\_Power J1+), C3: Vout ripple



# 3 Efficiency



Efficiency Curve for Vin = 36 V, 48V, 57V

Fig.5 Efficiency curves for Vin=36V, Vin=48V and Vin=57V and output load swinging from 0 to 1A.

Efficiency detailed results are shown in the following tables.

Vin[V]	lin[A]	Vout1[V]	lout1[A]	Pin[W]	Pout2[W]	η%
36	0.009	12	0.000	0.324	0.000	0.0
37.148	0.042	11.98	0.101	1.560	1.210	77.6
37.158	0.085	11.98	0.221	3.158	2.648	83.8
37.152	0.116	11.98	0.311	4.310	3.726	86.5
37.144	0.148	11.98	0.402	5.497	4.816	87.6
37.135	0.19	11.98	0.522	7.056	6.254	88.6
37.122	0.223	11.98	0.612	8.278	7.332	88.6
37.118	0.256	11.98	0.703	9.502	8.422	88.6
37.115	0.3	11.98	0.823	11.135	9.860	88.5
37.099	0.333	11.98	0.912	12.354	10.926	88.4
37.083	0.367	11.98	1.002	13.609	12.004	88.2

Tab.1 Efficiency values with Vin=36V, and no load consumption

# <sup>10/20/09</sup> PMP4679 Rev. A - Test Results



Vin[V]	lin[A]	Vout1[V]	lout1[A]	Pin[W]	Pout2[W]	η%
48	0.0086	11.99	0.000	0.413	0.000	0.0
49.098	0.033	11.99	0.101	1.620	1.211	74.7
49.088	0.066	11.99	0.221	3.240	2.650	81.8
49.082	0.09	11.99	0.311	4.417	3.729	84.4
49.084	0.1143	11.99	0.402	5.610	4.820	85.9
49.075	0.147	11.99	0.523	7.214	6.271	86.9
49.062	0.171	11.99	0.613	8.390	7.350	87.6
49.058	0.196	11.99	0.704	9.615	8.441	87.8
49.055	0.229	11.99	0.823	11.234	9.868	87.8
49.049	0.254	11.99	0.912	12.458	10.935	87.8
49.033	0.2798	11.99	1.005	13.719	12.050	87.8

Tab.2 Efficiency values with Vin=48V, and no load consumption

Vin[V]	lin[A]	Vout1[V]	lout1[A]	Pin[W]	Pout2[W]	η%
57	0.0085	12	0.000	0.485	0.000	0.0
58.068	0.0296	12	0.101	1.719	1.212	70.5
58.108	0.057	12	0.221	3.312	2.652	80.1
58.132	0.078	11.99	0.311	4.534	3.729	82.2
58.154	0.098	11.99	0.402	5.699	4.820	84.6
58.175	0.125	11.99	0.522	7.272	6.259	86.1
58.192	0.146	11.99	0.613	8.496	7.350	86.5
58.218	0.167	11.99	0.704	9.722	8.441	86.8
58.245	0.195	11.99	0.823	11.358	9.868	86.9
58.259	0.216	11.99	0.912	12.584	10.935	86.9
58.303	0.237	11.99	1.005	13.818	12.050	87.2

Tab.3 Efficiency values with Vin=57V, and no load consumption



### 4 Loop measurements

Open Loop Gain and Phase of the Type II Compensation is measured in the next picture at full 1A load, with changing input Vin=36v, Vin=57V.




Fig.6 Open Loop Gain with full load and Vin = 36V and Vin=57V.





# 5 Step-Load Variations




Fig.7 Output voltage (C3) AC variation, at step Load (C4)changing from 0.2A to 0.9A and viceversa @ Vin=48V.





# 6 Thermal Pictures




Fig.8 Thermal picture with hot spots at Vin=36V@lout=1A



### 7 Warning

**For Feasibility Evaluation Only, in Laboratory/Development Environments.** The EVM is not a complete product. It is intended solely for use for preliminary feasibility evaluation in laboratory / development environments by technically qualified electronics experts who are familiar with the dangers and application risks associated with handling electrical / mechanical components, systems and subsystems. It should not be used as all or part of a production unit.

Your Sole Responsibility and Risk. You acknowledge, represent and agree that:

- You have unique knowledge concerning Federal, State and local regulatory requirements (including but not limited to Food and Drug Administration regulations, if applicable) which relate to your products and which relate to your use (and/or that of your employees, affiliates, contractors or designees) of the EVM for evaluation, testing and other purposes.
- 2. You have full and exclusive responsibility to assure the safety and compliance of your products with all such laws and other applicable regulatory requirements, and also to assure the safety of any activities to be conducted by you and/or your employees, affiliates, contractors or designees, using the EVM. Further, you are responsible to assure that any interfaces (electronic and/or mechanical) between the EVM and any human body are designed with suitable isolation and means to safely limit accessible leakage currents to minimize the risk of electrical shock hazard.
- 3. Since the EVM is not a completed product, it may not meet all applicable regulatory and safety compliance standards (such as UL, CSA, VDE, CE, RoHS and WEEE) which may normally be associated with similar items. You assume full responsibility to determine and/or assure compliance with any such standards and related certifications as may be applicable. You will employ reasonable safeguards to ensure that your use of the EVM will not result in any property damage, injury or death, even if the EVM should fail to perform as described or expected.

<u>Certain Instructions</u>. Exceeding the specified EVM ratings (including but not limited to input and output voltage, current, power, and environmental ranges) may cause property damage, personal injury or death. If there are questions concerning these ratings please contact a TI field representative prior to connecting interface electronics including input power and intended loads. Any loads applied outside of the specified output range may result in unintended and/or inaccurate operation and/or possible permanent damage to the EVM and/or interface electronics. Please consult the EVM User's Guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative. During normal operation, some circuit components may have case temperatures greater than 60℃ as long as the input and output ranges are maintained at nominal ambient operating temperature. These components include but are not limited to linear regulators, switching transistors, pass transistors, and current sense resistors which can be indentified using the EVM schematic located in the EVM User's Guide. When placing measurement probes near these devices during normal operation, please be aware that these devices may be very warm to the touch.

Agreement to Defend, Indemnify and Hold Harmless. You agree to defend, indemnify and hold TI, its licensors and their representatives harmless from and against any and all claims, damages, losses, expenses, costs and liabilities (collectively, "Claims") arising out of or in connection with any use of the EVM that is not in accordance with the terms of this agreement. This obligation shall apply whether Claims arise under the law of tort or contract or any other legal theory, and even if the EVM fails to perform as described or expected.

<u>Safety-Critical or Life-Critical Applications</u>. If you intend to evaluate TI components for possible use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, such as devices which are classified as FDA Class III or similar classification, then you must specifically notify TI of such intent and enter into a separate Assurance and Indemnity Agreement.

#### IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (https://www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2021, Texas Instruments Incorporated