

PMP11112 REV B Bill of Materials

Designator	Quantity	Value	PartNumber	Manufacturer	Description	Package
C1, C2, C19, C20,	9	330uF	EEE-FP1V331AP	Panasonic	CAP ALUM 330UF 35V 20% SMD	SMT Radial G
C33, C34, C50,						
C51, C62						
C3, C4, C5, C6,	16	4.7uF	GRM31CR71H475KA12L	MuRata	CAP, CERM, 4.7uF, 50V, +/-10%, X7R, 1206	1206
C21, C22, C23,						
C24, C35, C36,						
C37, C38, C52,						
C53, C54, C55						
C7, C25, C39,	4	10uF	GRM32ER7YA106KA12L	MuRata	CAP, CERM, 10uF, 35V, +/-10%, X7R, 1210	1210
C56	-					1-10
C8, C10, C26,	8	0.47uF	GRM188R71E474KA12D	MuRata	CAP, CERM, 0.47uF, 25V, +/-10%, X7R, 0603	0603
C28, C40, C43,	-					
C57, C59						
C9, C27, C41,	4	100pF	GRM1885C1H101JA01D	MuRata	CAP, CERM, 100pF, 50V, +/-5%, C0G/NP0, 0603	0603
C58	-					
C11, C29, C44,	4	1uF	GRM188R71E105KA12D	MuRata	CAP, CERM, 1uF, 25V, +/-10%, X7R, 0603	0603
C60		1				
C12, C30, C45,	4	470pF	GRM2165C2A471JA01D	MuRata	CAP, CERM, 470pF, 100V, +/-5%, C0G/NP0, 0805	0805
C46		1.7 001	G140121000271171071012	Martata	6.11 , 62.1111, 11 66.1 , 10 6.1 , 17 67.0 , 66.6 , 11 6, 66.6 c	
C13, C47, C49	3	0.1uF	GRM188R71E104KA01D	MuRata	CAP, CERM, 0.1uF, 25V, +/-10%, X7R, 0603	0603
C14		0.047uF	GRM188R71E473KA01D	MuRata	CAP, CERM, 0.047uF, 25V, +/-10%, X7R, 0603	0603
C16	1	330pF	GRM1885C1H331JA01D	MuRata	CAP, CERM, 330 pF, 50 V, +/- 5%, C0G/NP0, 0603	0603
C18	1	0.033uF	C1608X8R2A333K	TDK	CAP, CERM, 0.033 µF, 50 V, +/- 10%, X7R, 0603	0603
C31	1	0.1uF	GCM188R71H104KA57D	MuRata	CAP, CERM, 0.1uF, 50V, +/-10%, X7R, 0603	0603
C32	1	10uF	GRM21BR71A106KE51L	MuRata	CAP, CERM, 10uF, 10V, +/-10%, X7R, 0805	0805
C42	1	220pF	C1608C0G1H221J	TDK	CAP, CERM, 220pF, 50V, +/-5%, C0G/NP0, 0603	0603
D1, D2, D3, D5	4	0.57V	PMEG6010CEH,115	NXP	Diode, Schottky, 60V, 1A, SOD-123F	SOD-123F
IN1, OUT1, Sync	6	White	5007	Keystone	Test Point, TH, Compact, White	Keystone5007
In 1, Sync In 2,	Ū					1.10,0100000.
Sync In 3, Sync In						
4						
J1, J2, J3, J5	4	50A	CB35-36-CY	Panduit	Terminal 50A Lug	CB35-36-CY
L1, L2, L3, L4	4	3uH	XAL1580-302MEB	Coilcraft	Inductor, Shielded, Composite, 3 µH, 34.4 A, 0.002619 ohm, SMD	15.2x8x16.2mm
2., 22, 23, 2.			74 12 1000 002 M2B	Conoran	madatar, emicrosa, composito, e pri, e irri, e icezo le cinii, emb	10.2.00.10.2.11.11
Q1, Q2, Q3, Q4,	8	40V	CSD18501Q5A	Texas Instruments	MOSFET, N-CH, 40 V, 22 A, SON 5x6mm	SON 5x6mm
Q5, Q6, Q7, Q8		1.0 \$	10001907	. JAGO MONGHIOMO	11.00. 21, 14 011, 10 V, 22 M, 0014 0X011111	3014 0,0111111
R1, R20, R31,	4	0.002	CSNL2512FT2L00	Stackpole	RES, 0.002, 1%, 2 W, 2512	2512
R44	4	0.002	CONLESTET TELOU	σιασκροίε	INLO, 0.002, 170, 2 VV, 2012	2012
R2, R4, R21, R22,	8	100	CRCW0603100RFKEA	Vishay-Dale	RES, 100, 1%, 0.1 W, 0603	0603
R32, R33, R45,	0	1100	CROWOODSTOURFREA	v ioliay-Dale	INCO, 100, 170, 0.1 VV, 0003	0003
R32, R33, R45, R46						
N40		<u> </u>		1		

Designator	Quantity	Value	PartNumber	Manufacturer	Description	Package
R5, R9, R10, R23,	12	0	ERJ-3GEY0R00V	Panasonic	RES, 0 ohm, 5%, 0.1W, 0603	0603
R27, R28, R34,						
R39, R41, R47,						
R51, R52						
R6	1	75.0k	CRCW060375K0FKEA	Vishay-Dale	RES, 75.0 k, 1%, 0.1 W, 0603	0603
R7, R25, R36,	4	3.3	CRCW06033R30JNEA	Vishay-Dale	RES, 3.3 ohm, 5%, 0.1W, 0603	0603
R49						
R8	1	11.5k	CRCW060311K5FKEA	Vishay-Dale	RES, 11.5 k, 1%, 0.1 W, 0603	0603
R11, R24, R26,	7	0	CRCW06030000Z0EA	Vishay-Dale	RES, 0 ohm, 5%, 0.1W, 0603	0603
R29, R68, R69,						
R70						
R12, R30, R43,	4	10.0k	CRCW060310K0FKEA	Vishay-Dale	RES, 10.0 k, 1%, 0.1 W, 0603	0603
R54						
R15	1	36.5k	CRCW060336K5FKEA	Vishay-Dale	RES, 36.5 k, 1%, 0.1 W, 0603	0603
R16	1	2.67k	CRCW06032K67FKEA	Vishay-Dale	RES, 2.67k ohm, 1%, 0.1W, 0603	0603
R17	1	52.3k	ERJ-6ENF5232V	Panasonic	RES, 52.3 k, 1%, 0.125 W, 0805	0805
R18	1	665	CRCW0805665RFKEA	Vishay-Dale	RES, 665, 1%, 0.125 W, 0805	0805
R35	1	1.0	CRCW06031R00JNEA	Vishay-Dale	RES, 1.0 ohm, 5%, 0.1W, 0603	0603
R37	1	8.66	CRCW06038R66FKEA	Vishay-Dale	RES, 8.66 ohm, 1%, 0.1W, 0603	0603
R40	1	2.37k	CRCW06032K37FKEA	Vishay-Dale	RES, 2.37 k, 1%, 0.1 W, 0603	0603
R48, R50, R55,	4	7.5	ERJ-12ZYJ7R5U	Panasonic	RESISTOR 7.5 OHM 3/4W 5% 2010	2010
R56						
R58	1	158k	CRCW0603158KFKEA	Vishay-Dale	RES, 158k ohm, 1%, 0.1W, 0603	0603
SW1, SW2, SW3,	4	White	5002	Keystone	Test Point, TH, Miniature, White	Keystone5002
SW4						Í
U1, U3, U4, U7	4		LM5122MH/NOPB	Texas Instruments	Wide Input Synchronous Boost Controller with Multiple Phase	PWP0020A
, , ,					Capability, PWP0020A	
U5	1		LMC555CMX	Texas Instruments	CMOS Timer, 8-pin Narrow SOIC	M08A
U6	1		CD4017BM96	Texas Instruments	IC 10-OUT DECADE COUNTER 16-SOIC	D (R-PDSO-G16)
U8	1		LM2936MP-3.3/NOPB	Texas Instruments	Ultra-Low Quiescent Current LDO Voltage Regulator, 4-pin SOT-	MP04A
					223, Pb-Free	
Vin Gnd, Vout	2	Black	5001	Keystone	Test Point, TH, Miniature, Black	Keystone5001
Gnd						'
Vin, Vout	2	Red	5000	Keystone	Test Point, TH, Miniature, Red	Keystone5000

IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ('TI") reference designs are solely intended to assist designers ("Designer(s)") who are developing systems that incorporate TI products. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design.

Tl's provision of reference designs and any other technical, applications or design advice, quality characterization, reliability data or other information or services does not expand or otherwise alter Tl's applicable published warranties or warranty disclaimers for Tl products, and no additional obligations or liabilities arise from Tl providing such reference designs or other items.

TI reserves the right to make corrections, enhancements, improvements and other changes to its reference designs and other items.

Designer understands and agrees that Designer remains responsible for using its independent analysis, evaluation and judgment in designing Designer's systems and products, and has full and exclusive responsibility to assure the safety of its products and compliance of its products (and of all TI products used in or for such Designer's products) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to its applications, it has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any systems that include TI products, Designer will thoroughly test such systems and the functionality of such TI products as used in such systems. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

Designers are authorized to use, copy and modify any individual TI reference design only in connection with the development of end products that include the TI product(s) identified in that reference design. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of the reference design or other items described above may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS AND OTHER ITEMS DESCRIBED ABOVE ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNERS AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS AS DESCRIBED IN A TI REFERENCE DESIGN OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Tl's standard terms of sale for semiconductor products (http://www.ti.com/sc/docs/stdterms.htm) apply to the sale of packaged integrated circuit products. Additional terms may apply to the use or sale of other types of TI products and services.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2016, Texas Instruments Incorporated