

Flash Variants Supported by the mmWave Sensor

ABSTRACT

This application note describes the flash variants supported by Texas Instrument's mmWave Sensor.

Contents

1	Serial Data FLASH Supported	2
1.1	AWR1243/xWR1443 ES1.0 and ES2.0 Devices	2
1.2	xWR1642, xWR1843, IWR6843 Devices and AWR1243/xWR1443 ES3.0 Devices	2
1.3	Known Issues (xWR1642 ES1.0 and IWR6843 ES1.0 Devices)	3
1.4	Flash Variants	3

List of Tables

1	Key Fields.....	2
2	Tested Flash Variants	3

Trademarks

All trademarks are the property of their respective owners.

1 Serial Data FLASH Supported

1.1 AWR1243/xWR1443 ES1.0 and ES2.0 Devices

The AWR1243/xWR1443 ES1.0 and ES2.0 devices work only with Spansion and Macronix devices. In particular, the flash variants tested to work with the ROM bootloader are:

- Spansion S25FL132K0XNFB010
- Macronix MX25L3233F
- Macronix MX25R1635FZNIH0 (wide voltage part variant)

1.2 xWR1642, xWR1843, IWR6843 Devices and AWR1243/xWR1443 ES3.0 Devices

There are several factors that determine if the xWR1xxx ROM bootloader can interface and work with the SFLASH on xWR1xxx devices.

1.2.1 Pre-requisite

Refer to the device data sheet for details on the timing and interfacing requirements with the SFLASH over the QSPI interface.

SFLASH device variants should support 40-MHz operation for all commands (including normal read command).

SFLASH supports the SFDP command and responds with JEDEC-compliant information regarding the capabilities and command set of the flash. The key fields interpreted are listed in [Table 1](#).

Table 1. Key Fields

Field	Byte Offset
SFDP signature	[3-0]
JEDEC flash parameter offset in bytes	[0xE-0xC]
(1-1-4) Read support	[JEDEC flash parameter offset in bytes + 0x2] – bit6
(1-1-2) Read support	[JEDEC flash parameter offset in bytes + 0x2] – bit0
(1-1-4) Read command code	[JEDEC flash parameter offset in bytes + 0xB]
(1-1-4) Read dummy cycles	[JEDEC flash parameter offset in bytes + 0xA] – bit[4:0]
(1-1-2) Read command code	[JEDEC flash parameter offset in bytes + 0xD]
(1-1-2) Read dummy cycles	[JEDEC flash parameter offset in bytes + 0xC] – bit[4:0]

- The number of address bytes = 3 (always).
- For single data line SPI read – Read Command Code (0xB), Read Dummy cycles (8bit).

1.2.2 ROM-Assisted Download to the FLASH (Device Management Mode - SOP5)

The ROM-assisted download should work with all flash variants that allow for “Memory mapped mode” and “Page program command (0x2)” with 1 dummy byte and 24-bit addressing.

In addition to writing to the flash, the ROM bootloader also supports setting the “Quad Enable” bit for Spansion and Macronix variants (certain specific part variants only).

1.2.3 ROM-Based Load From FLASH (Functional Mode – SOP4)

The ROM bootloader performs the read from the FLASH based on the highest capability mode (quad, dual, or single) as published by the SFLASH in response to the SFDP command. The commands used are as published by the SFDP response. Thus, if the quad read is supported, the expectation is that the Quad Enable (QE) bit is already set in the FLASH. The ROM bootloader uses the quad mode to perform the read.

1.2.4 Recommendation

The flash vendors have an orderable part variant with the Quad Enable (QE) bit set. TI recommends using these variants to work with TI mmWave SOCs.

1.3 Known Issues (xWR1642 ES1.0 and IWR6843 ES1.0 Devices)

The ROM bootloader in XWR1642 pre-production devices is not compatible with SFLASH variants that support extended addressing mode. In particular, the “Number of Address length” field of the SFDP command response being non-zero is not supported. The total SFLASH addressable region in XWR1642 devices is 8 MBytes. Thus, “Number of Address length” = 0 (corresponding to 3 bytes address length) satisfies the addressable range. However, the compatibility issue is with variants that allow for 3 or 4 bytes address length.

This incompatibility will be addressed in the production version of the XWR1642 silicon.

1.4 Flash Variants

Supported flash parts for xWR1642 ES2.0, xWR1842 ES1.0, xWR1443 ES3.0 and IWR6843 ES1.0 devices. The flash variants that have been tested to work on are shown in [Table 2](#).

Table 2. Tested Flash Variants

Flash Vendor	Variant	Remarks
CYPRESS (SPANSION)	S25FL132K0XNFB01	QE bit set by ROM bootloader in SOP5 while flash programming
	S25FL064LVF01	QE bit set by ROM bootloader in SOP5 while flash programming. This flash variant supports extended addressing mode. All mmWave devices may not be compatible with the extended addressing mode. Refer to Section 1.3 .
MACRONIX	MX25L3233F	QE bit set by ROM bootloader in SOP5 while flash programming
	MX25R1635FZNIH0	QE bit set by ROM bootloader in SOP5 while flash programming
	MX25V1635FZNQ	QE bit set by ROM bootloader in SOP5 while flash programming
	MX25U1633FZNQ	QE bit set by ROM bootloader in SOP5 while flash programming
	MX25V8035FM1Q	QE bit set by ROM bootloader in SOP5 while flash programming
ISSI	IS25LP080D	QE bit set
WINBOND	W25Q16DVZPIG	By setting QE bit externally once

Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Original (October 2018) to A Revision	Page
• Removed Spansion S25FL256S from list of AWR1243/xWR1443 ES1.0 and ES2.0 Devices.	2
• Updated Flash Variants section.	3
• Removed S25FL256S variant from Tested Flash Variants table.	3

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated