Item	Qty	Reference	MFG	PN	Part Name	Description	Notes
					2.2uF Capacitor, Ceramic Chip,		
13	1	C1			60V, ±10%,1206	Capacitor, Ceramic Chip, 60V, ±10% Capacitor, Poly Film 450 V, ±10%,	
32	2	C2-3	TDK	B32674D4155K	CA, 1.5 uF	B32674D4155K (DK 495-2917-ND)	
-	0	C4-5		DNI	NL 0.1uF,0603	NL Capacitor, Ceramic Chip, 100V, ±10%, X7R	DNI
5	1	C6			0.1uF,0603	Capacitor, Ceramic Chip, 100V, ±10%, X/R Capacitor, Poly Film 450 V, ±10%, DK p/n 495-	
33	1	C7	TDK	B32674D4475K	CAP, 4.7uF	2920-ND, EPCOS cap B32674D4475	
3	0	C8			NL	NL Capacitor, Elect, 450V, DK p/n 565-1481-ND,	DNI
			United			United Chemi-con p/n	
8	1	C9	Chemi-con	EKXG451ELL101MM40S	Cap, Elect,100uF	EKXG451ELL101MM40S	
7	0	C10	NL	DNI	NL	0	DNI
12	1	C11,C12			CAP 0805 25V 2.2uF	Capacitor, Ceramic, X7R, 25V Capacitor, Ceramic, X1/Y2, 250VAC,	
19	4	C13-16	Murata	GA355QR7GF222KW01L	C2220,2200pF	GA355QR7GF222KW01L	
	1	0.17		E00 110 100 1110	CAP, 0.22uF, 300V, ECQ-	CAP FILM 0.22UF 300VAC RADIAL, DK	
36	1	C17 C18 C19 C45 C49-50	Panasonic	ECQ-U3A224MG	U3A224MG	P11118-ND	
	0	C54 C67 C69		DNI	NL		DNI
		C26, C33 C56-57					
29	9	C59 C62 C65 C78, C98			CAP, 0603, 1n, 6.3V, 10%		
23	1	C93			CAP, 0603, 50V,10nF	Capacitor, Ceramic Chip, 50V, ±10%, X7R	
	1	C99			CAP, 0603, 50V,1nF	Capacitor, Ceramic Chip, 25V, ±10%, X7R	
	3	C21, C22 C27, C94-95			CAP, 0603, 0.22uF, 6.3V, 10% CAP, 0603, 1uF, 6.3V, 10%		· _
	1	C92			CAP, 0603, 10P, 6.3V, 10% CAP, 0603, 470p, 6.3V, 10%		
	2	C71, C81			CAP, 0603, 0.47u, 25V, 10%		
	2	C72, C82			CAP, 0805, 10u, 25V, 10%		
	5	C10 C25 C28 C75 C88			CAP, 0603, 100n, 25V, 10%		
	J	000			C/11 , 0000, 10011, 23 v , 1078		
		C35, C64, C66, C79,					
	1	C80, C89, C90, C130 C48		DNI	NL CAP,1uF,0603,16V	Ceramic Cap,X7R	DNI
	_	C46			CAP, Film, 47u, 100V, AVX p/n	Ceramic Cap,x/K	
38	2	C23-24	AVX	FFB44E0476K	FFB44E0476K	Capacitor, Film, 100V	
10	4	C32, C51-C52, C55			C0805, 1uF	Capacitor, Ceramic, 50V, X7R, +/- 10% Capacitor, Ceramic Chip, 100V, ±10%,	
15	2	C34 C36	AVX	12101A222JAT2A	C1210, 2200pF	12101A222JAT2A	
					•	Capacitor, Ceramic, 100V, +20-55%,	
35	2	C37-38	TDK	CKG57NX7S2A226M	CAP, 22uF	CKG57NX7S2A226M	
16	4	C39-40 C42-43	TDK	C3225X7S2A475M	C1210, 4.7uF	Capacitor, Ceramic Chip, 100V, ±10%, C3225X7S2A475M	
17	0	C41, C44	1511	DNI	NL	Capacitor, Ceramic Chip, 100V, ±10%	DNI
		C30 C46 C61 C63					
30	8	C70 C86 C91 C128 C20			CAP, 0.1uF, 0805 0.01uF,0603,25V	Capacitor, Ceramic Chip, 25V, ±10% Capacitor, Ceramic Chip, 16V, ±10%, X7R	
	0	C53	NL	DNI	0.01uF,0003,23V NL	Capacitor, Cerannic Chip, 10V, ±1076, A/R	DNI
		C29 C31 C47 C87					
4	7	C97 C124 C126 C58 C60 C68 C73-74			C0603, 0.1u	Capacitor, Ceramic Chip, 25V, ±10%	
11	10	C76-77 C83-85			C0805,1uF	Capacitor, Ceramic Chip, 25V, ±10%, X7R	
18	1	C96			C1812, 0.1uF, 500V, 10%	Capacitor, Ceramic, 500V, 1812, STD	
31	1 0	C127 C220		DNI	Cap, 0603, 0.01u, 6.3V, 10% NL	NL NL	DNI
20	U	CZZU		DINI	NL	INL	DINI
25	1	C:C1			C0805_25V_X7R,10u	CAP CER 25V 10% X7R 0805	
28	2	C:C8 C:C15		DIV = /= DE4E4 ND	C1206, 22u	CAP CER 25V 10% X7R 1206	
37 27	2	C:C11 C:C18 C:C12 C:C19		DK p/n P5154-ND	CAP, 330u C1206, 10u	CAP ALUM 330UF 25V 20% RADIAL CAP CER 25V 10% X7R 1206	
	0	C:C9-10 C:C16-17		DNI	NL		DNI
24	2	C:C13 C:C20			C0805,100n	CAP CER 25V 10% X7R 0805	
26	2	C:C14 C:C21			C0805, 4u7	CAP CER 25V 10% X7R 0805 SURFACE MOUNT CAPACITOR 0.080 X	
	1	C105	AVX	1812GC102KAT1A	1000pF,X7R,2000V	0.180 INCHES	
	1	C102			100nF,16V,X7R,0603		
42	2	C:JP2-3		DK p/n CP-002AH-ND	CONN, Power Jack	CONN PWR JACK 2.1X5.5MM HIGH CUR	
80	3	C:LD2-3 E:LD1		DK p/n 404-1021-1-ND	LED0805_GREEN,GREEN	LED GREEN 0805 SMD, Diffused, 567nm	
86	2	C:M2-3	TI	PTH08080WAH	MOD_PTH08080WAH	MODULE PIP .9-5.5V 2.25A HORZ TH	
125	2	C:R3 C:R5 C:R4 C:R6			R0805_1%,330R R0805_1%,470R	RES 1/8W 1% 0805 SMD RES 1/8W 1% 0805 SMD	
126 68	0	C:R4 C:R6 C:U2	NL	NL	R0805_1%,470R NL	RES 1/8W 1% 0805 SMD NL	DNI
67	1	C:U3	TI	TPS79533DCQ	IC_LDO_TPS79533DCQ	IC LDO REG 3.3V 500MA SOT223-6	

Item	Qty	Reference	MFG	PN	Part Name	Description	Notes
53	6	D1-5, D33	CREE	CSD10060G	Diode,CSD10060G	Diode, Schottky Rectifier, 10A, 600V	
33	0	D6, D19	CREE	DNI	NL	NL	DNI
		D7 D9-10 D13 D23-	DIODES			Diode, Dual Schottky, 200-mA, 30-V, Vishay	
46	9	24 D26-27 D29	INC	BAT54S	D-BAT54S, SOT23-3	p/n BAT54S	
			SPC MULTICOM				
50	4	D8 D11-12 D16	Р	BZT52C15	D-ZENER_SOD-123, BZT52C15	Diode, Zener, 15V, 500mW	
		D14-15 D22 D25 D18			Diode, Schottky, MBR0530, SOD-		
2	8	D30-32	FAIRCHILD	MBR0530	123	Diode, Schottky, 0.5A, 30V	
	1	D34 D35		SDM10U45-7-F DFLS1100-7	SDM10U45-7-F DFLS1100-7	Diode, Schottky, 45V,100mA Diode, Schottky, 1A, 100V	
	·	D33		DI L31100-7	DI E31100-1	Diode, Schottky, 200-mA, 30-V, DK p/n	
45	2	D17 D20	FAIRCHILD	BAT54	Diode,BAT54	BAT54FSCT-ND	
44	0	D21		DNI	NL	NL	DNI
48	1	D28	COMCHIP	DF06-G	D-BRIDGE, DF06-G	Bridge Rectifier, 600V, 1A, Glass Passivated, SMD	
47	1	D220	VISHAY	BAV70-E3-08	Diode Dual, BAV70-V	Diode, Switching, Dual, 70-V, 250-mA	
	Ė	5220	*1011/11	271170 20 00	Blodd Bddi, Britio	Blodd, Owtoming, Bdai, 10 1, 200 mil	
34	1	E:C1	KYOCERA	SA111E104MAR	CAP_CER_SA111E104MAR,100n	CAP CER 0.1UF 100V 20% AXIAL	
22	3 14	E:C2 E:C5-6 E:C3-4 E:C8-19			C0603_16V_X7R,1u C0603_16V_X7R,100n	CAP CER 16V 10% X7R 0603 CAP CER 16V 10% X7R 0603	
23	1	E:C7			C0603_16V_X7R,10011 C0603_16V_X7R,2u2	CAP CER 16V 10% X7R 0603 CAP CER 16V 10% X7R 0603	
			ZETEX /		;		
			DIODES	B.111-1			
52	1	E:DA1	INC NL	BAW567DW-7-F	DIODE_ARRAY_BAW567DW-7-F	DIODE ARRAY SW QUAD 200MW SC70-6	DNI
59 57	0	E:J1 E:J2-3	INL	NL	NL HEADER_1X2_100	NL Header, Male, 1x2-pin, 100mil spacing	DINI
43	0	E:JP1	NL	NL	NL	NL	DNI
78	2	E:L1-2	MURATA	LQM21FN220N00L	L0805_LQM21FN220N00L,22u	INDUCTOR 22UH 13MA 0805	
117	1	E:R1			R0603_1%,470R	RES 1/10W 1% 0603 SMD	
109	1	E:R2			R0603_1%,1K	RES 1/10W 1% 0603 SMD RES 1/10W 1% 0603 SMD	
106 111	1	E:R3 E:R4			R0603_1%,10K R0603_1%,1M	RES 1/10W 1% 0603 SMD RES 1/10W 1% 0603 SMD	
114	3	E:R5 E:R10-11			R0603_1%,1W	RES 1/10W 1% 0603 SMD	
118	1	E:R6			R0603_1%,47K	RES 1/10W 1% 0603 SMD	
113	2	E:R7 E:R9			R0603_1%,27R	RES 1/10W 1% 0603 SMD	
119	1	E:R8 E:R12			R0603_1%,680R	RES 1/10W 1% 0603 SMD	
107	1	E:R12 E:R13			R0603_1%,120 R0603_1%,19.6K	Resistor, Chip, 1/16W, 1% Resistor, Chip, 1/16W, 1%	
120	3	E:R14			R0603_1%,NL	Resistor, Chip, 1/16W, 1%	
69	0	E:U1	NL	NL	NL	NL	DNI
70	0	E:U2	NL	NL	NL	NL	DNI
66 65	0	E:U3 E:U4	NL NL	NL NL	NL NL	NL NL	DNI DNI
63	0	E:U5	NL	NL NL	NL NL	NL NL	DNI
64	0	E:U6	NL	NL	NL	NL NL	DNI
93	0	E:X1	NL	NL	NL	NL	DNI
		F4 F4	Cabanda	3101.004		FUSEHOLDER SLOT FPG4 IP40, DK 486-	
55	2	F1 F4 F1 F4	Schurter Bussmann	GMC-2-R		1159-ND FUSE 2A 250V MED T-LAG GLASS	
		1117	Dassinailli	GIVIO-2-IX		. COL ZA ZOUV MILD I LAG OLAGO	
							Install HS1 (marked
							on the PCB). HS1 is used for MOSFETs
62	3	HS1, HS4-5	Aavid	782653B02000	HEATSINK, 782653B02000	Heatsink, Vertical-mount, Clip Extrusion	Q8 & Q9
	Ť	. ,			,	,,,,	HS2 assiciated with
							Q10 & Q13. Q10 &
		LICO		DNII	NII.	NII.	Q13 is NL and so
	0	HS2		DNI	NL CONN AC RECEPT 7MM R/A	NL Connector, 10A 250 VAC RA, DK p/n Q218-	HS2 is also NL
39	1	J1	QUALTEK	Q218-ND	RND PCB, 703W-00/52	ND	
41	2	J2 J5	PHOENIX	MKDS3/2	CONN, MKDS3/2	Header, Side Entry 2-pin, 5mm spacing,	
		10 :-	044/==0	TEM 440 00 C	HEADER, TFM-110-02-SM-D-A-K-	II. I ONT 1017	
61	2	J3 J7	SAMTEC	TFM-110-02-SM-D-A-K-TR	TR	Header, SMT 10X2 pin, Shrouded	
56	11	J12 J14 J16 J18 J22- 26, J43-44	MILMAX	3115-2-00-15-00-00-08-0	HEADER, 3115-2-00-15-00-00-08- 0	Header, Single pin	
50	0	J43-44	IVIILIVIAA	DNI	NL	ricador, offigie piri	DNI
		J4 J6 J8-11, J15, J17			_		**
		J19-21 J27-37, J39-					
	27	J40, J42, J45-46	NL	NL	HEADER_1X2_100	Header, Male, 1x2-pin, 100mil spacing	DNI
	U	J13, J38, J41	PANASONI	INL	NL	Relay, 380Vac, 250VDC, 8A, DPST, 12V coil	DINI
127	1	К3	C	ST2-DC12V-F	RELAY, ST2-DC12V-F	volt	
			-			* *	

14	04	Deference	MFG	PN	Part Name	Description	Notes
Item	Qty	Reference	INIFG	FIN	IND, Differential Mode, Bourns	Description	Notes
74	2	L5-6	BOURNS	2320-V-RC	2320-V-RC	Inductor, Line Filter, DK p/n M8894-ND	
73	2	L7 L11	VITEC	53PR105	IND. ViTEC, 53PR105	Inductor.	
			BOURNS /				
71	1	L10	JW MILLER	8115-RC	IND, J.W.Miller 8115, 1.2mH	Inductor, Common mode	
79	2	LED1-2		DK p/n 404-1017-1-ND PTI TO MAKE/THIS IS A	LED0,Red	Typical INFRARED GaAs LED Aux Bias Supply, 400Vin, +12Vout sec,	
85	1	M1		SUB ASSEMBLY	MOD, PR798-12	+12Vout prim, 5W	
00	0	M2	NL	NL	NL	NL	DNI
60	0	P1	NL		HEADER 9X2	Header, 9-Pin, Dual row	DNI
58	0	P2	NL		HEADER_4X2	Header, 4-Pin, Dual row	DNI
			POWER				
			SEMI		TR_NFET, TO-220V,		
144 87	2	Q1-4 Q5-6	MICRO FAIRCHILD	APT11N80KC3G 2N7002	APT11N80KC3G MOS, 2N7002, NMOS	CoolMOS, MicroSemi, , N-ch, 800V 11A	
90	2	Q8-9	IR	IRFB4227PBF	MOSFET, IRFB4227PBF	MOSFET N-CH 200V 65A TO-220AB	
50	0	Q10, Q13	IIX	DNI	NL NL	NL	DNI
143	1	Q220	ST MICRO	2N7002	TR, 2N7002	MOSFET, N-ch, 60-V, 115-mA, 1.2-Ohms	
102	1	R1			R0603,127K	Resistor, Chip, 1/16W, 1%	
101	1	R2			R0603,	Resistor, Chip, 1/16W, 1%	DNI
98	1	R3 R4			R0603,130K R0603, 634 ohm, 0.5%	Resistor, Chip, 1/16W, 1% Resistor, 634 ohm, 0.5%	
-	_	17.4			11,0003, 034 01111, 0.376	110313101, 004 011111, 0.076	
	0	R139-140, R151-152		DNI	NL	NL	DNI
		R107, R131, R133-					
		135, R143, R145-					
	9	147			RES, 0805, 100 ohm, 1%	D8	
	2	R105 R119 R20 R23 R100	NL	DNI	RES, 0805, 15K, 1% NL		DNI
	U	R58 R59 R61 R64	INL	DINI	INL		DINI
	8	R166-169			RES, 0805, 10K, 1%		
	2	R82 R102			RES, 0805, 7.5K, 1%		
	2	R45 R92			RES, 0805, 1K, 0.5%		
	1	R39			RES, 0805, 3.32K_0.5%	RES, 0805, 3.32K_0.5%	
	1	R66			RES 0603, 0	Resistor, Chip, 1/16W, 1%	
	4	R5, R202, R203-204			RES, 0805, 0 ohm	Resistor, 0 ohm	
	1	R9			RES 0603 20K	Resistor, Chip, 1/16W, 1%	
97	1	R6			RES 0603 169K	Resistor, Chip, 1/16W, 1%	
99	1	R7			R0603,1K	RES 1/10W 1% 0603 SMD	
	1	R200			RES, 0603, 1K, 0.5%		
	1	R118			RES, 0603, 200.0K, 0.5%		
	2	R76 R34, R36			RES, 0603, 1M, 1%		
	4	R72, R22 R28 R33			RES, 0603, 50 ohm, 1% RES, 0603, 100 ohm, 1%		
	2	R62, R70			RES, 0603, 1.74K, 0.5%		
	2	R40, R74			RES, 0603, 0 ohm		
	5	R30-32, R35, R43			RES, 0603, 5K, 1%		
	2	R25, R26			RES, 0603, 1K, 1%		
	3	R29, R37, R38			RES, 0603, 510, 1%		
-	2	R18, R21 R16-17			RES, 0603, 4.81K, 1% RES, 0603, 2.2K, 1%		
		R14, R15, R19,			1120, 0000, 2.211, 170		
		R120, R123 R125					
	8	R128-129			RES, 0603, 24.9K, 0.5%		
	1	R13			RES, 0603, 3.32K, 0.5%		
	2	R12, R127			RES, 0603, 1.47K, 0.5%		
		R8 R10 R11 R46 R80 R88 R89 R138					
		R141 R150 R153					
	0	R199		DNI	NL		DNI
94	3	R24, R27, R106			R0603,10.0k	Resistor, Chip, 1/16W, 1%	
104	2	R41-42			RES 0805 1K	Resistor, Chip, 1/16W, x%	
95	1	R44			R0603,100	RES 1/10W 1% 0603 SMD	
123	4	R47 R49-51 R48 R112 R121			R0805_1%,10.0k	Resistor, Chip, 1/10W, 1%	
124	6	R159-160 R173			R0805, 1%, 15 ohm	Resistor, Chip, 1/10W, 1%	
132	4	R52-53 R55-56			RES, 0603, 1K, 1%		
122	2	R54 R57			RES, 0805, 0 ohm	Resistor, Chip, 1/10W, 1%	
129	2	R73 R75			RES, 0603, 3.6K, 1%		
	3	R90 R130 R142			RES, 0603, 0 ohm		
	3	R83, R98, R201 R81			RES, 0603, 10.0 ohm, 1% RES, 0603, 510.0 ohm, 1%		
-	4	R68-69, R78-79			RES, 0603, 510.0 0hm, 1%		
	2	R63, R65			RES, 0603, 3.6K, 1%		
		R60, R67, R71, R77			RES, 0603, 10K, 1%		

96 115 121 116 105 103	8 16 1 4 1	Reference R132 R136 R144 R148 R207-208 R1030 R1040 R84-87, R94-97, R108-111, R113-116 R99 R103 R158, R122,	MFG	PN	Part Name	Description	Notes
96 115 121 116 105 103	16 1 4	R148 R207-208 R1030 R1040 R84-87, R94-97, R108-111, R113-116 R99					
96 115 121 116 105 103	16 1 4	R84-87, R94-97, R108-111, R113-116 R99					
96 115 121 116 105 103	4	R108-111, R113-116 R99			RES, 1206, 2.2 ohm, 1%		
96 115 121 116 105 103	4	R99			DEC 4200 4751/ 0.50/		
115 121 116 105 103	4				RES, 1206, 475K, 0.5% R0603,10K	Resistor, Chip, 1/16W, x%	
121 116 105 103	1				10003,100	itesisioi, Chip, 1/10vv, x/6	
121 116 105 103		R161			R0603, 1%, 0	Resistor, Chip, 1/16W, 1%	
121 116 105 103	1	R183			R0603,10K	Resistor, Chip, 1/16W, 1%	
116 105 103		R184			R0603,2K	Resistor, Chip, 1/16W, 1%	
116 105 103		R101, R124, R126, R154, R157, R162,					
116 105 103	0	R163, R164,		DNI	NL	Resistor, Chip, 1/16W, 1%	DNI
105 103	Ŭ				· · -	, , , , , , , , , , , , , , , , , , , ,	
105 103							
103	2	R137 R155			R0603, 1%, 464	Resistor, Chip, 1/16W, 1%	
	1	R149 R156 R165			R0603, 1%, 1.37K R0805, 200	Resistor, Chip, 1/16W, 1% Resistor, Chip, 1/16W, x%	
80	-	KIDO			R0805, 200	Resistor, Chip, 1/16W, X%	
UU	1	RV1	TDK	B72210S0381K101	MOV, B72210S0381K101	MOV, wA	
	1	RV2	TDK	B72210S0321K101	MOV, B72210S0321K101	MOV, 3.5A	
ا ہے ا	,]	TO	VITEO	ENDDCOCO	TEMP EL LA VITEO FORDOSCO		
	0	T2 T1	VITEC NL	58PR6962 DNI	TFMR Flyback, ViTEC 58PR6962 NL	NL	DNI
	1	T4	PULSE	PA1005.050NL	XFMR, Pulse PA1005.050NL	Transformer, 3 Pri, 2Sec	DINI
	0	T3		DNI	NL	NL NL	DNI
	1	T5	Coilcraft	MSD1278 -273ML	27uH Coupled Inductor ,2A RMS	SMT Coupled Inductor ,2A RMS	
138	27	TP2 TP6 TP79 TP85- 91 TP93-94	KEYSTONE	5002	TP-5002-WHITE,5002	Test Point, White, Thru Hole Color Keyed	
138	21	91 1193-94	KE 15 I UNE	5002	TP-5002-WHITE,5002	Test Point, White, Thru Hole Color Reyed	
1 1		TP97-105 TP108-109					
		TP111-113 TP115					
ا ۔۔۔ ا		TP3					
137	1	TP4-5 TP7 TP11	KEYSTONE	5000	TP-5000-RED,5000	Test Point, Red, Thru Hole Color Keyed	
140	20	TP14 TP19-21 TP24	KEYSTONE	5011	TP-5011-BLACK,5011	Test Point, Black, Thru Hole	
		TP32-35 TP41 TP49	112 1 0 1 0 1 12	5511	TI COTT BETOINGOTT	Toot Form, Black, This Field	
1 1		TP71-74					
\vdash	0	TP45 TP8-10 TP12-13	NL	NL	NL		DNI
40	7	TP15-16		Digi p/n: 501-1115-ND	CONN BANANA JACK	HDWR BANANA JACK UNINS	
40		11 10 10		Digi pini. Son Tino ND	CONTENTE DATE OF CONTENT	TIBWIC BAILWAY SACK CIVING	
139	1	TP17	KEYSTONE	5002	TP-5002-WHITE,5002	Test Point, White, Thru Hole Color Keyed	
		TP45, TP61, TP70,					
141	5	TP75-76	KEYSTONE	5013	TP-5013-ORANGE,5013	Test Point, Orange, Thru Hole	
136	1	U2	TI	TL431AIDBZ	TL431AIDBZ	IC, Precision Adjustable Shunt Regulator	
100	-	52	- ''	ILTOINIDDL	I E-O IAIDBE	IC, High Speed Low Side Power MOSFET	
147	1	U3	TI	UCC27324D	UCC27324D	driver	
						IC, 45nsec, R-R Input Comparator With Open-	
83	3	U4-5 U8		LMV7235M5/NOPBCT	LMV7235M5/NOPBCT	Drain/Push-Pull Output	
51	,	U6		100 pin DIMM socket - Molex 0876301001	DIM100		
_	1	U7	TI	AMC1200SDUB	AMC1200SDUB	IC, Fully-Differential Isolation Amplifier	
	1	U9	NATIONAL	LM61CIM3/NOPB	LM61CIM3/NOPB	, ranj binoromar isolation ranpintel	
91	7	U1, U10-15	TI	OPA2171	OPAMP, DUAL, OPA2171, SO-8		
145	1	U24	TI	SM72295MA	SM72295MA		
02	,	1147 1107	TI	1007420	Digital Isolator, ISO7420 (Texas Instruments)	IC Dual shannel Law Bower Digital ICO	
92	2	U17 U27	11	ISO7420	instruments)	IC, Dual-channel Low Power, Digital ISO IC, 2.5A/5A, 40Vmax VDD FET/IGBT Single	
146	2	U19 U28	TI	UCC27531DBV	UCC27531DBV	Gate Drivers	
			RECOM				
133	2	U20 U22	POWER	RP-1212S	RP-1212S	IC, DC/DC-Converter, 12Vin, 12Vout, 84 mA	
	,]	LIC:	LEM	17000	LEM, Current Sensor with Ref	LEM LEGGE	
	1	U21 U23 U29	HOLDINGS	LTSR6_NP LM317LIPK	output, LTSR6_NP LM317LIPK	LEM, LTSR6_NP	
81	2	U23 U29	TI	LIVI31/LIPK	Current Sensor, ACS712ELCTR-	IC, 3-Terminal Pos. Adj. Regulator, 100 mA	
134	1	U25	ALLEGRO	ACS712ELCTR-20A-T	20A-T	SO-8SM	
	1	U30	TI	ISO7240CFDW	ISO7240CFDW		
	1	M3	TI	LM5017MR	LM5017MR		
455		70.4 77.7		D			D.::
150	0	ZD1 ZD5-7		DNI	NL		DNI

	Page	5

Item	Otv	Reference	MFG	PN I	Part Name	Description	Notes
	۳.,	11010101100	0		T unt Humo	2000.15.10.11	Short these on PCB
							with wire rated for
	1	JP3, JP2					high current(15A).
							Short these on PCB
							with wire rated for
							high voltage (400V)
	1	TP8, TP9					& current(5A).
				Insulators, DK p/n BER156-			
	6	Ref Q1~Q4, Q8, Q9	Bergquist	ND	Insulators for TO220		
	_	D. (O (O) O O	Aavid	OF MAYOR	O!'. /. TO000		
	6	Ref Q1~Q4, Q8, Q9	Thermalloy	Clip MAX01	Clip for TO220		L
							between Heatsink
	6	Ref HS1, HS4, HS5		Insulating Washers	Digi p/n 3118K-ND		and PCB
							Install near TP8
							TP10
							Added line item per DN-
	1				MANEX 831-0019759	HIGH VOLTAGE LABEL	385. KG 04/15/14
							Install near T2 & HS1
							Added line item per DN-
	1				MANEX 831-0019760	HIGH TEMP WARNING LABEL	385. KG 04/15/14

IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ("TI") reference designs are solely intended to assist designers ("Buyers") who are developing systems that incorporate TI semiconductor products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products.

TI reference designs have been created using standard laboratory conditions and engineering practices. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design. TI may make corrections, enhancements, improvements and other changes to its reference designs.

Buyers are authorized to use TI reference designs with the TI component(s) identified in each particular reference design and to modify the reference design in the development of their end products. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of such information may require a license from a third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS ARE PROVIDED "AS IS". TI MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. TI DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO TI REFERENCE DESIGNS OR USE THEREOF. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY BUYERS AGAINST ANY THIRD PARTY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON A COMBINATION OF COMPONENTS PROVIDED IN A TI REFERENCE DESIGN. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES, HOWEVER CAUSED, ON ANY THEORY OF LIABILITY AND WHETHER OR NOT TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, ARISING IN ANY WAY OUT OF TI REFERENCE DESIGNS OR BUYER'S USE OF TI REFERENCE DESIGNS.

TI reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques for TI components are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

Reproduction of significant portions of TI information in TI data books, data sheets or reference designs is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in Buyer's safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed an agreement specifically governing such use.

Only those TI components that TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components that have *not* been so designated is solely at Buyer's risk, and Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.