RF Sampling Resource Guide



Russell Hoppenstein

Introduction

This resource guide provides links to blog entries related to RF sampling data converters. The document is a handy resource guide to various topics pertinent to high-speed data converter designers, FPGA firmware designers, and communication engineers.

RF Sampling Data Converter Topics

- RF Sampling: The new architecture on the block
 Introduces a new transceiver architecture with the availability of RF sampling data converters capable of
 converting digital bits to and from RF signals directly.
- 2. Why Bother with RF Sampling? Investigates one of the primary benefits of RF sampling related to supporting large instantaneous bandwidths and multi-mode signals.
- 3. Managing Input Data Rates Is a Breeze
 RF sampling converters operate at very high sample rates, but it is not possible to reasonably transfer all
 of that digital data to the FPGA or processor. Learn how interpolation (TX) and decimation (RX) reduce the
 data rates to reasonable speeds without impacting the signal.
- 4. RF Sampling: Aliasing Can Be Your Friend
 Traditional sample theory dictates that your signal must be within the first Nyquist zone (Fs/2) and that aliasing is bad. Not so. See how aliasing is advantageous to operate at higher frequencies in higher Nyquist zones.
- RF Sampling: How Over-sampling Is Cheating Physics
 Maybe your signal bandwidth or frequency is not that large. You can still take advantage of the high speed sampling. See how over-sampling provides some key performance advantages in your system.
- 6. RF Sampling: Digital Mixers Make Mixing Fun
 Analog mixers are troublesome with unwanted noise, images, and spurs. Not the digital ones; they make
 mixing up and down to arbitrary frequency bands easy and fast.
- 7. RF Sampling: Interleaving Builds Faster ADCs
 When sampling speed requirements exceed the capability of the core ADC sample rate, interleaving multiple devices is a viable approach. Review the limitations and pitfalls of interleaved ADCs.
- 8. RF Sampling: Frequency Planning Yields a Clean Spectrum
 With so much spectrum at your disposal wiht RF sampling converters, frequency planning is a must to work around Nyquist zone boundaries and troublesome harmonic spurs.
- RF Sampling: Clocking Is the Key Every Time
 High quality clocking is critical for best RF sampling data converter performance. See how the clocking
 specifications impact overall data converter performance.
- 10. How to Select a Power-efficient Narrowband Receiver for Active Antenna-array Systems Introduces a narrow band receiver for a phased array system to electronically steer the antenna beam pattern.
- Push Your Receiver Bandwidths past 1-GHz in High-end Applications
 You need more capacity and more users on your system. RF sampling converters support large instantaneous bandwidth of 1GHz and beyond.
- 12. Blast past Interference Using Digital-down Converters in RF Sampling Receivers

 Take advantage of the large spectrum capabilities and digital mixing of the RF sampling converters to work around interference signals that can derail your design.



- 13. What's the Fuss about Noise in RF Sampling Converters?
 - Certainly noise performance in data converters is a key metric, but how to characterize it for high speed ADCs. Investigate the parameters of Noise Figure (NF) and Noise Spectral Density (NSD) to properly characterize signal-to-noise ratio of the converter.
- 14. RF Sampling: Linearity Performance Is Not So Straightforward
 Investigate the linearity of the data converter with large signals or in the presence of large blocking signals.
- 15. RF Sampling: Analog-to-digital Converter Linearity Sets Sensitivity Investigate how device linearity performance impacts system sensitivity.
- 16. Why Phase Noise Matters in RF Sampling Converters
 Investigate how phase noise performance of the data converter sampling clock impacts real-world system specifications.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2024, Texas Instruments Incorporated