

**SCANSTA112**



Literature Number: SNLA199

# SCANSTA112 Quick Reference

## Operating Modes

**Scan Bridge** – SCANSTA112 addressed by Level 1 protocol. Set up by register settings.

**Stitcher** – no Level 1 protocol; always addressed. Set up by pins or register settings.

**Normal (not transparent)** – instruction register in scan chain. Responds to most JTAG instructions. Pad bit between TDI and TDO on each local scan port.

**Full Transparent** – instruction register not accessible. No response to JTAG instructions. No pad bits between TDI and TDO.

**Transparent Local Scan Port (LSP)** – instruction register in scan chain. Responds to most JTAG instructions. Pad bit between TDI and TDO on last LSP.

## Mode Availability

- Normal and full transparent modes are available in both Scan Bridge and Stitcher modes.
- Transparent LSP mode in Scan Bridge mode only.
- Full transparent mode can be exited only by reset.

## Reset Sequence

Reset	IgnoreReset	Normal	Transparent
RESET	0	Full reset	Full reset
RESET	1	Full reset	Full reset
TRST	0	Full reset	Full reset
TRST	1	Ignored	Ignored
5-High TMS	0	Full reset	Ignored
5-High TMS	1	Ignored	Ignored

## Addressing After Reset

**Scan Bridge mode** – Scan instruction register; data = slot address

**Stitcher mode** – always active; no addressing

## Address Space

Address Type	Hex Address	TDO <sub>b</sub> State
Direct address	0x00 to 0x39 0x40 to 0xFF	Normal per 1149.1 std.
Interrogation	0x3A	Address out (see AN-1259)
Broadcast	0x3B	TRI-STATE®
Multi-Cast 0	0x3C	TRI-STATE
Multi-Cast 1	0x3D	TRI-STATE
Multi-Cast 2	0x3E	TRI-STATE
Multi-Cast 3	0x3F	TRI-STATE

## Registers

Name	Bits
Instruction register	8
Boundary register	22
Bypass register	1
Device ID register	32
Multi-Cast Group register	2
Mode Register 0	8
Mode Register 1	8
Mode Register 2	8
Linear Feedback Shift Register (LFSR)	16
TCK Counter register	32
Shared GPIO <sub>(0-6)</sub> registers	8
Control register	8
Local Scan Port (LSP) Select register	8

## Register Access

**Instruction register** – transition IEEE-1149.1 TAP controller to Capture-IR/Shift-IR state

**Boundary register** – EXTEST or SAMPLE/PRELOAD

**Bypass register** – BYPASS

**Device ID register** – IDCODE, UNPARK, PARKTLR, PARKRTI, PARKPAUSE, GOTOWAIT, LFSRON, LFSROFF, CNTRON, CNTROFF

**Multi-Cast Group register** – MCGRSEL

**Mode Register 0** – MODESEL

**Mode Register 1** – MODESEL1

**Mode Register 2** – MODESEL2

**LFSR - LFSRSEL**

**TCK Counter register** – CNTRSEL

**Shared GPIO<sub>(0-6)</sub> registers** – SGPIO<sub>n</sub>

**Control register** – CONTROLSEL

**LSP Select register** – LSPSEL

## Op-Codes

Instruction	Op-Code	Description
BYPASS	0xFF	Bypass register
EXTEST	0x00	Boundary register
SAMPLE/PRE-LOAD	0x81	Boundary register
IDCODE	0xAA	Device ID register
UNPARK	0xE7	Unparks LSPs
PARKTLR	0xC5	Parks LSPs in TLR
PARKRTI	0x84	Parks LSPs in RTI
PARKPAUSE	0xC6	Parks LSPs in Pause-IR or Pause-DR; Unparks parked LSPs
GOTOWAIT	0xC3	Sends all SCANSTA112s to wait for address
MODESEL	0x8E	Mode Register 0
MODESEL1	0x82	Mode Register 1
MODESEL2	0x83	Mode Register 2
MCGRSEL	0x03	Multi-Cast Group register
SOFTRESET	0x88	Parks all LSPs in TLR
LFSRSEL	0xC9	LFSR
LFSRON	0x0C	Accumulates signature
LFSROFF	0x8D	Stops signature accumulation
CNTRSEL	0xCE	TCK Counter register
CNTRON	0x0F	Enables TCK counter
CNTROFF	0x90	Disables TCK counter
DEFAULT_BYPASS	0x07	Sets bypass register as default data register

# SCANSTA112 Quick Reference

## Op-Codes (continued)

Instruction	Op-Code	Description
TRANSPARENT0 to TRANSPARENT6	0xA0 to 0xA6	Sets single LSP and transparent mode
SGPIO <sub>0</sub> to SGPIO <sub>6</sub>	0xB8 to 0xBE	Shared GPIO <sub>n</sub> register
CONTROLSEL	0x87	Control register
LSPSEL	0x86	LSP Select register
TRANSPARENTEN	0xA8	Sets transparent mode

## General Sequence for Register Writes

- 1) Set TAP controller to RTI
- 2) Sequence to Shift-IR (TMS 1-1-0-0)
- 3) Shift in op-code to select register (TMS 0)  
Example – MODESEL = 0x8E on TDI
- 4) Sequence to Exit1-IR (TMS 1)
- 5) Sequence to Update-IR (TMS 1)
- 6) Return to RTI (TMS 0)
- 7) Sequence to Shift-DR (TMS 1-0-0)
- 8) Shift register contents in (TMS 0) example – Shift 0x01 on TDI into Mode Register 0 to select LSP 0
- 9) Sequence to Exit1-DR (TMS 1)
- 10) Sequence to Update-DR (TMS 1)
- 11) Return to RTI (TMS 0)

## Register Functions

**Instruction register** – receives op-codes in Shift-IR TAP controller state

**Boundary register** – all boundary cells connected as a 22-bit shift register

**Bypass register** – one-bit bypass data register required by 1149.1

**Device ID register** – 32-bit read-only register containing device ID code

**Multi-Cast Group register** – Binary multi-cast group selection (00 = 0, 01 = 1, etc.)

**National Semiconductor**  
2900 Semiconductor Drive  
Santa Clara, CA 95051  
1 800 272 9959

Visit our website at:  
national.com

**Mailing address:**  
PO Box 58090  
Santa Clara, CA 95052

**For more information,**  
send email to:  
support@nsc.com

## Mode Registers

Bit	Mode Reg 0	Mode Reg 1	Mode Reg 2
0	LSP0	LSP5	LSP0/GPIO0
1	LSP1	LSP6	LSP1/GPIO1
2	LSP2	Reserved	LSP2/GPIO2
3	TCK Free Run	Reserved	LSP3/GPIO3
4	TDIB-TDOB Loopback	Reserved	LSP4/GPIO4
5	LSP3	Reserved	LSP5/GPIO5
6	LSP4	Reserved	LSP6/GPIO6
7	TCK Counter status	Transparent LSP mode	LSP7/GPIO7

**LFSR register** – signature compactor; LFSRSEL allows scanning in a seed or scanning out a signature

**TCK counter** – when counter is enabled and LSP is parked, TCK<sub>LSP</sub> drives clock pulses while TCK counter counts down to 0

**Shared GPIO<sub>(0-6)</sub>** – in GPIO mode (see Mode Register 2):

Bit	I/O	Function
0	0	TMS
1	0	TDO
2	I	TDI
3 to 7	N/A	Reserved

## Control Registers

Bit	Function	Default
0	IgnoreReset	0
1	Transparent	TRANS pin
2	Scan Bridge/Stitcher	SB/S pin
3	MPSEL <sub>B1/B0</sub>	MPSEL <sub>B1/B0</sub> pin
4	TLR-TRST	TLR_TRST pin
5	TLR-TRST <sub>6</sub>	TLR_TRST <sub>6</sub> pin
6	Reserved	0
7	Reserved	0

**LSP Select register** – Stitcher only; selects LSPs to be inserted in the scan chain

## Pin Descriptions

Pin Name	I/O	Description
RESET	I	Resets device regardless of state
ADDMASK	I	Masks 6 lower-slot address bits
MPSEL <sub>B1/B0</sub>	I	Selects master backplane port
SB/S	I	Selects Scan Bridge or Stitcher mode
LSPsel <sub>(0-6)</sub>	I	Selects LSPs in Stitcher mode
TRANS	I	Enables transparent mode at startup or reset – Stitcher only
TLR_TRST	I	Value of TRST <sub>(0-5)</sub> when LSP <sub>(0-5)</sub> is in TLR
TLR_TRST <sub>6</sub>	I	As above for LSP6
TRIST <sub>BO</sub> , TRIST <sub>B1</sub> , TRIST <sub>(01-03)</sub>	0	Indicates associated TDO output is TRI-STATE
A0 <sub>BO</sub> , A1 <sub>BO</sub> , A0 <sub>B1</sub> , A1 <sub>B1</sub>	I	Backplane pass-through inputs
Y0 <sub>BO</sub> , Y1 <sub>BO</sub> , Y1 <sub>B1</sub> , Y1 <sub>B1</sub>	0	Backplane pass-through outputs
S <sub>(0-7)</sub>	I	Slot identification
OE	I	Output enable for LSPs
A0 <sub>01</sub> , A1 <sub>01</sub>	I	Local pass-through inputs
Y0 <sub>01</sub> , Y1 <sub>01</sub>	0	Local pass-through outputs
TCK <sub>BO,B1</sub> , TMS <sub>BO,B1</sub> , TDI <sub>BO,B1</sub> , TDO <sub>BO,B1</sub> , TRST <sub>BO,B1</sub>	I/O	Backplane JTAG TAPs
TCK <sub>(01-06)</sub> , TMS <sub>(01-06)</sub> , TDI <sub>(01-06)</sub> , TDO <sub>(01-06)</sub> , TRST <sub>(01-06)</sub>	I/O	LSP JTAG TAPs

## Miscellaneous

- Always reset SCANSTA112 if MPSEL<sub>B1/B0</sub> pin changes
- Transparent mode can be set by TRANSPARENTN or TRANSPARENTEN instruction – must reset SCANSTA112 multiplexer to cancel transparent mode
- LSP Select register defaults to pin setting after reset



## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

Audio	<a href="http://www.ti.com/audio">www.ti.com/audio</a>
Amplifiers	<a href="http://amplifier.ti.com">amplifier.ti.com</a>
Data Converters	<a href="http://dataconverter.ti.com">dataconverter.ti.com</a>
DLP® Products	<a href="http://www.dlp.com">www.dlp.com</a>
DSP	<a href="http://dsp.ti.com">dsp.ti.com</a>
Clocks and Timers	<a href="http://www.ti.com/clocks">www.ti.com/clocks</a>
Interface	<a href="http://interface.ti.com">interface.ti.com</a>
Logic	<a href="http://logic.ti.com">logic.ti.com</a>
Power Mgmt	<a href="http://power.ti.com">power.ti.com</a>
Microcontrollers	<a href="http://microcontroller.ti.com">microcontroller.ti.com</a>
RFID	<a href="http://www.ti-rfid.com">www.ti-rfid.com</a>
OMAP Mobile Processors	<a href="http://www.ti.com/omap">www.ti.com/omap</a>
Wireless Connectivity	<a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a>

### Applications

Communications and Telecom	<a href="http://www.ti.com/communications">www.ti.com/communications</a>
Computers and Peripherals	<a href="http://www.ti.com/computers">www.ti.com/computers</a>
Consumer Electronics	<a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>
Energy and Lighting	<a href="http://www.ti.com/energy">www.ti.com/energy</a>
Industrial	<a href="http://www.ti.com/industrial">www.ti.com/industrial</a>
Medical	<a href="http://www.ti.com/medical">www.ti.com/medical</a>
Security	<a href="http://www.ti.com/security">www.ti.com/security</a>
Space, Avionics and Defense	<a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a>
Transportation and Automotive	<a href="http://www.ti.com/automotive">www.ti.com/automotive</a>
Video and Imaging	<a href="http://www.ti.com/video">www.ti.com/video</a>

TI E2E Community Home Page

[e2e.ti.com](http://e2e.ti.com)

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2011, Texas Instruments Incorporated