Variant: 001

Generated: 10/28/2015 8:25:03 AM TID #: <Parameter TID not found>

## PMP11295 REV D Bill of Materials



| T  | Item # | Designator | Quantity | Value  | PartNumber         | Manufacturer        | Description   | PackageReference   |
|--|--------|------------|----------|--------|--------------------|---------------------|---|--------------------|
| C12, C100    C12, C100    C12, C100    C14, C100    C14   | 1      | !PCB1      | 1        |        | PMP11295           | Any                 | Printed Circuit Board   |                    |
| 4  | 2      |            | 6        | 1uF    | GRM155R61A105KE15D | MuRata              | CAP, CERM, 1uF, 10V, +/-10%, X5R, 0402                                | 0402               |
| S   CS   1   0.1 UF   8.25622.310AM   EPCOS Inc   CAP_Film_0.1 µF, 630 V, + 20%, 1 H   8.25622.10Smm   | 3      | C2, C3     | 2        | 10uF   | UCY2G100MPD1TD     | Nichicon            | CAP, AL, 10 μF, 400 V, +/- 20%, ohm, TH                               |                    |
| 6   GS, C7   2   820Lif   RLBSURE*MDM*IXX   Nucleon   CAP, ALL, 820Lif   6.3V, ++20%, 0.008 cbm, TH   DiskL8     7   Ci1   | 4      | C4         | 1        | 47pF   | GRM1555C1H470FA01D | MuRata              | CAP, CERM, 47 pF, 50 V, +/- 1%, C0G/NP0, 0402                         | 0402               |
| 7  | 5      |            |          | 0.1uF  | B32922C3104M       | EPCOS Inc           | CAP, Film, 0.1 μF, 630 V, +/- 20%, TH                                 | B32922_10.5mm      |
| 8  | 6      |            | 2        |        |                    |                     |   |                    |
| 9  | 7      |            | 1        | 1      |                    |                     |   |                    |
| 10 D1  |        |            |          | -      |                    |                     |   |                    |
| 11   D2  | 9      | C15        | 1        | 1000pF | VY2102M29Y5UG63V7  | Vishay-Bccomponents | CAP, CERM, 1000 pF, 300 V, +/- 20%, Y5U, Radial Disc 7.5mm, Is=7.5    |                    |
| Components   |        |            |          |        |                    |                     |   |                    |
| 12   D3  | 11     | D2         | 1        | 150V   | SMCJ150A-TP        |                     | Diode, TVS, Uni, 150 V, 1500 W, SMC                                   | SMC                |
| 13   D5  |        |            |          |        |                    |                     |   |                    |
| 14   |        |            |          |        |                    |                     |   |                    |
| 15   |        |            |          |        | _                  |                     |   |                    |
| 10   |        |            |          | Blue   |                    |                     |   |                    |
| 14.5415422 mm  | 15     | F1         | 1        |        |                    |                     |   | 1                  |
| Receptacle, USB   Type C, R/A, Th   Type C, R/   | 16     | J1         | 1        |        | 770W-X2/10         |                     | AC Receptacle, 2.5A, R/A, TH  |                    |
| 19   | 17     | J2         | 1        |        | 12401548E4#2A      | Amphenol Canada     | Connector, Receptacle, USB Type C, R/A, TH                            | Receptacle, USB    |
| Products   | 18     | L1         | 1        | 100uH  | CDRH6D28NP-101NC   | Sumida              | inductor, Shielded Drum Core, Ferrite, 100 μH, 0.54 A, 0.535 ohm, SMD | CDRH6D28           |
| 21   | 19     | L3         | 1        | 50 ohm | HI1206T500R-10     |                     | Ferrite Bead, 50 ohm @ 100MHz, 6A, 1206                               | 1206               |
| 22   | 20     |            | 1        |        |                    | AOS                 |   |                    |
| 23   R2  |        |            | 1        |        |                    |                     |   |                    |
| 24   |        |            | 1        |        |                    |                     |   |                    |
| 25   R7  |        | 1          |          | -      |                    |                     |   |                    |
| 26         R8         1         20.0         CRCW040220R0FKED         Vishay-Dale         RES, 20.0, 1%, 0.063 W, 0402         0402           27         R9         1         110k         CRCW0402110KFKED         Vishay-Dale         RES, 110 k, 1%, 0.063 W, 0402         0402           28         R10         1         1.78k         CRCW040210KFKED         Vishay-Dale         RES, 178 k, 1%, 0.063 W, 0402         0402           29         R11         1         100k         CRCW040210KFKED         Vishay-Dale         RES, 100 k, 1%, 0.063 W, 0402         0402           30         R12         1         35.7k         CRCW04023K7FKED         Vishay-Dale         RES, 35.7 k, 1%, 0.063 W, 0402         0402           31         R13         1         0.51         CRM0805-FX-R510ELF         Bourns         RES, 0.51, 1%, 0.25 W, 0805         0805           32         R15         1         499         CRCW040210KFKED         Vishay-Dale         RES, 3.7 k, 1%, 0.063 W, 0402         0402           33         R16         1         10.0k         CRCW040227KFKED         Vishay-Dale         RES, 10.0 k, 1%, 0.063 W, 0402         0402           34         R17         1         37.4k         CRCW040227KFKED         Vishay-Dale         RES, 3.7 k, 1%, 0.063 W  |        |            |          |        |                    |                     |   |                    |
| 27 R9  |        |            |          |        |                    |                     |   |                    |
| 28   R10   |        |            |          |        |                    |                     |   |                    |
| 29   |        |            |          | _      |                    |                     |   |                    |
| 30   |        |            |          |        |                    |                     |   |                    |
| State  |        |            |          |        |                    |                     |   |                    |
| 32   R15   |        |            | 1        |        |                    |                     |   |                    |
| 33   R16   |        |            | 1        |        |                    |                     |   |                    |
| 34         R17         1         37.4k         CRCW040237K4FKED         Vishay-Dale         RES, 37.4 k, 1%, 0.063 W, 0402         0402           35         R18, R100         2         20.0k         CRCW040220K0FKED         Vishay-Dale         RES, 20.0 k, 1%, 0.063 W, 0402         0402           36         T1         1         220 uH         G154042LF         GCI Technologies         Transformer, 170 uH, TH         21x21mm           37         TP2         1         Black         5011         Keystone         Test Point, Multipurpose, Black, TH         Black Multipurpose Testpoint           38         TP3         1         Red         5000         Keystone         Test Point, Miniature, Red, TH         Red Miniature           39         U1         1         TPS2514ADBV         Texas Instruments         USB Dedicated Charging Port Controller, DBV0006A         DBV0006A           40         U2         1         TPS25810RVC         Texas Instruments         USB Type-C DFP Controller and Power Switch with Load Detection, RVC0020A         RVC0020A           41         U3         1         UCC28730DR         Texas Instruments         Constant-Voltage Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A         Wake-Up Monitoring, D0007A           42         U4         1   |        |            |          |        |                    |                     |   |                    |
| 35 R18, R100 2 20.0k CRCW040220K0FKED Vishay-Dale RES, 20.0 k, 1%, 0.063 W, 0402 0402  36 T1 1 220 uH G154042LF GCI Technologies Transformer, 170 uH, TH 21x21mm  37 TP2 1 Black 5011 Keystone Test Point, Multipurpose, Black, TH Black Multipurpose Testpoint  38 TP3 1 Red 5000 Keystone Test Point, Miniature, Red, TH Red Miniature Red Miniature Testpoint  39 U1 1 TPS2514ADBV Texas Instruments USB Dedicated Charging Port Controller, DBV0006A DBV0006A  40 U2 1 TPS25810RVC Texas Instruments USB Type-C DFP Controller and Power Switch with Load Detection, RVC0020A  41 U3 1 UCC28730DR Texas Instruments Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A  42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  |        |            |          |        |                    |                     |   |                    |
| 36 T1 1 220 uH G154042LF GCI Technologies Transformer, 170 uH, TH 21x21mm  37 TP2 1 Black 5011 Keystone Test Point, Multipurpose, Black, TH Black Multipurpose Testpoint  38 TP3 1 Red 5000 Keystone Test Point, Miniature, Red, TH Red Miniature Test Point, Miniature, Red, TH Red Miniature Testpoint  39 U1 1 TPS2514ADBV Texas Instruments USB Dedicated Charging Port Controller, DBV0006A DBV0006A  40 U2 1 TPS25810RVC Texas Instruments USB Type-C DFP Controller and Power Switch with Load Detection, RVC0020A  41 U3 1 UCC28730DR Texas Instruments Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A  42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  |        |            |          |        |                    | ,                   |   |                    |
| Test Point, Multipurpose, Black, TH  Black Multipurpose Testpoint  Red 5000 Keystone Test Point, Miniature, Red, TH  Red Miniature Testpoint  Red Miniature Testpoint  Test Point, Miniature, Red, TH  Red Miniature Testpoint  Test Point, Miniature, Red, TH  Red Miniature Testpoint  Seption Test Point, Miniature, Red, TH  Red Miniature Testpoint  Test Point, Miniature, Red, TH  Red Miniature Testpoint  Seption Test Point, Miniature, Red, TH  Red Miniature Testpoint  Seption Testpoint  Seption Testpoint  Seption Testpoint  Seption Testpoint  Seption Testpoint  Test Point, Multipurpose, Black, TH  Red Miniature Testpoint  Seption Testpoint  Test Point, Multipurpose, Black, TH  Red Miniature Testpoint  Seption Te |        |            |          |        |                    |                     |   |                    |
| 38 TP3 1 Red 5000 Keystone Test Point, Miniature, Red, TH Red Miniature Testpoint 39 U1 1 TPS2514ADBV Texas Instruments USB Dedicated Charging Port Controller, DBV0006A DBV0006A 40 U2 1 TPS25810RVC Texas Instruments USB Type-C DFP Controller and Power Switch with Load Detection, RVC0020A 41 U3 1 UCC28730DR Texas Instruments Constant-Voltage Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A 42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  |        |            |          |        |                    | •                   | ,                               | Black Multipurpose |
| 40 U2 1 TPS25810RVC Texas Instruments USB Type-C DFP Controller and Power Switch with Load Detection, RVC0020A  41 U3 1 UCC28730DR Texas Instruments Constant-Voltage Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A  42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  5TANDBY, DBV0006A   | 38     | TP3        | 1        | Red    | 5000               | Keystone            | Test Point, Miniature, Red, TH  | Red Miniature      |
| RVC0020A  41 U3 1 UCC28730DR Texas Instruments Constant-Voltage Constant-Current Flyback Controller With PSR and Wake-Up Monitoring, D0007A  42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  STANDBY, DBV0006A   | 39     | ~ .        | 1        |        | TPS2514ADBV        | Texas Instruments   |   |                    |
| Wake-Up Monitoring, D0007A  42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A  STANDBY, DBV0006A  | 40     | U2         | 1        |        | TPS25810RVC        | Texas Instruments   |   | RVC0020A           |
| 42 U4 1 UCC24636DBVR Texas Instruments SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER DBV0006A STANDBY, DBV0006A   | 41     | U3         | 1        |        | UCC28730DR         | Texas Instruments   | ,   | D0007A             |
|  | 42     | U4         | 1        |        | UCC24636DBVR       | Texas Instruments   | SYNCRONOUS RECTIFIER CONTROLLER WITH LOW POWER                        | DBV0006A           |
|  | 43     | U100       | 1        |        | UCC24650DBVR       | Texas Instruments   |   | DBV0005A           |

## IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ("TI") reference designs are solely intended to assist designers ("Buyers") who are developing systems that incorporate TI semiconductor products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products.

TI reference designs have been created using standard laboratory conditions and engineering practices. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design. TI may make corrections, enhancements, improvements and other changes to its reference designs.

Buyers are authorized to use TI reference designs with the TI component(s) identified in each particular reference design and to modify the reference design in the development of their end products. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS ARE PROVIDED "AS IS". TI MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. TI DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO TI REFERENCE DESIGNS OR USE THEREOF. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY BUYERS AGAINST ANY THIRD PARTY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON A COMBINATION OF COMPONENTS PROVIDED IN A TI REFERENCE DESIGN. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES, HOWEVER CAUSED, ON ANY THEORY OF LIABILITY AND WHETHER OR NOT TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, ARISING IN ANY WAY OUT OF TI REFERENCE DESIGNS OR BUYER'S USE OF TI REFERENCE DESIGNS.

TI reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques for TI components are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

Reproduction of significant portions of TI information in TI data books, data sheets or reference designs is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in Buyer's safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed an agreement specifically governing such use.

Only those TI components that TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components that have *not* been so designated is solely at Buyer's risk, and Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.