

Understanding the Clock Architecture of the OMAP36xx - Public -

OMCCB Application Engineering - Japan

ABSTRACT

This application note describes the clock architecture of OMAP36xx from the perspective of the PRCM. A single diagram of the clock architecture summarizes all of the clock signals including the PRCM register bits that affect them. Using this diagram, SW developers can quickly understand and find the relevant register bits necessary for configuring the clocks within the OMAP36xx.

Preliminary

Recipient agrees that it will not knowingly export or re-export, directly or indirectly, any product or technical data (as defined by the U.S, EU and other Export Administration Regulations) including software, or any controlled product restricted by other applicable national regulations, received from Disclosing party under this Agreement, or any direct product of such technology, to any destination to which such export or re-export is restricted or prohibited by U.S or other applicable laws, without obtaining prior authorization from U.S. Department of Commerce and other competent Government authorities to the extent required by those laws. This provision shall survive termination or expiration of this Agreement.

According to our best knowledge of the state and end-use of this product or technology, and in compliance with the export control regulations of dual-use goods in force in the origin and exporting countries, this technology is classified as follows:

- US ECCN: 3E991
- EU ECCN: 3E991

and may require export or re-export license for shipping it in compliance with certain countries regulations

Contents

History	3
1 Introduction	4
2 How to use this clock architecture diagram	4
2.1 Supported Silicon Revision	4
2.2 Multiple Instances of a Module	4
2.3 Power Domain Colors	4
2.4 Not supported in the figure	4
3 Figure of the Clock configuration	6
References	7
OMAP36xx Disclaimer	7

Figures

Figure 1. OMAP36xx Clock Architecture	6
--	----------

Tables

Table 1. Document History	3
--	----------

Preliminary

History

Table 1. Document History

Version	Date	Author	Notes
1.0	May/20/2010	A0783816	1

1. Created Document

Preliminary

1 Introduction

This application note provides an overview of the clock architecture for OMAP36xx. A power reset clock manager (PRCM) module has multiple registers that are used to control the clocks for each module in the OMAP device. It is useful to find which bits should be set to enable a module.

2 How to use this clock architecture diagram

Please read the important information in this section before using the diagram.

2.1 Supported Silicon Revision

This figure supports OMAP36xx ES1.0 device.

2.2 Multiple Instances of a Module

OMAP36xx has multiple instances of some modules. For example, there are multiple instances for the GPIO, McBSP and GPTimer modules. For simplicity's sake, these modules are combined. However some modules are not assigned to the same power domain, so they are drawn separately. For example, GPIO1 & GPIO2-6 are drawn separately since they are in different power domains.

2.3 Power Domain Colors

Background colors show the assigned power domain. The color details are as follows:

Light Gray	: Core domain
Light Blue	: Wakeup domain
Purple	: MPU domain
Red	: IVA domain
Pink	: SGX domain
Yellow	: CAM domain
Light Green	: DSS domain
Gray	: PERIPHERAL domain
Blue	: DPLLx domain
Emerald Green	: USB HOST domain
Green	: SmartReflex domain
Brown	: EMU domain

2.4 Not supported in the figure

This figure does not support all clock control features for the OMAP36xx because some modules have an internal clock that is not controlled by the PRCM. This figure comes from the PRCM's standpoint.

For example: DSI PLL output can be used for DSS_FCLK instead of DSS1_ALWON_FCLK. It is controlled by DISPC_CLK_SWITCH bit in DSS.

Preliminary

3 Figure of the Clock configuration




Figure 1. OMAP36xx Clock Architecture

References

1. *Understanding the OMAP34xx Clock Architecture – Public - (SWPAxxx)*
2. *CTT-OMAP3630ES1.0-v1.6.0.1-Public*

OMAP36xx Disclaimer

All programming models and use cases presented in this document are provided for educative purposes only and may differ from or be optimized for your applications.

All OMAP peripheral devices presented in this document are provided for illustration purposes and may be different from those in your system.

Preliminary

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright 2009, Texas Instruments Incorporated