

LP5866 具有 8 位模拟和 8 位/16 位 PWM 调光的 6 x 18 LED 矩阵驱动器

1 特性

- LED 矩阵拓扑：
 - 18 个恒定电流阱，具有 6 个扫描开关，可实现 108 个 LED 点
 - 可针对 1 至 6 个扫描开关进行配置
- 工作电压范围：
 - V_{CC}/V_{LED} 范围：2.7V 至 5.5V
 - 逻辑引脚兼容 1.8V、3.3V 和 5V 电压
- 18 个高精度恒定电流阱：
 - 当 $V_{CC} \geq 3.3V$ 时，每个电流阱的电流为 0.1mA - 50mA
 - 器件间误差：当通道电流 = 50mA 时为 $\pm 3\%$
 - 通道间误差：当通道电流 = 50mA 时为 $\pm 3\%$
 - 相移可平衡瞬态功耗
- 超低功耗：
 - 关断模式：当 $EN =$ 低电平时 $I_{CC} \leq 1 \mu A$
 - 待机模式：当 EN 为高电平且 $CHIP_EN$ 为 0 (保留数据) 时， $I_{CC} \leq 10 \mu A$ (LP5866MDBT 为 $\leq 15 \mu A$)
 - 工作模式：当通道电流为 5mA 时， $I_{CC} = 4.3mA$ (典型值)
- 灵活的调光选项：
 - 对每个 LED 点进行单独的开/关控制
 - 模拟调光 (电流增益控制)
 - 为所有 LED 点提供全局 3 位最大电流 (MC) 设置
 - 为红色、绿色和蓝色提供 3 组 7 位颜色电流 (CC) 设置
 - 为每个 LED 点提供单独的 8 位点电流 (DC) 设置
 - 以无可闻噪声的频率进行 PWM 调光
 - 为所有 LED 点实现全局 8 位 PWM 调光
 - 为 LED 点任意映射实现 3 组可编程 8 位 PWM 调光
 - 为每个 LED 点实现单独的 8 位或 16 位 PWM 调光
- 完整的可寻址 SRAM，可更大限度地减少数据流量
- 针对各个 LED 点进行开路和短路检测
- 提供重影消除和低亮度补偿功能
- 接口选项：
 - 当 $IFS =$ 低电平时采用 1MHz (最大值) I²C 接口
 - 当 $IFS =$ 高电平时采用 12MHz (最大值) SPI 接口

2 应用

- 用于以下设备的 LED 动画和指示：
 - 键盘、鼠标和游戏附件
 - 大型和智能家用电器
 - 智能音箱、有线和无线音箱
 - 混音器、DJ 设备和广播
 - 接入设备、交换机和服务器
- 用于光学模块的恒定电流阱

3 说明

电子设备变得越来越智能，而且需要使用更多的 LED 提供动画效果和指示功能，因此需要使用高性能 LED 矩阵驱动器以小尺寸解决方案改善用户体验。

LP5866x 器件是高性能 LED 矩阵驱动器系列。该系列器件集成了 18 个具有 N ($N = 1/2/4/6/8/11$) 个开关 MOSFET 的恒定电流阱，以支持 $N \times 18$ 个 LED 点或 $N \times 6$ 个 RGB LED。LP5866 集成了 6 个 MOSFET，从而支持多达 108 个 LED 点或 36 个 RGB LED。


LP5866 同时支持模拟调光和 PWM 调光方法。对于模拟调光，能够以 256 个阶跃来调节每个 LED 点。对于 PWM 调光，集成式 8 位或 16 位可配置 PWM 发生器可实现平滑且无可闻噪声的调光控制。也可以将每个 LED 点任意映射到 8 位组 PWM，以实现共同调光控制。

LP5866 器件实现了完整的可寻址 SRAM，从而更大程度减少数据流量。集成了重影消除电路以消除上下重影。LP5866 还支持 LED 开路和短路检测功能。LP5866 同时支持 1MHz (最大值) I²C 和 12MHz (最大值) SPI。

器件信息

| 器件型号 | 封装 ⁽¹⁾ | 本体尺寸 (标称值) |
|--------|-------------------|-----------------|
| LP5866 | VQFN (40) | 5.00mm × 5.00mm |
| | TSSOP (38) | 9.70mm × 4.40mm |

- (1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。



简化原理图



Table of Contents

| | | | |
|--|-----------|--|-----------|
| 1 特性 | 1 | 7.4 Device Functional Modes..... | 25 |
| 2 应用 | 1 | 7.5 Programming..... | 26 |
| 3 说明 | 1 | 7.6 Register Maps..... | 29 |
| 4 Device Comparison | 3 | 8 Application and Implementation | 41 |
| 5 Pin Configuration and Functions | 4 | 8.1 Application Information..... | 41 |
| 6 Specifications | 7 | 8.2 Typical Application..... | 41 |
| 6.1 Absolute Maximum Ratings..... | 7 | 8.3 Power Supply Recommendations..... | 44 |
| 6.2 ESD Ratings | 7 | 8.4 Layout..... | 44 |
| 6.3 Recommended Operating Conditions..... | 7 | 9 Device and Documentation Support | 46 |
| 6.4 Thermal Information..... | 7 | 9.1 接收文档更新通知..... | 46 |
| 6.5 Electrical Characteristics..... | 8 | 9.2 支持资源..... | 46 |
| 6.6 Timing Requirements..... | 9 | 9.3 Trademarks..... | 46 |
| 6.7 Typical Characteristics..... | 12 | 9.4 静电放电警告..... | 46 |
| 7 Detailed Description | 14 | 9.5 术语表..... | 46 |
| 7.1 Overview..... | 14 | 10 Revision History | 46 |
| 7.2 Functional Block Diagram..... | 14 | 11 Mechanical, Packaging, and Orderable Information | 47 |
| 7.3 Feature Description..... | 15 | | |

4 Device Comparison

| PART NUMBER | MATERIAL | LED DOT NUMBER | PACKAGE ⁽²⁾ | SOFTWARE COMPATIBLE |
|-------------|-----------------------------|----------------|------------------------|---------------------|
| LP5861 | LP5861RSMR | 18 × 1 = 18 | VQFN-32 | Yes |
| LP5862 | LP5862RSMR | 18 × 2 = 36 | VQFN-32 | |
| | LP5862DBTR | | TSSOP-38 | |
| LP5864 | LP5864RSMR | 18 × 4 = 72 | VQFN-32 | |
| | LP5864MRSRMR ⁽¹⁾ | | | |
| LP5866 | LP5866RKPR | 18 × 6 = 108 | VQFN-40 | |
| | LP5866DBTR | | TSSOP-38 | |
| | LP5866MDBTR ⁽¹⁾ | | | |
| LP5868 | LP5868RKPR | 18 × 8 = 144 | VQFN-40 | |
| LP5860 | LP5860RKPR | 18 × 11 = 198 | VQFN-40 | |
| | LP5860MRKPR ⁽¹⁾ | | | |

(1) Extended temperature devices, supporting - 55°C to approximately 125°C operating ambient temperature.

(2) The same packages are hardware compatible.

5 Pin Configuration and Functions




图 5-1. LP5866 RKP Package 40-Pin VQFN With Exposed Thermal Pad Top View




图 5-2. LP5866 DBT Package 38-Pin TSSOP Top View

表 5-1. Pin Functions

| PIN | | | I/O | DESCRIPTION |
|------|----------|-----------|-----|--|
| NAME | VQFN NO. | TSSOP NO. | | |
| CS0 | 1 | 15 | O | Current sink 0. If not used, this pin must be left floating. |
| CS1 | 2 | 16 | O | Current sink 1. If not used, this pin must be left floating. |
| CS2 | 3 | 17 | O | Current sink 2. If not used, this pin must be left floating. |
| CS3 | 4 | 18 | O | Current sink 3. If not used, this pin must be left floating. |
| CS4 | 5 | 19 | O | Current sink 4. If not used, this pin must be left floating. |
| CS5 | 6 | 20 | O | Current sink 5. If not used, this pin must be left floating. |
| CS6 | 7 | 21 | O | Current sink 6. If not used, this pin must be left floating. |
| CS7 | 8 | 22 | O | Current sink 7. If not used, this pin must be left floating. |
| CS8 | 9 | 23 | O | Current sink 8. If not used, this pin must be left floating. |
| SW0 | 10 | 24 | O | High-side PMOS switch output for scan line 0. If not used, this pin must be left floating. |
| SW1 | 11 | 25 | O | High-side PMOS switch output for scan line 1. If not used, this pin must be left floating. |
| SW2 | 12 | 26 | O | High-side PMOS switch output for scan line 2. If not used, this pin must be left floating. |
| SW3 | 13 | 31 | O | High-side PMOS switch output for scan line 3. If not used, this pin must be left floating. |
| SW4 | 14 | 32 | O | High-side PMOS switch output for scan line 4. If not used, this pin must be left floating. |

表 5-1. Pin Functions (续)

| PIN | | | I/O | DESCRIPTION |
|------------|---------------------|-----------|---------|---|
| NAME | VQFN NO. | TSSOP NO. | | |
| SW5 | 15 | 33 | O | High-side PMOS switch output for scan line 5. If not used, this pin must be left floating. |
| VLED | 16 | 30 | Power | Power input for high-side switches |
| NC | 17, 18, 19, 20, 21 | 27, 29 | - | No internal connection |
| CS9 | 22 | 34 | O | Current sink 9. If not used, this pin must be left floating. |
| CS10 | 23 | 35 | O | Current sink 10. If not used, this pin must be left floating. |
| CS11 | 24 | 36 | O | Current sink 11. If not used, this pin must be left floating. |
| CS12 | 25 | 37 | O | Current sink 12. If not used, this pin must be left floating. |
| CS13 | 26 | 38 | O | Current sink 13. If not used, this pin must be left floating. |
| CS14 | 27 | 1 | O | Current sink 14. If not used, this pin must be left floating. |
| CS15 | 28 | 2 | O | Current sink 15. If not used, this pin must be left floating. |
| CS16 | 29 | 3 | O | Current sink 16. If not used, this pin must be left floating. |
| CS17 | 30 | 4 | O | Current sink 17. If not used, this pin must be left floating. |
| AGND | 31 | 5 | Ground | Analog ground. Must be connected to exposed thermal pad and common ground plane. |
| VCAP | 32 | 6 | O | Internal LDO output. A 1- μ F capacitor must be connected between this pin with GND. Place the capacitor as close to the device as possible. |
| IFS | 33 | 7 | I | Interface type select. I ² C is selected when IFS is low. SPI is selected when IFS is high. A resistor must be connected between VIO and this pin. |
| VSYNC | 34 | 8 | I | External synchronize signal for display mode 2 and mode 3 |
| SCL_SCLK | 35 | 9 | I | I ² C clock input or SPI clock input. Pull up to VIO when configured as I ² C. |
| SDA_MOSI | 36 | 10 | I/O | I ² C data input or SPI leader output follower input. Pull up to VIO when configured as I ² C. |
| ADDR0_MISO | 37 | 11 | I/O | I ² C address select 0 or SPI leader input follower output |
| ADDR1_SS | 38 | 12 | I | I ² C address select 1 or SPI follower select |
| VIO_EN | 39 | 13 | Power,I | Power supply for digital circuits and chip enable. A 1-nF capacitor must be connected between this pin with GND and be placed as close to the device as possible. |
| VCC | 40 | 14 | Power | Power supply for device. A 1- μ F capacitor must be connected between this pin with GND and be placed as close to the device as possible. |
| GND | Exposed Thermal Pad | / | Ground | Must be connected to AGND and common ground plane |

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)⁽¹⁾

| | | MIN | MAX | UNIT |
|--|----------------------|-------|-----|------|
| Voltage on V _{CC} / V _{LED} / VIO / EN / CS / SW / SDA / SCL / SCLK / MOSI / MISO / SS / ADDR0 / ADDR1 / VSYNC / IFS | | – 0.3 | 6 | V |
| Voltage on VCAP | | – 0.3 | 2 | V |
| T _J | Junction temperature | – 55 | 150 | °C |
| T _{stg} | Storage temperature | – 65 | 150 | °C |

- (1) Operation outside the Absolute Maximum Ratings may cause permanent device damage. Absolute Maximum Ratings do not imply functional operation of the device at these or any other conditions beyond those listed under Recommended Operating Conditions. If used outside the Recommended Operating Conditions but within the Absolute Maximum Ratings, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.

6.2 ESD Ratings

| | | | VALUE | UNIT |
|--------------------|-------------------------|--|-------|------|
| V _(ESD) | Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/ JEDEC JS-001, all pins ⁽¹⁾ | ±3000 | V |
| | | Charged device model (CDM), per ANSI/ESDA/ JEDEC JS-002, all pins ⁽²⁾ | ±1000 | |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

| | | MIN | NOM | MAX | UNIT |
|--|---|------|-----|-----|------|
| Input voltage on V _{CC} | Supply voltage | 2.7 | | 5.5 | V |
| Input voltage on V _{LED} | LED supply voltage | 2.7 | | 5.5 | V |
| Input voltage on VIO_EN | | 1.65 | | 5.5 | V |
| Voltage on SDA / SCL / SCLK / MOSI / MISO / SS / ADDR _x / VSYNC / IFS | | | | VIO | V |
| T _A | Operating ambient temperature | – 40 | | 85 | °C |
| T _A | Operating ambient temperature, LP5866MDBT | – 55 | | 125 | °C |

6.4 Thermal Information

| THERMAL METRIC ⁽¹⁾ | | LP5866, LP5866M | | UNIT |
|-------------------------------|--|-----------------|-------------|------|
| | | RKP (VQFN) | DBT (TSSOP) | |
| | | 40 Pins | 38 Pins | |
| R _{θJA} | Junction-to-ambient thermal resistance | 31.4 | 67.0 | °C/W |
| R _{θJC(top)} | Junction-to-case (top) thermal resistance | 22.9 | 20.1 | °C/W |
| R _{θJB} | Junction-to-board thermal resistance | 12.0 | 27.4 | °C/W |
| Ψ _{JT} | Junction-to-top characterization parameter | 0.3 | 1.0 | °C/W |
| Ψ _{JB} | Junction-to-board characterization parameter | 12.0 | 27.0 | °C/W |
| R _{θJC(bot)} | Junction-to-case (bottom) thermal resistance | 3.5 | n/a | °C/W |

- (1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

6.5 Electrical Characteristics

$V_{CC} = 3.3\text{ V}$, $V_{LED} = 3.8\text{ V}$, $V_{IO} = 1.8\text{ V}$ and $T_A = -40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$ ($T_A = -55\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ for LP5866MDBT); Typical values are at $T_A = 25\text{ }^{\circ}\text{C}$ (unless otherwise specified)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-----------------------|---|---|-------|------|-----|---------------|
| Power supplies | | | | | | |
| V_{CC} | Device supply voltage | | 2.7 | | 5.5 | V |
| V_{UVR} | Undervoltage restart | V_{CC} rising, Test mode | | | 2.5 | V |
| V_{UVF} | Undervoltage shutdown | V_{CC} falling, Test mode | 1.9 | | | V |
| V_{UV_HYS} | Undervoltage shutdown hysteresis | | | 0.3 | | V |
| V_{CAP} | Internal LDO output | $V_{CC} = 2.7\text{ V}$ to 5.5 V | | 1.78 | | V |
| I_{CC} | Shutdown supply current $I_{SHUTDOWN}$ | $V_{EN} = 0\text{ V}$, CHIP_EN = 0 (bit), measure the total current from V_{CC} and V_{LED} | | 0.1 | 1 | μA |
| | Standby supply current $I_{STANDBY}$ | $V_{EN} = 3.3\text{ V}$, CHIP_EN = 0 (bit), measure the total current from V_{CC} and V_{LED} | | 5.5 | 10 | μA |
| | | $V_{EN} = 3.3\text{ V}$, CHIP_EN = 0 (bit), measure the total current from V_{CC} and V_{LED} , LP5866MDBT | | 5.5 | 15 | μA |
| | Active mode supply current I_{NORMAL} | $V_{EN} = 3.3\text{ V}$, CHIP_EN = 1 (bit), all channels $I_{OUT} = 5\text{ mA}$ (MC = 1, CC = 127, DC = 256), measure the current from V_{CC} | | 4.3 | 6 | mA |
| V_{LED} | LED supply voltage | | 2.7 | | 5.5 | V |
| V_{VIO} | VIO supply voltage | | 1.65 | | 5.5 | V |
| I_{VIO} | VIO supply current | Interface idle | | | 5 | μA |
| Output Stages | | | | | | |
| I_{CS} | Constant current sink output range (CS0 - CS17) | $2.7 \leq V_{CC} < 3.3\text{ V}$, PWM = 100% | 0.1 | | 40 | mA |
| | | $V_{CC} \geq 3.3\text{ V}$ PWM = 100% | 0.1 | | 50 | mA |
| I_{LKG} | Leakage current (CS0 - CS17) | channels off, up_degghost = 0, $V_{CS} = 5\text{ V}$ | | 0.1 | 1 | μA |
| I_{ERR_DD} | Device to device current error, $I_{ERR_DD} = (I_{AVE} - I_{SET}) / I_{SET} \times 100\%$ | All channels ON. Current set to 0.1 mA. MC = 0 CC = 42 DC = 25 PWM = 100% | - 7 | | 7 | % |
| | | All channels ON. Current set to 1 mA. MC = 2 CC = 127 DC = 25 PWM = 100% | - 5 | | 5 | % |
| | | All channels ON. Current set to 10 mA. MC = 2 CC = 127 DC = 255 PWM = 100% | - 3.5 | | 3.5 | % |
| | | All channels ON. Current set to 25 mA. MC = 7 CC = 64 DC = 255 PWM = 100% | - 3.5 | | 3.5 | % |
| | | All channels ON. Current set to 50 mA. MC = 7 CC = 127 DC = 255 PWM = 100% | - 3 | | 3 | % |
| I_{ERR_CC} | Channel to channel current error, $I_{ERR_CC} = (I_{OUTX} - I_{AVE}) / I_{AVE} \times 100\%$ | All channels ON. Current set to 0.1 mA. MC = 0 CC = 42 DC = 25 PWM = 100% | - 5.5 | | 5.5 | % |
| | | All channels ON. Current set to 1 mA. MC = 2 CC = 127 DC = 25 PWM = 100% | - 5 | | 5 | % |
| | | All channels ON. Current set to 10 mA. MC = 2 CC = 127 DC = 255 PWM = 100% | - 4 | | 4 | % |
| | | All channels ON. Current set to 25 mA. MC = 7 CC = 64 DC = 255 PWM = 100% | - 3.5 | | 3.5 | % |
| | | All channels ON. Current set to 50 mA. MC = 7 CC = 127 DC = 255 PWM = 100% | - 3 | | 3 | % |
| f_{PWM} | LED PWM frequency | PWM_Fre = 1, PWM = 100% | | 62.5 | | KHz |
| | | PWM_Fre = 0, PWM = 100% | | 125 | | KHz |

6.5 Electrical Characteristics (续)

$V_{CC} = 3.3\text{ V}$, $V_{LED} = 3.8\text{ V}$, $V_{IO} = 1.8\text{ V}$ and $T_A = -40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$ ($T_A = -55\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ for LP5866MDBT); Typical values are at $T_A = 25\text{ }^{\circ}\text{C}$ (unless otherwise specified)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-----------------------|--|--|-----------------------|-----------------------|------|------|
| V _{SAT} | Output saturation voltage | I _{OUT} = 50 mA, decreasing output voltage, when the LED current has dropped 5% | | | 0.45 | V |
| | | I _{OUT} = 30 mA, decreasing output voltage, when the LED current has dropped 5% | | | 0.4 | V |
| | | I _{OUT} = 10 mA, decreasing output voltage, when the LED current has dropped 5% | | | 0.35 | V |
| R _{SW} | High-side PMOS ON resistance | V _{LED} = 2.7 V, I _{SW} = 200 mA | | 450 | | m Ω |
| | | V _{LED} = 3.8 V, I _{SW} = 200 mA | | 380 | | m Ω |
| | | V _{LED} = 5 V, I _{SW} = 200 mA | | 310 | | m Ω |
| Logic Interfaces | | | | | | |
| V _{LOGIC_IL} | Low-level input voltage, SDA, SCL, SCLK, MOSI, SS, ADDR _x , VSYNC, IFS | | | 0.3 × V _{IO} | | V |
| V _{LOGIC_IH} | High-level input voltage, SDA, SCL, SCLK, MOSI, SS, ADDR _x , VSYNC, IFS | | 0.7 × V _{IO} | | | V |
| V _{EN_IL} | Low-level input voltage of EN | | | 0.4 | | V |
| V _{EN_IH} | High-level input voltage of EN | When V _{CAP} powered up | 1.4 | | | V |
| I _{LOGIC_I} | Input current, SDA, SCL, SCLK, MOSI, SS, ADDR _x | | – 1 | | 1 | μA |
| V _{LOGIC_OL} | Low-level output voltage, SDA, MISO | I _{PULLUP} = 3 mA | | 0.4 | | V |
| V _{LOGIC_OH} | High-level output voltage, MISO | I _{PULLUP} = – 3 mA | 0.7 × V _{IO} | | | V |
| Protection Circuits | | | | | | |
| V _{LOD_TH} | Thershold for channel open detection | | | 0.25 | | V |
| V _{LSD_TH} | Thershold for channel short detection | | | V _{LED} – 1 | | V |
| T _{TSD} | Thermal-shutdown junction temperature | | | 150 | | °C |
| T _{HYS} | Thermal shutdown temperature hysteresis | | | 15 | | °C |

6.6 Timing Requirements

| | | MIN | NOM | MAX | UNIT |
|----------------------------------|---|------|------|-----|---------------|
| MISC. Timing Requirements | | | | | |
| f_{OSC} | Internal oscillator frequency | | 31.2 | | MHz |
| f_{OSC_ERR} | Device to device oscillator frequency error | - 3% | | 3% | |
| t_{POR_H} | Wait time from UVLO disactive to device NORMAL | | | 500 | μs |
| t_{CHIP_EN} | Wait time from setting Chip_EN (Register) =1 to device NORMAL | | | 100 | μs |
| t_{RISE} | LED output rise time | | 10 | | ns |
| t_{FALL} | LED output fall time | | 15 | | ns |
| t_{VSYNC_H} | The minimum high-level pulse width of VSYNC | 200 | | | μs |
| SPI timing requirements | | | | | |
| f_{SCLK} | SPI Clock frequency | | | 12 | MHz |
| 1 | Cycle time | 83.3 | | | ns |
| 2 | SS active lead-time | 50 | | | ns |
| 3 | SS active leg time | 50 | | | ns |
| 4 | SS inactive time | 50 | | | ns |

6.6 Timing Requirements (续)

| | | MIN | NOM | MAX | UNIT |
|--|--|------|-----|------|------|
| 5 | SCLK low time | 36 | | | ns |
| 6 | SCLK high time | 36 | | | ns |
| 7 | MOSI set-up time | 20 | | | ns |
| 8 | MOSI hold time | 20 | | | ns |
| 9 | MISO disable time | | | 30 | ns |
| 10 | MISO data valid time | | | 35 | ns |
| C _b | Bus capacitance | 5 | | 40 | pF |
| I²C standard mode timing requirements | | | | | |
| I²C fast mode timing requirements | | | | | |
| f _{SCL} | I ² C clock frequency | 0 | | 400 | KHz |
| 1 | Hold time (repeated) START condition | 0.6 | | | μs |
| 2 | Clock low time | 1.3 | | | μs |
| 3 | Clock high time | 0.6 | | | μs |
| 4 | Setup time for a repeated START condition | 0.6 | | | μs |
| 5 | Data hold time | 0 | | | μs |
| 6 | Data setup time | 100 | | | ns |
| 7 | Rise time of SDA and SCL | | | 300 | ns |
| 8 | Fall time of SDA and SCL | | | 300 | ns |
| 9 | Setup time for STOP condition | 0.6 | | | μs |
| 10 | Bus free time between a STOP and a START condition | 1.3 | | | μs |
| I²C fast mode plus timing requirements | | | | | |
| f _{SCL} | I ² C clock frequency | 0 | | 1000 | KHz |
| 1 | Hold time (repeated) START condition | 0.26 | | | μs |
| 2 | Clock low time | 0.5 | | | μs |
| 3 | Clock high time | 0.26 | | | μs |
| 4 | Setup time for a repeated START condition | 0.26 | | | μs |
| 5 | Data hold time | 0 | | | μs |
| 6 | Data setup time | 50 | | | ns |
| 7 | Rise time of SDA and SCL | | | 120 | ns |
| 8 | Fall time of SDA and SCL | | | 120 | ns |
| 9 | Setup time for STOP condition | 0.26 | | | μs |
| 10 | Bus free time between a STOP and a START condition | 0.5 | | | μs |




图 6-1. SPI Timing Parameters




图 6-2. I²C Timing Parameters

6.7 Typical Characteristics

Unless specified otherwise, typical characteristics apply over the full ambient temperature range ($-40^{\circ}\text{C} < T_A < +85^{\circ}\text{C}$), $V_{CC} = 3.3\text{V}$, $V_{IO} = 3.3$, $V_{LED} = 5\text{V}$, $I_{LED_Peak} = 50\text{mA}$, $C_{VLED} = 1\text{ }\mu\text{F}$, $C_{VCC} = 1\text{ }\mu\text{F}$




图 6-3. V_{CC} UVLO Rising and Falling Thresholds




图 6-4. V_{CC} UVLO Hysteresis




图 6-5. V_{SAT} vs Temperature




图 6-6. V_{SAT} vs Current Sinks (50mA)




图 6-7. V_{SAT} vs Current Sinks (30mA)




图 6-8. V_{SAT} vs Current Sinks (10mA)

6.7 Typical Characteristics (continued)

Unless specified otherwise, typical characteristics apply over the full ambient temperature range ($-40^{\circ}\text{C} < T_A < +85^{\circ}\text{C}$), $V_{CC} = 3.3\text{V}$, $V_{IO} = 3.3$, $V_{LED} = 5\text{V}$, $I_{LED_Peak} = 50\text{mA}$, $C_{VLED} = 1\text{ }\mu\text{F}$, $C_{VCC} = 1\text{ }\mu\text{F}$




图 6-9. Current Sinks Voltage vs Current ($V_{CC} = 3.3\text{V}$)




图 6-10. High-Side Switch $R_{DS(on)}$

7 Detailed Description


7.1 Overview

The LP5866 is an 6×18 LED matrix driver. The device integrates 6 switching FETs with 18 constant current sinks. One LP5866 device can drive up to 108 LED dots or 36 RGB pixels by using time-multiplexing matrix scheme.

The LP5866 supports both analog dimming and PWM dimming methods. For analog dimming, the current gain of each individual LED dot can be adjusted with 256 steps through 8-bits dot correction. For PWM dimming, the integrated 8-bits or 16-bits configurable, $> 20\text{kHz}$ PWM generators for each LED dot enable smooth, vivid animation effects without audible noise. Each LED can also be mapped into a 8-bits group PWM to achieve the group control with minimum data traffic.

The LP5866 device implements full addressable SRAM. The device supports entire SRAM data refresh and partial SRAM data update on demand to minimize the data traffic. The LP5866 implements the ghost cancellation circuit to eliminate both upside and downside ghosting. The LP5866 also uses low brightness compensation technology to support high density LED pixels. Both 1MHz (maximum) I²C and 12MHz (maximum) SPI interfaces are available in the LP5866.

7.2 Functional Block Diagram



7.3 Feature Description

7.3.1 Time-Multiplexing Matrix

The LP5866 device uses time-multiplexing matrix scheme to support up to 108 LED dots with one chip. The device integrates 18 current sinks with 6 scan lines to drive $18 \times 6 = 108$ LED dots or $6 \times 6 = 36$ RGB pixels. In matrix control scheme, the device scans from Line 0 to Line 5 sequentially as shown in 图 7-1. Current gain and PWM duty registers are programmable for each LED dot to support individual analog and PWM dimming.




图 7-1. Scan Line Control Scheme

There are 6 high-side p-channel MOSFETs (PMOS) integrated in LP5866 device. Users can flexibly set the active scan numbers from 1 to 6 by configuring the 'Max_Line_Num' in Dev_initial register. The time-multiplexing matrix timing sequence follows the 图 7-2.




图 7-2. Time-Multiplexing Matrix Timing Sequence

One cycle time of the line switching can be calculated as below:

$$t_{\text{line_switch}} = t_{\text{PWM}} + t_{\text{SW_BLK}} + 2 \times t_{\text{phase_shift}} \quad (1)$$

- t_{PWM} is the current sink active time, which equals to 8 us (PWM frequency set at 125 kHz) or 16 us (PWM frequency set at 62.5 kHz) by configuring 'PWM_Fre' in Dev_initial register.
- $t_{\text{SW_BLK}}$ is the switch blank time, which equals to 1 us or 0.5 us by configuring 'SW_BLK' in Dev_config1 register.
- $t_{\text{phase_shift}}$ is the PWM phase shift time, which equal to 0 or 125 ns by configuring 'PWM_Phase_Shift' in Dev_config1 register.

Total display time for one complete sub-period is $t_{\text{sub_period}}$ and it can be calculated by the following equation:

$$t_{\text{sub_period}} = t_{\text{line_switch}} \times \text{Scan_line\#} \quad (2)$$

- Scan_line# is the scan line number determined by 'Max_Line_Num' in Dev_initial register.

The time-multiplexing matrix scheme time diagram is shown in 图 7-3. The $t_{CS_ON_Shift}$ is the current sink turning on shift by configuring 'CS_ON_Shift' bit in Dev_config1 register.




图 7-3. Time-Multiplexing Matrix Timing Diagram

The LP5866 device implements deghosting and low brightness compensation to remove the side effects of matrix topology:

- **Deghosting:** Both upside deghosting and downside deghosting are implemented to eliminate the LED unexpected weak turn-on.
 - Upside_deghosting: discharge each scan line during its off state. By configuring the 'Up_Deghost' in Dev_config3 register, the LP5866 discharges and clamps the scan line switch to a certain voltage.
 - Downside_deghosting: pre-charge each current sink voltage during its OFF state. The deghosting capability can be adjusted through the 'Down_Deghost' in Dev_config3 register.
- **Low Brightness Compensation:** three groups compensation are implemented to overcome the color-shift and non-uniformity in low brightness conditions. The compensation capability can be through 'Comp_Group1', 'Comp_Group2', and 'Comp_Group3' in Dev_config2 register.
 - Compensation_group 1: CS0, CS3, CS6, CS9, CS12, CS15.
 - Compensation_group 2: CS1, CS4, CS7, CS10, CS13, CS16.
 - Compensation_group 3: CS2, CS5, CS8, CS11, CS14, CS17.

7.3.2 Analog Dimming (Current Gain Control)

Analog dimming of LP5866 is achieved by configuring the current gain control. There are several methods to control the current gain of each LED.

- Global 3-bits Maximum Current (MC) setting without external resistor
- 3 groups of 7-bits Color Current (CC) setting
- Individual 8-bit Dot Current (DC) setting

Global 3-Bits Maximum Current (MC) Setting

The MC is used to set the maximum current I_{OUT_MAX} for each current sink and this current is the maximum peak current for each LED dot. The MC can be set with 3 bits (8 steps) from 3 mA to 50 mA. When the device is powered on, the MC data is set to default value, which is 15 mA.

For data refresh **Mode 1**, MC data is effective immediately after new data is updated. For **Mode 2** and **Mode 3**, to avoid unexpected MC data change during high speed data refreshing, MC data must be changed when all channels are off and new MC data is only be updated when the 'Chip_EN' bit in Chip_en register is set to 0, and

after the 'Chip_EN' returns to 1, the new MC data is effective. 'Down_Deghost' and 'Up_Deghost' in Dev_config3 work in the similar way with MC.

表 7-1. Maximum Current (MC) Register Setting

| 3-BITS MAXIMUM_CURRENT REGISTER | | I _{OUT_MAX} |
|---------------------------------|-------------|----------------------|
| Binary | Decimal | mA |
| 000 | 0 | 3 |
| 001 | 1 | 5 |
| 010 | 2 | 10 |
| 011 (default) | 3 (default) | 15 (default) |
| 100 | 4 | 20 |
| 101 | 5 | 30 |
| 110 | 6 | 40 |
| 111 | 7 | 50 |

3 Groups of 7-Bits Color Current (CC) Setting

The LP5866 device can adjust the output current of three color groups separately. For each color, the device has 7-bits data in 'CC_Group1', 'CC_Group2', and 'CC_Group3'. Thus, all color group currents can be adjusted in 128 steps from 0% to 100% of the maximum output current, I_{OUT_MAX}.

The 18 current sinks have fixed mapping to the three color groups:

- CC-Group 1: CS0, CS3, CS6, CS9, CS12, CS15.
- CC-Group 2: CS1, CS4, CS7, CS10, CS13, CS16.
- CC-Group 3: CS2, CS5, CS8, CS11, CS14, CS17.

表 7-2. 3 Groups of 7-bits Color Current (CC) Setting

| 7-BITS CC_GROUP1/CC_GROUP2/CC_GROUP3 REGISTER | | RATIO OF OUTPUT CURRENT TO I _{OUT_MAX} |
|---|--------------|---|
| Binary | Decimal | % |
| 000 0000 | 0 | 0 |
| 000 0001 | 1 | 0.79 |
| 000 0010 | 2 | 1.57 |
| --- | --- | --- |
| 100 0000 (default) | 64 (default) | 50.4 (default) |
| --- | --- | --- |
| 111 1101 | 125 | 98.4 |
| 111 1110 | 126 | 99.2 |
| 111 1111 | 127 | 100 |

Individual 8-bit Dot Current (DC) Setting

The LP5866 can individually adjust the output current of each LED by using dot current function through DC setting. The device allows the brightness deviations of the LEDs to adjusted be individually. Each output DC is programmed with a 8-bit depth, so the value can be adjusted with 256 steps within the range from 0% to 100% of (I_{OUT_MAX} × CC/127).

表 7-3. Individual 8-bit Dot Current (DC) Setting

| 8-BIT DC REGISTER | | RATIO OF OUTPUT CURRENT TO I _{OUT_MAX} × CC/127 |
|-------------------|---------|--|
| Binary | Decimal | % |
| 0000 0000 | 0 | 0 |
| 0000 0001 | 1 | 0.39 |
| 0000 0010 | 2 | 0.78 |
| --- | --- | --- |

表 7-3. Individual 8-bit Dot Current (DC) Setting (续)

| 8-BIT DC REGISTER | | RATIO OF OUTPUT CURRENT TO $I_{OUT_MAX} \times CC/127$ |
|---------------------|---------------|---|
| Binary | Decimal | % |
| 1000 0000 (default) | 128 (default) | 50.2 (default) |
| --- | --- | --- |
| 1111 1101 | 253 | 99.2 |
| 1111 1110 | 254 | 99.6 |
| 1111 1111 | 255 | 100 |

In summary, the current gain of each current sink can be calculated as below:

$$I_{OUT} \text{ (mA)} = I_{OUT_MAX} \times (CC/127) \times (DC/255) \quad (3)$$

For time-multiplexing scan scheme, if the scan number is N, each LED dot average current I_{AVG} is shown as below:

$$I_{AVG} \text{ (mA)} = I_{OUT} / N = I_{OUT_MAX} \times (CC/127) \times (DC/255) / N \quad (4)$$

7.3.3 PWM Dimming

There are several methods to control the PWM duty cycle of each LED dot.

- **Individual 8-bit / 16-bit PWM for Each LED Dot**

Every LED has an individual 8-bit or 16-bit PWM register that is used to change the LED brightness by PWM duty. The LP5866 uses an enhanced spectrum PWM (ES-PWM) algorithm to achieve 16-bit depth with high refresh rate, which can avoid flicker under a high speed camera. Comparing with conventional 8-bit PWM, 16-bit PWM can help to achieve ultimate high dimming resolution in LED animation applications.

- **3 Programmable Groups of 8-bit PWM Dimming**

The group PWM Control is used to select LEDs into 1 to 3 groups where each group has a separate register for duty cycle control. Every LED has 2-bit selection in LED_DOT_GROUP Registers ($x = 0, 1, \dots, 29.$) to select whether it belongs to one of the three groups or not:

- 00: not a member of any group
- 01: member of group 1
- 10: member of group 2
- 11: member of group 3

- **8-bit PWM for Global Dimming**

The Global PWM Control function affects all LEDs simultaneously.

The final PWM duty cycle can be calculated as below:

$$PWM_Final(8 \text{ bit}) = PWM_Individual(8 \text{ bit}) \times PWM_Group(8 \text{ bit}) \times PWM_Global(8\text{-bit}) \quad (5)$$

$$PWM_Final(16 \text{ bit}) = PWM_Individual(16 \text{ bit}) \times PWM_Group(8 \text{ bit}) \times PWM_Global(8\text{-bit}) \quad (6)$$

The LP5866 supports 125-kHz or 62.5-kHz PWM output frequency. The PWM frequency is selected by configuring the 'PWM_Fre' in Dev_initial register. An internal 31.2-MHz oscillator is used for generating PWM outputs. The high-accuracy design of the oscillator ($f_{OSC_ERR} \leq \pm 2\%$) enables a better synchronization if multiple LP5866 devices are connected together.

A PWM phase-shifting scheme is implemented in each current sink to avoid the current overshoot when turning on simultaneously. As the LED drivers are not activated simultaneously, the peak load current from the pre-stage

power supply is significantly decreased. This scheme also reduces input-current ripple and ceramic-capacitor audible ringing. LED drivers are grouped into three different phases. By configuring the 'PWM_Phase_Shift' in Dev_config1 register, which is default off, the LP5866 supports $t_{\text{phase_shift}} = 125\text{-ns}$ shifting time shown in 图 7-4.

- Phase 1: CS0, CS3, CS6, CS9, CS12, CS15.
- Phase 2: CS1, CS4, CS7, CS10, CS13, CS16.
- Phase 3: CS2, CS5, CS8, CS11, CS14, CS17.




图 7-4. Phase Shift

To avoid high current sinks output ripple during line switching, current sinks can be configured to turn on with 1 clock delay (62.5 ns or 31.25 ns according to the PWM frequency) after lines turn on, as shown in 图 7-3. This function can be configured by 'CS_ON_Shift' in Dev_config1 register.

The LP5866 allows users to configure the dimming scale either exponentially (Gamma Correction) or linearly through the 'PWM_Scale_Mode' in Dev_config1 register. If a human-eye-friendly dimming curve is desired, using the internal fixed exponential scale is an easy approach. If a special dimming curve is desired, TI recommends using the linear scale with software correction. The LP5866 supports both linear and exponential dimming curves under 8-bit and 16-bit PWM depth. 图 7-5 is an example of 8-bit PWM depth.




图 7-5. Linear and Exponential Dimming Curves

In summary, 图 7-6 illustrates the PWM control method:




图 7-6. PWM Control Scheme

7.3.4 ON and OFF Control

The LP5866 device supports the individual ON and OFF control of each LED. For indication purpose, users can turn on and off the LED directly by writing 1-bit ON and OFF data to the corresponding Dot_onoffx (x = 0, 1, ..., 17) register.

7.3.5 Data Refresh Mode

The LP5866 supports three data refresh modes: Mode 1, Mode 2, and Mode 3, by configuring 'Data_Ref_Mode' in Dev_initial register.

Mode 1: 8-bit PWM data without VSYNC command. Data is sent out for display instantly after received. With Mode 1, users can refresh the corresponding dot data, only instead of updating the whole SRAM. It is called 'on demand data refresh', which can save the total data volume effectively. As shown in 图 7-7, the red LED dots can be refreshed after sending the corresponding data while the others kept the same with last frame.




图 7-7. On Demand Data Refresh - Mode 1

Mode 2: 8-bit PWM data with VSYNC command. Data is held and sent out simultaneously by frame after receiving the VSYNC command.

Mode 3: 16-bit PWM data with VSYNC command. Data is held and sent out simultaneously by frame after receiving the VSYNC command.

Frame control is implemented in Mode 2 and Mode 3. Instead of refreshing the output instantly after data is received (Mode 1), the device holds the data and refreshes the whole frame data by a fixed frame rate, f_{VSYNC} . Usually, 24Hz, 50Hz, 60Hz, 120Hz or even higher frame rate is selected to achieve vivid animation effects. Whole SRAM Data Refresh is shown in 图 7-8, a new frame is updated after receiving the VSYNC command.




图 7-8. Whole SRAM Data Refresh

Comparing with Mode 1, Mode 2 and Mode 3 provide a better synchronization when multiple LP5866 devices used together. A high-level pulse width longer than $t_{\text{SYNC_H}}$ is required at the beginning of each VSYNC frame. 图 7-9 shows the VSYNC connections and 图 7-10 shows the timing requirements.




图 7-9. Multiple Devices Sync




图 7-10. VSYNC Timing

Table 8-4 is the summary of the three data refresh modes.

表 7-4. Data Refresh Mode

| MODE TYPE | PWM RESOLUTION | PWM OUTPUT | EXTERNAL VSYNC |
|-----------|----------------|-----------------------|----------------|
| Mode 1 | 8 Bits | Data update instantly | No |
| Mode 2 | 8 Bits | Data update by frame | Yes |
| Mode 3 | 16 Bits | | |

7.3.6 Full Addressable SRAM

SRAM is implemented inside the LP5866 device to support data writing and reading at the same time.

Although data refresh mechanisms are not the same for Mode 1 and Mode 2, and Mode 3, the data writing and reading follow the same method. Users can update partial of the SRAM data only or the whole SRAM page simultaneously. The LP5866 supports auto-increment function to minimize data traffic and increase data transfer efficiency.

Please note that 16-bit PWM (Mode 3) and 8-bit PWM (Mode 1 and Mode 2) are assigned with different SRAM addresses.

7.3.7 Protections and Diagnostics

LED Open Detection

The LP5866 includes LED open detection (LOD) for the fault caused by any opened LED dot. The threshold for LED open is 0.25V typical. LED open detection is only performed when $\text{PWM} \geq 25$ (Mode 1 and Mode 2) or $\text{PWM} \geq 6400$ (Mode 3) and voltage on CSn is detected lower than open threshold for continuously 4 sub-periods.

图 7-11 shows the detection circuit of LOD function. When open fault is detected, 'Global_LOD' bit in Fault_state register is set to 1 and detailed fault state for each LED is also monitored in register Dot_lodx ($x = 0, 1, \dots, 17$). All open fault indicator bits can be cleared by setting LOD_clear = 0Fh after the open condition is removed.

LOD removal function can be enabled by setting 'LOD_removal' bit in Dev_config2 register to 1. This function turns off the current sink of the open channel when scanning to the line where the opened LED is included.




图 7-11. LOD Circuits

LED Short Detection

The LP5866 includes LED short detection (LSD) for the fault caused by any shorted LED. Threshold for channel short is $(V_{LED} - 1)$ V typical. LED short detection only performed when $PWM \geq 25$ (Mode 1 and Mode 2) or $PWM \geq 6400$ (Mode 3) and voltage on CSn is detected higher than short threshold for continuously 4 sub-periods. As there is parasitic capacitance for the current sink, to make sure the LSD result is correct, TI recommends to set the LED current higher than 0.5mA.

图 7-12 shows the detection circuit of LSD function. When short fault is detected, 'Global_LSD bit' in Fault_state register is set to 1 and detailed fault state for every channel can also be monitored in register Dot_Isdx ($x = 0, 1, \dots, 17$). All short fault indicator bits can be cleared by setting LSD_clear = 0Fh after the short condition is removed.

LSD removal function can be enabled by setting 'LSD_removal' bit in Dev_config2 register to 1. This function turns off the upside deghosting function of the scan line where short LED is included.




图 7-12. LSD Circuit

Thermal Shutdown

The LP5866 device implements thermal shutdown mechanism to protect the device from damage due to overheating. When the junction temperature rises to 160°C (typical) and above, the device switches into shutdown mode. The LP5866 exits thermal shutdown when the junction temperature of the device drops to 145°C (typical) and below.

UVLO (Undervoltage Lockout)

The LP5866 has an internal comparator that monitors the voltage at VCC. When VCC is below V_{UVF} , reset is active and the LP5866 enters INITIALIZATION state.

7.4 Device Functional Modes




图 7-13. Device Functional Modes

- Shutdown: The device enters into shutdown mode from all states on VCC power up or EN pin is low.
- Hardware POR: The device enters into hardware POR when Enable pin is high or VCC fall under V_{UVF} causing $UVLO = H$ from all states.
- Software reset: The device enters into software reset mode when VCC rise higher than V_{UVR} with the time $t > t_{POR_H}$. In this mode, all the registers are reset. Entry can also be from any state when the RESET (register) = FFh or UVLO is low.
- Standby: The device enters the standby mode when Chip_EN (register) = 0. In this mode, the device enters into low power mode, but the I²C/SPI are still available for Chip_EN only and the register data is retained.
- Normal: The device enters the normal mode when 'Chip_EN' = 1 with the time $t > t_{CHIP_EN}$.
- Thermal shutdown: The device automatically enters the thermal shutdown mode when the junction temperature exceeds 160°C (typical). If the junction temperature decreases below 145°C (typical), the device returns to the normal mode.

7.5 Programming

Interface Selection

The LP5866 supports two communication interfaces: I²C and SPI. If IFS is high, it enters into SPI mode. If IFS is low, it enters into I²C mode.

表 7-5. Interface Selection

| INTERFACE TYPE | ENTRY CONDITION |
|------------------|-----------------|
| I ² C | IFS = Low |
| SPI | IFS = High |

I²C Interface

The LP5866 is compatible with I²C standard specification. the device supports both fast mode (400kHz maximum) and fast plus mode (1MHz maximum).

I²C Data Transactions

The data on SDA line must be stable during the HIGH period of the clock signal (SCL). In other words, state of the data line can only be changed when clock signal is LOW. START and STOP conditions classify the beginning and the end of the data transfer session. A START condition is defined as the SDA signal transitioning from HIGH to LOW while SCL line is HIGH. A STOP condition is defined as the SDA transitioning from LOW to HIGH while SCL is HIGH. The bus leader always generates START and STOP conditions. The bus is considered to be busy after a START condition and free after a STOP condition. During data transmission, the bus leader can generate repeated START conditions. First START and repeated START conditions are functionally equivalent.

Each byte of data has to be followed by an acknowledge bit. The acknowledge related clock pulse is generated by the leader. The leader releases the SDA line (HIGH) during the acknowledge clock pulse. The device pulls down the SDA line during the 9th clock pulse, signifying an acknowledge. The device generates an acknowledge after each byte has been received.

There is one exception to the acknowledge after every byte rule. When the leader is the receiver, it must indicate to the transmitter an end of data by not acknowledging (*negative acknowledge*) the last byte clocked out of the follower. This negative acknowledge still includes the acknowledge clock pulse (generated by the leader), but the SDA line is not pulled down.

I²C Data Format

The address and data bits are transmitted MSB first with 8-bits length format in each cycle. Each transmission is started with Address Byte 1, which are divided into 5-bits of the chip address, 2 higher bits of the register address, and 1 read and write bit. The other 8 lower bits of register address are put in Address Byte 2. The device supports both independent mode and broadcast mode. The auto-increment feature allows writing and reading several consecutive registers within one transmission. If not consecutive, a new transmission must be started.

表 7-6. I²C Data Format

| Address Byte 1 | Chip Address | | | | | Register Address | | R/W |
|----------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| | Bit 7 | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0 |
| Independent | 1 | 0 | 0 | ADDR1 | ADDR0 | 9 th bit | 8 th bit | R: 1 W: 0 |
| Broadcast | 1 | 0 | 1 | 0 | 1 | | | |
| Address Byte 2 | Register Address | | | | | | | |
| | Bit 7 | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0 |
| | 7 th bit | 6 th bit | 5 th bit | 4 th bit | 3 th bit | 2 th bit | 1 th bit | 0 th bit |




图 7-14. I²C Write Timing




图 7-15. I²C Read Timing

Multiple Devices Connection

The LP5866 enters into I²C mode if IFS is connected to GND. The ADDR0/1 pin is used to select the unique I²C follower address for each device. The SCL and SDA lines must each have a pullup resistor (4.7K Ω for 400kHz, 2K Ω for 1MHz) placed somewhere on the line and remain HIGH even when the bus is idle. VIO_EN can either be connected with VIO power supply or GPIO. TI suggests to put one 1nF cap as closer to VIO_EN pin as possible. Up to four LP5866 follower devices can share the same I²C bus by the different ADDR configurations.




图 7-16. I²C Multiple Devices Connection

SPI Interface

The LP5866 is compatible with SPI serial-bus specification, and it operates as a follower. The maximum frequency supported by LP5866 is 12MHz.

SPI Data Transactions

MISO output is normally in a high impedance state. When the follower-select pin SS for the device is active (low) the MISO output is pulled low for read only. During write cycle MISO stays in high-impedance state. The follower-select signal SS must be low during the cycle transmission. SS resets the interface when high. Data is clocked in on the rising edge of the SCLK clock signal, while data is clocked out on the falling edge of SCLK.

SPI Data Format

The address and data bits are transmitted MSB first with 8-bits length format in each cycle. Each transmission is started with Address Byte 1, which contains 8 higher bits of the register address. The Address Byte 2 is started with 2 lower bits of the register address and 1 read and write bit. The auto-increment feature allows writing and reading several consecutive registers within one transmission. If not consecutive, a new transmission must be started.

表 7-7. SPI Data Format

| Address Byte 1 | Register Address | | | | | | | |
|----------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| | Bit 7 | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0 |
| | 9 th bit | 8 th bit | 7 th bit | 6 th bit | 5 th bit | 4 th bit | 3 th bit | 2 th bit |
| Address Byte 2 | Register Address | | | | | | | |
| | Bit 7 | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0 |
| | 1 th bit | 0 th bit | R: 0 W: 1 | Don't Care | | | | |




图 7-17. SPI Write Timing




图 7-18. SPI Read Timing

Multiple Devices Connection

The device enters into SPI mode if IFS is pulled high to VIO through a pullup resistor (4.7KΩ recommended). VIO_EN can either be connected with VIO power supply or GPIO. TI suggests to put one 1nF cap as closer to VIO_EN pin as possible. In SPI mode host can address as many devices as there are follower select pins on host.




图 7-19. SPI Multiple Devices Connection

7.6 Register Maps

This section provides a summary of the register maps. For detailed register functions and descriptions, please refer to [LP5866 11x18 LED Matrix Driver Register Maps](#).

表 7-8. Register Section, Block Access Type Codes

| Access Type | Code | Description |
|-------------------------------|--------------|---|
| Read Type | | |
| R | R | Read |
| RC | R C | Read to Clear |
| R-0 | R -0 | Read Returns 0s |
| Write Type | | |
| W | W | Write |
| W0CP | W 0C P | W 0 to clear Requires privileged access |
| Reset or Default Value | | |
| -n | | Value after reset or the default value |

| Register Acronym | Address | Type | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Default |
|------------------|---------|------|-------------|--------------|-------------|----------|-------------|--------------------|---------------------|-----------------|---------|
| Chip_en | 000h | R/W | Reserved | | | | | | | Chip_EN | 00h |
| Dev_initial | 001h | R/W | Reserved | Max_Line_Num | | | | Data_Ref_Mode | | PWM_Fre | 5Eh |
| Dev_config1 | 002h | R/W | Reserved | Reserved | Reserved | Reserved | SW_BLK | PWM_Sc ale_Mode | PWM_Ph ase_Shift | CS_ON_ Shift | 00h |
| Dev_config2 | 003h | R/W | Comp_Group3 | | Comp_Group2 | | Comp_Group1 | | LOD_rem oval | LSD_rem oval | 00h |

| | | | | | | | | | | | | |
|---------------|------|-----|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|------------------|-------------------|-----|
| Dev_config3 | 004h | R/W | Down_Deghost | | Up_Deghost | | Maximum_Current | | | | Up_Deghost_enable | 47h |
| Global_bri | 005h | R/W | PWM_Global | | | | | | | | | FFh |
| Group0_bri | 006h | R/W | PWM_Group1 | | | | | | | | | FFh |
| Group1_bri | 007h | R/W | PWM_Group2 | | | | | | | | | FFh |
| Group2_bri | 008h | R/W | PWM_Group3 | | | | | | | | | FFh |
| R_current_set | 009h | R/W | Reserved | CC_Group1 | | | | | | | | 40h |
| G_current_set | 00Ah | R/W | Reserved | CC_Group2 | | | | | | | | 40h |
| B_current_set | 00Bh | R/W | Reserved | CC_Group3 | | | | | | | | 40h |
| Dot_grp_sel0 | 00Ch | R/W | Dot L0-CS3 group | | Dot L0-CS2 group | | Dot L0-CS1 group | | Dot L0-CS0 group | | 00h | |
| Dot_grp_sel1 | 00Dh | R/W | Dot L0-CS7 group | | Dot L0-CS6 group | | Dot L0-CS5 group | | Dot L0-CS4 group | | 00h | |
| Dot_grp_sel2 | 00Eh | R/W | Dot L0-CS11 group | | Dot L0-CS10 group | | Dot L0-CS9 group | | Dot L0-CS8 group | | 00h | |
| Dot_grp_sel3 | 00Fh | R/W | Dot L0-CS15 group | | Dot L0-CS14 group | | Dot L0-CS13 group | | Dot L0-CS12 group | | 00h | |
| Dot_grp_sel4 | 010h | R/W | Reserved | | | | Dot L0-CS17 group | | Dot L0-CS16 group | | 00h | |
| Dot_grp_sel5 | 011h | R/W | Dot L1-CS3 group | | Dot L1-CS2 group | | Dot L1-CS1 group | | Dot L1-CS0 group | | 00h | |
| Dot_grp_sel6 | 012h | R/W | Dot L1-CS7 group | | Dot L1-CS6 group | | Dot L1-CS5 group | | Dot L1-CS4 group | | 00h | |
| Dot_grp_sel7 | 013h | R/W | Dot L1-CS11 group | | Dot L1-CS10 group | | Dot L1-CS9 group | | Dot L1-CS8 group | | 00h | |
| Dot_grp_sel8 | 014h | R/W | Dot L1-CS15 group | | Dot L1-CS14 group | | Dot L1-CS13 group | | Dot L1-CS12 group | | 00h | |
| Dot_grp_sel9 | 015h | R/W | Reserved | | | | Dot L1-CS17 group | | Dot L1-CS16 group | | 00h | |
| Dot_grp_sel10 | 016h | R/W | Dot L2-CS3 group | | Dot L2-CS2 group | | Dot L2-CS1 group | | Dot L2-CS0 group | | 00h | |
| Dot_grp_sel11 | 017h | R/W | Dot L2-CS7 group | | Dot L2-CS6 group | | Dot L2-CS5 group | | Dot L2-CS4 group | | 00h | |
| Dot_grp_sel12 | 018h | R/W | Dot L2-CS11 group | | Dot L2-CS10 group | | Dot L2-CS9 group | | Dot L2-CS8 group | | 00h | |
| Dot_grp_sel13 | 019h | R/W | Dot L2-CS15 group | | Dot L2-CS14 group | | Dot L2-CS13 group | | Dot L2-CS12 group | | 00h | |
| Dot_grp_sel14 | 01Ah | R/W | Reserved | | | | Dot L2-CS17 group | | Dot L2-CS16 group | | 00h | |
| Dot_grp_sel15 | 01Bh | R/W | Dot L3-CS3 group | | Dot L3-CS2 group | | Dot L3-CS1 group | | Dot L3-CS0 group | | 00h | |
| Dot_grp_sel16 | 01Ch | R/W | Dot L3-CS7 group | | Dot L3-CS6 group | | Dot L3-CS5 group | | Dot L3-CS4 group | | 00h | |
| Dot_grp_sel17 | 01Dh | R/W | Dot L3-CS11 group | | Dot L3-CS10 group | | Dot L3-CS9 group | | Dot L3-CS8 group | | 00h | |
| Dot_grp_sel18 | 01Eh | R/W | Dot L3-CS15 group | | Dot L3-CS14 group | | Dot L3-CS13 group | | Dot L3-CS12 group | | 00h | |
| Dot_grp_sel19 | 01Fh | R/W | Reserved | | | | Dot L3-CS17 group | | Dot L3-CS16 group | | 00h | |
| Dot_grp_sel20 | 020h | R/W | Dot L4-CS3 group | | Dot L4-CS2 group | | Dot L4-CS1 group | | Dot L4-CS0 group | | 00h | |
| Dot_grp_sel21 | 021h | R/W | Dot L4-CS7 group | | Dot L4-CS6 group | | Dot L4-CS5 group | | Dot L4-CS4 group | | 00h | |
| Dot_grp_sel22 | 022h | R/W | Dot L4-CS11 group | | Dot L4-CS10 group | | Dot L4-CS9 group | | Dot L4-CS8 group | | 00h | |
| Dot_grp_sel23 | 023h | R/W | Dot L4-CS15 group | | Dot L4-CS14 group | | Dot L4-CS13 group | | Dot L4-CS12 group | | 00h | |
| Dot_grp_sel24 | 024h | R/W | Reserved | | | | Dot L4-CS17 group | | Dot L4-CS16 group | | 00h | |
| Dot_grp_sel25 | 025h | R/W | Dot L5-CS3 group | | Dot L5-CS2 group | | Dot L5-CS1 group | | Dot L5-CS0 group | | 00h | |
| Dot_grp_sel26 | 026h | R/W | Dot L5-CS7 group | | Dot L5-CS6 group | | Dot L5-CS5 group | | Dot L5-CS4 group | | 00h | |
| Dot_grp_sel27 | 027h | R/W | Dot L5-CS11 group | | Dot L5-CS10 group | | Dot L5-CS9 group | | Dot L5-CS8 group | | 00h | |
| Dot_grp_sel28 | 028h | R/W | Dot L5-CS15 group | | Dot L5-CS14 group | | Dot L5-CS13 group | | Dot L5-CS12 group | | 00h | |
| Dot_grp_sel29 | 029h | R/W | Reserved | | | | Dot L5-CS17 group | | Dot L5-CS16 group | | 00h | |
| Dot_onoff0 | 043h | R/W | Dot L0-CS7 onoff | Dot L0-CS6 onoff | Dot L0-CS5 onoff | Dot L0-CS4 onoff | Dot L0-CS3 onoff | Dot L0-CS2 onoff | Dot L0-CS1 onoff | Dot L0-CS0 onoff | FFh | |
| Dot_onoff1 | 044h | R/W | Dot L0-CS15 onoff | Dot L0-CS14 onoff | Dot L0-CS13 onoff | Dot L0-CS12 onoff | Dot L0-CS11 onoff | Dot L0-CS10 onoff | Dot L0-CS9 onoff | Dot L0-CS8 onoff | FFh | |
| Dot_onoff2 | 045h | R/W | Reserved | | | | | | Dot L0-CS17 onoff | | Dot L0-CS16 onoff | 03h |

| | | | | | | | | | | | |
|--------------------|------|-----|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|-----|
| Dot_onoff3 | 046h | R/W | Dot L1- CS7 onoff | Dot L1- CS6 onoff | Dot L1- CS5 onoff | Dot L1- CS4 onoff | Dot L1- CS3 onoff | Dot L1- CS2 onoff | Dot L1- CS1 onoff | Dot L1- CS0 onoff | FFh |
| Dot_onoff4 | 047h | R/W | Dot L1- CS15 onoff | Dot L1- CS14 onoff | Dot L1- CS13 onoff | Dot L1- CS12 onoff | Dot L1- CS11 onoff | Dot L1- CS10 onoff | Dot L1- CS9 onoff | Dot L1- CS8 onoff | FFh |
| Dot_onoff5 | 048h | R/W | Reserved | | | | | | Dot L1- CS17 onoff | Dot L1- CS16 onoff | 03h |
| Dot_onoff6 | 049h | R/W | Dot L2- CS7 onoff | Dot L2- CS6 onoff | Dot L2- CS5 onoff | Dot L2- CS4 onoff | Dot L2- CS3 onoff | Dot L2- CS2 onoff | Dot L2- CS1 onoff | Dot L2- CS0 onoff | FFh |
| Dot_onoff7 | 04Ah | R/W | Dot L2- CS15 onoff | Dot L2- CS14 onoff | Dot L2- CS13 onoff | Dot L2- CS12 onoff | Dot L2- CS11 onoff | Dot L2- CS10 onoff | Dot L2- CS9 onoff | Dot L2- CS8 onoff | FFh |
| Dot_onoff8 | 04Bh | R/W | Reserved | | | | | | Dot L2- CS17 onoff | Dot L2- CS16 onoff | 03h |
| Dot_onoff9 | 04Ch | R/W | Dot L3- CS7 onoff | Dot L3- CS6 onoff | Dot L3- CS5 onoff | Dot L3- CS4 onoff | Dot L3- CS3 onoff | Dot L3- CS2 onoff | Dot L3- CS1 onoff | Dot L3- CS0 onoff | FFh |
| Dot_onoff10 | 04Dh | R/W | Dot L3- CS15 onoff | Dot L3- CS14 onoff | Dot L3- CS13 onoff | Dot L3- CS12 onoff | Dot L3- CS11 onoff | Dot L3- CS10 onoff | Dot L3- CS9 onoff | Dot L3- CS8 onoff | FFh |
| Dot_onoff11 | 04Eh | R/W | Reserved | | | | | | Dot L3- CS17 onoff | Dot L3- CS16 onoff | 03h |
| Dot_onoff12 | 04Fh | R/W | Dot L4- CS7 onoff | Dot L4- CS6 onoff | Dot L4- CS5 onoff | Dot L4- CS4 onoff | Dot L4- CS3 onoff | Dot L4- CS2 onoff | Dot L4- CS1 onoff | Dot L4- CS0 onoff | FFh |
| Dot_onoff13 | 050h | R/W | Dot L4- CS15 onoff | Dot L4- CS14 onoff | Dot L4- CS13 onoff | Dot L4- CS12 onoff | Dot L4- CS11 onoff | Dot L4- CS10 onoff | Dot L4- CS9 onoff | Dot L4- CS8 onoff | FFh |
| Dot_onoff14 | 051h | R/W | Reserved | | | | | | Dot L4- CS17 onoff | Dot L4- CS16 onoff | 03h |
| Dot_onoff15 | 052h | R/W | Dot L5- CS7 onoff | Dot L5- CS6 onoff | Dot L5- CS5 onoff | Dot L5- CS4 onoff | Dot L5- CS3 onoff | Dot L5- CS2 onoff | Dot L5- CS1 onoff | Dot L5- CS0 onoff | FFh |
| Dot_onoff16 | 053h | R/W | Dot L5- CS15 onoff | Dot L5- CS14 onoff | Dot L5- CS13 onoff | Dot L5- CS12 onoff | Dot L5- CS11 onoff | Dot L5- CS10 onoff | Dot L5- CS9 onoff | Dot L5- CS8 onoff | FFh |
| Dot_onoff17 | 054h | R/W | Reserved | | | | | | Dot L5- CS17 onoff | Dot L5- CS16 onoff | 03h |
| Fault_state | 064h | R | Reserved | | | | | | Global_L OD | Global_L SD | 00h |
| Dot_lod0 | 065h | R | Dot L0- CS7 LOD | Dot L0- CS6 LOD | Dot L0- CS5 LOD | Dot L0- CS4 LOD | Dot L0- CS3 LOD | Dot L0- CS2 LOD | Dot L0- CS1 LOD | Dot L0- CS0 LOD | 00h |
| Dot_lod1 | 066h | R | Dot L0- CS15 LOD | Dot L0- CS14 LOD | Dot L0- CS13 LOD | Dot L0- CS12 LOD | Dot L0- CS11 LOD | Dot L0- CS10 LOD | Dot L0- CS9 LOD | Dot L0- CS8 LOD | 00h |
| Dot_lod2 | 067h | R | Reserved | | | | | | Dot L0- CS17 LOD | Dot L0- CS16 LOD | 00h |
| Dot_lod3 | 068h | R | Dot L1- CS7 LOD | Dot L1- CS6 LOD | Dot L1- CS5 LOD | Dot L1- CS4 LOD | Dot L1- CS3 LOD | Dot L1- CS2 LOD | Dot L1- CS1 LOD | Dot L1- CS0 LOD | 00h |
| Dot_lod4 | 069h | R | Dot L1- CS15 LOD | Dot L1- CS14 LOD | Dot L1- CS13 LOD | Dot L1- CS12 LOD | Dot L1- CS11 LOD | Dot L1- CS10 LOD | Dot L1- CS9 LOD | Dot L1- CS8 LOD | 00h |
| Dot_lod5 | 06Ah | R | Reserved | | | | | | Dot L1- CS17 LOD | Dot L1- CS16 LOD | 00h |

| | | | | | | | | | | | |
|------------------|------|---|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|-----|
| Dot_lod6 | 06Bh | R | Dot L2- CS7 LOD | Dot L2- CS6 LOD | Dot L2- CS5 LOD | Dot L2- CS4 LOD | Dot L2- CS3 LOD | Dot L2- CS2 LOD | Dot L2- CS1 LOD | Dot L2- CS0 LOD | 00h |
| Dot_lod7 | 06Ch | R | Dot L2- CS15 LOD | Dot L2- CS14 LOD | Dot L2- CS13 LOD | Dot L2- CS12 LOD | Dot L2- CS11 LOD | Dot L2- CS10 LOD | Dot L2- CS9 LOD | Dot L2- CS8 LOD | 00h |
| Dot_lod8 | 06Dh | R | Reserved | | | | | | Dot L2- CS17 LOD | Dot L2- CS16 LOD | 00h |
| Dot_lod9 | 06Eh | R | Dot L3- CS7 LOD | Dot L3- CS6 LOD | Dot L3- CS5 LOD | Dot L3- CS4 LOD | Dot L3- CS3 LOD | Dot L3- CS2 LOD | Dot L3- CS1 LOD | Dot L3- CS0 LOD | 00h |
| Dot_lod10 | 06Fh | R | Dot L3- CS15 LOD | Dot L3- CS14 LOD | Dot L3- CS13 LOD | Dot L3- CS12 LOD | Dot L3- CS11 LOD | Dot L3- CS10 LOD | Dot L3- CS9 LOD | Dot L3- CS8 LOD | 00h |
| Dot_lod11 | 070h | R | Reserved | | | | | | Dot L3- CS17 LOD | Dot L3- CS16 LOD | 00h |
| Dot_lod12 | 071h | R | Dot L4- CS7 LOD | Dot L4- CS6 LOD | Dot L4- CS5 LOD | Dot L4- CS4 LOD | Dot L4- CS3 LOD | Dot L4- CS2 LOD | Dot L4- CS1 LOD | Dot L4- CS0 LOD | 00h |
| Dot_lod13 | 072h | R | Dot L4- CS15 LOD | Dot L4- CS14 LOD | Dot L4- CS13 LOD | Dot L4- CS12 LOD | Dot L4- CS11 LOD | Dot L4- CS10 LOD | Dot L4- CS9 LOD | Dot L4- CS8 LOD | 00h |
| Dot_lod14 | 073h | R | Reserved | | | | | | Dot L4- CS17 LOD | Dot L4- CS16 LOD | 00h |
| Dot_lod15 | 074h | R | Dot L5- CS7 LOD | Dot L5- CS6 LOD | Dot L5- CS5 LOD | Dot L5- CS4 LOD | Dot L5- CS3 LOD | Dot L5- CS2 LOD | Dot L5- CS1 LOD | Dot L5- CS0 LOD | 00h |
| Dot_lod16 | 075h | R | Dot L5- CS15 LOD | Dot L5- CS14 LOD | Dot L5- CS13 LOD | Dot L5- CS12 LOD | Dot L5- CS11 LOD | Dot L5- CS10 LOD | Dot L5- CS9 LOD | Dot L5- CS8 LOD | 00h |
| Dot_lsd0 | 086h | R | Dot L0- CS7 LSD | Dot L0- CS6 LSD | Dot L0- CS5 LSD | Dot L0- CS4 LSD | Dot L0- CS3 LSD | Dot L0- CS2 LSD | Dot L0- CS1 LSD | Dot L0- CS0 LSD | 00h |
| Dot_lsd1 | 087h | R | Dot L0- CS15 LSD | Dot L0- CS14 LSD | Dot L0- CS13 LSD | Dot L0- CS12 LSD | Dot L0- CS11 LSD | Dot L0- CS10 LSD | Dot L0- CS9 LSD | Dot L0- CS8 LSD | 00h |
| Dot_lsd2 | 088h | R | Reserved | | | | | | Dot L0- CS17 LSD | Dot L0- CS16 LSD | 00h |
| Dot_lsd3 | 089h | R | Dot L1- CS7 LSD | Dot L1- CS6 LSD | Dot L1- CS5 LSD | Dot L1- CS4 LSD | Dot L1- CS3 LSD | Dot L1- CS2 LSD | Dot L1- CS1 LSD | Dot L1- CS0 LSD | 00h |
| Dot_lsd4 | 08Ah | R | Dot L1- CS15 LSD | Dot L1- CS14 LSD | Dot L1- CS13 LSD | Dot L1- CS12 LSD | Dot L1- CS11 LSD | Dot L1- CS10 LSD | Dot L1- CS9 LSD | Dot L1- CS8 LSD | 00h |
| Dot_lsd5 | 08Bh | R | Reserved | | | | | | Dot L1- CS17 LSD | Dot L1- CS16 LSD | 00h |
| Dot_lsd6 | 08Ch | R | Dot L2- CS7 LSD | Dot L2- CS6 LSD | Dot L2- CS5 LSD | Dot L2- CS4 LSD | Dot L2- CS3 LSD | Dot L2- CS2 LSD | Dot L2- CS1 LSD | Dot L2- CS0 LSD | 00h |
| Dot_lsd7 | 08Dh | R | Dot L2- CS15 LSD | Dot L2- CS14 LSD | Dot L2- CS13 LSD | Dot L2- CS12 LSD | Dot L2- CS11 LSD | Dot L2- CS10 LSD | Dot L2- CS9 LSD | Dot L2- CS8 LSD | 00h |
| Dot_lsd8 | 08Eh | R | Reserved | | | | | | Dot L2- CS17 LSD | Dot L2- CS16 LSD | 00h |
| Dot_lsd9 | 08Fh | R | Dot L3- CS7 LSD | Dot L3- CS6 LSD | Dot L3- CS5 LSD | Dot L3- CS4 LSD | Dot L3- CS3 LSD | Dot L3- CS2 LSD | Dot L3- CS1 LSD | Dot L3- CS0 LSD | 00h |
| Dot_lsd10 | 090h | R | Dot L3- CS15 LSD | Dot L3- CS14 LSD | Dot L3- CS13 LSD | Dot L3- CS12 LSD | Dot L3- CS11 LSD | Dot L3- CS10 LSD | Dot L3- CS9 LSD | Dot L3- CS8 LSD | 00h |

| | | | | | | | | | | | | |
|-----------|------|-----|---|------------------------|------------------------|------------------------|------------------------|------------------------|--------------------|------------------------|------------------------|-----|
| Dot_Isd11 | 091h | R | Reserved | | | | | | | Dot L3- CS17 LSD | Dot L3- CS16 LSD | 00h |
| Dot_Isd12 | 092h | R | Dot L4- CS7 LSD | Dot L4- CS6 LSD | Dot L4- CS5 LSD | Dot L4- CS4 LSD | Dot L4- CS3 LSD | Dot L4- CS2 LSD | Dot L4- CS1 LSD | Dot L4- CS0 LSD | 00h | |
| Dot_Isd13 | 093h | R | Dot L4- CS15 LSD | Dot L4- CS14 LSD | Dot L4- CS13 LSD | Dot L4- CS12 LSD | Dot L4- CS11 LSD | Dot L4- CS10 LSD | Dot L4- CS9 LSD | Dot L4- CS8 LSD | 00h | |
| Dot_Isd14 | 094h | R | Reserved | | | | | | | Dot L4- CS17 LSD | Dot L4- CS16 LSD | 00h |
| Dot_Isd15 | 095h | R | Dot L5- CS7 LSD | Dot L5- CS6 LSD | Dot L5- CS5 LSD | Dot L5- CS4 LSD | Dot L5- CS3 LSD | Dot L5- CS2 LSD | Dot L5- CS1 LSD | Dot L5- CS0 LSD | 00h | |
| Dot_Isd16 | 096h | R | Dot L5- CS15 LSD | Dot L5- CS14 LSD | Dot L5- CS13 LSD | Dot L5- CS12 LSD | Dot L5- CS11 LSD | Dot L5- CS10 LSD | Dot L5- CS9 LSD | Dot L5- CS8 LSD | 00h | |
| Dot_Isd17 | 097h | R | Reserved | | | | | | | Dot L5- CS17 LSD | Dot L5- CS16 LSD | 00h |
| LOD_clear | 0A7h | W | Reserved | | | | | LOD_Clear | | | | 00h |
| LSD_clear | 0A8h | W | Reserved | | | | | LSD_Clear | | | | 00h |
| Reset | 0A9h | W | Reset | | | | | | | | | 00h |
| DC0 | 100h | R/W | LED dot current setting for Dot L0-CS0 | | | | | | | | | 80h |
| DC1 | 101h | R/W | LED dot current setting for Dot L0-CS1 | | | | | | | | | 80h |
| DC2 | 102h | R/W | LED dot current setting for Dot L0-CS2 | | | | | | | | | 80h |
| DC3 | 103h | R/W | LED dot current setting for Dot L0-CS3 | | | | | | | | | 80h |
| DC4 | 104h | R/W | LED dot current setting for Dot L0-CS4 | | | | | | | | | 80h |
| DC5 | 105h | R/W | LED dot current setting for Dot L0-CS5 | | | | | | | | | 80h |
| DC6 | 106h | R/W | LED dot current setting for Dot L0-CS6 | | | | | | | | | 80h |
| DC7 | 107h | R/W | LED dot current setting for Dot L0-CS7 | | | | | | | | | 80h |
| DC8 | 108h | R/W | LED dot current setting for Dot L0-CS8 | | | | | | | | | 80h |
| DC9 | 109h | R/W | LED dot current setting for Dot L0-CS9 | | | | | | | | | 80h |
| DC10 | 10Ah | R/W | LED dot current setting for Dot L0-CS10 | | | | | | | | | 80h |
| DC11 | 10Bh | R/W | LED dot current setting for Dot L0-CS11 | | | | | | | | | 80h |
| DC12 | 10Ch | R/W | LED dot current setting for Dot L0-CS12 | | | | | | | | | 80h |
| DC13 | 10Dh | R/W | LED dot current setting for Dot L0-CS13 | | | | | | | | | 80h |
| DC14 | 10Eh | R/W | LED dot current setting for Dot L0-CS14 | | | | | | | | | 80h |
| DC15 | 10Fh | R/W | LED dot current setting for Dot L0-CS15 | | | | | | | | | 80h |
| DC16 | 110h | R/W | LED dot current setting for Dot L0-CS16 | | | | | | | | | 80h |
| DC17 | 111h | R/W | LED dot current setting for Dot L0-CS17 | | | | | | | | | 80h |
| DC18 | 112h | R/W | LED dot current setting for Dot L1-CS0 | | | | | | | | | 80h |
| DC19 | 113h | R/W | LED dot current setting for Dot L1-CS1 | | | | | | | | | 80h |
| DC20 | 114h | R/W | LED dot current setting for Dot L1-CS2 | | | | | | | | | 80h |
| DC21 | 115h | R/W | LED dot current setting for Dot L1-CS3 | | | | | | | | | 80h |
| DC22 | 116h | R/W | LED dot current setting for Dot L1-CS4 | | | | | | | | | 80h |
| DC23 | 117h | R/W | LED dot current setting for Dot L1-CS5 | | | | | | | | | 80h |
| DC24 | 118h | R/W | LED dot current setting for Dot L1-CS6 | | | | | | | | | 80h |
| DC25 | 119h | R/W | LED dot current setting for Dot L1-CS7 | | | | | | | | | 80h |
| DC26 | 11Ah | R/W | LED dot current setting for Dot L1-CS8 | | | | | | | | | 80h |
| DC27 | 11Bh | R/W | LED dot current setting for Dot L1-CS9 | | | | | | | | | 80h |

LP5866

ZHC50A5A - DECEMBER 2021 - REVISED SEPTEMBER 2024

| | | | | |
|------|------|-----|---|-----|
| DC28 | 11Ch | R/W | LED dot current setting for Dot L1-CS10 | 80h |
| DC29 | 11Dh | R/W | LED dot current setting for Dot L1-CS11 | 80h |
| DC30 | 11Eh | R/W | LED dot current setting for Dot L1-CS12 | 80h |
| DC31 | 11Fh | R/W | LED dot current setting for Dot L1-CS13 | 80h |
| DC32 | 120h | R/W | LED dot current setting for Dot L1-CS14 | 80h |
| DC33 | 121h | R/W | LED dot current setting for Dot L1-CS15 | 80h |
| DC34 | 122h | R/W | LED dot current setting for Dot L1-CS16 | 80h |
| DC35 | 123h | R/W | LED dot current setting for Dot L1-CS17 | 80h |
| DC36 | 124h | R/W | LED dot current setting for Dot L2-CS0 | 80h |
| DC37 | 125h | R/W | LED dot current setting for Dot L2-CS1 | 80h |
| DC38 | 126h | R/W | LED dot current setting for Dot L2-CS2 | 80h |
| DC39 | 127h | R/W | LED dot current setting for Dot L2-CS3 | 80h |
| DC40 | 128h | R/W | LED dot current setting for Dot L2-CS4 | 80h |
| DC41 | 129h | R/W | LED dot current setting for Dot L2-CS5 | 80h |
| DC42 | 12Ah | R/W | LED dot current setting for Dot L2-CS6 | 80h |
| DC43 | 12Bh | R/W | LED dot current setting for Dot L2-CS7 | 80h |
| DC44 | 12Ch | R/W | LED dot current setting for Dot L2-CS8 | 80h |
| DC45 | 12Dh | R/W | LED dot current setting for Dot L2-CS9 | 80h |
| DC46 | 12Eh | R/W | LED dot current setting for Dot L2-CS10 | 80h |
| DC47 | 12Fh | R/W | LED dot current setting for Dot L2-CS11 | 80h |
| DC48 | 130h | R/W | LED dot current setting for Dot L2-CS12 | 80h |
| DC49 | 131h | R/W | LED dot current setting for Dot L2-CS13 | 80h |
| DC50 | 132h | R/W | LED dot current setting for Dot L2-CS14 | 80h |
| DC51 | 133h | R/W | LED dot current setting for Dot L2-CS15 | 80h |
| DC52 | 134h | R/W | LED dot current setting for Dot L2-CS16 | 80h |
| DC53 | 135h | R/W | LED dot current setting for Dot L2-CS17 | 80h |
| DC54 | 136h | R/W | LED dot current setting for Dot L3-CS0 | 80h |
| DC55 | 137h | R/W | LED dot current setting for Dot L3-CS1 | 80h |
| DC56 | 138h | R/W | LED dot current setting for Dot L3-CS2 | 80h |
| DC57 | 139h | R/W | LED dot current setting for Dot L3-CS3 | 80h |
| DC58 | 13Ah | R/W | LED dot current setting for Dot L3-CS4 | 80h |
| DC59 | 13Bh | R/W | LED dot current setting for Dot L3-CS5 | 80h |
| DC60 | 13Ch | R/W | LED dot current setting for Dot L3-CS6 | 80h |
| DC61 | 13Dh | R/W | LED dot current setting for Dot L3-CS7 | 80h |
| DC62 | 13Eh | R/W | LED dot current setting for Dot L3-CS8 | 80h |
| DC63 | 13Fh | R/W | LED dot current setting for Dot L3-CS9 | 80h |
| DC64 | 140h | R/W | LED dot current setting for Dot L3-CS10 | 80h |
| DC65 | 141h | R/W | LED dot current setting for Dot L3-CS11 | 80h |
| DC66 | 142h | R/W | LED dot current setting for Dot L3-CS12 | 80h |
| DC67 | 143h | R/W | LED dot current setting for Dot L3-CS13 | 80h |
| DC68 | 144h | R/W | LED dot current setting for Dot L3-CS14 | 80h |
| DC69 | 145h | R/W | LED dot current setting for Dot L3-CS15 | 80h |
| DC70 | 146h | R/W | LED dot current setting for Dot L3-CS16 | 80h |
| DC71 | 147h | R/W | LED dot current setting for Dot L3-CS17 | 80h |
| DC72 | 148h | R/W | LED dot current setting for Dot L4-CS0 | 80h |
| DC73 | 149h | R/W | LED dot current setting for Dot L4-CS1 | 80h |
| DC74 | 14Ah | R/W | LED dot current setting for Dot L4-CS2 | 80h |

| | | | | |
|------------------|------|-----|---|-----|
| DC75 | 14Bh | R/W | LED dot current setting for Dot L4-CS3 | 80h |
| DC76 | 14Ch | R/W | LED dot current setting for Dot L4-CS4 | 80h |
| DC77 | 14Dh | R/W | LED dot current setting for Dot L4-CS5 | 80h |
| DC78 | 14Eh | R/W | LED dot current setting for Dot L4-CS6 | 80h |
| DC79 | 14Fh | R/W | LED dot current setting for Dot L4-CS7 | 80h |
| DC80 | 150h | R/W | LED dot current setting for Dot L4-CS8 | 80h |
| DC81 | 151h | R/W | LED dot current setting for Dot L4-CS9 | 80h |
| DC82 | 152h | R/W | LED dot current setting for Dot L4-CS10 | 80h |
| DC83 | 153h | R/W | LED dot current setting for Dot L4-CS11 | 80h |
| DC84 | 154h | R/W | LED dot current setting for Dot L4-CS12 | 80h |
| DC85 | 155h | R/W | LED dot current setting for Dot L4-CS13 | 80h |
| DC86 | 156h | R/W | LED dot current setting for Dot L4-CS14 | 80h |
| DC87 | 157h | R/W | LED dot current setting for Dot L4-CS15 | 80h |
| DC88 | 158h | R/W | LED dot current setting for Dot L4-CS16 | 80h |
| DC89 | 159h | R/W | LED dot current setting for Dot L4-CS17 | 80h |
| DC90 | 15Ah | R/W | LED dot current setting for Dot L5-CS0 | 80h |
| DC91 | 15Bh | R/W | LED dot current setting for Dot L5-CS1 | 80h |
| DC92 | 15Ch | R/W | LED dot current setting for Dot L5-CS2 | 80h |
| DC93 | 15Dh | R/W | LED dot current setting for Dot L5-CS3 | 80h |
| DC94 | 15Eh | R/W | LED dot current setting for Dot L5-CS4 | 80h |
| DC95 | 15Fh | R/W | LED dot current setting for Dot L5-CS5 | 80h |
| DC96 | 160h | R/W | LED dot current setting for Dot L5-CS6 | 80h |
| DC97 | 161h | R/W | LED dot current setting for Dot L5-CS7 | 80h |
| DC98 | 162h | R/W | LED dot current setting for Dot L5-CS8 | 80h |
| DC99 | 163h | R/W | LED dot current setting for Dot L5-CS9 | 80h |
| DC100 | 164h | R/W | LED dot current setting for Dot L5-CS10 | 80h |
| DC101 | 165h | R/W | LED dot current setting for Dot L5-CS11 | 80h |
| DC102 | 166h | R/W | LED dot current setting for Dot L5-CS12 | 80h |
| DC103 | 167h | R/W | LED dot current setting for Dot L5-CS13 | 80h |
| DC104 | 168h | R/W | LED dot current setting for Dot L5-CS14 | 80h |
| DC105 | 169h | R/W | LED dot current setting for Dot L5-CS15 | 80h |
| DC106 | 16Ah | R/W | LED dot current setting for Dot L5-CS16 | 80h |
| DC107 | 16Bh | R/W | LED dot current setting for Dot L5-CS17 | 80h |
| pwm_bri0 | 200h | R/W | 8-bits PWM for Dot L0-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS0 | 00h |
| pwm_bri1 | 201h | R/W | 8-bits PWM for Dot L0-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS0 | 00h |
| pwm_bri2 | 202h | R/W | 8-bits PWM for Dot L0-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS1 | 00h |
| pwm_bri3 | 203h | R/W | 8-bits PWM for Dot L0-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS1 | 00h |
| pwm_bri4 | 204h | R/W | 8-bits PWM for Dot L0-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS2 | 00h |
| pwm_bri5 | 205h | R/W | 8-bits PWM for Dot L0-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS2 | 00h |
| pwm_bri6 | 206h | R/W | 8-bits PWM for Dot L0-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS3 | 00h |
| pwm_bri7 | 207h | R/W | 8-bits PWM for Dot L0-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS3 | 00h |
| pwm_bri8 | 208h | R/W | 8-bits PWM for Dot L0-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS4 | 00h |
| pwm_bri9 | 209h | R/W | 8-bits PWM for Dot L0-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS4 | 00h |
| pwm_bri10 | 20Ah | R/W | 8-bits PWM for Dot L0-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS5 | 00h |
| pwm_bri11 | 20Bh | R/W | 8-bits PWM for Dot L0-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS5 | 00h |
| pwm_bri12 | 20Ch | R/W | 8-bits PWM for Dot L0-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS6 | 00h |
| pwm_bri13 | 20Dh | R/W | 8-bits PWM for Dot L0-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS6 | 00h |

| | | | | |
|-----------|------|-----|--|-----|
| pwm_bri14 | 20Eh | R/W | 8-bits PWM for Dot L0-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS7 | 00h |
| pwm_bri15 | 20Fh | R/W | 8-bits PWM for Dot L0-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS7 | 00h |
| pwm_bri16 | 210h | R/W | 8-bits PWM for Dot L0-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS8 | 00h |
| pwm_bri17 | 211h | R/W | 8-bits PWM for Dot L0-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS8 | 00h |
| pwm_bri18 | 212h | R/W | 8-bits PWM for Dot L1-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS9 | 00h |
| pwm_bri19 | 213h | R/W | 8-bits PWM for Dot L1-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS9 | 00h |
| pwm_bri20 | 214h | R/W | 8-bits PWM for Dot L1-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS10 | 00h |
| pwm_bri21 | 215h | R/W | 8-bits PWM for Dot L1-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS10 | 00h |
| pwm_bri22 | 216h | R/W | 8-bits PWM for Dot L1-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS11 | 00h |
| pwm_bri23 | 217h | R/W | 8-bits PWM for Dot L1-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS11 | 00h |
| pwm_bri24 | 218h | R/W | 8-bits PWM for Dot L1-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS12 | 00h |
| pwm_bri25 | 219h | R/W | 8-bits PWM for Dot L1-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS12 | 00h |
| pwm_bri26 | 21Ah | R/W | 8-bits PWM for Dot L1-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS13 | 00h |
| pwm_bri27 | 21Bh | R/W | 8-bits PWM for Dot L1-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS13 | 00h |
| pwm_bri28 | 21Ch | R/W | 8-bits PWM for Dot L1-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS14 | 00h |
| pwm_bri29 | 21Dh | R/W | 8-bits PWM for Dot L1-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS14 | 00h |
| pwm_bri30 | 21Eh | R/W | 8-bits PWM for Dot L1-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS15 | 00h |
| pwm_bri31 | 21Fh | R/W | 8-bits PWM for Dot L1-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS15 | 00h |
| pwm_bri32 | 220h | R/W | 8-bits PWM for Dot L1-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS16 | 00h |
| pwm_bri33 | 221h | R/W | 8-bits PWM for Dot L1-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS16 | 00h |
| pwm_bri34 | 222h | R/W | 8-bits PWM for Dot L1-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L0-CS17 | 00h |
| pwm_bri35 | 223h | R/W | 8-bits PWM for Dot L1-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L0-CS17 | 00h |
| pwm_bri36 | 224h | R/W | 8-bits PWM for Dot L2-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS0 | 00h |
| pwm_bri37 | 225h | R/W | 8-bits PWM for Dot L2-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS0 | 00h |
| pwm_bri38 | 226h | R/W | 8-bits PWM for Dot L2-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS1 | 00h |
| pwm_bri39 | 227h | R/W | 8-bits PWM for Dot L2-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS1 | 00h |
| pwm_bri40 | 228h | R/W | 8-bits PWM for Dot L2-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS2 | 00h |
| pwm_bri41 | 229h | R/W | 8-bits PWM for Dot L2-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS2 | 00h |
| pwm_bri42 | 22Ah | R/W | 8-bits PWM for Dot L2-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS3 | 00h |
| pwm_bri43 | 22Bh | R/W | 8-bits PWM for Dot L2-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS3 | 00h |
| pwm_bri44 | 22Ch | R/W | 8-bits PWM for Dot L2-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS4 | 00h |
| pwm_bri45 | 22Dh | R/W | 8-bits PWM for Dot L2-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS4 | 00h |
| pwm_bri46 | 22Eh | R/W | 8-bits PWM for Dot L2-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS5 | 00h |
| pwm_bri47 | 22Fh | R/W | 8-bits PWM for Dot L2-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS5 | 00h |
| pwm_bri48 | 230h | R/W | 8-bits PWM for Dot L2-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS6 | 00h |
| pwm_bri49 | 231h | R/W | 8-bits PWM for Dot L2-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS6 | 00h |
| pwm_bri50 | 232h | R/W | 8-bits PWM for Dot L2-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS7 | 00h |
| pwm_bri51 | 233h | R/W | 8-bits PWM for Dot L2-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS7 | 00h |
| pwm_bri52 | 234h | R/W | 8-bits PWM for Dot L2-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS8 | 00h |
| pwm_bri53 | 235h | R/W | 8-bits PWM for Dot L2-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS8 | 00h |
| pwm_bri54 | 236h | R/W | 8-bits PWM for Dot L3-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS9 | 00h |
| pwm_bri55 | 237h | R/W | 8-bits PWM for Dot L3-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS9 | 00h |
| pwm_bri56 | 238h | R/W | 8-bits PWM for Dot L3-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS10 | 00h |
| pwm_bri57 | 239h | R/W | 8-bits PWM for Dot L3-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS10 | 00h |
| pwm_bri58 | 23Ah | R/W | 8-bits PWM for Dot L3-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS11 | 00h |
| pwm_bri59 | 23Bh | R/W | 8-bits PWM for Dot L3-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS11 | 00h |
| pwm_bri60 | 23Ch | R/W | 8-bits PWM for Dot L3-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS12 | 00h |

| | | | | |
|------------|------|-----|--|-----|
| pwm_bri61 | 23Dh | R/W | 8-bits PWM for Dot L3-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS12 | 00h |
| pwm_bri62 | 23Eh | R/W | 8-bits PWM for Dot L3-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS13 | 00h |
| pwm_bri63 | 23Fh | R/W | 8-bits PWM for Dot L3-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS13 | 00h |
| pwm_bri64 | 240h | R/W | 8-bits PWM for Dot L3-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS14 | 00h |
| pwm_bri65 | 241h | R/W | 8-bits PWM for Dot L3-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS14 | 00h |
| pwm_bri66 | 242h | R/W | 8-bits PWM for Dot L3-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS15 | 00h |
| pwm_bri67 | 243h | R/W | 8-bits PWM for Dot L3-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS15 | 00h |
| pwm_bri68 | 244h | R/W | 8-bits PWM for Dot L3-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS16 | 00h |
| pwm_bri69 | 245h | R/W | 8-bits PWM for Dot L3-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS16 | 00h |
| pwm_bri70 | 246h | R/W | 8-bits PWM for Dot L3-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L1-CS17 | 00h |
| pwm_bri71 | 247h | R/W | 8-bits PWM for Dot L3-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L1-CS17 | 00h |
| pwm_bri72 | 248h | R/W | 8-bits PWM for Dot L4-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS0 | 00h |
| pwm_bri73 | 249h | R/W | 8-bits PWM for Dot L4-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS0 | 00h |
| pwm_bri74 | 24Ah | R/W | 8-bits PWM for Dot L4-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS1 | 00h |
| pwm_bri75 | 24Bh | R/W | 8-bits PWM for Dot L4-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS1 | 00h |
| pwm_bri76 | 24Ch | R/W | 8-bits PWM for Dot L4-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS2 | 00h |
| pwm_bri77 | 24Dh | R/W | 8-bits PWM for Dot L4-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS2 | 00h |
| pwm_bri78 | 24Eh | R/W | 8-bits PWM for Dot L4-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS3 | 00h |
| pwm_bri79 | 24Fh | R/W | 8-bits PWM for Dot L4-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS3 | 00h |
| pwm_bri80 | 250h | R/W | 8-bits PWM for Dot L4-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS4 | 00h |
| pwm_bri81 | 251h | R/W | 8-bits PWM for Dot L4-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS4 | 00h |
| pwm_bri82 | 252h | R/W | 8-bits PWM for Dot L4-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS5 | 00h |
| pwm_bri83 | 253h | R/W | 8-bits PWM for Dot L4-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS5 | 00h |
| pwm_bri84 | 254h | R/W | 8-bits PWM for Dot L4-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS6 | 00h |
| pwm_bri85 | 255h | R/W | 8-bits PWM for Dot L4-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS6 | 00h |
| pwm_bri86 | 256h | R/W | 8-bits PWM for Dot L4-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS7 | 00h |
| pwm_bri87 | 257h | R/W | 8-bits PWM for Dot L4-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS7 | 00h |
| pwm_bri88 | 258h | R/W | 8-bits PWM for Dot L4-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS8 | 00h |
| pwm_bri89 | 259h | R/W | 8-bits PWM for Dot L4-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS8 | 00h |
| pwm_bri90 | 25Ah | R/W | 8-bits PWM for Dot L5-CS0 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS9 | 00h |
| pwm_bri91 | 25Bh | R/W | 8-bits PWM for Dot L5-CS1 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS9 | 00h |
| pwm_bri92 | 25Ch | R/W | 8-bits PWM for Dot L5-CS2 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS10 | 00h |
| pwm_bri93 | 25Dh | R/W | 8-bits PWM for Dot L5-CS3 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS10 | 00h |
| pwm_bri94 | 25Eh | R/W | 8-bits PWM for Dot L5-CS4 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS11 | 00h |
| pwm_bri95 | 25Fh | R/W | 8-bits PWM for Dot L5-CS5 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS11 | 00h |
| pwm_bri96 | 260h | R/W | 8-bits PWM for Dot L5-CS6 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS12 | 00h |
| pwm_bri97 | 261h | R/W | 8-bits PWM for Dot L5-CS7 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS12 | 00h |
| pwm_bri98 | 262h | R/W | 8-bits PWM for Dot L5-CS8 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS13 | 00h |
| pwm_bri99 | 263h | R/W | 8-bits PWM for Dot L5-CS9 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS13 | 00h |
| pwm_bri100 | 264h | R/W | 8-bits PWM for Dot L5-CS10 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS14 | 00h |
| pwm_bri101 | 265h | R/W | 8-bits PWM for Dot L5-CS11 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS14 | 00h |
| pwm_bri102 | 266h | R/W | 8-bits PWM for Dot L5-CS12 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS15 | 00h |
| pwm_bri103 | 267h | R/W | 8-bits PWM for Dot L5-CS13 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS15 | 00h |
| pwm_bri104 | 268h | R/W | 8-bits PWM for Dot L5-CS14 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS16 | 00h |
| pwm_bri105 | 269h | R/W | 8-bits PWM for Dot L5-CS15 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS16 | 00h |
| pwm_bri106 | 26Ah | R/W | 8-bits PWM for Dot L5-CS16 OR 16-bits PWM lower 8 bits [7:0] for Dot L2-CS17 | 00h |
| pwm_bri107 | 26Bh | R/W | 8-bits PWM for Dot L5-CS17 OR 16-bits PWM higher 8 bits [15:8] for Dot L2-CS17 | 00h |

| | | | | |
|------------|------|-----|--|-----|
| pwm_bri108 | 26Ch | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS0 | 00h |
| pwm_bri109 | 26Dh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS0 | 00h |
| pwm_bri110 | 26Eh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS1 | 00h |
| pwm_bri111 | 26Fh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS1 | 00h |
| pwm_bri112 | 270h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS2 | 00h |
| pwm_bri113 | 271h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS2 | 00h |
| pwm_bri114 | 272h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS3 | 00h |
| pwm_bri115 | 273h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS3 | 00h |
| pwm_bri116 | 274h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS4 | 00h |
| pwm_bri117 | 275h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS4 | 00h |
| pwm_bri118 | 276h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS5 | 00h |
| pwm_bri119 | 277h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS5 | 00h |
| pwm_bri120 | 278h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS6 | 00h |
| pwm_bri121 | 279h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS6 | 00h |
| pwm_bri122 | 27Ah | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS7 | 00h |
| pwm_bri123 | 27Bh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS7 | 00h |
| pwm_bri124 | 27Ch | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS8 | 00h |
| pwm_bri125 | 27Dh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS8 | 00h |
| pwm_bri126 | 27Eh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS9 | 00h |
| pwm_bri127 | 27Fh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS9 | 00h |
| pwm_bri128 | 280h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS10 | 00h |
| pwm_bri129 | 281h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS10 | 00h |
| pwm_bri130 | 282h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS11 | 00h |
| pwm_bri131 | 283h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS11 | 00h |
| pwm_bri132 | 284h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS12 | 00h |
| pwm_bri133 | 285h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS12 | 00h |
| pwm_bri134 | 286h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS13 | 00h |
| pwm_bri135 | 287h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS13 | 00h |
| pwm_bri136 | 288h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS14 | 00h |
| pwm_bri137 | 289h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS14 | 00h |
| pwm_bri138 | 28Ah | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS15 | 00h |
| pwm_bri139 | 28Bh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS15 | 00h |
| pwm_bri140 | 28Ch | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS16 | 00h |
| pwm_bri141 | 28Dh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS16 | 00h |
| pwm_bri142 | 28Eh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L3-CS17 | 00h |
| pwm_bri143 | 28Fh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L3-CS17 | 00h |
| pwm_bri144 | 290h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS0 | 00h |
| pwm_bri145 | 291h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS0 | 00h |
| pwm_bri146 | 292h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS1 | 00h |
| pwm_bri147 | 293h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS1 | 00h |
| pwm_bri148 | 294h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS2 | 00h |
| pwm_bri149 | 295h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS2 | 00h |
| pwm_bri150 | 296h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS3 | 00h |
| pwm_bri151 | 297h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS3 | 00h |
| pwm_bri152 | 298h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS4 | 00h |
| pwm_bri153 | 299h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS4 | 00h |
| pwm_bri154 | 29Ah | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS5 | 00h |

| | | | | |
|------------|------|-----|--|-----|
| pwm_bri155 | 29Bh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS5 | 00h |
| pwm_bri156 | 29Ch | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS6 | 00h |
| pwm_bri157 | 29Dh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS6 | 00h |
| pwm_bri158 | 29Eh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS7 | 00h |
| pwm_bri159 | 29Fh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS7 | 00h |
| pwm_bri160 | 2A0h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS8 | 00h |
| pwm_bri161 | 2A1h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS8 | 00h |
| pwm_bri162 | 2A2h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS9 | 00h |
| pwm_bri163 | 2A3h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS9 | 00h |
| pwm_bri164 | 2A4h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS10 | 00h |
| pwm_bri165 | 2A5h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS10 | 00h |
| pwm_bri166 | 2A6h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS11 | 00h |
| pwm_bri167 | 2A7h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS11 | 00h |
| pwm_bri168 | 2A8h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS12 | 00h |
| pwm_bri169 | 2A9h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS12 | 00h |
| pwm_bri170 | 2AAh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS13 | 00h |
| pwm_bri171 | 2ABh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS13 | 00h |
| pwm_bri172 | 2ACh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS14 | 00h |
| pwm_bri173 | 2ADh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS14 | 00h |
| pwm_bri174 | 2AEh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS15 | 00h |
| pwm_bri175 | 2AFh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS15 | 00h |
| pwm_bri176 | 2B0h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS16 | 00h |
| pwm_bri177 | 2B1h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS16 | 00h |
| pwm_bri178 | 2B2h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L4-CS17 | 00h |
| pwm_bri179 | 2B3h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L4-CS17 | 00h |
| pwm_bri180 | 2B4h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS0 | 00h |
| pwm_bri181 | 2B5h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS0 | 00h |
| pwm_bri182 | 2B6h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS1 | 00h |
| pwm_bri183 | 2B7h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS1 | 00h |
| pwm_bri184 | 2B8h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS2 | 00h |
| pwm_bri185 | 2B9h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS2 | 00h |
| pwm_bri186 | 2BAh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS3 | 00h |
| pwm_bri187 | 2BBh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS3 | 00h |
| pwm_bri188 | 2BCh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS4 | 00h |
| pwm_bri189 | 2BDh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS4 | 00h |
| pwm_bri190 | 2BEh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS5 | 00h |
| pwm_bri191 | 2BFh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS5 | 00h |
| pwm_bri192 | 2C0h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS6 | 00h |
| pwm_bri193 | 2C1h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS6 | 00h |
| pwm_bri194 | 2C2h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS7 | 00h |
| pwm_bri195 | 2C3h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS7 | 00h |
| pwm_bri196 | 2C4h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS8 | 00h |
| pwm_bri197 | 2C5h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS8 | 00h |
| pwm_bri198 | 2C6h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS9 | 00h |
| pwm_bri199 | 2C7h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS9 | 00h |
| pwm_bri200 | 2C8h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS10 | 00h |
| pwm_bri201 | 2C9h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS10 | 00h |

LP5866

ZHCSOA5A - DECEMBER 2021 - REVISED SEPTEMBER 2024

| | | | | |
|-------------------|------|-----|--|-----|
| pwm_bri202 | 2CAh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS11 | 00h |
| pwm_bri203 | 2CBh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS11 | 00h |
| pwm_bri204 | 2CCh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS12 | 00h |
| pwm_bri205 | 2CDh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS12 | 00h |
| pwm_bri206 | 2CEh | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS13 | 00h |
| pwm_bri207 | 2CFh | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS13 | 00h |
| pwm_bri208 | 2D0h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS14 | 00h |
| pwm_bri209 | 2D1h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS14 | 00h |
| pwm_bri210 | 2D2h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS15 | 00h |
| pwm_bri211 | 2D3h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS15 | 00h |
| pwm_bri212 | 2D4h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS16 | 00h |
| pwm_bri213 | 2D5h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS16 | 00h |
| pwm_bri214 | 2D6h | R/W | 16-bits PWM lower 8 bits [7:0] for Dot L5-CS17 | 00h |
| pwm_bri215 | 2D7h | R/W | 16-bits PWM higher 8 bits [15:8] for Dot L5-CS17 | 00h |

8 Application and Implementation

备注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

8.1 Application Information

The LP5866 integrates 18 constant current sinks with 6 switching FETs and one LP5866 can drive up to 108 LED dots or 36 RGB pixels and achieve great dimming effect. In smart home, gaming keyboards, and other human-machine interaction applications, the device can greatly improve user experience with a small amount of components.

8.2 Typical Application

8.2.1 Application

图 8-1 shows an example of typical application, which uses one LP5866 to drive 36 common-anode RGB LEDs through I²C communication.




图 8-1. Typical Application - LP5866 Driving 36 RGB LEDs (108 LED Dots)

8.2.2 Design Requirements

表 8-1. Design Parameters

| PARAMETER | VALUE |
|--|------------------|
| VCC / VIO | 3.3V |
| VLED | 5V |
| RGB LED count | 36 |
| Scan number | 6 |
| Interface | I ² C |
| LED maximum average current (red, green, blue) | 4mA, 3mA, 2mA |
| LED maximum peak current (red, green, blue) | 24mA, 18mA, 12mA |

8.2.3 Detailed Design Procedure

LP5866 requires an external capacitor $C_{V_{CAP}}$, whose value is $1\ \mu\text{F}$ connected from V_{CAP} to GND for proper operation of internal LDO. The capacitor must be placed as close to the device as possible.

TI recommends $1\ \mu\text{F}$ capacitors be placed between VCC / VLED with GND, and a 1nF capacitor placed between VIO with GND. Place the capacitors as close to the device as possible.

Pull-up resistors $R_{\text{pull-up}}$ are a requirement for SCL and SDA when using I²C as communication method. In typical applications, TI recommends $1.8\text{k}\Omega$ to $4.7\text{k}\Omega$ resistors.

To decrease thermal dissipation from device to ambient, resistors R_{CS} can optionally be placed in serial with the LED. Voltage drop on these resistors must left enough margins for VSAT to ensure the device works normally.

8.2.3.1 Program Procedure

When selecting data refresh Mode 1, outputs are refreshed instantly after data is received.

When selecting data refresh Mode 2/3, VSYNC signal is required for synchronized display. Programming flow is shown as 图 8-2. To display full pixel of last frame, VSYNC pulse must be sent to the device after the end of last PWM. Time between two pulses t_{SYNC} must be larger than the whole PWM time of all Dots t_{frame} . Common selection like 60Hz, 90Hz, 120Hz or even higher refresh frequency can be supported. High pulse width longer than $t_{\text{SYNC_H}}$ is required at the beginning of each VSYNC frame, and data must not be write to PWM registers during high pulse width.




图 8-2. Program Procedure

8.2.4 Application Performance Plots

The following figures show the application performance plots.






图 8-3. Scan Lines and Current Sinks Waveforms of SW0, SW1, CS0, CS1




PWM frequency = 62.5kHz

图 8-4. Scan Lines and Current Sinks Waveforms of SW0, SW1, CS0, CS1




PWM frequency = 125kHz

图 8-5. Scan Lines and Current Sinks Waveforms of SW0, SW1, CS0, CS1




Switch blank time $t_{SW_BLK} = 0.5 \mu s$

图 8-6. Scan Lines Switching Waveforms of SW0, SW1, SW2




Switch blank time $t_{SW_BLK} = 1 \mu s$

图 8-7. Scan Lines Switching Waveforms of SW0, SW1, SW2



PWM_Phase_Shift = 0h

图 8-8. PWM Phase Shift Disabled



PWM_Phase_Shift = 1h

图 8-9. PWM Phase Shift Enabled

8.3 Power Supply Recommendations

8.3.1 Power Supply Recommendations

VDD Input Supply Recommendations

LP5866 is designed to operate from a 2.7V to 5.5V VDD voltage supply. This input supply must be well regulated and can provide the peak current required by the LED matrix. The resistance of the VDD supply rail must be low enough such that the input current transient does not cause the LP5866 VDD supply voltage to drop below the maximum POR voltage.

8.3.2 Power Supply Recommendations

VIO Input Supply Recommendations

LP5866 is designed to operate with a 1.65V to 5.5V VIO_EN voltage supply. The VIO_EN supply must be well regulated and can provide the peak current required by the LED configuration without voltage drop under load transients like start-up or rapid brightness change.

8.3.3 Power Supply Recommendations

VLED Input Supply Recommendations

LP5866 is designed to operate with a 2.7V to 5.5V VLED voltage supply. The VLED supply must be well regulated and can provide the peak current required by the LED configuration without voltage drop, under load transients like start-up or rapid brightness change. The resistance of the input supply rail must be low enough so that the input current transient does not cause the VLED supply voltage to drop below LED $V_f + V_{SAT}$ voltage.

8.4 Layout

8.4.1 Layout Guidelines

the below guidelines for layout design can help to get a better on-board performance.

- The decoupling capacitors C_{VCC} and C_{VLED} for power supply must be close to the chip to have minimized the impact of high-frequency noise and ripple from power. C_{VCAP} for internal LDO must be put as close to chip as possible. GND plane connections to C_{VLED} and GND pins must be on TOP layer copper with multiple vias connecting to system ground plane. C_{VIO} for internal enable block also must be put as close to chip as possible.
- The exposed thermal pad must be well soldered to the board, which can have better mechanical reliability. The action can optimize heat transfer so that increasing thermal performance. AGND pin must be connected to thermal pad and system ground.

- The major heat flow path from the package to the ambient is through copper on the PCB. Several methods can help thermal performance. Below exposed thermal pad of IC, putting much vias through the PCB to other ground layer can dissipate more heat. Maximizing the copper coverage on the PCB can increase the thermal conductivity of the board.
- Low inductive and resistive path of switch load loop can help to provide a high slew rate. Therefore, path of VLED - SWx must be short and wide and avoid parallel wiring and narrow trace. Transient current in SWx pins is much larger than CSy pins, so that trace for SWx must be wider than CSy.

8.4.2 Layout Example




图 8-10. LP5866 Layout Example

9 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

9.1 接收文档更新通知

要接收文档更新通知，请导航至 ti.com 上的器件产品文件夹。点击 [通知](#) 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

9.2 支持资源

[TI E2E™ 中文支持论坛](#) 是工程师的重要参考资料，可直接从专家处获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题，获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的 [使用条款](#)。

9.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.

所有商标均为其各自所有者的财产。

9.4 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

9.5 术语表

[TI 术语表](#) 本术语表列出并解释了术语、首字母缩略词和定义。

10 Revision History

注：以前版本的页码可能与当前版本的页码不同

| Changes from Revision * (December 2021) to Revision A (September 2024) | Page |
|--|------|
| • Updated DBT package information..... | 4 |
| • Updated thermal information of DBT package..... | 7 |
| • Updated I ² C Timing Requirements..... | 7 |
| • Added I ² C Standard Mode Timing Requirements..... | 7 |
| • Added timing parameters diagrams..... | 11 |
| • Updated application design parameters..... | 42 |

11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package Pins | Package qty Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|-----------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| LP5866DBTR | Active | Production | TSSOP (DBT) 38 | 2000 LARGE T&R | Yes | NIPDAU | Level-2-260C-1 YEAR | -40 to 85 | LP5866DBT |
| LP5866DBTR.A | Active | Production | TSSOP (DBT) 38 | 2000 LARGE T&R | Yes | NIPDAU | Level-2-260C-1 YEAR | -40 to 85 | LP5866DBT |
| LP5866MDBTR | Active | Production | TSSOP (DBT) 38 | 2000 LARGE T&R | Yes | NIPDAU | Level-2-260C-1 YEAR | -55 to 125 | 5866MDBT |
| LP5866MDBTR.A | Active | Production | TSSOP (DBT) 38 | 2000 LARGE T&R | Yes | NIPDAU | Level-2-260C-1 YEAR | -55 to 125 | 5866MDBT |
| LP5866RKPR | Active | Production | VQFN (RKP) 40 | 3000 LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | LP5866 |
| LP5866RKPR.A | Active | Production | VQFN (RKP) 40 | 3000 LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | LP5866 |

(1) **Status:** For more details on status, see our [product life cycle](#).

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION



*All dimensions are nominal


| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LP5866RKPR | VQFN | RKP | 40 | 3000 | 330.0 | 12.4 | 5.3 | 5.3 | 1.1 | 8.0 | 12.0 | Q2 |

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LP5866RKPR | VQFN | RKP | 40 | 3000 | 367.0 | 367.0 | 35.0 |



4220221/A 05/2020

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

EXAMPLE BOARD LAYOUT


DBT0038A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X




SOLDER MASK DETAILS

4220221/A 05/2020

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE
 BASED ON 0.125 mm THICK STENCIL
 SCALE: 10X

4220221/A 05/2020

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

GENERIC PACKAGE VIEW


RKP 40


VQFN - 1 mm max height

5 x 5, 0.4 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD


This image is a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.





NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for optimal thermal and mechanical performance.



LAND PATTERN EXAMPLE

EXPOSED METAL SHOWN


SCALE: 15X



4219083/A 03/2021

NOTES: (continued)

4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/sluea271).
5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.



SOLDER PASTE EXAMPLE
 BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD
 74% PRINTED COVERAGE BY AREA
 SCALE: 15X

4219083/A 03/2021

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 [TI 销售条款](#)、[TI 通用质量指南](#) 或 [ti.com](#) 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2025，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月