具有电源正常状态指示功能的 TPS7A26 500mA、18V、超低 I_Q、低压降线性稳压器

1 特性

- 超低 I_Q：2.0μA
- 输入电压：2.4V 至 18V
- 可用输出电压选项：
  - 固定电压：1.25V 至 5.5V
  - 可调节：1.24V 至 17.4V
- 在温度范围内的精度为 1%
- 低压降：电流 500mA 时为 590mV（最大值）
- 开漏电源正常状态输出
- 主动过冲下拉保护
- 热关断保护和过流保护
- 工作结温范围：–40°C 至 +125°C
- 与 1μF 输出电容器一起工作时保持稳定
- 封装：6 引脚 WSON

2 应用

- 家庭和楼宇自动化
- 多电池移动电源
- 智能电网和计量
- 便携式电动工具
- 电机驱动器
- 白色家电
- 便携式电器

3 说明

TPS7A26 低压降 (LDO) 线性稳压器支持 2.4V 至 18V 输入电压范围，并具有极低的静态电流 (I_Q)。这些 特性 能更好地帮助现代电器满足日益严苛的能源要求，并有助于延长便携式电源解决方案的电池寿命。

TPS7A26 有固定电压和可调节电压两种版本可供选用。为了获得更大的灵活性或更高的输出电压，可调节电压版本使用反馈电阻器将输出电压从 1.24V 设置到 17.4V。两种版本都具有 1% 的输出调节精度，可对微控制器 (MCU) 基准电压进行精密调节。

凭借开漏电源正常状态 (PG) 输出，该器件可为 MCU 提供复位，或者与其他开漏 PG 进行线或 (wire-OR) 和电平转换，从而提供系统范围的 PG 或复位。

在电流为 500mA 时，TPS7A26 LDO 拥有小于 590mV 的最大压降，因此它比标准线性稳压器的工作效率更高。该最大压降电压使得器件可从 5.7V 输入电压 (V_{IN}) 获得 5.0V 输出电压 (V_{OUT})，实现 87.7% 的效率。


对于低功耗 应用，请考虑使用 TPS7A25。

器件信息(1)

器件型号	封装	封装尺寸（标称值）
TPS7A26	WSON (6)	2.00mm × 2.00mm

(1) 如需了解所有可用封装，请参阅产品说明书末尾的封装选项附录。

典型应用电路



本文档旨在为方便起见，提供有关 TI 产品中文版本的信息，以确认产品的概要。 有关适用的官方英文版本的最新信息，请访问 www.ti.com，其内容始终优先。 TI 不保证翻译的准确性和有效性。 在实际设计之前，请务必参考最新版本的英文版本。

目录

1 特性 ... 1
2 应用 ... 1
3 说明 ... 1
4 修订历史记录 ... 2
5 **Pin Configuration and Functions** ... 3
6 **Specifications** ... 4
6.1 Absolute Maximum Ratings ... 4
6.2 ESD Ratings ... 4
6.3 Recommended Operating Conditions ... 4
6.4 Thermal Information ... 4
6.5 Electrical Characteristics ... 5
6.6 Typical Characteristics ... 6
7 **Detailed Description** ... 12
7.1 Overview ... 12
7.2 Functional Block Diagram ... 12
7.3 Feature Description ... 13
7.4 Device Functional Modes ... 16
8 **Application and Implementation** ... 17
8.1 Application Information ... 17
8.2 Typical Application ... 20
9 **Power Supply Recommendations** ... 23
10 **Layout** ... 23
10.1 Layout Guidelines ... 23
10.2 Layout Examples ... 23
11 器件和文档支持 ... 24
11.1 器件支持 ... 24
11.2 文档支持 ... 24
11.3 接收文档更新通知 ... 24
11.4 社区资源 ... 24
11.5 商标 ... 24
11.6 静电放电警告 ... 24
11.7 Glossary ... 24
12 机械、封装和可订购信息 ... 24

4 修订历史记录

Changes from Revision A (March 2019) to Revision B **Page**

- 已添加 在文档中添加了固定电压版本 ... 1
- 已更改 将可调节电压版本输出电压从 *0.24V* 至 *17.45V* 更改为 *1.24V* 至 *17.4V* ... 1
- 已删除 删除了固定电压版本 说明 ，目标位置*说明* 部分 ... 1
- 已添加 添加了 TPS7A25 参考，目标位置：*说明* 部分 ... 1
- 已添加 *Active* to *Overshoot Pulldown Circuitry* title ... 15


Changes from Original (December 2019) to Revision A **Page**

- 已更改 将状态从“预告信息”更改为“生产数据” ... 1


Copyright © 2018–2019, Texas Instruments Incorporated

5 Pin Configuration and Functions

TPS7A26: DRV Package (Adjustable)
6-Pin WSON
Top View



TPS7A26: DRV Package (Fixed)
6-Pin WSON
Top View



Pin Functions

PIN			I/O	DESCRIPTION
NAME	DRV (Adjustable)	DRV (Fixed)		
EN	4	4	Input	Enable pin. Drive EN greater than $V_{EN(HI)}$ to enable the regulator. Drive EN less than $V_{EN(LOW)}$ to put the regulator into low-current shutdown. Do not float this pin. If not used, connect EN to IN.
FB	2	—	Input	Feedback pin. Input to the control-loop error amplifier. This pin is used to set the output voltage of the device with the use of external resistors. For adjustable-voltage version devices only.
GND	5	5	—	Ground pin.
IN	6	6	Input	Input pin. For best transient response and to minimize input impedance, use the recommended value or larger capacitor from IN to ground as listed in the *Recommended Operating Conditions* table. Place the input capacitor as close to the IN and GND pins of the device as possible.
NC	—	2	—	No internal connection. For fixed-voltage version devices only. Ths pin can be floated but the device has better thermal performance with this pin tied to GND.
OUT	1	1	Output	Output pin. A capacitor is required from OUT to ground for stability. For best transient response, use the nominal recommended value or larger capacitor from OUT to ground. Follow the recommended capacitor value as listed in the *Recommended Operating Conditions* table. Place the output capacitor as close to the OUT and GND pins of the device as possible.
PG	3	3	Output	Power-good pin; open-collector output. Pullup this pin externally to the OUT pin or another voltage rail. The PG pin goes high when $V_{OUT} > V_{IT(PG,RISING)}$, as discussed in the *Electrical Characteristics* table. The PG pin is driven low when $V_{OUT} < V_{IT(PG,FALLING)}$, as discussed in the *Electrical Characteristics* table. Ths pin can be floated but the device has better thermal performance with this pin tied to GND.
Thermal pad	Pad	Pad	—	Exposed pad of the package. Connect this pad to ground or leave floating. Connect the thermal pad to a large-area ground plane for best thermal performance.

Copyright © 2018–2019, Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
Voltage(2)	V_{IN}	–0.3	20	V
	V_{OUT}(3)	–0.3	V_{IN} + 0.3	
	V_{FB}	–0.3	5.5	
	V_{EN}	–0.3	20	
	V_{PG}	–0.3	20	
Current	Maximum output	Internally limited		A
Temperature	Operating junction, T_J	–50	150	°C
	Storage, T_{stg}	–65	150	

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) All voltages with respect to GND.
(3) V_{IN} + 0.3 V or 20 V (whichever is smaller).

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001(1)	±1500	V
		Charged device model (CDM), per JEDEC specification JESD22-C101(2)	±1000	

(1) JEDEC document JEP155 states that 2-kV HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 500-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

		MIN	NOM	MAX	UNIT
V_{IN}	Input voltage	2.4		18	V
V_{OUT}	Output voltage (adjustable version)	1.24		18-V_{DO}	V
V_{OUT}	Output voltage (fixed version)	1.25		5.5	V
I_{OUT}	Output current	0		500	mA
V_{EN}	Enable voltage	0		18	V
V_{PG}(1)	Power-good voltage	0		18	V
C_{IN}(2)	Input capacitor		1		µF
C_{OUT}(2)	Output capacitor	1	2.2	100	µF
T_J	Operating junction temperature	–40		125	°C

(1) Select pullup resistor to limit PG pin sink current when PG output is driven low. See *Power Good* section for details.
(2) All capacitor values are assumed to derate to 50% of the nominal capacitor value.

6.4 Thermal Information

THERMAL METRIC(1)		TPS7A26 DRV (WSON) 6 PINS	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	73.3	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	90.6	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	38.3	°C/W
Ψ_{JT}	Junction-to-top characterization parameter	3.7	°C/W
Ψ_{JB}	Junction-to-board characterization parameter	38.4	°C/W
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	14.3	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

Copyright © 2018–2019, Texas Instruments Incorporated

6.5 Electrical Characteristics


specified at T_J = –40°C to +125°C, V_{IN} = $V_{OUT(nom)}$ + 0.8 V or V_{IN} = 2.4 V (whichever is greater), FB tied to OUT, I_{OUT} = 1 mA, V_{EN} = 2 V, and C_{IN} = 1 µF, C_{OUT} = 2.2 µF (unless otherwise noted); typical values are at T_J = 25°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{UVLO(RISING)}$	UVLO threshold rising	V_{IN} rising	1.95	2.15	2.35	V
$V_{UVLO(HYS)}$	UVLO hysteresis			70		mV
$V_{UVLO(FALLING)}$	UVLO threshold falling	V_{IN} falling	1.85	2.09	2.25	V
V_{FB}	Feedback voltage	Adjustable version only		1.24		V
V_{OUT}	Output voltage accuracy	Adjustable version, V_{OUT} = V_{FB}	1.228	1.24	1.252	V
V_{OUT}	Output voltage accuracyaccuracy for fixed output options	Fixed output versions	–1		1	%
$\Delta V_{OUT(\Delta VIN)}$	Line regulation(1)	($V_{OUT(nom)}$ + 0.8 V or 2.4 V) ≤ V_{IN} ≤ 18 V	–0.1		0.1	%
$\Delta V_{OUT(\Delta IOUT)}$	Load regulation	1 mA ≤ I_{OUT} ≤ 500 mA	–0.5		0.5	%
V_{DO}	Dropout voltage(2)	I_{OUT} = 100 mA		92	145	mV
		I_{OUT} = 250 mA		173	280	
		I_{OUT} = 500 mA		355	590	
I_{CL}	Output current limit	V_{OUT} = 0.9 × $V_{OUT(nom)}$	525	717	970	mA
I_{GND}	Ground pin current	I_{OUT} = 0 mA		2	4.5	µA
		I_{OUT} = 1 mA		15		
$I_{SHUTDOWN}$	Shutdown current	V_{EN} ≤ 0.4 V, V_{IN} = 2.4 V, I_{out} = 0 mA		325	600	nA
I_{FB}	FB pin current			10		nA
I_{EN}	EN pin current	V_{EN} = 18 V		10		nA
$V_{EN(HI)}$	Enable pin high-level input voltage	Device enabled	0.9			V
$V_{EN(LOW)}$	Enable pin low-level input voltage	Device disabled			0.4	V
$V_{IT(PG,RISING)}$	PG pin threshold rising	R_{PULLUP} = 10 kΩ, V_{OUT} rising, V_{IN} ≥ $V_{UVLO(RISING)}$		93	96.5	%V_{OUT}
$V_{HYS(PG)}$	PG pin hysteresis	R_{PULLUP} = 10 kΩ, V_{OUT} falling, V_{IN} ≥ $V_{UVLO(RISING)}$		3		%V_{OUT}
$V_{IT(PG,FALLING)}$	PG pin threshold falling	R_{PULLUP} = 10 kΩ, V_{OUT} falling, V_{IN} ≥ $V_{UVLO(RISING)}$	84	90		%V_{OUT}
$V_{OL(PG)}$	PG pin low level output voltage	V_{OUT} < $V_{IT(PG,FALLING)}$, $I_{PG-SINK}$ = 500 µA			0.4	V
$I_{LKG(PG)}$	PG pin leakage current	V_{OUT} > $V_{IT(PG,RISING)}$, V_{PG} = 18 V		5	300	nA
PSRR	Power-supply rejection ratio	f = 10 Hz		75		dB
		f = 100 Hz		62		
		f = 1 kHz		52		
V_n	Output noise voltage	BW = 10 Hz to 100 kHz, V_{OUT} = 1.2 V		300		μV_{RMS}
$T_{SD(shutdown)}$	Thermal shutdown temperature	Shutdown, temperature increasing		165		°C
$T_{SD(reset)}$	Thermal shutdown reset temperature	Reset, temperature decreasing		145		°C

(1) $V_{out(nom)}$ + 0.8 V or 2.4 V (whichever is greater).
(2) V_{DO} is measured with V_{IN} = 0.97 × $V_{OUT(nom)}$ for fixed output voltage versions. V_{DO} is not measured for fixed output voltage versions when V_{OUT} ≤ 2.5 V. For the adjustable output device, V_{DO} is measured with V_{FB} = 0.97 × $V_{FB(nom)}$.


6.6 Typical Characteristics

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C




I_{OUT} = 1 mA

图 1. Line Regulation vs V_{IN}




V_{OUT} = 1.24 V

图 2. Load Regulation vs I_{OUT}




I_{OUT} = 100 mA

图 3. Dropout Voltage vs V_{IN}




I_{OUT} = 250 mA

图 4. Dropout Voltage vs V_{IN}



I_{OUT} = 500 mA

图 5. Dropout Voltage vs V_{IN}




V_{IN} = 2.4 V

图 6. Dropout Voltage vs I_{OUT}

版权 © 2018–2019, Texas Instruments Incorporated

Typical Characteristics (接下页)

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C



V_{IN} = 18 V

图 7. Dropout Voltage vs I_{OUT}






图 8. Current Limit vs V_{IN}




V_{OUT} = 1.24 V, I_{OUT} = 1 mA

图 9. I_{GND} vs V_{IN}




V_{OUT} = 1.24 V, I_{OUT} = 0 A

图 10. I_Q vs V_{IN}



V_{OUT} = 1.24 V, I_{OUT} = 0 A

图 11. I_Q vs V_{IN}




V_{OUT} = 1.24 V

图 12. I_{GND} vs I_{OUT}


Typical Characteristics (接下页)

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C




V_{OUT} = 1.24 V

图 13. Shutdown Current vs V_{IN}




V_{OUT} = 1.24 V, 2.4 V ≤ V_{IN} ≤ 18 V

图 14. V_{EN} vs Temperature




V_{OUT} = 1.24 V, I_{OUT} = 1 mA

图 15. UVLO Thresholds vs Temperature




V_{OUT} = 1.24 V

图 16. PG Thresholds vs Temperature



V_{OUT} = 1.24 V

图 17. PG Leakage Current vs Temperature




V_{OUT} = 1.24 V, C_{IN} = 0 µF, C_{OUT} = 1 µF

图 18. PSRR vs Frequency and I_{OUT}

版权 © 2018–2019, Texas Instruments Incorporated


Typical Characteristics (接下页)

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C




V_{OUT} = 3.3 V, V_{IN} = 4.3 V,
C_{IN} = 0 µF, C_{OUT} = 1 µF, C_{FF} = 10 nF

图 19. PSRR vs Frequency and I_{OUT}




V_{OUT} = 3.3 V, I_{OUT} = 0.5 A,
C_{IN} = 0 µF, C_{OUT} = 1 µF, C_{FF} = 10 nF

图 20. PSRR vs Frequency and V_{IN}




V_{OUT} = 3.3 V, V_{IN} = 4.3 V, I_{OUT} = 0.5 A,
C_{IN} = 0 µF, C_{FF} = 10 nF

图 21. PSRR vs Frequency and C_{OUT}




V_{OUT} = 3.3 V, V_{IN} = 4.3 V, I_{OUT} = 0.5 A,
C_{IN} = 0 µF, C_{OUT} = 1 µF

图 22. PSRR vs Frequency and C_{FF}



V_{IN} = V_{OUT} + 1 V or 2.4 V (whichever is greater), I_{OUT} = 0.5 A,
C_{IN} = 0 µF, C_{OUT} = 1 µF, C_{FF} = 10 nF

图 23. PSRR vs Frequency and V_{OUT}




V_{IN} = V_{OUT} + 1 V or 2.4 V (whichever is greater),
I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF, C_{FF} = 10 nF,
V_{RMS} BW = 10 Hz to 100 kHz

图 24. Output Noise (V_n) vs Frequency and V_{OUT}


Typical Characteristics (接下页)

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C




V_{OUT} = 1.24 V, C_{IN} = 1 µF, C_{OUT} = 1 µF, C_{FF} = 10 nF, V_{RMS} BW = 10 Hz to 100 kHz

图 25. Output Noise (V_n) vs Frequency and I_{OUT}




V_{OUT} = 1.24 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{FF} = 10 nF, V_{RMS} BW = 10 Hz to 100 kHz

图 26. Output Noise (V_n) vs Frequency and C_{OUT}




V_{OUT} = 3.3 V, V_{IN} = 4.3 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF, V_{RMS} BW = 10 Hz to 100 kHz

图 27. Output Noise (V_n) vs Frequency and C_{FF}




I_{OUT} = 0.001 A to 0.5 A, slew rate = 0.5 A/µs, V_{OUT} = 3.3 V, V_{IN} = 4.3 V, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 28. Load Transient



I_{OUT} = 0.5 A to 0.001 A, slew rate = 0.5 A/µs, V_{OUT} = 3.3 V, V_{IN} = 4.3 V, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 29. Load Transient




V_{IN} = 5.3 V to 4.3 V, slew rate = 0.5 V/µs, V_{OUT} = 3.3 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 30. Line Transient

版权 © 2018–2019, Texas Instruments Incorporated


Typical Characteristics (接下页)

at operating temperature T_J = 25°C, I_{OUT} = 1 mA, V_{EN} = 0.9 V, C_{IN} = 2.2 µF, C_{OUT} = 2.2 µF, and V_{IN} = $V_{OUT(typ)}$ + 0.8 V or 2.4 V (whichever is greater), unless otherwise noted; typical values are at T_J = 25°C




V_{IN} = 4.3 V to 5.3 V, slew rate = 0.5 V/µs, V_{OUT} = 3.3 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 31. Line Transient



V_{EN}= 0 V to 2 V, V_{OUT} = 3.3 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 32. Start-Up With Enable



V_{IN} = 0 V to 5 V, V_{EN} = V_{IN}, V_{OUT} = 3.3 V, I_{OUT} = 0.5 A, C_{IN} = 1 µF, C_{OUT} = 1 µF

图 33. Start-Up With Enable Pin Tied to Input

7 Detailed Description

7.1 Overview

The TPS7A26 is an 18-V, low quiescent current, low-dropout (LDO) linear regulator. The low I_Q performance makes the TPS7A26 an excellent choice for battery-powered or line-power applications that are expected to meet increasingly stringent standby-power standards.

The 1% accuracy over temperature and power-good indication make this device an excellent choice for meeting a wide range of microcontroller power requirements.

For increased reliability, the TPS7A26 also incorporates overcurrent, overshoot pulldown, and thermal shutdown protection. The operating junction temperature is –40°C to +125°C, and adds margin for applications concerned with higher working ambient temperatures.

The TPS7A26 is available in a thermally enhanced WSON package.

7.2 Functional Block Diagram




图 34. Adjustable Version

Copyright © 2018–2019, Texas Instruments Incorporated

Functional Block Diagram (continued)




图 35. Fixed Version

7.3 Feature Description

7.3.1 Output Enable

The enable pin for the device is an active-high pin. The output voltage is enabled when the voltage of the enable pin is greater than the high-level input voltage of the EN pin and disabled with the enable pin voltage is less than the low-level input voltage of the EN pin. If independent control of the output voltage is not needed, connect the enable pin to the input of the device.

7.3.2 Dropout Voltage

Dropout voltage (V_{DO}) is defined as the input voltage minus the output voltage ($V_{IN} – V_{OUT}$) at the rated output current (I_{RATED}), where the pass transistor is fully on. I_{RATED} is the maximum I_{OUT} listed in the *Recommended Operating Conditions* table. The pass transistor is in the ohmic or triode region of operation, and acts as a switch. The dropout voltage indirectly specifies a minimum input voltage greater than the nominal programmed output voltage at which the output voltage is expected to stay in regulation. If the input voltage falls to less than the nominal output regulation, then the output voltage falls as well.

版权 © 2018–2019, Texas Instruments Incorporated

Feature Description (continued)

For a CMOS regulator, the dropout voltage is determined by the drain-source on-state resistance ($R_{DS(ON)}$) of the pass transistor. Therefore, if the linear regulator operates at less than the rated current, the dropout voltage for that current scales accordingly. Use Equation 1 to calculate the $R_{DS(ON)}$ of the device.

$$R_{DS(ON)} = \frac{V_{DO}}{I_{RATED}} \quad (1)$$

7.3.3 Current Limit

The device has an internal current limit circuit that protects the regulator during transient high-load current faults or shorting events. The current limit is a brickwall scheme. In a high-load current fault, the brickwall scheme limits the output current to the current limit (I_{CL}). I_{CL} is listed in the *Electrical Characteristics* table.

The output voltage is not regulated when the device is in current limit. When a current limit event occurs, the device begins to heat up because of the increase in power dissipation. When the device is in brickwall current limit, the pass transistor dissipates power [(V_{IN} – V_{OUT}) × I_{CL}]. If thermal shutdown is triggered, the device turns off. After the device cools down, the internal thermal shutdown circuit turns the device back on. If the output current fault condition continues, the device cycles between current limit and thermal shutdown. For more information on current limits, see the *Know Your Limits* application report.

Figure 36 shows a diagram of the current limit.




Figure 36. Current Limit

7.3.4 Undervoltage Lockout (UVLO)

The device has an independent undervoltage lockout (UVLO) circuit that monitors the input voltage, allowing a controlled and consistent turn on and off of the output voltage. To prevent the device from turning off if the input drops during turn on, the UVLO has hysteresis as specified in the *Electrical Characteristics* table.

7.3.5 Thermal Shutdown

The device contains a thermal shutdown protection circuit to disable the device when the junction temperature (T_J) of the pass transistor rises to $T_{SD(shutdown)}$ (typical). Thermal shutdown hysteresis assures that the device resets (turns on) when the temperature falls to $T_{SD(reset)}$ (typical).

The thermal time-constant of the semiconductor die is fairly short, thus the device may cycle on and off when thermal shutdown is reached until power dissipation is reduced. Power dissipation during startup can be high from large V_{IN} – V_{OUT} voltage drops across the device or from high inrush currents charging large output capacitors. Under some conditions, the thermal shutdown protection disables the device before startup completes.

Copyright © 2018–2019, Texas Instruments Incorporated

Feature Description (continued)

When the thermal limit is triggered with load currents near the value of the current limit, the output may oscillate prior to the output switching off.

For reliable operation, limit the junction temperature to the maximum listed in the *Recommended Operating Conditions* table. Operation above this maximum temperature causes the device to exceed its operational specifications. Although the internal protection circuitry of the device is designed to protect against thermal overall conditions, this circuitry is not intended to replace proper heat sinking. Continuously running the device into thermal shutdown or above the maximum recommended junction temperature reduces long-term reliability.

7.3.6 Power Good

The power-good (PG) pin is an open-drain output and can be connected to a regulated supply through an external pullup resistor. The maximum pullup voltage is listed as V_{PG} in the *Recommended Operating Conditions* table. For the PG pin to have a valid output, the voltage on the IN pin must be greater than $V_{UVLO(RISING)}$, as listed in the *Electrical Characteristics* table. When the V_{OUT} exceeds $V_{IT(PG,RISING)}$, the PG output is high impedance and the PG pin voltage pulls up to the connected regulated supply. When the regulated output falls below $V_{IT(PG,FALLING)}$, the open-drain output turns on and pulls the PG output low after a short deglitch time. If output voltage monitoring is not needed, the PG pin can be left floating or connected to ground.

By connecting a pullup resistor to an external supply, any downstream device can receive power-good (PG) as a logic signal that can be used for sequencing. Make sure that the external pullup supply voltage results in a valid logic signal for the receiving device.

The recommended maximum PG pin sink current ($I_{PG-SINK}$) and the leakage current into the PG pin ($I_{LKG(PG)}$) are listed in the *Electrical Characteristics* table.

The PG pullup voltage (V_{PG_PULLUP}), the desired minimum power-good output voltage ($V_{PG(MIN)}$), and $I_{LKG(PG)}$ limit the maximum PG pin pullup resistor value (R_{PG_PULLUP}). V_{PG_PULLUP}, the PG pin low-level output voltage ($V_{OL(PG)}$), and $I_{PG-SINK}$ limit the minimum R_{PG_PULLUP}. Maximum and minimum values for R_{PG_PULLUP} can be calculated from the following equations:

$$R_{PG_PULLUP(MAX)} = (V_{PG_PULLUP} – V_{PG(MIN)}) / I_{LKG(PG)_MAX} \quad (2)$$

$$R_{PG_PULLUP(MIN)} = (V_{PG_PULLUP} – V_{OL(PG)}) / I_{PG-SINK} \quad (3)$$

For example, if the PG pin is connected to a pullup resistor with a 3.3-V external supply, from Equation 2, $R_{PG_PULLUP(MAX)}$ is 11 MΩ. From Equation 3, $R_{PG_PULLUP(MIN)}$ is 5.8 kΩ.

7.3.7 Active Overshoot Pulldown Circuitry

This device has pulldown circuitry connected to V_{OUT}. This circuitry is a 100-μA current sink, in series with a 5.5-kΩ resistor, controlled by V_{EN}. When V_{EN} is below $V_{EN(LOW)}$, the pulldown circuitry is disabled and the LDO output is in high-impedance mode.

If the output voltage is more than 60 mV above nominal voltage when $V_{EN} \geq V_{EN(LOW)}$, the pulldown circuitry turns on and the output is pulled down until the output voltage is within 60 mV from the nominal voltage. This feature helps reduce overshoot during the transient response.

版权 © 2018–2019, Texas Instruments Incorporated

7.4 Device Functional Modes

7.4.1 Device Functional Mode Comparison

The *Device Functional Mode Comparison* table shows the conditions that lead to the different modes of operation. See the *Electrical Characteristics* table for parameter values.

Table 1. Device Functional Mode Comparison

OPERATING MODE	PARAMETER			
	V_{IN}	V_{EN}	I_{OUT}	T_J
Normal operation	$V_{IN} > V_{OUT(nom)} + V_{DO}$ and $V_{IN} > V_{IN(min)}$	$V_{EN} > V_{EN(HI)}$	$I_{OUT} < I_{OUT(max)}$	$T_J < T_{SD(shutdown)}$
Dropout operation	$V_{IN(min)} < V_{IN} < V_{OUT(nom)} + V_{DO}$	$V_{EN} > V_{EN(HI)}$	$I_{OUT} < I_{OUT(max)}$	$T_J < T_{SD(shutdown)}$
Disabled (any true condition disables the device)	$V_{IN} < V_{UVLO}$	$V_{EN} < V_{EN(LOW)}$	Not applicable	$T_J > T_{SD(shutdown)}$

7.4.2 Normal Operation

The device regulates to the nominal output voltage when the following conditions are met:

- The input voltage is greater than the nominal output voltage plus the dropout voltage ($V_{OUT(nom)} + V_{DO}$)
- The output current is less than the current limit ($I_{OUT} < I_{CL}$)
- The device junction temperature is less than the thermal shutdown temperature ($T_J < T_{SD}$)
- The enable voltage has previously exceeded the enable rising threshold voltage and has not yet decreased to less than the enable falling threshold

7.4.3 Dropout Operation

If the input voltage is lower than the nominal output voltage plus the specified dropout voltage, but all other conditions are met for normal operation, the device operates in dropout mode. In this mode, the output voltage tracks the input voltage. During this mode, the transient performance of the device becomes significantly degraded because the pass transistor is in the ohmic or triode region, and acts as a switch. Line or load transients in dropout can result in large output-voltage deviations.

When the device is in a steady dropout state (defined as when the device is in dropout, $V_{IN} < V_{OUT(NOM)} + V_{DO}$, directly after being in a normal regulation state, but *not* during startup), the pass transistor is driven into the ohmic or triode region. When the input voltage returns to a value greater than or equal to the nominal output voltage plus the dropout voltage ($V_{OUT(NOM)} + V_{DO}$), the output voltage can overshoot for a short period of time while the device pulls the pass transistor back into the linear region.

7.4.4 Disabled

The output of the device can be shutdown by forcing the voltage of the enable pin to less than the maximum EN pin low-level input voltage (see the *Electrical Characteristics* table). When disabled, the pass transistor is turned off and internal circuits are shutdown.

版权 © 2018–2019, Texas Instruments Incorporated

8 Application and Implementation

注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

8.1 Application Information

8.1.1 Adjustable Device Feedback Resistors

The adjustable-version device requires external feedback divider resistors to set the output voltage. V_{OUT} is set using the feedback divider resistors, R_1 and R_2, according to the following equation:

$$V_{OUT} = V_{FB} \times (1 + R_1 / R_2) \quad (4)$$

To ignore the FB pin current error term in the V_{OUT} equation, set the feedback divider current to 100x the FB pin current listed in the *Electrical Characteristics* table. This setting provides the maximum feedback divider series resistance, as shown in the following equation:

$$R_1 + R_2 \leq V_{OUT} / (I_{FB} \times 100) \quad (5)$$

8.1.2 Recommended Capacitor Types

The device is designed to be stable using low equivalent series resistance (ESR) capacitors at the input and output. Multilayer ceramic capacitors have become the industry standard for these types of applications and are recommended, but must be used with good judgment. Ceramic capacitors that employ X7R-, X5R-, and C0G-rated dielectric materials provide relatively good capacitive stability across temperature, whereas the use of Y5V-rated capacitors is discouraged because of large variations in capacitance.

Regardless of the ceramic capacitor type selected, the effective capacitance varies with operating voltage and temperature. As a rule of thumb, expect the effective capacitance to decrease by as much as 50%. The input and output capacitors recommended in the *Recommended Operating Conditions* table account for an effective capacitance of approximately 50% of the nominal value.

8.1.3 Input and Output Capacitor Requirements

Although an input capacitor is not required for stability, good analog design practice is to connect a capacitor from IN to GND. This capacitor counteracts reactive input sources and improves transient response, input ripple, and PSRR. An input capacitor is recommended if the source impedance is more than 0.5 Ω. A higher value capacitor may be necessary if large, fast load transient or line transients are anticipated or if the device is located several inches from the input power source.

Dynamic performance of the device is improved with the use of an output capacitor. Use an output capacitor within the range specified in the *Recommended Operating Conditions* table for stability.

The effective output capacitance value is recommended to not exceed 50 µF.

8.1.4 Reverse Current

Excessive reverse current can damage this device. Reverse current flows through the intrinsic body diode of the pass transistor instead of the normal conducting channel. At high magnitudes, this current flow degrades the long-term reliability of the device.

Conditions where reverse current can occur are outlined in this section, all of which can exceed the absolute maximum rating of $V_{OUT} \leq V_{IN} + 0.3$ V.

- If the device has a large C_{OUT} and the input supply collapses with little or no load current
- The output is biased when the input supply is not established
- The output is biased above the input supply

Copyright © 2018–2019, Texas Instruments Incorporated

Application Information (continued)

If reverse current flow is expected in the application, external protection is recommended to protect the device. Reverse current is not limited in the device, so external limiting is required if extended reverse voltage operation is anticipated.

Figure 37 shows one approach for protecting the device.




Figure 37. Example Circuit for Reverse Current Protection Using a Schottky Diode

图 38 shows another, more commonly used, approach in high input voltage applications.




图 38. Reverse Current Prevention Using A Diode Before the LDO

8.1.5 Feed-Forward Capacitor (C_{FF})

For the adjustable-voltage version device, a feed-forward capacitor (C_{FF}) can be connected from the OUT pin to the FB pin. C_{FF} improves transient, noise, and PSRR performance, but is not required for regulator stability. Recommended C_{FF} values are listed in the *Recommended Operating Conditions* table. A higher capacitance C_{FF} can be used; however, the startup time increases. For a detailed description of C_{FF} tradeoffs, see the *Pros and Cons of Using a Feedforward Capacitor with a Low-Dropout Regulator* application report.

8.1.6 Power Dissipation (P_D)

Circuit reliability requires consideration of the device power dissipation, location of the circuit on the printed circuit board (PCB), and correct sizing of the thermal plane. The PCB area around the regulator must have few or no other heat-generating devices that cause added thermal stress.

To first-order approximation, power dissipation in the regulator depends on the input-to-output voltage difference and load conditions. Equation 6 calculates power dissipation (P_D).

$$P_D = (V_{IN} - V_{OUT}) \times I_{OUT} \quad (6)$$

NOTE

Power dissipation can be minimized, and therefore greater efficiency can be achieved, by correct selection of the system voltage rails. For the lowest power dissipation use the minimum input voltage required for correct output regulation.

版权 © 2018–2019, Texas Instruments Incorporated

Application Information (continued)

For devices with a thermal pad, the primary heat conduction path for the device package is through the thermal pad to the PCB. Solder the thermal pad to a copper pad area under the device. This pad area must contain an array of plated vias that conduct heat to additional copper planes for increased heat dissipation.

The maximum power dissipation determines the maximum allowable ambient temperature (T_A) for the device. According to Equation 7, power dissipation and junction temperature are most often related by the junction-to-ambient thermal resistance ($R_{\theta JA}$) of the combined PCB and device package and the temperature of the ambient air (T_A).

$$T_J = T_A + (R_{\theta JA} \times P_D) \quad (7)$$

Thermal resistance ($R_{\theta JA}$) is highly dependent on the heat-spreading capability built into the particular PCB design, and therefore varies according to the total copper area, copper weight, and location of the planes. The junction-to-ambient thermal resistance listed in the *Thermal Information* table is determined by the JEDEC standard PCB and copper-spreading area, and is used as a relative measure of package thermal performance.

8.1.7 Estimating Junction Temperature

The JEDEC standard now recommends the use of psi (Ψ) thermal metrics to estimate the junction temperatures of the linear regulator when in-circuit on a typical PCB board application. These metrics are not thermal resistance parameters and instead offer a practical and relative way to estimate junction temperature. These psi metrics are determined to be significantly independent of the copper area available for heat-spreading. The *Thermal Information* table lists the primary thermal metrics, which are the junction-to-top characterization parameter (ψ_{JT}) and junction-to-board characterization parameter (ψ_{JB}). These parameters provide two methods for calculating the junction temperature (T_J). As described in , use the junction-to-top characterization parameter (ψ_{JT}) with the temperature at the center-top of device package (T_T) to calculate the junction temperature. As described in , use the junction-to-board characterization parameter (ψ_{JB}) with the PCB surface temperature 1 mm from the device package (T_B) to calculate the junction temperature.

$$T_J = T_T + \psi_{JT} \times P_D$$

where:

- P_D is the dissipated power
- T_T is the temperature at the center-top of the device package

(8)

$$T_J = T_B + \psi_{JB} \times P_D$$

where

- T_B is the PCB surface temperature measured 1 mm from the device package and centered on the package edge

(9)

For detailed information on the thermal metrics and how to use them, see the *Semiconductor and IC Package Thermal Metrics* application report.

Application Information (continued)

8.1.8 Special Consideration for Line Transient

During a line transient, the response of this LDO to a very large or fast input voltage change can cause a brief shutdown lasting up to a few hundred microseconds from the voltage transition. This shutdown can be avoided by reducing the voltage step size, increasing the transition time, or a combination of both. 图 39 provides a boundary to follow to avoid this behavior. If necessary, reduce slew rate and the voltage step size to stay below the curve.




图 39. Recommended Input Voltage Step and Slew Rate in a Line transient

8.2 Typical Application




图 40. Generating a 5-V Rail From a Multicell Power Bank

8.2.1 Design Requirements

表 2 summarizes the design requirements for 图 40.

表 2. Design Parameters

PARAMETER	DESIGN VALUES
V_{IN}	7.2 V
V_{OUT}	5 V ±1%
$I_{(IN)}$ (no load)	< 5 µA
I_{OUT} (max)	330 mA
T_A	70°C (max)

版权 © 2018–2019, Texas Instruments Incorporated

8.2.2 Detailed Design Procedure

Select a 5-V output, fixed or adjustable device to generate the 5-V rail. The fixed-version LDO has internal feedback divider resistors, and thus has lower quiescent current. The adjustable-version LDO requires external feedback divider resistors, and is described in the *Selecting Feedback Divider Resistors* section.

8.2.2.1 Transient Response

As with any regulator, increasing the output capacitor value reduces over- and undershoot magnitude, but increases transient response duration.

8.2.2.2 Selecting Feedback Divider Resistors

For this design example, V_{OUT} is set to 5 V. The following equations set the output voltage:

$$V_{OUT} = V_{FB} \times (1 + R_1 / R_2) \quad (10)$$

$$R_1 + R_2 \leq V_{OUT} / (I_{FB} \times 100) \quad (11)$$

For improved output accuracy, use Equation 11 and $I_{FB(TYP)}$ = 10 nA as listed in the *Electrical Characteristics* table to calculate the upper limit for series feedback resistance, $R_1 + R_2 \leq 5$ MΩ.

The control-loop error amplifier drives the FB pin to the same voltage as the internal reference (V_{FB} = 1.24 V as listed in the *Electrical Characteristics* table). Use Equation 10 to determine the ratio of R_1 / R_2 = 3.03. Use this ratio and solve Equation 11 for R_2. Now calculate the upper limit for $R_2 \leq 1.24$ MΩ. Select a standard value resistor of R_2 = 1.18 MΩ.

Reference Equation 10 and solve for R_1:

$$R_1 = (V_{OUT} / V_{FB} - 1) \times R_2 \quad (12)$$

From 公式 12, R_1 = 3.64 MΩ can be determined. Select a standard resistor value for R_1 = 3.6 MΩ. From Equation 10, select V_{OUT} = 5.023 V.

8.2.2.3 Thermal Dissipation

Junction temperature can be determined using the junction-to-ambient thermal resistance ($R_{\theta JA}$) and the total power dissipation (P_D). Use 公式 13 to calculate the power dissipation. Multiply P_D by $R_{\theta JA}$ and add the ambient temperature (T_A), as 公式 14 shows, to calculate the junction temperature (T_J).

$$P_D = (I_{GND} + I_{OUT}) \times (V_{IN} - V_{OUT}) \quad (13)$$

$$T_J = R_{\theta JA} \times P_D + T_A \quad (14)$$


公式 15 calculates the maximum ambient temperature. 公式 16 calculates the maximum ambient temperature for typical design applications.

$$T_{A(MAX)} = T_{J(MAX)} - (R_{\theta JA} \times P_D) \quad (15)$$

$$T_{A(MAX)} = 125°C - [73.3°C/W \times (7.2\ V - 5\ V) \times 0.33\ A] = 71.8°C \quad (16)$$

版权 © 2018–2019, Texas Instruments Incorporated

8.2.3 Application Curve



I_{OUT} = 1 mA to 0.33 A, slew rate = 0.5 A/µs,
V_{OUT} = 5 V, V_{IN} = 7.2 V, C_{IN} = 1 µF, C_{OUT} = 1 µF, C_{FF} = 0 µF

图 41. TPS7A26 Load Transient 1 mA to 330 mA)

版权 © 2018–2019, Texas Instruments Incorporated

9 Power Supply Recommendations

The device is designed to operate with an input supply range of 2.4 V to 18 V. If the input supply is noisy, additional input capacitors with low ESR can help improve output noise performance.

10 Layout

10.1 Layout Guidelines

- Place input and output capacitors as close to the device pins as possible
- Use copper planes for device connections to optimize thermal performance
- Place thermal vias around the device and under the DRV thermal pad to distribute heat

10.2 Layout Examples




图 42. Adjustable Version Layout Example




图 43. Fixed Version Layout Example

11 器件和文档支持

11.1 器件支持

11.1.1 器件命名规则

表 3. 器件命名规则(1)

产品	V_{OUT}
TPS7A26**xx(x)yyyz**	**xx(x)** 是标称输出电压。对于分辨率为 100mV 的输出电压，订购编号使用两位数字；对于分辨率为 50mV 的输出电压，则使用三位数字（例如，28 = 2.8V；125 = 1.25V）。01 表示可调节输出版本。 **yyy** 为封装标识符。 **z** 为封装数量。R 表示大数量卷带，T 表示小数量卷带。

(1) 要获得最新的封装和订货信息，请参阅本文档末尾的封装选项附录，或者访问器件产品文件夹，此文件夹位于www.ti.com.cn内。

11.2 文档支持

11.2.1 相关文档

- 德州仪器 (TI)，*《具有电源正常状态指示功能的 TPS7A25 300mA、18V、超低 IQ、低压降线性稳压器》* 数据表
- 德州仪器 (TI)，*《了解限制》* 应用报告
- 德州仪器 (TI)，*《使用前馈电容器和低压降稳压器的优缺点》*应用报告

11.3 接收文档更新通知

要接收文档更新通知，请导航至 ti.com. 上的器件产品文件夹。单击右上角的*通知我*进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

11.4 社区资源

TI E2E™ support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

11.5 商标

E2E is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

11.6 静电放电警告

ESD 可能会损坏该集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理措施和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。 精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

11.7 Glossary

SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

12 机械、封装和可订购信息

以下页面包含机械、封装和可订购信息。这些信息是指定器件的最新可用数据。数据如有变更，恕不另行通知，且不会对此文档进行修订。如需获取此数据表的浏览器版本，请查阅左侧的导航栏。

版权 © 2018–2019, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS7A2601DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A2601DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A2601DRVT	Active	Production	WSON (DRV) | 6	250 | SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A2601DRVT.A	Active	Production	WSON (DRV) | 6	250 | SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A2601DRVTG4	Active	Production	WSON (DRV) | 6	250 | SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A2601DRVTG4.A	Active	Production	WSON (DRV) | 6	250 | SMALL T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7A26
TPS7A26125DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X9P
TPS7A26125DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X9P
TPS7A2618DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X8P
TPS7A2618DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X8P
TPS7A2625DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X7P
TPS7A2625DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1X7P
TPS7A2633DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WRP
TPS7A2633DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WRP
TPS7A2633DRVRG4	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WRP
TPS7A2633DRVRG4.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WRP
TPS7A2650DRVR	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WPP
TPS7A2650DRVR.A	Active	Production	WSON (DRV) | 6	3000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	1WPP

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.


Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS7A2601DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2601DRVT	WSON	DRV	6	250	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2601DRVTG4	WSON	DRV	6	250	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A26125DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2618DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2625DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2633DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2633DRVRG4	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS7A2650DRVR	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS7A2601DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2601DRVT	WSON	DRV	6	250	205.0	200.0	33.0
TPS7A2601DRVTG4	WSON	DRV	6	250	205.0	200.0	33.0
TPS7A26125DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2618DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2625DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2633DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2633DRVRG4	WSON	DRV	6	3000	205.0	200.0	33.0
TPS7A2650DRVR	WSON	DRV	6	3000	205.0	200.0	33.0

DRV 6 WSON - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.




NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.
4. Minimum 0.1 mm solder wetting on pin side wall. Available for wettable flank version only.



LAND PATTERN EXAMPLE
SCALE:25X




SOLDER MASK DETAILS

4222173/D 09/2026

NOTES: (continued)

5. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
6. Vias are optional depending on application, refer to device data sheet. If some or all are implemented, recommended via locations are shown.



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD #7
88% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE
SCALE:30X

4222173/D 09/2026

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做出任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 TI 销售条款)、TI 通用质量指南 或 ti.com 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。 除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2026，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月