


# PMP30122RevA Test Results

---

1	Startup .....	2
2	Shutdown .....	2
3	Efficiency .....	3
4	Load Regulation .....	4
5	Ripple Voltage .....	5
6	Control Loop Frequency Response .....	7
7	Load Transients .....	8
8	Miscellaneous Waveforms .....	10
8.1	Switch node (D2) .....	10
9	Thermal Performance .....	11


Topology: Nonsynchronous Buck Converter  
Device: TPS54160A, controller & driver w/ integrated FET

- *measurements taken at 48V input voltage and 28V output voltage*
- *switching frequency measured 376kHz*




## 1 Startup

The startup waveform is shown in Figure 1. The input voltage was set to 48V, with 500mA load at the output. Startup takes around 15ms.



## 2 Shutdown

The shutdown waveform is shown in Figure 2. The input voltage was set to 48V, with 1A load on the output.



### 3 Efficiency

The efficiency is shown in Figure 3 below. The input voltage was set to 48V.




Figure 3

- at nominal load 500mA efficiency is **96.57%**
- at light load condition 100mA efficiency is **92.98%**
- at peak load 1000mA efficiency is **96.15%**
  
- peak efficiency of 96.60% is around 600mA load,
- efficiency is >96% in a range of 300mA to 1000mA

## 4 Load Regulation

The load regulation of the output is shown in **Figure 4** below. The input voltage was set to 48V.






Figure 4


Deviation by load in between 50mA to 1000mA load is 30mV, so around 0.1%

## 5 Ripple Voltage


The output ripple voltage is shown in Figure 5 and 6. The images were taken with 1A load and 48V input. **Ripple is almost sinusoidal <20mVpp, NO switching spikes at full bandwidth**



The filtered input ripple voltage is shown in Figure 7. The image was taken with 1A load and 48V at the input. **The input filter attenuates the reflected converter ripple <10mVpp.**



The unfiltered input ripple voltage 400mVpp at power stage input C7, C8 is shown in Figure 8. The image was taken with 1A load and 48V at the input. For sensitive bus filter is recommended.



## 6 Control Loop Frequency Response

Figure 9 below shows the loop response with 1A load and 48V input, Fco 11.7kHz:




Figure 9

Phase Margin: 47.71°

Gain Margin: 17.5 dB

## 7 Load Transients

Figure 10 shows the response to load transients. The load is switching from 0.1A to 0.6A with 500 Hz frequency. The input voltage was set to 48V. **Deviation 2.5%**




Figure 10

Figure 11 shows a load transient from 0.25A to 0.5A with 500 Hz frequency. The input voltage was set to 48V. **Deviation <1.5% for standard transient 50%**.




Figure 11

Figure 12 shows a load transient from 0.1A to 1A with 500 Hz frequency. The input voltage was set to 48V. **Deviation 4% for a 90% transient to peak load condition 1000mA.**





Figure 12

## 8 Miscellaneous Waveforms

### 8.1 Switch node (D2)


With input voltage set to 48V and 1A peak output current the drain waveform can be observed at the switch node – **full bandwidth**:




**dedicated low impedance layout results in drain waveform w/out RF ringing at switch node**

## 9 Thermal Performance

Thermal image at 48V input and 500mA nominal load after 30 min continuous operation [Rt = 25°C] – temperature rise dT slightly more than 20K at nominal load:



Thermal image at 48V input and 1000mA peak load after 30 min continuous operation [Rt = 25°C] – temperature rise dT around 45K at peak load:



## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2021, Texas Instruments Incorporated