

Notes:

- 1) Refer to BOM for stuffing options.
- 2) Observe polarity on diodes and capacitors.

REVISIONS			
REV.	REV.	DESCRIPTION	DATE APPROVED

D

D

C


C

B

B

A

A



Primary Side

APPLICATION USED ON	NEXT ASSY.	CONTRACT NO.	DWN: www.WSTScorp.com	11/14	TEXAS INSTRUMENTS ASSEMBLY DRAWING, C2000 Solar Micro Inverter, PPD		
		UNLESS OTHERWISE SPECIFIED	CHK:				
		1. TOLERANCES: LINEAR = ± 0.26 (.010) ANGULAR = ± 0.50 °	P.E.:				
		2. ALL DIMENSIONS ARE IN MM (INCHES).	DES.ENG.:				
		3. INTERPRET DRAWING IN ACCORDANCE WITH DOD-STD-100.	P.C.:				
MATERIAL: SEE NOTE FINISH: SEE NOTE	DO NOT SCALE DRAWING	C.M.:	Q.C.:				
		REL.:					
		MFG.:					
		ENG.MCR.:					
		OTHER:					
		OTHER:					
		OTHER:					
		SIZE C	CAGE CODE NO.	DRAWING NO. C2000SolarMicroInverterPPD	REV: 3.0		
		SCALE: 1:1			SHEET 1 OF 2		