

**UC1842/UC1842A FAMILY  
SUMMARY OF FUNCTIONAL DIFFERENCES**

The industry standard series of UC1842/43/44/45 devices has been improved for higher frequency, off-line power supplies. This new "A" series of controllers,

UC1842A/43A/44A/45A, feature three major advantages over their predecessors as shown in the summary below.

**Start Up Current**

	<b>UC1842/45</b>	<b>UC1842A/45A</b>
<b>Typical (T<sub>J</sub> = 25°C)</b>	0.5ma	0.3ma
<b>Maximum (T<sub>J</sub> = 25°C)</b>	1.0ma	0.5ma

**Oscillator Discharge Current**

	<b>UC1842/45</b>			<b>UC1842A/45A</b>		
	MIN	TYP	MAX	MIN	TYP	MAX
<b>At T<sub>J</sub> = 25°C (mA)</b>	7	10	13	7.8	8.3	8.8
<b>Overtemp. Range</b>	6	—	14	7.5	—	8.8

**Output Saturation**

	<b>UC1842/45</b>	<b>UC1842/45A</b>
<b>During UVLO</b>	1V @ 0.2ma	1V @ 10ma

The reduced start-up current is of particular concern in offline supplies where the IC is "powered-up" from the high voltage DC rail, then bootstrapped to an auxiliary winding on the main transformer. Power is then dissipated in the start-up resistor which is sized by the IC's start-up current. Lowering this by 50% in the "A" version family will reduce the resistors power loss by the same percentage.

Precision operation at high frequencies with an accurate maximum duty cycle can now be obtained with the "A"

family of devices due to its trimmed oscillator discharge current. This nullifies the effects of production variations in the initial discharge current or deadtime.

Another significant improvement has been made in the output section, specifically to the lower totem-pole transistor's operation during undervoltage lockout. The "A" series of devices prevent the power MOSFETs from parasitically turning-on at powerup due to the "Miller" effect. This new technique allows the IC to sink higher currents at lower saturation voltages than it's predecessors.

## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

**CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.**

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.