CD4069UB CMOS ヘクス・インバータ

1 特長

- 標準化された対称出力特性
- 中程度の速度での動作： 10V で t_{PHL}、t_{PLH} = 30ns (標準値)
- 20V で静止電流を 100% テスト済み
- パッケージの温度範囲全体で 18V 時に最大入力電流 1μA、25℃ で 18V 時に 100nA
- JEDEC 暫定標準 No. 13B、*「B シリーズ CMOS デバイスの記述の標準仕様」*のすべての要件に適合

2 アプリケーション

- 論理反転
- パルス成形
- 発振器
- 高入力インピーダンスのアンプ

3 概要


CD4069UB デバイスは、6 つの CMOS インバータ回路で構成されます。これらのデバイスは、(CD4009 や CD4049 ヘクス・インバータなどが持つ) 中程度の電力の TTL 駆動や論理レベル変換能力、およびバッファを必要としない、すべての汎用インバータ用途を目的としています。

製品情報(1)

型番	パッケージ(ピン数)	本体サイズ(公称)
CD4069UBE	PDIP (14)	19.30mm×6.35mm
CD4069UBF	CDIP (14)	19.56mm×6.67mm
CD4069UBM	SOIC (14)	8.65mm×3.91mm
CD4069UBNSR	SO (14)	10.30mm×5.30mm
CD4069UBPW	TSSOP (14)	5.00mm×4.40mm

(1) 提供されているすべてのパッケージについては、データシートの末尾にある注文情報を参照してください。

CD4069UB の機能図



V_{DD} = Pin 14
V_{SS} = Pin 7

英語版のTI製品についての情報を翻訳したこの資料は、製品の概要を確認する目的で便宜的に提供しているものです。該当する正式な英語版の最新情報は、www.ti.comで閲覧でき、その内容が常に優先されます。TIでは翻訳の正確性および妥当性につきましては一切保証いたしません。実際の設計などの前には、必ず最新版の英語版をご参照くださいますようお願いいたします。

目次

1 特長 ... 1
2 アプリケーション ... 1
3 概要 ... 1
4 改訂履歴 ... 2
5 **Pin Configuration and Functions** ... 3
6 **Specifications** ... 4
6.1 Absolute Maximum Ratings ... 4
6.2 ESD Ratings ... 4
6.3 Recommended Operating Conditions ... 4
6.4 Thermal Information ... 4
6.5 Electrical Characteristics – Dynamic ... 5
6.6 Electrical Characteristics – Static ... 5
6.7 Typical Characteristics ... 8
7 **Parameter Measurement Information** ... 9
8 **Detailed Description** ... 13
8.1 Overview ... 13
8.2 Functional Block Diagram ... 13
8.3 Feature Description ... 13
8.4 Device Functional Modes ... 13
9 **Application and Implementation** ... 14
9.1 Application Information ... 14
9.2 Typical Application ... 14
10 **Power Supply Recommendations** ... 16
11 **Layout** ... 16
11.1 Layout Guidelines ... 16
11.2 Layout Example ... 16
12 デバイスおよびドキュメントのサポート ... 17
12.1 デバイス・サポート ... 17
12.2 ドキュメントのサポート ... 17
12.3 コミュニティ・リソース ... 17
12.4 商標 ... 17
12.5 静電気放電に関する注意事項 ... 17
12.6 Glossary ... 17
13 メカニカル、パッケージ、および注文情報 ... 17

4 改訂履歴

資料番号末尾の英字は改訂を表しています。その改訂履歴は英語版に準じています。

Revision D (February 2016) から **Revision E** に変更 **Page**

- 「特長」の 2 番目の箇条書き項目で、t_{PHL} から余分な文字「–」を削除 ... 1
- Corrected V_I spec MIN/MAX values in the Abs Max Ratings table ... 4
- Corrected parameter I_{DD} max term to I_{DD} in the Elec Characteristics table ... 5
- Corrected parameter I_{OL} min term to I_{OL} in the Elec Characteristics table ... 5
- Corrected parameter V_{OL} max term to V_{OL} in the Elec Characteristics table ... 6
- Corrected parameter V_{IL} max term to V_{IL} in the Elec Characteristics table ... 6
- Corrected parameter V_{IH} min term to V_{IH} in the Elec Characteristics table ... 6
- Corrected parameter I_{IN} max term to I_{IN} in the Elec Characteristics table ... 7
- Added Y-axis label to Figure 1 image object ... 8
- Changed text string from " $–t_{PHL}$" to "of t_{PHL}" in the Feature Description paragraph. ... 13


Revision C (August 2003) から **Revision D** に変更 **Page**

- 「*ESD定格*」の表、「*機能説明*」セクション、「*デバイスの機能モード*」セクション、「*アプリケーションと実装*」セクション、「*電源に関する推奨事項*」セクション、「*レイアウト*」セクション、「*デバイスおよびドキュメントのサポート*」セクション、「*メカニカル、パッケージ、および注文情報*」セクションを追加 ... 1

Copyright © 1998–2019, Texas Instruments Incorporated

5 Pin Configuration and Functions

D, J, N, NS, and PW Packages
14-Pin PDIP, CDIP, SOIC, SO, and TSSOP
Top View



Pin Functions

PIN		I/O	DESCRIPTION
NAME	NO.		
A	1	I	A input
B	3	I	B input
C	5	I	C input
D	9	I	D input
E	11	I	E input
F	13	I	F input
G = $\overline{A}$	2	O	G output
H = $\overline{B}$	4	O	H output
I = $\overline{C}$	6	O	I output
J = $\overline{D}$	8	O	J output
K = $\overline{E}$	10	O	K output
L = $\overline{F}$	12	O	L output
V_{DD}	14	—	Positive supply
V_{SS}	7	—	Negative supply

Copyright © 1998–2019, Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

			MIN	MAX	UNIT
V_{DD}	DC supply-voltage (voltages referenced to V_{SS} terminal)		–0.5	20	V
V_I	Input voltage, all inputs		–0.5	V_{DD} + 0.5	V
I_{IK}	DC input current, any one input		–10	10	mA
P_D	Power dissipation per package	–55°C to 100°C		500	mW
		100°C to 125°C	12	200	
	Device dissipation per output transistor	Full range (all package types)		100	mW
	Lead temperature(2)			265	°C
T_J	Junction temperature			150	°C
T_{stg}	Storage temperature		–65	150	°C

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) During soldering at distance 1/16 inch ± 1/32 inch (1.59 mm ± 0.79 mm) from case for 10 s maximum

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001(1)	±500	V
		Charged-device model (CDM), per JEDEC specification JESD22-C101(2)	±200	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V_{DD}	Supply voltage	3	18	V
T_A	Operating temperature	–55	125	°C

6.4 Thermal Information

THERMAL METRIC(1)		CD4069UB					UNIT
		D (SOIC)	J (CDIP)	N (PDIP)	NS (SO)	PW (TSSOP)	
		14 PINS	14 PINS	14 PINS	14 PINS	14 PINS	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	94.9	—	57.9	91.2	122.1	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	56.4	28.5	45.5	48.8	50.8	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	49.2	—	37.7	50	63.8	°C/W
ψ_{JT}	Junction-to-top characterization parameter	21.1	—	30.6	15	6.3	°C/W
ψ_{JB}	Junction-to-board characterization parameter	48.9	—	37.6	49.6	63.3	°C/W
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	N/A	N/A	N/A	N/A	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, SPRA953.

Copyright © 1998–2019, Texas Instruments Incorporated

6.5 Electrical Characteristics – Dynamic

T_A = 25°C; input t_r, t_f = 20 ns; C_L = 50 pF; R_L = 200 kΩ (unless otherwise noted)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_{PLH}, t_{PHL}	Propagation delay time	V_{DD} (V) = 5		55	110	ns
		V_{DD} (V) = 10		30	60	
		V_{DD} (V) = 15		25	50	
t_{THL}, t_{TLH}	Transition time	V_{DD} (V) = 5		100	200	ns
		V_{DD} (V) = 10		50	100	
		V_{DD} (V) = 15		40	80	
C_{IN}	Input capacitance	Any input		10	15	pF

6.6 Electrical Characteristics – Static

T_A = 25°C; input t_r, t_f = 20 ns; C_L = 50 pF; R_L = 200 kΩ (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
I_{DD}	Quiescent device current	V_{IN} = 0V or 5 V , V_{DD} = 5 V	T_A = –55°C			0.25	µA
			T_A = –40°C			0.25	
			T_A = 25°C		0.01	0.25	
			T_A = 85°C			7.5	
			T_A = 125°C			7.5	
		V_{IN} = 0 or 10 V, V_{DD} = 10 V	T_A = –55°C			0.5	
			T_A = –40°C			0.5	
			T_A = 25°C		0.01	0.5	
			T_A = 85°C			15	
			T_A = 125°C			15	
		V_{IN} = 0 or 15 V, V_{DD} = 15 V	T_A = –55°C			1	
			T_A = –40°C			1	
			T_A = 25°C		0.01	1	
			T_A = 85°C			30	
			T_A = 125°C			30	
		V_{IN} = 0 or 20 V, V_{DD} = 20 V	T_A = –55°C			5	
			T_A = –40°C			5	
			T_A = 25°C		0.02	5	
			T_A = 85°C			150	
			T_A = 125°C			150	
I_{OL}	Output low (sink) current	V_O = 0.4 V, V_{IN} = 5 V, V_{DD} = 5 V	T_A = –55°C	0.64			mA
			T_A = –40°C	0.61			
			T_A = 25°C	0.51	1		
			T_A = 85°C	0.42			
			T_A = 125°C	0.36			
		V_O = 0.5 V, V_{IN} = 10 V, V_{DD} = 10 V	T_A = –55°C	1.6			
			T_A = –40°C	1.5			
			T_A = 25°C	1.3	2.6		
			T_A = 85°C	1.1			
			T_A = 125°C	0.9			
		V_O = 1.5 V, V_{IN} = 15 V, V_{DD} = 15 V	T_A = –55°C	4.2			
			T_A = –40°C	4			
			T_A = 25°C	3.4	6.8		
			T_A = 85°C	2.8			
			T_A = 125°C	2.4			

Copyright © 1998–2019, Texas Instruments Incorporated

Electrical Characteristics – Static (continued)

T_A = 25°C; input t_r, t_f = 20 ns; C_L = 50 pF; R_L = 200 kΩ (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
I_{OH}	Output high (source) current	V_O = 4.6 V, V_{IN} = 0 V, V_{DD} = 5 V	T_A = –55°C	–0.64			mA
			T_A = –40°C	–0.61			
			T_A = 25°C	–0.51	–1		
			T_A = 85°C	–0.42			
			T_A = 125°C	–0..36			
		V_O = 2.5 V, V_{IN} = 0 V, V_{DD} = 5 V	T_A = –55°C	–2			
			T_A = –40°C	–1.8			
			T_A = 25°C	–1.6	–3.2		
			T_A = 85°C	–1.3			
			T_A = 125°C	–1.15			
		V_O = 9.5 V, V_{IN} = 0 V, V_{DD} = 10 V	T_A = –55°C	–1.6			
			T_A = –40°C	–1.5			
			T_A = 25°C	–1.3	–2.6		
			T_A = 85°C	–1.1			
			T_A = 125°C	–0.9			
		V_O = 13.5 V, V_{IN} = 0 V, V_{DD} = 15 V	T_A = –55°C	–4.2			
			T_A = –40°C	–4			
			T_A = 25°C	–3.4	–6.8		
			T_A = 85°C	–2.8			
			T_A = 125°C	–2.4			
V_{OL}	Low-level output voltage	V_{IN} = 5 V, V_{DD} = 5 V	T_A = 25°C		0	0.05	V
			All other temperatures			0.05	
		V_{IN} = 10 V, V_{DD} = 10 V	T_A = 25°C		0	0.05	
			All other temperatures			0.05	
		V_{IN} = 15 V, V_{DD} = 15 V	T_A = 25°C		0	0.05	
			All other temperatures			0.05	
V_{OH}	High-level output voltage	V_{IN} = 0 V, V_{DD} = 5 V	T_A = 25°C	4.95	5		V
			All other temperatures	4.95			
		V_{IN} = 0 V, V_{DD} = 10 V	T_A = 25°C	9.95	10		
			All other temperatures	9.95			
		V_{IN} = 0 V, V_{DD} = 15 V	T_A = 25°C	14.95	15		
			All other temperatures	14.95			
V_{IL}	Input low voltage	V_O = 4.5 V, V_{DD} = 5 V, all temperatures				1	V
		V_O = 9 V, V_{DD} = 10 V, all temperatures				2	
		V_O = 13.5 V, V_{DD} = 15 V, all temperatures				2.5	
V_{IH}	Input high voltage	V_O = 0.5 V, V_{DD} = 5 V, all temperatures		4			V
		V_O = 1 V, V_{DD} = 10 V, all temperatures		8			
		V_O = 1.5 V, V_{DD} = 15 V, all temperatures		12.5			

Copyright © 1998–2019, Texas Instruments Incorporated

Electrical Characteristics – Static (continued)

T_A = 25°C; input t_r, t_f = 20 ns; C_L = 50 pF; R_L = 200 kΩ (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
I_{IN}	Input current	V_{IN} = 0 V to 18 V, V_{DD} = 18 V	T_A = –55°C			±01	µA
			T_A = –40°C			±01	
			T_A = 25°C		$±10^{-5}$	±1	
			T_A = 85°C			±1	
			T_A = 125°C			±1	

Copyright © 1998–2019, Texas Instruments Incorporated

6.7 Typical Characteristics




Figure 1. Minimum and Maximum Voltage Transfer Characteristics




Figure 2. Typical Voltage Transfer Characteristics as a Function of Temperature




Figure 3. Typical Current and Voltage Transfer Characteristics




Figure 4. Typical Output Low (Sink) Current Characteristics




Figure 5. Minimum Output Low (Sink) Current Characteristics




Figure 6. Typical Output High (Source) Current Characteristics

Copyright © 1998–2019, Texas Instruments Incorporated

Typical Characteristics (continued)




Figure 7. Minimum Output High (Source) Current Characteristics




Figure 8. Typical Propagation Delay Time vs Load Capacitance




Figure 9. Typical Propagation Delay Time vs Supply Voltage

7 Parameter Measurement Information




Figure 10. Schematic Diagram of One of Six Identical Inverters

Copyright © 1998–2019, Texas Instruments Incorporated




Figure 11. Quiescent Device Current Test Circuit




Figure 12. Noise Immunity Test Circuit




Figure 13. Input Leakage Current Test Circuit

Copyright © 1998–2019, Texas Instruments Incorporated




Figure 14. Dynamic Electrical Characteristics Test Circuit and Waveform




Figure 15. Typical Crystal Oscillator Circuit




Figure 16. High-Input Impedance Amplifier





Figure 17. Typical RC Oscillator Circuit

Copyright © 1998–2019, Texas Instruments Incorporated



Upper Switching Point :

$$V_P = \frac{R_S + R_f}{R_f} \times \frac{V_{DD}}{2}$$

Lower Switching Point :

$$V_N = \frac{R_f - R_S}{R_f} \times \frac{V_{DD}}{2}$$

$$R_f > R_S$$

Figure 18. Input Pulse Shaping Circuit




Figure 19. Dynamic Power Dissipation Test Circuit


Copyright © 1998–2019, Texas Instruments Incorporated

8 Detailed Description

8.1 Overview

The CD4069UB device has six inverter circuits. The recommended operating range is from 3 V to 18 V. The CD4069UB-series types are supplied in 14-pin hermetic dual-in-line ceramic packages (F3A suffix), 14-pin dual-in-line plastic packages (E suffix), 14-pin small-outline packages (M, MT, M96, and NSR suffixes), and 14-pin thin shrink small-outline packages (PW and PWR suffixes).

8.2 Functional Block Diagram



8.3 Feature Description

CD4069UB has standardized symmetrical output characteristics and a wide operating voltage range from 3 V to 18 V with quiescent current tested at 20 V. This has a medium operation speed of t_{PHL}, t_{PLH} = 30 ns (typical) at 10 V. The operating temperature is from –55°C to 125°C. CB4069B meets all requirements of JEDEC tentative standard No. 13B, *Standard Specifications for Description of B Series CMOS Devices*.

8.4 Device Functional Modes

Table 1 shows the functional modes for CD4069UB.

Table 1. Function Table

INPUT A, B, C, D, E, F	OUTPUT G, H, I, J, K, L
H	L
L	H

Copyright © 1998–2019, Texas Instruments Incorporated

9 Application and Implementation


NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

9.1 Application Information

The CD4069UB device has a low input current of 1 µA at 18 V over full package-temperature range and 100 nA at 18 V, 25°C. This device has a wide operating voltage range from 3 V to 18 V and used in high voltage applications.

9.2 Typical Application



Copyright © 2016,
Texas Instruments Incorporated

Figure 20. CD4069UB Application

9.2.1 Design Requirements

The CD4069UB device is the industry's highest logic inverter operating at 18 V under recommended conditions. The lower drive capabilities makes it suitable for driving light loads like LED and greatly reduces chances of overshoots and undershoots.

9.2.2 Detailed Design Procedure

The recommended input conditions for Figure 20 includes rise time and fall time specifications (see $\Delta t/\Delta V$ in *Recommended Operating Conditions*) and specified high and low levels (see V_{IH} and V_{IL} in *Recommended Operating Conditions*). Inputs are not overvoltage tolerant and must be below V_{CC} level because of the presence of input clamp diodes to V_{CC}.

The recommended output condition for the CD4069UB application includes specific load currents. Load currents must be limited so as to not exceed the total power (continuous current through V_{CC} or GND) for the device. These limits are located in the *Absolute Maximum Ratings*. Outputs must not be pulled above V_{CC}.

Copyright © 1998–2019, Texas Instruments Incorporated

Typical Application (continued)

9.2.3 Application Curves




Figure 21. Typical Transition Time vs Load Capacitance




Figure 22. Typical Dynamic Power Dissipation vs Frequency




Figure 23. Variation of Normalized Propagation Delay Time (t_{PHL} and t_{PLH}) With Supply Voltage

Copyright © 1998–2019, Texas Instruments Incorporated

10 Power Supply Recommendations

The power supply can be any voltage between the minimum and maximum supply voltage rating located in *Recommended Operating Conditions*.

Each V_{CC} pin must have a good bypass capacitor to prevent power disturbance. For devices with a single supply, TI recommends a 0.1-μF capacitor. If there are multiple V_{CC} pins, then TI recommends a 0.01-μF or 0.022-μF capacitor for each power pin. It is acceptable to parallel multiple bypass capacitors to reject different frequencies of noise. 0.1-μF and 1-μF capacitors are commonly used in parallel. The bypass capacitor must be installed as close to the power pin as possible for best results.

11 Layout


11.1 Layout Guidelines

When using multiple bit logic devices, inputs must never float.

In many cases, digital logic device functions or parts of these functions are unused (for example, when only two inputs of a triple-input and gate are used, or only 3 of the 4 buffer gates are used). Such input pins must not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. This rule must be observed under all circumstances specified in the next paragraph.

All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating. See the application note, *Implications of Slow or Floating CMOS Inputs* (SCBA004), for more information on the effects of floating inputs. The logic level must apply to any particular unused input depending on the function of the device. Generally, they are tied to GND or V_{CC} (whichever is convenient).

11.2 Layout Example



Copyright © 1998–2019, Texas Instruments Incorporated

12 デバイスおよびドキュメントのサポート

12.1 デバイス・サポート

12.1.1 デベロッパー・ネットワークの製品に関する免責事項

デベロッパー・ネットワークの製品またはサービスに関するTIの出版物は、単独またはTIの製品、サービスと一緒に提供される場合に関係なく、デベロッパー・ネットワークの製品またはサービスの適合性に関する是認、デベロッパー・ネットワークの製品またはサービスの是認の表明を意味するものではありません。

12.2 ドキュメントのサポート

12.2.1 関連資料

関連資料については、以下を参照してください。

- *『低速またはフローティングCMOS入力の影響』*、SCBA004

12.3 コミュニティ・リソース

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

TI E2E™オンライン・コミュニティ ***TIのE2E (Engineer-to-Engineer) コミュニティ。*** エンジニア間の共同作業を促進するために開設されたものです。e2e.ti.comでは、他のエンジニアに質問し、知識を共有し、アイディアを検討して、問題解決に役立てることができます。

設計サポート ***TIの設計サポート*** 役に立つE2Eフォーラムや、設計サポート・ ツールをすばやく見つけることができます。技術サポート用の連絡先情報も参照できます。

12.4 商標

E2E is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

12.5 静電気放電に関する注意事項



これらのデバイスは、限定的なESD（静電破壊）保護機能を内 蔵しています。保存時または取り扱い時は、MOSゲートに対す る静電破壊を防止するために、リード線同士をショートさせて おくか、デバイスを導電フォームに入れる必要があります。

12.6 Glossary

SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

13 メカニカル、パッケージ、および注文情報

以降のページには、メカニカル、パッケージ、および注文に関する情報が記載されています。この情報は、そのデバイスについて利用可能な最新のデータです。このデータは予告なく変更されることがあり、ドキュメントが改訂される場合もあります。本データシートのブラウザ版を使用されている場合は、画面左側の説明をご覧ください。

Copyright © 1998–2019, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
CD4069UBE	Active	Production	PDIP (N) | 14	25 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-55 to 125	CD4069UBE
CD4069UBE.A	Active	Production	PDIP (N) | 14	25 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-55 to 125	CD4069UBE
CD4069UBEE4	Active	Production	PDIP (N) | 14	25 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-55 to 125	CD4069UBE
CD4069UBF	Active	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	CD4069UBF
CD4069UBF.A	Active	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	CD4069UBF
CD4069UBF3A	NRND	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	CD4069UBF3A
CD4069UBF3A.A	NRND	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	CD4069UBF3A
CD4069UBM	Active	Production	SOIC (D) | 14	50 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UBM
CD4069UBM.A	Active	Production	SOIC (D) | 14	50 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UBM
CD4069UBM96	Active	Production	SOIC (D) | 14	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UBM
CD4069UBM96.A	Active	Production	SOIC (D) | 14	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UBM
CD4069UBMT	Obsolete	Production	SOIC (D) | 14	-	-	Call TI	Call TI	-55 to 125	CD4069UBM
CD4069UBNSR	Active	Production	SOP (NS) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UB
CD4069UBNSR.A	Active	Production	SOP (NS) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CD4069UB
CD4069UBPW	Obsolete	Production	TSSOP (PW) | 14	-	-	Call TI	Call TI	-55 to 125	CM069UB
CD4069UBPWR	Active	Production	TSSOP (PW) | 14	2000 | LARGE T&R	Yes	NIPDAU | SN	Level-1-260C-UNLIM	-55 to 125	CM069UB
CD4069UBPWR.A	Active	Production	TSSOP (PW) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CM069UB
CD4069UBPWRG4.A	Active	Production	TSSOP (PW) | 14	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	CM069UB
JM38510/17401BCA	NRND	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	JM38510/ 17401BCA
JM38510/17401BCA.A	NRND	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	JM38510/ 17401BCA
M38510/17401BCA	NRND	Production	CDIP (J) | 14	25 | TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	JM38510/ 17401BCA

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF CD4069UB, CD4069UB-MIL :


- Catalog : CD4069UB
- Military : CD4069UB-MIL

NOTE: Qualified Version Definitions:


- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CD4069UBM96	SOIC	D	14	2500	330.0	16.4	6.5	9.0	2.1	8.0	16.0	Q1
CD4069UBNSR	SOP	NS	14	2000	330.0	16.4	8.1	10.4	2.5	12.0	16.0	Q1
CD4069UBPWR	TSSOP	PW	14	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
CD4069UBPWR	TSSOP	PW	14	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1


TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CD4069UBM96	SOIC	D	14	2500	353.0	353.0	32.0
CD4069UBNSR	SOP	NS	14	2000	353.0	353.0	32.0
CD4069UBPWR	TSSOP	PW	14	2000	353.0	353.0	32.0
CD4069UBPWR	TSSOP	PW	14	2000	356.0	356.0	35.0

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
CD4069UBE	N	PDIP	14	25	506	13.97	11230	4.32
CD4069UBE.A	N	PDIP	14	25	506	13.97	11230	4.32
CD4069UBEE4	N	PDIP	14	25	506	13.97	11230	4.32
CD4069UBM	D	SOIC	14	50	506.6	8	3940	4.32
CD4069UBM.A	D	SOIC	14	50	506.6	8	3940	4.32




PACKAGE OUTLINE

D0014A


SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT




NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm, per side.
5. Reference JEDEC registration MS-012, variation AB.



LAND PATTERN EXAMPLE
SCALE:8X



SOLDER MASK DETAILS

4220718/A 09/2016

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:8X

4220718/A 09/2016


NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

MECHANICAL DATA

NS (R-PDSO-G)** **PLASTIC SMALL-OUTLINE PACKAGE**

14-PINS SHOWN



DIM \ PINS **	14	16	20	24
A MAX	10,50	10,50	12,90	15,30
A MIN	9,90	9,90	12,30	14,70


4040062/C 03/03

NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

GENERIC PACKAGE VIEW

J 14 CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.

4040083-5/G




PACKAGE OUTLINE

J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



NOTES:


1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermitically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.

EXAMPLE BOARD LAYOUT


J0014A

CDIP - 5.08 mm max height


CERAMIC DUAL IN LINE PACKAGE



LAND PATTERN EXAMPLE
NON-SOLDER MASK DEFINED
SCALE: 5X



DETAIL A
SCALE: 15X




DETAIL B
13X, SCALE: 15X

4214771/A 05/2017


N (R–PDIP–T**)

PLASTIC DUAL–IN–LINE PACKAGE

16 PINS SHOWN



DIM \ PINS **	14	16	18	20
A MAX	0.775 (19,69)	0.775 (19,69)	0.920 (23,37)	1.060 (26,92)
A MIN	0.745 (18,92)	0.745 (18,92)	0.850 (21,59)	0.940 (23,88)
MS–001 VARIATION (C)	AA	BB	AC	AD



4040049/E 12/2002


NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001, except 18 and 20 pin minimum body length (Dim A).
D. The 20 pin end lead shoulder width is a vendor option, either half or full width.

PACKAGE OUTLINE

PW0014A


TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE




NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X




SOLDER MASK DETAILS

4220202/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE: 10X

4220202/B 12/2023

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

重要なお知らせと免責事項

TI は、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、TI 製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した TI 製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとします。

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている TI 製品を使用するアプリケーションの開発の目的でのみ、TI はその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。TI や第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、TI およびその代理人を完全に補償するものとし、TI は一切の責任を拒否します。

TI の製品は、 TI の販売条件 、 TI の総合的な品質ガイドライン 、 ti.com または TI 製品などに関連して提供される他の適用条件に従い提供されます。TI がこれらのリソースを提供することは、適用される TI の保証または他の保証の放棄の拡大や変更を意味するものではありません。 TI がカスタム、またはカスタマー仕様として明示的に指定していない限り、TI の製品は標準的なカタログに掲載される汎用機器です。

お客様がいかなる追加条項または代替条項を提案する場合も、TI はそれらに異議を唱え、拒否します。

Copyright © 2026, Texas Instruments Incorporated

最終更新日：2025 年 10 月