

ESD2CANFD24 24V、車載ネットワーク用 2 チャネル ESD 保護ダイオード

1 特長

- IEC 61000-4-2 レベル 4 ESD 保護
 - 接触放電 $\pm 25\text{kV}$
 - 空中放電 $\pm 25\text{kV}$
- IEC 61000-4-5 に従ってテスト済み
- 24V の動作電圧
- 双方向 ESD 保護
- 1 つの部品で完全な ESD 保護機能を実現できる 2 チャネル・デバイス
- 下流の部品を保護する低いクランピング電圧
- I/O 容量: 2.5pF (標準値)
- SOT-23 (DBZ): 小型、標準、共通フットプリント
- 自動光学検査 (AOI) に適したリード付きパッケージ

2 アプリケーション

- 産業用制御ネットワーク:
 - DeviceNet IEC 62026-3
 - CANopen – CiA 301/302-2, EN 50325-4

3 概要

ESD2CANFD24 は、CAN (Controller Area Network) インターフェイス保護用の双方向 ESD 保護ダイオードです。ESD2CANFD24 は、IEC 61000-4-2 規格 (接触 $\pm 25\text{kV}$ 、気中 $\pm 25\text{kV}$) に規定された最大レベルを超える接触 ESD 衝撃を放散できるように定格が規定されています。低い動的抵抗および低いクランピング電圧により、過渡現象に対してシステム・レベルの保護を実現します。システムでは、安全アプリケーションに対して高レベルの堅牢性と信頼性が求められるので、この保護機能は重要です。


このデバイスはチャネルごとの IO 容量が低く、静電放電 (ESD) とその他の過渡現象に起因する損傷から保護されるように 2 つの CAN バス・ライン (CANH、CANL) に適合したピン配置を備えています。また、ESD2CANFD24 の 2.5pF (標準値) 以下のライン容量は、最大 10Mbps のデータ・レートをサポートできる CAN、CANFD、CAN SiC、CAN-XL アプリケーションに適しています。

ESD2CANFD24 は、リード付きパッケージで供給され、フロー・スルー配線が容易になっています。

パッケージ情報 (1)

部品番号	パッケージ	本体サイズ (公称)
ESD2CANFD24	DBZ (SOT-23, 3)	2.92mm × 1.30mm

(1) 利用可能なパッケージについては、このデータシートの末尾にある注文情報を参照してください。



ESD2CANFD24 の代表的なアプリケーション



Table of Contents

1 特長	1	7.4 Device Functional Modes.....	9
2 アプリケーション	1	8 Application and Implementation	10
3 概要	1	8.1 Application Information.....	10
4 Revision History	2	8.2 Typical Application.....	10
5 Pin Configuration and Functions	3	9 Power Supply Recommendations	12
6 Specifications	4	10 Layout	12
6.1 絶対最大定格.....	4	10.1 Layout Guidelines.....	12
6.2 ESD 定格 - JEDEC 仕様.....	4	10.2 Layout Example.....	12
6.3 ESD 定格 - IEC 仕様.....	4	11 Device and Documentation Support	13
6.4 推奨動作条件.....	4	11.1 Documentation Support.....	13
6.5 熱に関する情報.....	4	11.2 Receiving Notification of Documentation Updates..	13
6.6 電気的特性.....	5	11.3 サポート・リソース.....	13
6.7 Typical Characteristics – ESD2CANFD24.....	6	11.4 Trademarks.....	13
7 Detailed Description	8	11.5 Electrostatic Discharge Caution.....	13
7.1 Overview.....	8	11.6 Glossary.....	13
7.2 Functional Block Diagram.....	8	12 Mechanical, Packaging, and Orderable Information	13
7.3 Feature Description.....	8		

4 Revision History

DATE	REVISION	NOTES
November 2022	*	Initial Release

5 Pin Configuration and Functions




图 5-1. DBZ Package, 3-Pin SOT-23 (Top View)

表 5-1. Pin Functions

PIN		TYPE ⁽¹⁾	DESCRIPTION
NAME	NO.		
IO	1, 2	I/O	ESD protected IO
GND	3	G	Connect to ground.

(1) I = Input, O = Output, I/O = Input or Output, G = Ground, P = Power

6 Specifications

6.1 絶対最大定格

自由気流での動作温度範囲内 (特に記述のない限り) ⁽¹⁾

パラメータ		デバイス	最小値	最大値	単位
P _{PP}	25°Cでの IEC 61000-4-5 の電力 (t _p – 8/20μs)	ESD2CANFD24		133	W
I _{PP}	25°Cでの IEC 61000-4-5 の電流 (t _p – 8/20μs)			3.5	A
T _A	自由気流での動作温度		-55	150	°C
T _J	接合部温度		-55	150	
T _{stg}	保存温度		-65	155	

- (1) 絶対最大定格の範囲外の動作は、デバイスの永続的な損傷の原因となる可能性があります。絶対最大定格は、この値の条件においても、または「推奨動作条件」に示された値を超えるいかなる条件においても、デバイスが正しく動作することを暗に示すものではありません。絶対最大定格の範囲内であっても、推奨動作条件の範囲外で使用した場合、本デバイスは完全に機能するとは限らず、このことが本デバイスの信頼性、機能、性能に影響を及ぼし、本デバイスの寿命を縮める可能性があります。

6.2 ESD 定格 - JEDEC 仕様

PARAMETER		TEST CONDITION	値	単位
V _(ESD)	静電気放電	人体モデル (HBM)、ANSI/ESDA/JEDEC JS-001 に準拠 ⁽¹⁾	±2500	V
		デバイス帯電モデル (CDM)、JEDEC 仕様 JS-002 に準拠 ⁽²⁾	±1000	

- (1) JEDEC のドキュメント JEP155 には、500V HBM であれば標準的な ESD 管理プロセスで安全な製造が可能であると記載されています。
(2) JEDEC のドキュメント JEP157 には、250V CDM であれば標準的な ESD 管理プロセスで安全な製造が可能であると記載されています。

6.3 ESD 定格 - IEC 仕様

T_A = 25°C (特に記述のない限り)

パラメータ		テスト条件	デバイス	値	単位
V _(ESD)	静電気放電	IEC 61000-4-2 接触放電、すべてのピン	ESD2CANFD24	±25000	V
		IEC 61000-4-2 空中放電、すべてのピン		±25000	

6.4 推奨動作条件

自由気流での動作温度範囲内 (特に記述のない限り)

パラメータ		最小値	公称値	最大値	単位
V _{IN}	入力電圧	-24		24	V
T _A	自由気流での動作温度	-55		150	°C

6.5 熱に関する情報

熱評価基準 ⁽¹⁾		ESD2CANFD24	単位
		DBZ (SOT-23)	
		3 ピン	
R _{θJA}	接合部から周囲への熱抵抗	316.3	°C/W
R _{θJC(top)}	接合部からケース (上面) への熱抵抗	170.7	°C/W
R _{θJB}	接合部から基板への熱抵抗	156.2	°C/W
Ψ _{JT}	接合部から上部までの特性評価パラメータ	45.9	°C/W
Ψ _{JB}	接合部から基板までの特性評価パラメータ	155.1	°C/W
R _{θJC(bot)}	接合部からケース (底面) への熱抵抗	N/A	°C/W

- (1) 従来および最新の熱評価基準の詳細については、『半導体および IC パッケージの熱評価基準』アプリケーション・レポートを参照してください。

6.6 電気的特性

$T_A = 25^\circ\text{C}$ (特に記述のない限り)⁽¹⁾

パラメータ	テスト条件	デバイス	最小値	代表値	最大値	単位
V_{RWM}	逆スタンバイ電圧	ESD2CANFD24	-24		24	V
V_{BRF}	ブレイクダウン電圧 ⁽²⁾	$I_{IO} = 10\text{mA}$, IO から GND へ	25.5		35.5	V
V_{BRR}	ブレイクダウン電圧 ⁽²⁾	$I_{IO} = -10\text{mA}$, IO から GND へ	-35.5		-25.5	V
V_{CLAMP}	クランプ電圧 ⁽³⁾	$I_{PP} = 3.5\text{A}$, $t_p = 8/20\mu\text{s}$, IO から GND へ		37		V
V_{CLAMP}	クランプ電圧 ⁽⁴⁾	$I_{PP} = 16\text{A}$, TLP, IO から GND または GND から IO へ		36		V
I_{LEAK}	リーク電流	$V_{IO} = \pm 24\text{V}$, IO から GND へ	-50	5	50	nA
R_{DYN}	動的抵抗 ⁽⁴⁾	IO から GND または GND から IO へ		0.45		Ω
C_L	ライン容量 ⁽⁵⁾	$V_{IO} = 0\text{V}$, $f = 1\text{MHz}$, $V_{pp} = 30\text{mV}$		2.5	4.2	pF
V_{Hold}	スナップバック後の保持電圧	TLP		30		V

(1) 各 IO チャンネルで測定を行います


(2) V_{BRF} と V_{BRR} は、デバイスがスナップバック状態にラッチする前に、それぞれ正方向と負方向に $\pm 10\text{mA}$ を印加したときの電圧として定義されます

(3) IEC 61000-4-5 に従い、 $8/20\mu\text{s}$ の指数減衰波形でデバイスにストレスを加えました

(4) 非反復電流パルス、伝送ライン・パルス (TLP)、方形パルス、ANSI/ESD STM5.5.1-2008


(5) 各チャンネルで IO から GND への測定

6.7 Typical Characteristics – ESD2CANFD24



tp = 100 ns, Transmission Line Pulse (TLP)

Figure 6-1. Positive TLP Curve



tp = 100 ns, Transmission Line Pulse (TLP)

Figure 6-2. Negative TLP Curve




Figure 6-3. +8-kV Clamped IEC Waveform




Figure 6-4. -8-kV Clamped IEC Waveform




Figure 6-5. Capacitance vs. Bias Voltage




Figure 6-6. Leakage Current vs. Bias Voltage Across Temperature

6.7 Typical Characteristics – ESD2CANFD24 (continued)





Fig 6-7. 8/20 μs Surge Response at 3.5 A

7 Detailed Description

7.1 Overview

The ESD2CANFD24 is a dual-channel ESD TVS diode in SOT-23 leaded package which is convenient for automatic optical inspection. This product offers IEC 61000-4-2 ± 25 -kV air-gap, ± 25 -kV contact ESD protection, and has a clamp circuit with a back-to-back TVS diode for bidirectional signal support. The 2.5 pF (typical) or less line capacitance of this ESD protection diode is suitable for CAN, CANFD, CAN SiC, and CAN-XL applications that can support data rates up to 10 Mbps. A typical application for this product is ESD circuit protection for CAN transceivers.

7.2 Functional Block Diagram



7.3 Feature Description

The ESD2CANFD24 is a bidirectional TVS with a high ESD protection level. This device protects the circuit from ESD strikes up to ± 25 -kV contact and ± 25 -kV air-gap specified in the IEC 61000-4-2 standard. The device can also handle up to 3.5 A surge current (IEC 61000-4-5 8/20 μ s). The I/O capacitance of 2.5-pF (typical) supports a data rate up to 10 Mbps. This clamping device has a small dynamic resistance, which makes the clamping voltage low when the device is actively protecting other circuits. For example, the clamping voltage is only 37 V when the device is taking 3.5 A transient surge current. The breakdown is bidirectional so this protection device is a good fit for CAN which is a differential signal. Low leakage allows the diode to conserve power when working below the V_{RWM} . The temperature range of -55°C to $+150^{\circ}\text{C}$ makes this ESD device work at extensive temperatures in most environments. The leaded SOT-23 package is good for applications requiring automatic optical inspection (AOI).

7.3.1 Temperature Range

This device is qualified to operate from -55°C to $+150^{\circ}\text{C}$.

7.3.2 IEC 61000-4-2 ESD Protection

The I/O pins can withstand ESD events of at least ± 25 -kV contact and ± 25 -kV air-gap in the leaded SOT-23 package according to the IEC 61000-4-2 standard. An ESD-surge clamp diverts the current to ground.

7.3.3 IEC 61000-4-5 Surge Protection

The IO pins can withstand surge events up to 3.5 A (8/20 μ s waveform). An ESD-surge clamp diverts this current to ground.

7.3.4 IO Capacitance

The capacitance between the I/O pins is 2.5 pF (typical) or less. This capacitance supports data rates for CAN, CANFD, CAN SiC, and CAN-XL up to 10 Mbps.

7.3.5 Dynamic Resistance

The IO pins feature an ESD clamp that has a low R_{DYN} of 0.45 Ω (Pin 1 or Pin 2 to Pin 3) and 0.45 Ω (Pin 3 to Pin 1 or Pin 2) or less which prevents system damage during ESD events.

7.3.6 DC Breakdown Voltage

The DC breakdown voltage between the IO pins is a minimum of ± 25.5 V. This protects sensitive equipment from surges above the reverse standoff voltage of ± 24 V.

7.3.7 Ultra Low Leakage Current

The IO pins feature an ultra-low leakage current of ± 50 nA (maximum) with a bias of ± 24 V.

7.3.8 Clamping Voltage

The IO pins feature an ESD clamp that is capable of clamping the voltage to 37 V ($I_{PP} = 3.5$ A) and 36 V ($I_{PP} = 16$ A for TLP).

7.3.9 Industry Standard Leaded Packages

This device features an industry standard SOT-23 (DBZ) leaded package for automatic optical inspection (AOI).

7.4 Device Functional Modes

The ESD2CANFD24 is a dual channel passive clamp that has low leakage during normal operation when the voltage between pin 1 or pin 2 and pin 3 is below V_{RWM} , and activates when the voltage between pin 1 or pin 2 and pin 3 goes above V_{BR} . During IEC 61000-4-2 ESD events, transient voltages as high as ± 25 kV can be clamped on either channel. When the voltages on the protected lines fall below the V_{HOLD} , the device reverts back to the low leakage passive state.

8 Application and Implementation

注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

8.1 Application Information

The ESD2CANFD24 is a dual channel TVS diode which is used to provide a path to ground for dissipating ESD events on differential CAN signal lines. As the current from ESD passes through the TVS, only a small voltage drop is present across the diode. This is the voltage presented to the protected IC. The low R_{DYN} of the triggered TVS holds this voltage, V_{CLAMP} , to a safe level for the protected IC.

8.2 Typical Application




图 8-1. ESD2CANFD24 Typical Application

8.2.1 Design Requirements

For this design example, the ESD2CANFD24 is used to provide ESD protection for a CAN transceiver. 表 8-1 lists the known design parameters for this application.


表 8-1. Design Parameters for the ESD2CANFD24 Typical Application

Design Parameter	Value
Diode configuration	Bidirectional
V_{IO} differential signal range	$> \pm 1.5$ V
V_{RWM}	± 24 V
Data rate	Up to 10 Mbps
$R_{T/2}$	60 Ω


8.2.2 Detailed Design Procedure

The ESD2CANFD24 has a V_{RWM} of ± 24 V. The bidirectional characteristic enables the signal integrity of the differential CAN lines to not be impacted by the diode. The low capacitance of 2.5 pF (typical) or less enables data rates up to 10 Mbps, which allows the designer to meet the requirements for CAN, CANFD, CAN SiC, and CAN-XL. The 60 Ω split termination improves the electromagnetic emissions behavior of the network by filtering higher-frequency common-mode noise that may be present on the differential signal lines.


8.2.3 Application Curves



8-2. +8-kV Clamped IEC Waveform



8-3. -8-kV Clamped IEC Waveform



8-4. 8/20 μ s Surge Response at 3.5 A

9 Power Supply Recommendations

This device is a passive TVS diode-based ESD protection device, therefore there is no requirement to power it. Ensure that the maximum voltage specifications for each pin are not violated.


10 Layout

10.1 Layout Guidelines

- The optimum placement of the device is as close to the connector as possible.
 - EMI during an ESD event can couple from the trace being struck to other nearby unprotected traces, resulting in early system failures.
 - The PCB designer must minimize the possibility of EMI coupling by keeping any unprotected traces away from the protected traces which are between the TVS and the connector.
- Route the protected traces as straight as possible.
- Eliminate any sharp corners on the protected traces between the TVS and the connector by using rounded corners with the largest radii possible.
 - Electric fields tend to build up on corners, increasing EMI coupling.
- If pin 3 is connected to ground, use a thick and short trace for this return path.

10.2 Layout Example

This example is typical of a dual channel differential data pair application, such as CAN.



 **10-1. Routing with DBZ Package**

11 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

11.1 Documentation Support

11.1.1 Related Documentation

For related documentation, see the following:

- Texas Instruments, [ESD Layout Guide user's guide](#)
- Texas Instruments, [ESD Protection Diodes EVM user's guide](#)
- Texas Instruments, [Generic ESD Evaluation Module user's guide](#)
- Texas Instruments, [Reading and Understanding an ESD Protection data sheet](#)

11.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](https://www.ti.com). Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

11.3 サポート・リソース

TI E2E™ サポート・フォーラムは、エンジニアが検証済みの回答と設計に関するヒントをエキスパートから迅速かつ直接得ることができる場所です。既存の回答を検索したり、独自の質問をしたりすることで、設計に必要な支援を迅速に得ることができます。

リンクされているコンテンツは、該当する貢献者により、現状のまま提供されるものです。これらは TI の仕様を構成するものではなく、必ずしも TI の見解を反映したものではありません。TI の[使用条件](#)を参照してください。

11.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

すべての商標は、それぞれの所有者に帰属します。

11.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

11.6 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
ESD2CANFD24DBZR	Active	Production	SOT-23 (DBZ) 3	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 150	2QO8
ESD2CANFD24DBZR.B	Active	Production	SOT-23 (DBZ) 3	3000 LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 150	2QO8

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


OTHER QUALIFIED VERSIONS OF ESD2CANFD24 :

- Automotive : [ESD2CANFD24-Q1](#)

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects


TAPE AND REEL INFORMATION



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
ESD2CANFD24DBZR	SOT-23	DBZ	3	3000	180.0	8.4	2.9	3.35	1.35	4.0	8.0	Q3

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
ESD2CANFD24DBZR	SOT-23	DBZ	3	3000	210.0	185.0	35.0

EXAMPLE BOARD LAYOUT



DBZ0003A

SOT-23 - 1.12 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE
SCALE:15X



SOLDER MASK DETAILS

4214838/F 08/2024

NOTES: (continued)


5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

DBZ0003A

SOT-23 - 1.12 mm max height

SMALL OUTLINE TRANSISTOR



SOLDER PASTE EXAMPLE
BASED ON 0.125 THICK STENCIL
SCALE:15X

4214838/F 08/2024

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

重要なお知らせと免責事項

TI は、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含みいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、TI 製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した TI 製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとし、TI は一切の責任を拒否します。

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている TI 製品を使用するアプリケーションの開発の目的でのみ、TI はその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。TI や第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、TI およびその代理人を完全に補償するものとし、TI は一切の責任を拒否します。

TI の製品は、[TI の販売条件](#)、[TI の総合的な品質ガイドライン](#)、[ti.com](https://www.ti.com) または TI 製品などに関連して提供される他の適用条件に従い提供されます。TI がこれらのリソースを提供することは、適用される TI の保証または他の保証の放棄の拡大や変更を意味するものではありません。TI がカスタム、またはカスタマー仕様として明示的に指定していない限り、TI の製品は標準的なカタログに掲載される汎用機器です。

お客様がいかなる追加条項または代替条項を提案する場合も、TI はそれらに異議を唱え、拒否します。

Copyright © 2026, Texas Instruments Incorporated

最終更新日：2025 年 10 月