

## TPS6126x 0.8V入力、同期整流昇圧コンバータ、100mA出力電流

### 1 特長

- 入力電圧範囲: 0.8V~4.0V
- 最大95%の効率
- 3.3V<sub>out</sub>時出力電流100mA (VIN>1V)
- 1.8V~4.0Vの固定および可変出力電圧オプション
- 10mA~100mAのプログラミング可能な平均出力電流
- 可変出力電流制限により超小型インダクタに対応
- パワー・セーブ・モードによる低出力電力時の効率向上
- 29μAの静止電流
- 高度なソフトスタート
- 2.5MHzの疑似固定周波数動作
- 出力過電圧保護
- シャットダウン中の負荷切断
- 低電圧誤動作防止
- 2.00x2.00mmの6ピンWSOパッケージで供給

### 2 アプリケーション

- あらゆる1セル/2セルのアルカリ/ニッカド/ニッケル水素バッテリー駆動製品
- 高出力インピーダンス・バッテリー(コイン電池)駆動製品
- 個人用医療機器
- LEDドライバ
- レーザーポインタ
- ワイヤレス・ヘッドセット
- 産業用の計測機器

### 3 概要


TPS6126xは、1セル/2セルのアルカリ/ニッカド/ニッケル水素バッテリーで駆動する製品向けの電源ソリューションを提供します。独自の高度なソフトスタートにより、コイン電池などの高出力インピーダンス・バッテリーで駆動する製品にも適しています。1セルのアルカリ・バッテリーから最大100Aの電流を出力でき、0.8V以下まで放電できます。

この昇圧コンバータは、疑似固定周波数のパルス幅変調(PWM)コントローラを基礎とし、同期整流を使用して最大の効率を実現しています。負荷電流が低い時にはコンバータがパワー・セーブ・モードに移行し、広い負荷電流範囲にわたって高効率を維持します。スイッチの最大平均電流は、最大700mAまでのプログラミング可能な値に制限されます。出力電圧については、外付けの分圧抵抗を使用してプログラミングすることも、チップ内部で固定された電圧を使用することもできます。また、平均出力電流もプログラミング可能です。プログラミングされた出力電圧や出力電流は、コンバータによりレギュレートされるため、出力電力は低減されます。コンバータをディセーブルして、バッテリーの消耗を最小限に抑えることができます。シャットダウン時には、バッテリーから負荷が切断されます。このデバイスは、6ピンのWSO (DRV)パッケージに封止されています。

#### 製品情報<sup>(1)</sup>

型番	パッケージ	本体サイズ(公称)
TPS61260	WSO (6)	2.00mmx2.00mm
TPS61261		

(1) 利用可能なすべてのパッケージについては、このデータシートの末尾にある注文情報を参照してください。



## 目次

1	特長	1	8.4	Device Functional Modes	12
2	アプリケーション	1	8.5	Programming	13
3	概要	1	<b>9</b>	<b>Application and Implementation</b>	<b>14</b>
4	改訂履歴	2	9.1	Application Information	14
<b>5</b>	<b>Pin Configuration and Functions</b>	<b>3</b>	9.2	Typical Applications	14
<b>6</b>	<b>Specifications</b>	<b>4</b>	<b>10</b>	<b>Power Supply Recommendations</b>	<b>17</b>
6.1	Absolute Maximum Ratings	4	<b>11</b>	<b>Layout</b>	<b>17</b>
6.2	Handling Ratings	4	11.1	Layout Guidelines	17
6.3	Recommended Operating Conditions	4	11.2	Layout Example	18
6.4	Thermal Information	4	11.3	Thermal Considerations	18
6.5	Electrical Characteristics	5	<b>12</b>	<b>デバイスおよびドキュメントのサポート</b>	<b>19</b>
6.6	Typical Characteristics	6	12.1	デバイス・サポート	19
<b>7</b>	<b>Parameter Measurement Information</b>	<b>8</b>	12.2	ドキュメントのサポート	19
7.1	Schematic and List of Components	8	12.3	関連リンク	19
<b>8</b>	<b>Detailed Description</b>	<b>10</b>	12.4	商標	19
8.1	Overview	10	12.5	静電気放電に関する注意事項	19
8.2	Functional Block Diagrams	10	12.6	Glossary	19
8.3	Feature Description	11	<b>13</b>	<b>メカニカル、パッケージ、および注文情報</b>	<b>19</b>

## 4 改訂履歴


資料番号末尾の英字は改訂を表しています。その改訂履歴は英語版に準じています。

Revision B (November 2014) から Revision C に変更	Page
• 変更 term from $\mu\text{s}$ to ( $\mu\text{H}$ ) in 式 3.	14

Revision A (February 2013) から Revision B に変更	Page
• 「取り扱いに関する定格」の表、「機能説明」セクション、「デバイスの機能モード」、「アプリケーションと実装」セクション、「電源に関する推奨事項」セクション、「レイアウト」セクション、「デバイスおよびドキュメントのサポート」セクション、「メカニカル、パッケージ、および注文情報」セクション 追加	1
• Changed Minimum input voltage for startup, $-40^\circ\text{C} < T_J < 105^\circ\text{C}$ , Max from 0.8 V to 1.2 V	5
• Added $V_{\text{EN}} = 0\text{ V}$ , $V_{\text{IN}} = 1.2\text{ V}$ , $T_A = 25^\circ\text{C}$ Test Condition and values to Shutdown current	5

2011年5月発行のものから更新	Page
• Changed Supply voltage to Input supply in RECOMMENDED OPERATING CONDITIONS	4
• Changed ELECTRICAL CHARACTERISTICS	5
• 変更 Synchronous Boost Operation section	11
• 削除 Dynamic Current Limit section	12
• 変更 Inductor Selection section	14
• 変更 Capacitor Selection section	15
• 変更 PowerPAD™ to Exposed Thermal Pad	18

## 5 Pin Configuration and Functions



### Pin Functions

PIN		I/O	DESCRIPTION
NAME	NUMBER		
EN	2	I	Enable input. (High = enabled, Low = disabled). Do not leave floating.
FB	3	I	Voltage feedback of adjustable versions. Must be connected to VOUT on fixed output voltage versions.
GND	Exposed Thermal Pad		Must be soldered to achieve appropriate power dissipation and mechanical reliability. Must be connected to GND.
L	5	I	Connection for inductor
RI	1	I	Average output current programming input. A resistor with a value between 2 k $\Omega$ and 20 k $\Omega$ must be connected between the RI pin and GND.
VIN	6	I	Supply voltage for control stage
VOUT	4	O	Boost converter output

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) <sup>(1)</sup>

		MIN	MAX	UNIT
Voltage range <sup>(2)</sup>	VIN, L, VOUT, EN, FB	-0.3	5.0	V
	RI	-0.3	3.6	V
Operating junction temperature range, T <sub>J</sub>		-40	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltages are with respect to network ground terminal.

### 6.2 Handling Ratings

		MIN	MAX	UNIT	
T <sub>stg</sub>	Storage temperature range	-65	150	°C	
V <sub>ESD</sub>	Electrostatic discharge <sup>(1)</sup>	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(2)</sup>		2	kV
		Charged device model (CDM), per JEDEC specification JESD22-C101, all pins <sup>(3)</sup>		0.5	kV

- (1) ESD testing is performed according to the respective JESD22 JEDEC standard.
- (2) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (3) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	NOM	MAX	UNIT
Input supply voltage at VIN		0.8		4.0	V
Operating free air temperature range, T <sub>A</sub>		-40		85	°C
Operating junction temperature range, T <sub>J</sub>		-40		125	°C

### 6.4 Thermal Information

THERMAL METRIC <sup>(1)</sup>		TPS61260, TPS61261	UNIT
		DRV (6 PINS)	
R <sub>θJA</sub>	Junction-to-ambient thermal resistance	89	°C/W
R <sub>θJC(top)</sub>	Junction-to-case (top) thermal resistance	100	
R <sub>θJB</sub>	Junction-to-board thermal resistance	35	
ψ <sub>JT</sub>	Junction-to-top characterization parameter	2	
ψ <sub>JB</sub>	Junction-to-board characterization parameter	36	
R <sub>θJC(bot)</sub>	Junction-to-case (bottom) thermal resistance	8	

- (1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 6.5 Electrical Characteristics

over recommended free-air temperature range and over recommended input voltage range (typical at an ambient temperature range of 25°C) (unless otherwise noted)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT	
<b>DC/DC STAGE</b>							
V <sub>IN</sub>	Input voltage range		0.8		4.0	V	
V <sub>IN</sub>	Minimum input voltage for startup	-40°C < T <sub>J</sub> < 105°C			1.2	V	
V <sub>OUT</sub>	TPS61260 output voltage range		1.8		4.0	V	
V <sub>FB</sub>	TPS61260 feedback voltage	-40°C < T <sub>J</sub> < 85°C	495	500	505	mV	
V <sub>OUT</sub>	TPS61261 output voltage		3.27	3.3	3.33	V	
I <sub>LIM</sub>	Average switch current limit			7 × I <sub>OUT</sub>		mA	
R <sub>DS(on)</sub>	High side switch on resistance	V <sub>IN</sub> = 1.2 V, V <sub>OUT</sub> = 3.3 V		1000		mΩ	
R <sub>DS(on)</sub>	Low side switch on resistance	V <sub>IN</sub> = 1.2 V, V <sub>OUT</sub> = 3.3 V		250		mΩ	
	Output voltage line regulation	PWM mode		0.5%			
	Output voltage load regulation	PWM mode		0.5%			
I <sub>OUT</sub>	Average output current programming range		10		100	mA	
	Average output current	R <sub>I</sub> = 10 kΩ, T <sub>A</sub> = 25 °C, V <sub>IN</sub> < V <sub>OUT</sub>	19	20	21	mA	
	Average output current	R <sub>I</sub> = 10 kΩ, 0°C < T <sub>J</sub> < 60°C, V <sub>IN</sub> < V <sub>OUT</sub>	18	20	22	mA	
	Average output current line regulation			0.5%			
	Average output current load regulation			0.5%			
I <sub>Q</sub>	Quiescent current	V <sub>IN</sub>	I <sub>O</sub> = 0 mA, V <sub>EN</sub> = V <sub>IN</sub> = 1.2 V, V <sub>OUT</sub> = 3.3 V, Device not switching		4	7	μA
		V <sub>OUT</sub>			25	40	μA
	TPS61261 FB pin input impedance	V <sub>EN</sub> = HIGH		1		MΩ	
I <sub>SD</sub>	Shutdown current	V <sub>EN</sub> = 0 V, V <sub>IN</sub> = 1.2 V		0.1	1.5	μA	
		V <sub>EN</sub> = 0 V, V <sub>IN</sub> = 1.2 V, T <sub>A</sub> = 25°C		0.1	0.3	μA	
<b>CONTROL STAGE</b>							
V <sub>UVLO</sub>	Under voltage lockout threshold	Falling V <sub>IN</sub>	0.6	0.7	0.8	V	
V <sub>UVLO</sub>	Under voltage lockout threshold hysteresis			200		mV	
V <sub>IL</sub>	Low level input threshold voltage (EN)	V <sub>IN</sub> ≤ 1.8 V, -40°C < T <sub>J</sub> < 85°C			0.2 × V <sub>IN</sub>	V	
V <sub>IL</sub>	Low level input threshold voltage (EN)	V <sub>IN</sub> > 1.8 V, -40°C < T <sub>J</sub> < 85°C			0.36	V	
V <sub>IH</sub>	High level input threshold voltage (EN)	V <sub>IN</sub> ≤ 1.5 V		0.8 × V <sub>IN</sub>		V	
V <sub>IH</sub>	High level input threshold voltage (EN)	V <sub>IN</sub> > 1.5 V		1.2		V	
I <sub>LKG</sub>	Input leakage current (EN)	EN = GND or V <sub>IN</sub>		0.01	0.1	μA	
V <sub>OVLP</sub>	Output overvoltage protection		4.0		4.5	V	

## 6.6 Typical Characteristics

Table of Graphs

DESCRIPTION		FIGURE
Maximum output current	vs Input voltage (TPS61260, V <sub>OUT</sub> = {1.8 V; 2.5 V; 4.0 V})	<a href="#">Figure 1</a>
	vs Input voltage (TPS61261, V <sub>OUT</sub> = 3.3 V)	<a href="#">Figure 2</a>
Efficiency	vs Output current (TPS61260, V <sub>OUT</sub> = {1.8 V; 2.5 V; 4.0 V})	<a href="#">Figure 3</a>
	vs Output current (TPS61261, V <sub>OUT</sub> = 3.3 V)	<a href="#">Figure 4</a>
	vs Input voltage (TPS61260, V <sub>OUT</sub> = 1.8 V, I <sub>OUT</sub> = {10; 20; 50 mA})	<a href="#">Figure 5</a>
	vs Input voltage (TPS61260, V <sub>OUT</sub> = 2.5 V, I <sub>OUT</sub> = {10; 20; 50 mA})	<a href="#">Figure 6</a>
	vs Input voltage (TPS61260, V <sub>OUT</sub> = 4.0 V, I <sub>OUT</sub> = {10; 20; 50; 100 mA})	<a href="#">Figure 7</a>
	vs Input voltage (TPS61261, V <sub>OUT</sub> = 3.3V, I <sub>OUT</sub> = {10; 20; 50 mA})	<a href="#">Figure 8</a>
	vs Resistance at R <sub>I</sub>	<a href="#">Figure 9</a>
Output voltage	vs Output current (TPS61260, V <sub>OUT</sub> = 1.8 V)	<a href="#">Figure 10</a>
	vs Output current (TPS61260, V <sub>OUT</sub> = 2.5 V)	<a href="#">Figure 11</a>
	vs Output current (TPS61260, V <sub>OUT</sub> = 4.0 V)	<a href="#">Figure 12</a>
	vs Output current (TPS61261, V <sub>OUT</sub> = 3.3 V)	<a href="#">Figure 13</a>
Output current	vs Output voltage	<a href="#">Figure 14</a>




Figure 1. Maximum Output Current vs Input Voltage




Figure 2. Maximum Output Current vs Input Voltage




Figure 3. Efficiency vs Output Current




Figure 4. Efficiency vs Output Current




Figure 5. Efficiency vs Input Voltage




Figure 6. Efficiency vs Input Voltage




Figure 7. Efficiency vs Input Voltage




Figure 8. Efficiency vs Input Voltage




Figure 9. Output Current vs Resistance at RI








Figure 10. Output Voltage vs Output Current



## 7 Parameter Measurement Information

### 7.1 Schematic and List of Components




表 1. List of Components

REFERENCE	DESCRIPTION	MANUFACTURER
	TPS61260 / 1	Texas Instruments
L1	4.7 $\mu$ H, 2.5 mm x 2 mm	LQM2HPN4R7MG0, Murata
C1	10 $\mu$ F 6.3 V, 0603, X5R ceramic	GRM188R60J106KME84D, Murata
C2	10 $\mu$ F 6.3 V, 0603, X5R ceramic	GRM188R60J106KME84D, Murata
R1	Depending on the output voltage at TPS61260. 0 $\Omega$ at TPS61261	

**Schematic and List of Components (continued)****表 1. List of Components (continued)**

REFERENCE	DESCRIPTION	MANUFACTURER
R2	Depending on the output voltage at TPS61260. Not used at TPS61261	
R3	Depending on the output current	

## 8 Detailed Description

### 8.1 Overview

The TPS6126x is based on a quasi-fixed frequency, pulse-width-modulation (PWM) controller using synchronous rectification to obtain maximum efficiency. At low load currents, the converter enters Power Save Mode to ensure high efficiency over a wide load current range. The TPS6126x is based on a current mode topology. The inductor current is regulated by a fast current regulator loop which is controlled by either a voltage control loop or a reference current. The controller also uses input and output voltage feedforward. Changes of the input and output voltages are monitored and immediately change the duty cycle in the modulator to achieve a fast response to those errors. In addition, the average output current can be programmed as well. An external resistor is used to program the average output current.

### 8.2 Functional Block Diagrams




图 15. TPS61260

## Functional Block Diagrams (continued)




图 16. TPS61261

## 8.3 Feature Description

### 8.3.1 Controller Circuit

The controlling circuit of the device is based on a current mode topology. The inductor current is regulated by a fast current regulator loop which is controlled by either a voltage control loop or a reference current. The controller also uses input and output voltage feedforward. Changes of the input and output voltages are monitored and immediately change the duty cycle in the modulator to achieve a fast response to those errors. The voltage error amplifier gets its feedback input from the FB pin. For the adjustable output voltage version, a resistive voltage divider must be connected to that pin. For the fixed output voltage version, the FB pin must be connected to the output voltage to directly sense the voltage. Fixed output voltage versions use a trimmed internal resistive divider. The feedback voltage is compared with the internal reference voltage to generate a stable and accurate output voltage. The reference current for average output current control is programmed with a resistor connected between the RI pin and GND.

The programming of the average output current also affects the maximum switch current in the main switch which basically is the input current. The lower the average output current is programmed, the lower the maximum input current. Now, maximum input power is controlled as well as the maximum peak current to achieve safe and stable operation under all possible conditions. Smaller inductors with lower saturation current ratings can be used, when lower average output currents are programmed.

### 8.3.2 Synchronous Boost Operation

The device uses 3 internal N-channel MOSFETs to maintain synchronous power conversion at all possible operating conditions. This enables the device to keep high efficiency over a wide input voltage and output power range. Using 2 rectifying switches also enables the device to control the output voltage and current during startup conditions when the input voltage is higher than the output voltage. During startup, the rectifying switch works in a linear mode until the output voltage is near the input voltage. Once in regulation, operating with the input voltage greater than the output voltage may cause either the output voltage or current to exceed its regulation value. Although this operating point is not recommended, the device will not be damaged by this as long as absolute maximum ratings are not violated.

## Feature Description (continued)

As opposed to a standard boost converter, the implemented 3 switch topology enables the output to be disconnected from the input during device shutdown when disabled. Current does not flow from output to input or from input to output.

### 8.3.3 Power Save Mode

At normal load conditions with continuous inductor current, the device operates at a quasi fixed frequency. If the load gets lower, the inductor current decreases and becomes discontinuous. If this happens and the load is further decreased, the device lowers the switching frequency and turns off parts of the control to minimize internal power consumption. The output voltage is controlled by a low power comparator at a level about 1% higher than the nominal output voltage. If the output voltage reaches the nominal value or drops below it, device control is turned on again to handle the new load condition. The boundary between power save mode and PWM mode is when the inductor current becomes discontinuous.

Accurate average output current regulation requires continuous inductor current. This means that there is no power save mode during current regulation.

### 8.3.4 Device Enable

The device is put into operation when EN is set high. It is put into a shutdown mode when EN is set to GND. In shutdown mode, the regulator stops switching, all internal control circuitry is switched off, and the load is disconnected from the input. This means that output voltage can drop below input voltage during shutdown.

### 8.3.5 Softstart and Short Circuit Protection

During startup of the converter, duty cycle and peak current are limited in order to avoid high peak currents flowing from the input. After being enabled, the device starts operating. Until the output voltage reaches about 0.4 V, the average output current ramps up from zero to the programmed value, as the output voltage increases. As soon as the output current has reached the programmed value, it stays regulated at that value until the load conditions demand less current. This typically happens when the output capacitor is charged and the output voltage is regulated.

During startup, the device can seamlessly change modes of operation. When the input voltage is higher than the output voltage, the device operates in a linear mode using the rectifying switches for control. If the input voltage is lower than the output voltage it operates in a standard boost conversion mode. Boost conversion is non-synchronous when the output voltage is below approximately 1.8 V and it is synchronous if the output voltage is higher than approximately 1.8 V.

At short circuit conditions at the output, the output current is limited to the programmed average current. If the short at the output causes the output voltage to drop below 0.4 V, the average current decreases approximately linearly with the output voltage down to zero.

The devices can monotonically start into a pre-bias on the output.

## 8.4 Device Functional Modes

### 8.4.1 Undervoltage Lockout

An undervoltage lockout function prevents device startup if the supply voltage on VIN is lower than the undervoltage lockout threshold defined in the [Electrical Characteristics](#). When in operation, the device automatically shuts down the power stage if the voltage on VIN drops below the undervoltage lockout threshold. The device automatically restarts if the input voltage recovers to the minimum operating input voltage.

### 8.4.2 Output Overvoltage Protection

If, for any reason, the output voltage of the device (as measured at the VOUT pin) exceeds its maximum recommended value, the device stops operating. It continues operating as soon as the output voltage has dropped below this threshold.

## 8.5 Programming

### 8.5.1 Programming the Output Voltage

Within the TPS6126x family, there are fixed and adjustable output voltage versions available. To properly configure the fixed output voltage devices, the FB pin is used to sense the output voltage. This means that it must be connected directly to VOUT. For the adjustable output voltage version, an external resistor divider is used to adjust the output voltage. The resistor divider must be connected between the VOUT, FB, and GND pins. When the output voltage is regulated properly, the typical value of the voltage at the FB pin is 500 mV. The maximum recommended value for the output voltage is 4.0 V. The current through the resistive divider should be about 100 times greater than the current into the FB pin. The typical current into the FB pin is 0.01  $\mu$ A, and the voltage across the resistor between the FB and GND pins, R<sub>2</sub>, is typically 500 mV. Based on these two values, the recommended value for R<sub>2</sub> should be lower than 500 k $\Omega$ , in order to set the divider current at 1  $\mu$ A or higher. It is also recommended to keep the total value for the resistor divider, **R<sub>1</sub> + R<sub>2</sub>**, in the range of 1 M $\Omega$ . From that, the value of the resistor connected between VOUT and FB, R<sub>1</sub>, depending on the needed output voltage (V<sub>OUT</sub>), can be calculated using 式 1:

$$R1 = R2 \cdot \left( \frac{V_{OUT}}{V_{FB}} - 1 \right) \quad (1)$$




图 17. Typical Application Circuit for Adjustable Output Voltage Option

### 8.5.2 Programming the Output Current

The devices of the TPS6126x family also support average output current regulation. An external resistor is used to program the average output current. The resistor must be connected between the RI and GND pins. When the average output current is regulated properly, the typical value of the voltage at the RI pin is 400 mV. The maximum recommended value for the regulated average output current is 100 mA. The value of the resistor R<sub>3</sub> should be between 2 k $\Omega$  and 20 k $\Omega$ . It can be calculated, depending on the needed average output current (I<sub>OUT</sub>), using 式 2:

$$R3 = \frac{200V}{I_{OUT}} \quad (2)$$

Accurate regulation of the average output current only is possible if the inductor current is continuous. Please check the [Inductor Selection](#) section to calculate the required parameters for selecting an appropriate inductor.

## 9 Application and Implementation

### 注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 9.1 Application Information

The devices are designed to operate from an input voltage supply range between 1.2 V ( $V_{in}$  falling UVLO is 0.8 V) and 4.0 V with a maximum output current of 100 mA. The devices operate in PWM mode for medium to heavy load conditions and in power save mode at light load currents. In PWM mode the TPS61260 converter operates with the nominal switching frequency of 2.5 MHz which provides a controlled frequency variation over the input voltage range. As the load current decreases, the converter enters power save mode, reducing the switching frequency and minimizing the IC quiescent current to achieve high efficiency over the entire load current range. The WEBENCH software uses an iterative design procedure and accesses a comprehensive database of components when generating a design.

### 9.2 Typical Applications

#### 9.2.1 TPS61260 3.3-V Output Application




图 18. TPS61260 Typical Application Circuit

#### 9.2.1.1 Design Requirements

表 2. Design Parameters

DESIGN PARAMETER	EXAMPLE VALUE
Input voltage range	1.2 V to 4.0 V
Output voltage	3.3 V
Input ripple voltage	±200 mV
Output ripple voltage	±3% $V_{OUT}$
Output current rating	100 mA
Operating frequency	2.5 MHz

#### 9.2.1.2 Detailed Design Procedure

##### 9.2.1.2.1 Inductor Selection

To properly configure the TPS6126x devices, an inductor must be connected between the VIN pin and the L pin. 式 3 is used to estimate the minimum inductance value for accurate average output current regulation; the inductor current should be continuous.

$$L_{MIN} = \frac{V_{IN}^2 \cdot (V_{OUT} - V_{IN})}{V_{OUT}^2 \cdot I_{OUT}} \cdot 0.2 \text{ (}\mu\text{H)} \quad (3)$$

In 式 3, the minimum inductance value required for accurate average output current regulation is calculated.  $V_{IN}$  is the input voltage. For typical applications which require voltage regulation, the recommended inductor value is 4.7  $\mu$ H. Applications with higher inductance values have lower light load efficiency. The recommended range for the inductor value is from 2.2  $\mu$ H up to 22  $\mu$ H. The current rating required for this inductor is  $I_{LIM}$  and depends on the programmed output current  $I_{OUT}$ . Please refer to the [Electrical Characteristics](#). 表 3 contains a list of inductors recommended for the TPS6126x:

**表 3. List of Inductors**

VENDOR	INDUCTOR SERIES
Murata	LQM2HP_G0
Toko	DFE252012C
Hitachi Metals	KSLI-252010AG

### 9.2.1.2.2 Capacitor Selection

#### 9.2.1.2.2.1 Input Capacitor

At least a 4.7- $\mu$ F input capacitor is recommended to improve transient behavior of the regulator and EMI behavior of the total power supply circuit. An X5R or X7R ceramic capacitor placed as close as possible to the VIN and GND pins of the IC is recommended.


#### 9.2.1.2.2.2 Output Capacitor


For the output capacitor, use of a small X5R or X7R ceramic capacitor placed as close as possible to the VOUT and GND pins of the IC is recommended. If, for any reason, the application requires the use of large capacitors which cannot be placed close to the IC, use a smaller ceramic capacitor in parallel to the large capacitor. The small capacitor should be placed as close as possible to the VOUT and GND pins of the IC.

The output capacitor should be at least 2.2  $\mu$ F. There are no additional requirements regarding minimum ESR. There is also no theoretical upper limit for the output capacitance value. The device has been tested with capacitors up to 100  $\mu$ F. In general, larger capacitors cause lower output voltage ripple as well as lower output voltage drop during load transients. To improve control performance, especially when using high output capacitance values, a feedforward capacitor in parallel to R1 is recommended. The value should be in the range of the value calculated in 式 4:


$$C_{ff} = 0.3 \cdot \Omega \cdot \frac{C2}{R2} \quad (4)$$

### 9.2.1.3 TPS61260 3.3-V Output Application Performance Plots





### 9.2.2 TPS61261 Application as LED Driver



23. TPS61260 LED Driver Application Circuit

#### 9.2.2.1 Design Requirements

表 4. Design Parameters

DESIGN PARAMETER	EXAMPLE VALUE
Input voltage range	1.2 V to 3 V
Output current rating	10 mA -100 mA
Operating frequency	2.5 MHz

#### 9.2.2.2 Detailed Design Procedure

23 shows the TPS61261 configured to drive an LED with analog and/or PWM dimming. This circuit does not require an external current sensing resistor and so provides high efficiency, as shown in 24. This design is available as the [TPS61261EVM-208](#).

### 9.2.2.3 TPS61261 Application as LED Driver Performance Plots




Figure 24. LED Driver Efficiency

## 10 Power Supply Recommendations

The device is designed to operate from an input voltage supply range between 1.2 V and 4.0 V. This input supply must be well regulated. If the input supply is located more than a few inches from the converter, additional bulk capacitance may be required in addition to the ceramic bypass capacitors. An electrolytic or tantalum capacitor with a value of 47  $\mu$ F is a typical choice.

## 11 Layout

### 11.1 Layout Guidelines

- For all switching power supplies, layout is an important step in the design, especially at high peak currents and high switching frequencies. If the layout is not carefully done, the regulator could show stability problems as well as EMI problems. Therefore, use wide and short traces for the main current path and for the power ground tracks. The input capacitor, output capacitor, and the inductor should be placed as close as possible to the IC. Use a common ground node for power ground and a different one for control ground to minimize the effects of ground noise. Connect these ground nodes at any place close to the ground pin of the IC.
- The feedback divider should be placed as close as possible to the control ground connection. To lay out the control ground, short traces are recommended as well, separated from the power ground traces. This avoids ground shift problems, which can occur due to superimposition of power ground current and control ground current. See Figure 25 for the recommended layout.

## 11.2 Layout Example




图 25. PCB Layout Suggestion

## 11.3 Thermal Considerations

Implementation of integrated circuits in low-profile and fine-pitch surface-mount packages typically requires special attention to power dissipation. Many system-dependent issues such as thermal coupling, airflow, added heat sinks and convection surfaces, and the presence of other heat-generating components affect the power-dissipation limits of a given component.

Three basic approaches for enhancing thermal performance are listed below.

- Improving the power dissipation capability of the PCB design
- Improving the thermal coupling of the component to the PCB by soldering the Exposed Thermal Pad
- Introducing airflow in the system

For more details on how to use the thermal parameters in the dissipation ratings table, please check the *Thermal Characteristics of Linear and Logic Packages Using JEDEC PCB Designs Application Report* ([SZZA017](#)) and the *Semiconductor and IC Package Thermal Metrics Application Report* ([SPRA953](#)).

## 12 デバイスおよびドキュメントのサポート

### 12.1 デバイス・サポート

#### 12.1.1 デベロッパー・ネットワークの製品に関する免責事項

デベロッパー・ネットワークの製品またはサービスに関するTIの出版物は、単独またはTIの製品、サービスと一緒に提供される場合に関係なく、デベロッパー・ネットワークの製品またはサービスの適合性に関する是認、デベロッパー・ネットワークの製品またはサービスの是認の表明を意味するものではありません。

### 12.2 ドキュメントのサポート

#### 12.2.1 関連資料

『TPS61261EVM-208評価モジュール・ユーザー・ガイド』(SLVU851)

『JEDEC PCB設計を使用するリニアおよびロジック・パッケージの熱特性』アプリケーション・レポート(SZZA017)

『半導体およびICパッケージの熱指標』アプリケーション・レポート(SPRA953)

#### 12.3 関連リンク

次の表に、クイック・アクセス・リンクを示します。カテゴリには、技術資料、サポートおよびコミュニティ・リソース、ツールとソフトウェア、およびサンプル注文またはご購入へのクイック・アクセスが含まれます。

表 5. 関連リンク

製品	プロダクト・フォルダ	サンプルとご購入	技術資料	ツールとソフトウェア	サポートとコミュニティ
TPS61260	<a href="#">ここをクリック</a>				
TPS61261	<a href="#">ここをクリック</a>				

#### 12.4 商標

All trademarks are the property of their respective owners.

#### 12.5 静電気放電に関する注意事項



これらのデバイスは、限定的なESD(静電破壊)保護機能を内蔵しています。保存時または取り扱い時は、MOSゲートに対する静電破壊を防止するために、リード線同士をショートさせておくか、デバイスを導電フォームに入れる必要があります。

#### 12.6 Glossary

[SLYZ022](#) — TI Glossary.

This glossary lists and explains terms, acronyms, and definitions.

## 13 メカニカル、パッケージ、および注文情報

以降のページには、メカニカル、パッケージ、および注文に関する情報が記載されています。この情報は、そのデバイスについて利用可能な最新のデータです。このデータは予告なく変更されることがあり、ドキュメントが改訂される場合もあります。本データシートのブラウザ版を使用されている場合は、画面左側の説明をご覧ください。

**PACKAGING INFORMATION**

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
<a href="#">TPS61260DRV R</a>	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
TPS61260DRV R.A	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
TPS61260DRV R.B	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
<a href="#">TPS61260DRV T</a>	Active	Production	WSON (DRV)   6	250   SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
TPS61260DRV T.A	Active	Production	WSON (DRV)   6	250   SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
TPS61260DRV T.B	Active	Production	WSON (DRV)   6	250   SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	QWD
<a href="#">TPS61261DRV R</a>	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	QWE
TPS61261DRV R.A	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	QWE
TPS61261DRV R.B	Active	Production	WSON (DRV)   6	3000   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	QWE
<a href="#">TPS61261DRV T</a>	Active	Production	WSON (DRV)   6	250   SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	QWE
TPS61261DRV T.B	Active	Production	WSON (DRV)   6	250   SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	QWE

(1) **Status:** For more details on status, see our [product life cycle](#).

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS61260DRV	WSON	DRV	6	3000	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS61260DRV	WSON	DRV	6	3000	180.0	8.4	2.3	2.3	1.15	4.0	8.0	Q2
TPS61260DRVT	WSON	DRV	6	250	178.0	8.4	2.25	2.25	1.0	4.0	8.0	Q2
TPS61260DRVT	WSON	DRV	6	250	180.0	8.4	2.3	2.3	1.15	4.0	8.0	Q2
TPS61261DRV	WSON	DRV	6	3000	180.0	8.4	2.3	2.3	1.15	4.0	8.0	Q2
TPS61261DRVT	WSON	DRV	6	250	180.0	12.4	2.3	2.3	1.15	4.0	8.0	Q2

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS61260DRVR	WSON	DRV	6	3000	205.0	200.0	33.0
TPS61260DRVR	WSON	DRV	6	3000	213.0	191.0	35.0
TPS61260DRVT	WSON	DRV	6	250	205.0	200.0	33.0
TPS61260DRVT	WSON	DRV	6	250	213.0	191.0	35.0
TPS61261DRVR	WSON	DRV	6	3000	213.0	191.0	35.0
TPS61261DRVT	WSON	DRV	6	250	213.0	191.0	35.0

## GENERIC PACKAGE VIEW

DRV 6




WSON - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4206925/F



4222173/C 11/2025

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.
4. Minimum 0.1 mm solder wetting on pin side wall. Available for wettable flank version only.




# EXAMPLE STENCIL DESIGN

DRV0006A

WSON - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD #7  
88% PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE  
SCALE:30X

4222173/C 11/2025

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

## 重要なお知らせと免責事項

TI は、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、TI 製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した TI 製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとし、

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている TI 製品を使用するアプリケーションの開発の目的でのみ、TI はその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。TI や第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、TI およびその代理人を完全に補償するものとし、TI は一切の責任を拒否します。

TI の製品は、[TI の販売条件](#)、[TI の総合的な品質ガイドライン](#)、[ti.com](#) または TI 製品などに関連して提供される他の適用条件に従い提供されます。TI がこれらのリソースを提供することは、適用される TI の保証または他の保証の放棄の拡大や変更を意味するものではありません。TI がカスタム、またはカスタマー仕様として明示的に指定していない限り、TI の製品は標準的なカタログに掲載される汎用機器です。

お客様がいかなる追加条項または代替条項を提案する場合も、TI はそれらに異議を唱え、拒否します。

Copyright © 2026, Texas Instruments Incorporated

最終更新日 : 2025 年 10 月