

- eXpressDSP Digital Media (XDM) interface compliant
- Validated on the DRA446 EVM
- Baseline sequential mode with both interleaved and non-interleaved input format supported
- Progressive mode supported
- YUV 444, YUV 422, YUV 420, YUV 411, and Gray scale color sub-sampling formats supported
- Maximum of three components supported
- Maximum of three quantization tables supported
- Maximum of four huffman tables each for AC and DC DCT coefficients supported
- Arbitrary image size for sequential JPEG supported
- 8-bit and 16-bit quantization tables supported
- Resizing the output image by a factor of 1/2, 1/4, and 1/8 supported
- On-the-fly resizing with respect to set maxHeight and maxWidth supported
- YUV planar or YUV 422 interleaved output format supported
- Frame level decoding of images for sequential mode and scan level decoding for progressive mode supported



- All the data buffers and tables are placed in the external memory
- Source images of 12-bits per sample not supported
- JPEG File Interchange Format (JFIF) header skipped
- Restart management for bit stream with Define Restart Interval Marker (DRI) and Restart Marker (RST) enabled

description

JPEG is an international standard for color image compression. This standard is defined in the ISO 10918-1 JPEG Draft International Standard | CCITT Recommendation T.81. Supports baseline sequential mode with both interleaved and non-interleaved input format and progressive mode.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



Copyright © 2007, Texas Instruments Incorporated

PRODUCT PREVIEW



summary of performance

Table 1. Configuration Table

CONFIGURATION	ID
Baseline sequential decoder(4:2:0 input and 4:2:2 interleaved output) with no internal memory	JPEG_DEC_001

Note: This decoder does not require DMA resource.

Table 2. Cycles Information – Profiled on DRA446 with Code Generation Tools Version 6.0.8

CONFIGURATION ID	PERFORMANCE STATISTICS (IN MEGA PIXELS PER SEC) ¹		
	TEST DESCRIPTION	AVERAGE ²	PEAK ³
JPEG_DEC_001	Measured with 10:1 compression ratio	26.5	None

¹ Measured with program memory, stack, and I/O buffers in external memory

² Measured for DRA446 at 500 MHz with REMI0003.jpg

³ Peak value is not calculated for this version of JPEG Decoder

Note: Default cache configuration (L1D cache: 16K-bytes, L2 cache: 64K-bytes, L1P cache: 32K-bytes).

Table 3. Memory Statistics - Generated with Code Generation Tools Version 6.0.8

CONFIGURATION ID	MEMORY STATISTICS ⁴				
	PROGRAM MEMORY	DATA MEMORY			TOTAL
		INTERNAL	EXTERNAL	STACK	
JPEG_DEC_001	68	0	37.3	8	113.3 ⁵
JPEG_DEC_001 (720 x 480)	68	0	2062.3	8	2138.3
JPEG_DEC_001 (1280 * 1024)	68	0	7717.3	8	7793.3
JPEG_DEC_001 (1600x1200)	68	0	11287.3	8	11363.3
JPEG_DEC_001 (2048x1536)	68	0	18469.3	8	18545.3
JPEG_DEC_001 (2560x2048)	68	0	30757.3	8	30833.3

⁴ All memory requirements are expressed in kilobytes (1K-byte = 1024 bytes).

⁵ Applicable for Baseline Sequential Images

PRODUCT PREVIEW

Table 4. Internal Data Memory Split-up

CONFIGURATION ID	DATA MEMORY – INTERNAL ⁶		
	SHARED		INSTANCE ⁷
	CONSTANTS	SCRATCH	
JPEG_DEC_001	0	0	0

⁶ All memory requirements are expressed in kilobytes

⁷ Does not include I/O buffer

Table 5. External Data Memory Split-up

CONFIGURATION ID	DATA MEMORY – EXTERNAL ⁸		
	SHARED		INSTANCE ⁹
	CONSTANTS	SCRATCH	
JPEG_DEC_001	0.3	7	30 ¹⁰
JPEG_DEC_001 (720 x 480)	0.3	7	2055
JPEG_DEC_001 (1280 * 1024)	0.3	7	7710
JPEG_DEC_001 (1600x1200)	0.3	7	11280
JPEG_DEC_001 (2048x1536)	0.3	7	18462
JPEG_DEC_001 (2560x2048)	0.3	7	30750

⁸ All memory requirements are expressed in kilobytes

⁹ I/O buffers not included.

¹⁰ Applicable for Baseline Sequential Images

Table 6. Co Processor(s) Memory Statistics

CONFIGURATION ID	SEQ DATA MEMORY	SEQ PROG MEMORY	IMX WORKING MEM	IMX IMG BUF	IMX CMD MEM
JPEG_DEC_001	0	0	0	0	0

Note: The decoder does not use co-processors and hence all the values are zero.



notes

- Total data memory for N non pre-emptive instances = Constants + Scratch + N*(Instance + I/O buffers + Stack)

references

- ITU-CCITT recommendation T.81 (reproduction of ISO/IEC 10918-1)
- eXpressDSP Algorithm Interoperability Standard (TMS320 Algorithm Interface Standard)
- JPEG Progressive Support Decoder on C64x+ User Guide (SPRUEZ2)

glossary

Constants	Elements that go into .const memory section
Scratch	Memory space that can be reused across different instances of the algorithm
Shared	Sum of Constants and Scratch
Instance	Persistent-memory that contains persistent information - allocated for each instance of the algorithm

acronyms

CCITT	Committee Consultative International Telephone and Telegraph
DCT	Discrete Cosine Transform
DRI	Define Restart Interval Marker
DSP	Digital Signal Processing
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
ITU	International Telecommunication Union
JFIF	JPEG File Interchange Format
JPEG	Joint Photographic Experts Group
RST	Restart Marker
XDAIS	eXpressDSP Algorithm Interface Standard
XDM	eXpressDSP Digital Media

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
Low Power Wireless	www.ti.com/lpw	Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2007, Texas Instruments Incorporated