

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
ISO7741EDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741EDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741EDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741FEDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741FEDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1
ISO7741FEDWRQ1	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
ISO7741EDWRQ1	SOIC	DW	16	2000	350.0	350.0	43.0
ISO7741EDWRQ1	SOIC	DW	16	2000	356.0	356.0	35.0
ISO7741EDWRQ1	SOIC	DW	16	2000	356.0	356.0	35.0
ISO7741FEDWRQ1	SOIC	DW	16	2000	356.0	356.0	35.0
ISO7741FEDWRQ1	SOIC	DW	16	2000	356.0	356.0	35.0
ISO7741FEDWRQ1	SOIC	DW	16	2000	350.0	350.0	43.0

**TUBE**


\*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (μm)	B (mm)
ISO7741EDWQ1	DW	SOIC	16	40	507	12.83	5080	6.6
ISO7741EDWQ1	DW	SOIC	16	40	506.98	12.7	4826	6.6
ISO7741FEDWQ1	DW	SOIC	16	40	507	12.83	5080	6.6
ISO7741FEDWQ1	DW	SOIC	16	40	506.98	12.7	4826	6.6