


## QML CLASS V RS-422 QUADRUPLE DIFFERENTIAL LINE RECEIVER

Check for Samples: [AM26LS33A-SP](#)

### FEATURES

- AM26LS33A Devices Meet or Exceed the Requirements of ANSI TIA/EIA-422-B, TIA/EIA-423-B, and ITU Recommendations V.10 and V.11
- **±15-V Common-Mode Range With ±500-mV Sensitivity**
- **Input Hysteresis . . . 50 mV Typical**
- **Operate From a Single 5-V Supply**
- **Low-Power Schottky Circuitry**
- **3-State Outputs**
- **Complementary Output-Enable Inputs**
- **Input Impedance . . . 12 kΩ Minimum**
- **Designed to Be Interchangeable With Advanced Micro Device AM26LS33™**
- **QML-V Qualified, SMD 5962-78020**
- **Military Temperature Range (-55°C to 125°C)**

- **Rad-Tolerant: 25 kRad (Si) TID<sup>(1)</sup>**



(1) Radiation tolerance is a typical value based upon initial device qualification with dose rate = 10 mrad/sec. Radiation Lot Acceptance Testing is available - contact factory for details.

### DESCRIPTION

The AM26LS33A is a quadruple differential line receiver for balanced and unbalanced digital data transmission. The enable function is common to all four receivers and offers a choice of active-high or active-low input. The 3-state outputs permit connection directly to a bus-organized system. Fail-safe design ensures that, if the inputs are open, the outputs always are high.

Compared to the AM26LS33, the AM26LS33A incorporates an additional stage of amplification to improve sensitivity. The input impedance has been increased, resulting in less loading of the bus line. The additional stage has increased propagation delay; however, this does not affect interchangeability in most applications.

The AM26LS33A is characterized for operation over the temperature range of -55°C to 125°C.

### ORDERING INFORMATION<sup>(1)</sup>

T <sub>A</sub>	PACKAGE <sup>(2)</sup>	ORDERABLE PART NUMBER	TOP-SIDE MARKING
-55°C to 125°C	CDIP - J	5962-7802007VEA	5962-7802007VEA

(1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at [www.ti.com](http://www.ti.com).

(2) Package drawings, thermal data, and symbolization are available at [www.ti.com/packaging](http://www.ti.com/packaging).




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.


**Table 1. FUNCTION TABLE**  
Each Receiver

DIFFERENTIAL A-B	ENABLES		OUTPUT Y
	G	$\bar{G}$	
$V_{ID} \geq V_{IT+}$	H	X	H
	X	L	H
$V_{IT-} \leq V_{ID} \leq V_{IT+}$	H	X	?
	X	L	?
$V_{ID} \leq V_{IT-}$	H	X	L
	X	L	L
X	L	H	Z
Open	H	X	H
	X	L	H

### LOGIC DIAGRAM (POSITIVE LOGIC)



### SCHEMATICS OF INPUTS AND OUTPUTS



## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>


over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
$V_{CC}$	Supply voltage <sup>(2)</sup>		7	V
$V_I$	Input voltage	Any differential input	$\pm 25$	V
		Other inputs	7	
$V_{ID}$	Differential input voltage <sup>(3)</sup>		$\pm 25$	V
	Continuous total power dissipation	See Dissipation Ratings Table		
	Lead temperature 1.6 mm (1/16 inch) from case for 60 seconds		300	°C
$T_{stg}$	Storage temperature range	-65	150	°C

(1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltage values, except differential voltages, are with respect to the network ground terminal.

(3) Differential voltage values are at the noninverting (A) input terminals with respect to the inverting (B) input terminals.



A. See datasheet for absolute maximum and minimum recommended operating conditions.

B. Silicon operating life design goal is 10 years at 105°C junction temperature (does not include package interconnect life).

**Figure 1. AM26LS33A 16/J Package Operating Life Derating Chart**

## RECOMMENDED OPERATING CONDITIONS

		MIN	NOM	MAX	UNIT
$V_{CC}$	Supply voltage	4.5	5	5.5	V
$V_{IH}$	High-level input voltage	2			V
$V_{IL}$	Low-level input voltage			0.8	V
$V_{IC}$	Common-mode input voltage			$\pm 15$	V
$I_{OH}$	High-level output current			-440	$\mu A$
$I_{OL}$	Low-level output current			8	mA
$T_A$	Operating free-air temperature	-55		125	$^{\circ}C$

## ELECTRICAL CHARACTERISTICS

over recommended ranges of  $V_{CC}$ ,  $V_{IC}$ , and operating free-air temperature (unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP <sup>(1)</sup>	MAX	UNIT
$V_{IT+}$ Positive-going input threshold voltage	$V_O = V_{OH\min}$ , $I_{OH} = -440 \mu A$ $-15 V \leq V_{IC} \leq 15 V$		0.5		V
$V_{IT-}$ Negative-going input threshold voltage	$V_O = 0.45 V$ , $I_{OL} = 8 mA$ $-15 V \leq V_{IC} \leq 15 V$	-0.5 <sup>(2)</sup>			V
$V_{hys}$ Hysteresis voltage ( $V_{IT+} - V_{IT-}$ )			50		mV
$V_{IK}$ Enable-input clamp voltage	$V_{CC} = 4.5 V$ , $I_I = -18 mA$		-1.5		V
$V_{OH}$ High-level output voltage	$V_{CC} = 4.5 V$ , $V_{ID} = 1 V$ , $V_{I(G)} = 0.8 V$ , $I_{OH} = -440 \mu A$	2.5			V
$V_{OL}$ Low-level output voltage	$V_{CC} = 4.5 V$ , $V_{ID} = -1 V$ , $V_{I(G)} = 0.8 V$	$I_{OL} = 4 mA$ $I_{OL} = 8 mA$	0.4 0.45		V
$I_{OZ}$ Off-state (high-impedance state) output current	$V_{CC} = 5.5 V$	$V_O = 2.4 V$ $V_O = 0.4 V$	20 -20		$\mu A$
$I_I$ Line input current	$V_I = 15 V$ ,	Other input at -10 V to 15 V	1.2		mA
	$V_I = -15 V$ ,	Other input at -15 V to 10 V	-1.7		
$I_{I(EN)}$ Enable input current	$V_I = 5.5 V$ , $V_{CC} = 5.5 V$		100		$\mu A$
$I_H$ High-level enable current	$V_I = 2.7 V$ , $V_{CC} = 5.5 V$		20		$\mu A$
$I_L$ Low-level enable current	$V_I = 0.4 V$ , $V_{CC} = 5.5 V$		-0.36		mA
$r_i$ Input resistance	$V_{IC} = -15 V$ to $15 V$ , One input to ac ground	12	15		$k\Omega$
$I_{OS}$ Short-circuit output current <sup>(3)</sup>	$V_{CC} = MAX$ , $V_{ID} = 1 V$ , $V_O = 0 V$	-15	-85		mA
$I_{CC}$ Supply current	$V_{CC} = MAX$ , data inputs = GND, All outputs disabled	52	70		mA

(1) All typical values are at  $V_{CC} = 5 V$ ,  $T_A = 25^{\circ}C$ , and  $V_{IC} = 0$ .

(2) The algebraic convention, in which the less positive (more negative) limit is designated as minimum, is used in this data sheet for threshold levels only.

(3) Not more than one output should be shorted to ground at a time, and duration of the short circuit should not exceed one second.



## SWITCHING CHARACTERISTICS

$V_{CC} = 5$  V, over operating free-air temperature (unless otherwise noted)



PARAMETER	TEST CONDITIONS	MIN	TYP <sup>(1)</sup>	MAX	UNIT
$t_{PLH}$ Propagation delay time, low-to-high-level output	$C_L = 15$ pF, See <a href="#">Figure 2</a>	20	35	53	ns
				53	
$t_{PHL}$ Propagation delay time, high-to-low-level output	$C_L = 15$ pF, See <a href="#">Figure 2</a>	22	35	53	ns
				53	
$t_{PZH}$ Output enable time to high level	$C_L = 15$ pF, See <a href="#">Figure 2</a>	17	25	38	ns
				38	
$t_{PZL}$ Output enable time to low level	$C_L = 15$ pF, See <a href="#">Figure 2</a>	20	25	38	ns
				38	
$t_{PHZ}$ Output disable time from high level	$C_L = 15$ pF, See <a href="#">Figure 2</a>	21	30	45	ns
				45	
$t_{PLZ}$ Output disable time from low level	$C_L = 15$ pF, See <a href="#">Figure 2</a>	30	40	60	ns
				60	

(1) All typical values are at  $V_{CC} = 5$  V,  $T_A = 25^\circ\text{C}$ , and  $V_{IC} = 0$ .

## PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT

VOLTAGE WAVEFORMS FOR  $t_{PLH}$ ,  $t_{PHL}$ VOLTAGE WAVEFORMS FOR  $t_{PHZ}$ ,  $t_{PZH}$ VOLTAGE WAVEFORMS FOR  $t_{PLZ}$ ,  $t_{PZL}$ 


NOTES: A.  $C_L$  includes probe and jig capacitance.

B. All diodes are 1N3064 or equivalent.

C. Enable  $G$  is tested with  $\bar{G}$  high;  $\bar{G}$  is tested with  $G$  low.

Figure 2. Test Circuit and Voltage Waveforms

### TYPICAL CHARACTERISTICS



†  $V_{CC} = 5.5$  V and  $V_{CC} = 4.5$  V applies to M-suffix devices only.

Figure 3.




Figure 4.




Figure 5.




Figure 6.

## TYPICAL CHARACTERISTICS (continued)




Figure 7.




Figure 8.




Figure 9.







Figure 10.

**TYPICAL CHARACTERISTICS (continued)**

**Figure 11.**


The unshaded area shows requirements of paragraph 4.2.1 of ANSI Standards EIA/TIA-422-B and EIA/TIA-423-B.

**Figure 12.**

## APPLICATION INFORMATION



$\dagger R_T$  equals the characteristic impedance of the line.

Figure 13. Circuit with Multiple Receivers

**PACKAGING INFORMATION**

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
5962-7802007VEA	Active	Production	CDIP (J)   16	25   TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	5962-7802007VEA
5962-7802007VEA.A	Active	Production	CDIP (J)   16	25   TUBE	No	SNPB	N/A for Pkg Type	-55 to 125	5962-7802007VEA

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF AM26LS33A-SP :**


---

- Catalog : [AM26LS33A](#)

- Military : [AM26LS33AM](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications

**TUBE**



\*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (μm)	B (mm)
5962-7802007VEA	J	CDIP	16	25	506.98	15.24	13440	NA
5962-7802007VEA.A	J	CDIP	16	25	506.98	15.24	13440	NA


J (R-GDIP-T\*\*)

14 LEADS SHOWN

CERAMIC DUAL IN-LINE PACKAGE



PINS ** DIM	14	16	18	20
A	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC
B MAX	0.785 (19,94)	.840 (21,34)	0.960 (24,38)	1.060 (26,92)
B MIN	—	—	—	—
C MAX	0.300 (7,62)	0.300 (7,62)	0.310 (7,87)	0.300 (7,62)
C MIN	0.245 (6,22)	0.245 (6,22)	0.220 (5,59)	0.245 (6,22)



4040083/F 03/03

NOTES: A. All linear dimensions are in inches (millimeters).  
B. This drawing is subject to change without notice.  
C. This package is hermetically sealed with a ceramic lid using glass frit.  
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.  
E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025