

TMDS181 and TMDS171 Configuration Guide

David Liu, Ikechukwu Anyiam

ABSTRACT

The purpose of this document is to provide a quick start-up guide for the TMDS171 and TMDS181 devices.

Contents

1	Device Configuration Guide	1
2	Summary.....	2

Trademarks

All trademarks are the property of their respective owners.

1 Device Configuration Guide

1. Choose I2C mode or pin-strap mode via I2C_EN:

- When I2C_EN is high, the device is in I2C mode and the configuration is done through I2C.
- When I2C_EN is low, the device is in pin-strap mode and the configuration is done through the device pins.

2. Choose functional mode via DEV_FUNC_MODE:

In pin-strap mode, the device can automatically configure itself as a redriver at low data rates (<1.0 Gbps) or as a retimer above this data rate. Additional configuration is available using the DEV_FUNC_MODE bits ([1:0] in register 0x0Ah) when the device is in I2C mode.

The DEV_FUNC_MODE bits select the device working function mode:

- 00 – Redriver mode: 250 Mbps – 3.4 Gbps
- 01 – Automatic redriver to retimer crossover at 1.0 Gbps (default)
- 10 – Automatic retimer when HDMI2.0a based on TMDS_CLOCK_RATIO_STATUS (reserved for TMDS171)
- 11 – Retimer mode across full range 250 Mbps to 6 Gbps

The difference between configuration of 0x01 and 0x10 is the crossover frequency for configuration of 0x01 is 1 Gbps while the crossover frequency for configuration of 0x10 is 3.4 Gbps.

When changing between the device configuration modes via Dev_Func_Mode, it is required to toggle the PD_EN bit or the external HPD_SNK for the change to take effect.

When in automatic redriver to retimer mode, it is not required to toggle the PD_EN bit or the external HPD_SNK when the device changes from the redriver to retimer or vice versa.

3. Choose transmit termination via TX_TERM_CTL:

In pin-strap mode, when the TX_TERM_CTL pin is configured as NC, TX_TERM_CTL automatically selects the termination impedance.

- For data rates greater than 3.4 Gbps, TX_TERM_CTL will be set to 75- to 150-Ω differential near-end termination. (TMDS181 only)
- For data rates between 2 Gbps and 3.4 Gbps, TX_TERM_CTL will be set to 150- to 300-Ω differential near-end termination.
- For data rates less than 2 Gbps, TX_TERM_CTL will be set to no termination.

When configured in I2C mode, TX_TERM_CTL bits (Register 0x0Bh, bits [4:3]) need to be set manually.

For data rates less than 3.4 Gbps, TX_TERM_CTL will be set to no termination (value of 0x00h) or

150- to 300- Ω (value of 0x01h) differential near-end termination. For data rates greater than 3.4 Gbps, TX_TERM_CTL will be set to 75- to 150- Ω differential near-end termination (value of 0x11h, TMDS181 only).

APPLY_RXTX_CHANGES (bit 2 in register 0x0Ah) needs to be set after any changes to the TX_TERM_CTL field.

4. Choose input receive equalization via EQ_SEL:

- In pin-strap mode, when the EQ_SEL pin is configured as NC, the equalization is adaptive. It is recommended to keep this pin as NC to enable adaptive equalization.
- When EQ_SEL is connected low, the equalization is fixed at 7.5 dB. When EQ_SEL is high, the equalization is fixed at 14 dB.
- Equalization control can also be configured in register 0x0Dh in I2C mode.
- APPLY_RXTX_CHANGES (bit 2 in register 0x0Ah) needs to be set after any changes to this register.

5. Choose de-emphasis settings via PRE_SEL:

- In pin-strap mode, when the PRE_SEL pin is configured as NC, no de-emphasis is applied. When PRE_SEL is connected low, 2 dB de-emphasis is applied.
- De-emphasis settings can also be configured with fields [7:5] and [4:2] in register 0x0Ch in I2C mode.
- APPLY_RXTX_CHANGES (bit 2 in register 0x0Ah) needs to be set after any changes to this register.

2 Summary

The guidelines provided in this application report serve as a starting point for configuring the TMDS181 and TMDS171 devices for your application.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2019, Texas Instruments Incorporated