

CSD25480F3 –20-V P-Channel FemtoFET™ MOSFET

1 Features


- Low on-resistance
- Ultra-low Q_g and Q_{gd}
- Ultra-small footprint
 - 0.73 mm × 0.64 mm
- Low profile
 - 0.36-mm max height
- Integrated ESD protection diode
- Lead and halogen free
- RoHS compliant

2 Applications

- Optimized for load switch applications
- Optimized for general purpose switching applications
- Battery applications
- Handheld and mobile applications

3 Description

This –20-V, 110-mΩ, P-Channel FemtoFET™ MOSFET is designed and optimized to minimize the footprint in many handheld and mobile applications. This technology is capable of replacing standard small signal MOSFETs while providing a substantial reduction in footprint size.



Typical Part Dimensions

Product Summary

$T_A = 25^\circ\text{C}$		TYPICAL VALUE	UNIT
V_{DS}	Drain-to-Source Voltage	–20	V
Q_g	Gate Charge Total (–4.5 V)	0.7	nC
Q_{gd}	Gate Charge Gate-to-Drain	0.10	nC
$R_{DS(on)}$	Drain-to-Source On-Resistance	$V_{GS} = -1.8\text{ V}$	420
		$V_{GS} = -2.5\text{ V}$	203
		$V_{GS} = -4.5\text{ V}$	132
		$V_{GS} = -8.0\text{ V}$	110
$V_{GS(th)}$	Threshold Voltage	–0.95	V

Device Information⁽¹⁾

DEVICE	QTY	MEDIA	PACKAGE	SHIP
CSD25480F3	3000		Femto 0.73-mm × 0.64-mm Land Grid Array (LGA)	Tape and Reel
CSD25480F3T	250	7-Inch Reel		


(1) For all available packages, see the orderable addendum at the end of the data sheet.

Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$ (unless otherwise stated)		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage	–20	V
V_{GS}	Gate-to-Source Voltage	–12	V
I_D	Continuous Drain Current ⁽¹⁾	–1.7	A
I_{DM}	Pulsed Drain Current ^{(1) (2)}	–10.6	A
P_D	Power Dissipation ⁽¹⁾	500	mW
$V_{(ESD)}$	Human-Body Model (HBM)	4000	V
	Charged-Device Model (CDM)	2000	
T_J , T_{stg}	Operating Junction, Storage Temperature	–55 to 150	°C

(1) Typical $R_{DS(on)} = 255\text{ m}\Omega$ mounted on FR4 material with minimum Cu mounting area.

(2) Pulse duration $\leq 100\text{ }\mu\text{s}$, duty cycle $\leq 1\%$.



Top View



An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

Table of Contents

1 Features	1	6 Device and Documentation Support	7
2 Applications	1	6.1 Receiving Notification of Documentation Updates.....	7
3 Description	1	6.2 Trademarks.....	7
4 Revision History	2	7 Mechanical, Packaging, and Orderable Information	8
5 Specifications	3	7.1 Mechanical Dimensions.....	8
5.1 Electrical Characteristics.....	3	7.2 Recommended Minimum PCB Layout.....	9
5.2 Thermal Information.....	3	7.3 Recommended Stencil Pattern.....	9
5.3 Typical MOSFET Characteristics.....	4		

4 Revision History

Changes from Revision A (August 2017) to Revision B (February 2022)	Page
• Changed ultra-low profile bullet from 0.35 mm to 0.36 mm in height.....	1
• Updated ultra-low profile image height from 0.35 mm to 0.36 mm.....	1
• Changed ultra-low profile image height from 0.35 mm to 0.36 mm.....	8
• Added FemtoFET Surface Mount Guide note.....	9

Changes from Revision * (April 2016) to Revision A (August 2017)	Page
• Added the Section 6.1 section in Section 6	7
• Added Recommended Minimum PCB Layout	9
• Updated the Section 7.3	9

5 Specifications

5.1 Electrical Characteristics

$T_A = 25^\circ\text{C}$ (unless otherwise stated)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC CHARACTERISTICS					
BV_{DSS}	Drain-to-source voltage $V_{\text{GS}} = 0 \text{ V}, I_{\text{DS}} = -250 \mu\text{A}$	-20			V
I_{DSS}	Drain-to-source leakage current $V_{\text{GS}} = 0 \text{ V}, V_{\text{DS}} = -16 \text{ V}$		-50		nA
I_{GSS}	Gate-to-source leakage current $V_{\text{DS}} = 0 \text{ V}, V_{\text{GS}} = -12 \text{ V}$		-25		nA
$V_{\text{GS}(\text{th})}$	Gate-to-source threshold voltage $V_{\text{DS}} = V_{\text{GS}}, I_{\text{DS}} = -250 \mu\text{A}$	-0.70	-0.95	-1.20	V
$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = -1.8 \text{ V}, I_{\text{DS}} = -0.1 \text{ A}$	420	840		$\text{m}\Omega$
	$V_{\text{GS}} = -2.5 \text{ V}, I_{\text{DS}} = -0.4 \text{ A}$	203	260		
	$V_{\text{GS}} = -4.5 \text{ V}, I_{\text{DS}} = -0.4 \text{ A}$	132	159		
	$V_{\text{GS}} = -8 \text{ V}, I_{\text{DS}} = -0.4 \text{ A}$	110	132		
g_{fs}	Transconductance $V_{\text{DS}} = -10 \text{ V}, I_{\text{DS}} = -0.4 \text{ A}$	8.0			S
DYNAMIC CHARACTERISTICS					
C_{iss}	Input capacitance	119	155		pF
C_{oss}	Output capacitance $V_{\text{GS}} = 0 \text{ V}, V_{\text{DS}} = -10 \text{ V}, f = 1 \text{ MHz}$	48	62		pF
C_{rss}	Reverse transfer capacitance	3.6	4.7		pF
R_G	Series gate resistance	16			Ω
Q_g	Gate charge total (-4.5 V)	0.70	0.91		nC
Q_{gd}	Gate charge gate-to-drain	0.10			nC
Q_{gs}	Gate charge gate-to-source	0.26			nC
$Q_{\text{g}(\text{th})}$	Gate charge at V_{th}	0.15			nC
Q_{oss}	Output charge $V_{\text{DS}} = -10 \text{ V}, V_{\text{GS}} = 0 \text{ V}$	1.3			nC
$t_{\text{d}(\text{on})}$	Turnon delay time	9			ns
t_r	Rise time $V_{\text{DS}} = -10 \text{ V}, V_{\text{GS}} = -4.5 \text{ V}, I_{\text{DS}} = -0.4 \text{ A}, R_G = 10 \Omega$	5			ns
$t_{\text{d}(\text{off})}$	Turnoff delay time	13			ns
t_f	Fall time	7			ns
DIODE CHARACTERISTICS					
V_{SD}	Diode forward voltage $I_{\text{SD}} = -0.4 \text{ A}, V_{\text{GS}} = 0 \text{ V}$	-0.78	-1.0		V
Q_{rr}	Reverse recovery charge $V_{\text{DS}} = -10 \text{ V}, I_F = -0.4 \text{ A}, \text{di/dt} = 100 \text{ A}/\mu\text{s}$	1.2			nC
t_{rr}	Reverse recovery time	6.4			ns

5.2 Thermal Information

$T_A = 25^\circ\text{C}$ (unless otherwise stated)

THERMAL METRIC		TYPICAL VALUES	UNIT
$R_{\theta\text{JA}}$	Junction-to-ambient thermal resistance ⁽¹⁾	90	$^\circ\text{C}/\text{W}$
	Junction-to-ambient thermal resistance ⁽²⁾	255	

(1) Device mounted on FR4 material with 1-in² (6.45-cm²), 2-oz. (0.071-mm) thick Cu.

(2) Device mounted on FR4 material with minimum Cu mounting area.

5.3 Typical MOSFET Characteristics

$T_A = 25^\circ\text{C}$ (unless otherwise stated)




Figure 5-1. Saturation Characteristics




Figure 5-2. Transfer Characteristics










Figure 5-3. Transient Thermal Impedance






Figure 5-10. Maximum Safe Operating Area




Figure 5-11. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

6.2 Trademarks



FemtoFET™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 Mechanical Dimensions




- A. All linear dimensions are in millimeters (dimensions and tolerancing per AME T14.5M-1994).
- B. This drawing is subject to change without notice.
- C. This package is a lead-free solder land design.

Table 7-1. Pin Configuration


POSITION	DESIGNATION
Pin 1	Gate
Pin 2	Source
Pin 3	Drain

7.2 Recommended Minimum PCB Layout



- A. All dimensions are in millimeters.
- B. For more information, see *FemtoFET Surface Mount Guide* (SLRA003D).

7.3 Recommended Stencil Pattern



- A. All dimensions are in millimeters.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
CSD25480F3	Active	Production	PICOSTAR (YJM) 3	3000 LARGE T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	4
CSD25480F3.B	Active	Production	PICOSTAR (YJM) 3	3000 LARGE T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	4
CSD25480F3T	Active	Production	PICOSTAR (YJM) 3	250 SMALL T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	4
CSD25480F3T.B	Active	Production	PICOSTAR (YJM) 3	250 SMALL T&R	Yes	NIAU	Level-1-260C-UNLIM	-55 to 150	4

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.



⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.


Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


TAPE AND REEL INFORMATION


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CSD25480F3	PICOSTAR	YJM	3	3000	180.0	8.4	1.94	0.79	0.44	4.0	8.0	Q2
CSD25480F3T	PICOSTAR	YJM	3	250	180.0	8.4	1.94	0.79	0.44	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CSD25480F3	PICOSTAR	YJM	3	3000	182.0	182.0	20.0
CSD25480F3T	PICOSTAR	YJM	3	250	182.0	182.0	20.0





PACKAGE OUTLINE

YJM0003A

PicoStar™ - 0.36 mm max height

PicoStar™



4222304/B 03/2022

NOTES:

PicoStar is a trademark of Texas Instruments.


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M
2. This drawing is subject to change without notice.
3. This package is a Pb-free bump design. Bump finish may vary. To determine the exact finish, refer to the device datasheet or contact a local TI representative.

EXAMPLE BOARD LAYOUT

YJM0003A

PicoStar™ - 0.36 mm max height

PicoStar™



LAND PATTERN EXAMPLE
SOLDER MASK DEFINED
SCALE:50X

4222304/B 03/2022

NOTES: (continued)


4. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).

EXAMPLE STENCIL DESIGN

YJM0003A

PicoStar™ - 0.36 mm max height

PicoStar™



**SOLDER PASTE EXAMPLE
BASED ON 0.075 - 0.1 mm THICK STENCIL
SCALE:50X**

4222304/B 03/2022

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025