

## Report

on the

# Certificate Z10 088989 0029 Rev. 00

of the

Safety Controller DRA829/TDA4VM

## **Applicant**

Texas Instruments Incorporated 13905 University Blvd. Dallas, Texas 77479 USA

Report No.: TD99727C

Version 1.0 of 2022-11-28

## **Testing Laboratory for Safety Components**

TÜV SÜD Rail GmbH

Rail Automation Barthstraße 16 D-80339 München

## **Certification Body**

TÜV SÜD Product Service GmbH Ridlerstraße 65 D-80339 München

(Page 1 of 10)

This report may be represented only in full wording. The use for promotion needs written permission. This report contains the result of a unique investigation of the product being tested and places no generally valid judgment about characteristics out of the running fabrication. Official translations of this technical report are to be authorised by the test and certification body.



Ta	Table of Contents		
1	Targ	et of Evaluation (ToE)	4
2	Scope of Testing		5
		Test Specimen	
	2.2	Nomenclature and Identification of DRA829/TDA4VM	5
3	Certification Requirements		6
	3.1	Certification Documentation	7
4	Standards and Guidelines		8
	4.1	Functional Safety	8
		Quality Management System	
5	Resu	ılts	9
	5.1	Functional Safety	9
6	Impl	ementation Conditions and Restrictions	10
7	Certi	ificate Number	10



## **Modification History**

Rev.	Status	Date	Author	Modification / Description
1.0	Active	2022-11-28	Axel Köhnen	initial

Table 1: Modification history



## 1 Target of Evaluation (ToE)

In May 2020 Texas Instruments Incorporated requested TÜV SÜD Rail GmbH to test and certify the DRA829/TDA4VM ASIC hardware as part of Texas Instruments Jacinto 7 family of products according to the standard listed in clause 4 of this report. The project number related to this Certificate Report is 717521003.

The ToE is a product used in safety related applications. The DRA829/TDA4VM is a Safety Controller and should be approved for

- up to ASIL D for the MCU domain
- up to ASIL B for the Main domain
- Systematic Capability ASIL D according to ISO 26262.

The DRA829/TDA4VM processor family is targeted at ADAS and Autonomous Vehicle (AV) applications and is built to meet the complex processing needs of modern industrial embedded products. Key cores include next generation DSP with scalar and vector cores, dedicated deep learning and traditional algorithm accelerators, latest ARM and GPU processors for general compute, an integrated next generation imaging subsystem (ISP), video codec, Ethernet hub and isolated MCU island.

TD99727C / v1.0 TD99727C\_1.0.docx creator: Axel Köhnen 2022-11-28 page 4 of 10



## 2 Scope of Testing

#### 2.1 Test Specimen

The target of evaluation are generic safety microcontroller devices based on the Jacinto<sup>™</sup> 7 family of products platform architecture DRA829/TDA4VM.

The assessment is based on a tailored safety lifecycle for safety elements out of context (SEooC) according to ISO 26262:2018. The certificate report gives an overview of the results of the certification process and the general safety relevant conditions and restrictions related to the use of the DRA829/TDA4VM in safety-related systems.

#### 2.2 Nomenclature and Identification of DRA829/TDA4VM

The DRA829/TDA4VM tested is identified by hardware as follows:

Name	Package	Silicon
DRA829/TDA4VM	FCBGA (827)	XJ721EGALF (ES 1.1)

Table 2: HW Identification of DRA829/TDA4VM

#### **Product Root Part Numbers**

- TDA4VM88**zY**BALF**c**Q1
- TDA4VM67zYBALFcQ1
- TDA4VM21zYBALFcQ1
- DRA829JMzYBALFcQ1
- DRA829VMzYBALFcQ1

#### Valid options:

z = Device Speed Grade	TDA4VMx	DRA829x
Т	yes	yes
L	yes	n/a
E	yes	n/a

c = Carrier designator	
R	
Blank	

Y = Device Type
С
5
R
D
Р



## 3 Certification Requirements

The certification of the DRA829/TDA4VM is according to the regulations and standards listed in clause 4 of this document. This certifies the successful completion of the following test segments.

- Functional Safety including
  - Functional safety management (FSM) and safety lifecycle
  - Avoidance of systematic faults / Systematic capability
  - Hardware Safety Requirements (including assumptions of use)
  - Analysis of the device structure (IP/Element FMAs)
  - Quantitative analysis of the hardware (FMEDA)
  - Fault injection and simulation
  - Dependent Failure Analysis (DFA)
  - Criteria for coexistence of elements
  - Hardware functional test and design verification
  - Hardware qualification
  - Development Tool qualification
- II. Safety information in the product documentation (safety manual, user manual, installation and operating instructions).
- III. Product-Related Quality Assurance in Manufacture and Product Development

phone: +49 89 5791-3011, fax: +49 89 5791-2933 e-mail: Axel.Koehnen@tuvsud.com



#### 3.1 Certification Documentation

The detailed technical evaluation is documented in the most recent version of the Technical Report:

Document No.	Description	Project No.
TD99609T	Technical Report	717521003
Safety related requirements, conditions and restrictions can be found in the following user documentation		
SPRUIR1_DRA829_TDA4VM_Safety_ Manual - Automotive.pdf v11, 2022-11-10	Safety Manual / Installation Manual	717521003

Table 3: Technical Report



#### 4 Standards and Guidelines

The regulations and guidelines which form the basis of the type testing are listed below.

#### 4.1 Functional Safety

No.	Reference	Description
/N1/	ISO 26262-2:2018	Road vehicles — Functional safety — Part 2: Management of functional safety
/N2/	ISO 26262-5:2018	Road vehicles — Functional safety — Part 5: Product development at the hardware level
/N3/	ISO 26262-7:2018	Road vehicles — Functional safety — Part 7: Production and operation
/N4/	ISO 26262-8:2018	Road vehicles — Functional safety — Part 8: Supporting processes
/N5/	ISO 26262-9:2018	Road vehicles — Functional safety — Part 9: Automotive Safety Integrity Level (ASIL)-oriented and safety-oriented analyses

Table 4: Basic safety standards

## 4.2 Quality Management System

No.	Reference	Description	
[M1]	QMS	Quality Management System TÜV SÜD Rail GmbH	
	TR_RA_P_04.50	Test Program Functional Safety	
		TR_RA_P_04.51 Definition Scope of testing TR_RA_P_04.07 Product Modification TR_RA_P_04.52 Concept Phase & Safety Lifecycle TR_RA_P_04.53 Detail Phase Hardware TR_RA_P_04.54 Detail Phase Software TR_RA_P_04.55 Safety Manual TR_RA_P_04.56 Result of Testing	
[M2]	D-IS-11190-01-00	DAkkS accreditation according to DIN EN ISO/IEC 17020:2012; inspection body type A	
[M3]	D-PL-11190-08-00	DAkkS accreditation according to DIN EN ISO 17025:2018 / EN ISO/IEC 17025:2017	

Table 5: Quality Management System

e-mail: Axel.Koehnen@tuvsud.com

TD99727C / v1.0 TD99727C\_1.0.docx creator: Axel Köhnen 2022-11-28 page 8 of 10



#### 5 Results

### 5.1 Functional Safety

The tests performed and quality assurance measures implemented by the Texas Instruments Incorporated have shown that the DRA829/TDA4VM complies with the testing criteria specified in clause 4 subject to the conditions defined in clause 6 and is suitable for safety-related use in applications up to

- up to ASIL D for the MCU domain
- up to ASIL B for the Main domain
- Systematic Capability ASIL D according to ISO 26262.



## 6 Implementation Conditions and Restrictions

The use of the DRA829/TDA4VM shall comply with the current version of the safety related information in the user manual and safety manual, and the following implementation and installation requirements have to be followed, if the DRA829/TDA4VM is used in safety-related installations.

- The guidelines and requirements specified in the user documentation shall be followed. Only
  modules certified for safety-related operation shall be used for safety-critical functions.
  Especially the requirements of the system integration section of the safety manual have to be
  regarded.
- The impact on the overall safety concept and the safety function has to be well understood and analyzed if a safety mechanism described in the safety manual is not used.
- All safety mechanisms implemented by the system integrator have to be developed and verified according to the targeted safety standards.
- All specific characteristics and behaviors of the DRA829/TDA4VM required by the final safety function have to be developed and verified according to the targeted safety standards. This includes also timing aspects like reaction times, test intervals or test execution times.
- The system integrator has to understand the conditions and restrictions defined in the documentation of the DRA829/TDA4VM.

#### 7 Certificate Number

This report specifies technical details and implementation conditions required for the application of DRA829/TDA4VM to the certificate:

Z10 088989 0029 Rev. 00

**Technical Certifier** 

#### **IMPORTANT NOTICE AND DISCLAIMER**

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2022, Texas Instruments Incorporated