DS26C31MQML CMOS Quad TRI-STATE Differential Line Driver

Check for Samples: DS26C31MQML

FEATURES

- **TTL Input Compatible**
- **Outputs Will Not Load Line When V_{CC} = 0V**
- **Meets the Requirements of EIA Standard RS-422**
- **Operation from Single 5V Supply**
- **TRI-STATE Outputs for Connection to System Buses**
- **Low Quiescent Current**

DESCRIPTION

The DS26C31 is a quad differential line driver designed for digital data transmission over balanced lines. The DS26C31 meets all the requirements of EIA standard RS-422 while retaining the low power characteristics of CMOS. The DS26C31 is compatible with EIA standard RS-422; however, one exception in test methodology is taken. This enables the construction of serial and terminal interfaces while maintaining minimal power consumption.

The DS26C31 accepts TTL or CMOS input levels and translates these to RS-422 output levels. This part uses special output circuitry that enables the drivers to power down without loading down the bus. This device has enable and disable circuitry common to all four drivers. The DS26C31 is pin compatible to the AM26LS31 and the DS26LS31.

All inputs are protected against damage due to electrostatic discharge by diodes to V_{CC} and ground.

Connection Diagram




Figure 1. CDIP, CLGA Packages- Top View
See Package Numbers NFE0016A, NAD0016A

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2010–2013, Texas Instruments Incorporated





Figure 2. 20-Lead LCCC Package- Top View
See Package Number NAJ0020A

Logic Diagram



Truth Table (1)

ENABLE	ENABLE	Input	Non-Inverting	Inverting
			Output	Output
L	H	X	Z	Z
All other		L	L	H
combinations of		H	H	L
enable inputs				

(1) L = Low logic state
X = Irrelevant
H = High logic state
Z = TRI-STATE (high impedance)

Copyright © 2010–2013, Texas Instruments Incorporated

These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

Absolute Maximum Ratings(1)(2)

Supply Voltage (V_{CC})	−0.5V to 7.0V
DC Input Voltage (V_I)	−1.5V to V_{CC} +0.5V
DC Output Voltage (V_O)	−0.5V to 7V
Clamp Diode Current (I_{IK}, I_{OK})	±20 mA
DC Output Current, per pin (I_O)	±150 mA
DC V_{CC} or Gnd Current, per pin (I_{CC})	±150 mA
Storage Temperature Range (T_{Stg})	−65°C ≤ T_A ≤ +150°C
Lead Temperature (T_L) Soldering, 4 sec.	260°C

(1) Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not verify specific performance limits. For verified specifications and test conditions, see the Electrical Characteristics. The verified specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.
(2) Unless otherwise specified, all voltages are referenced to ground. All currents into device pins are positive, all currents out of device pins are negative.

Operating Conditions

	Min	Max	Units
Supply Voltage (V_{CC})	4.50	5.50	V
DC Input or Output Voltage (V_I, V_O)	0	V_{CC}	V
Operating Temperature Range (T_A)	−55	+125	°C

Quality Conformance Inspection

Table 1. Mil-Std-883, Method 5005 - Group A

Subgroup	Description	Temp °C
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55
12	Settling time at	+25
13	Settling time at	+125
14	Settling time at	-55

Copyright © 2010–2013, Texas Instruments Incorporated

DS26C31M Electrical Characteristics DC Parameters

Parameter		Test Conditions	Notes	Min	Max	Unit	Sub-groups
V_{IH}	Logical "1" Input Voltage			2.0		V	1, 2, 3
V_{IL}	Logical "0" Input Voltage				0.8	V	1, 2, 3
V_{OH}	Logical "1" Output Voltage	$V_I = V_{IH}$ or V_{IL}, V_{CC} = 4.5V, I_O = -20mA		2.5		V	1, 2, 3
V_{OL}	Logical "0" Output Voltage	$V_I = V_{IH}$ or V_{IL}, I_O = 20mA, V_{CC} = 4.5V			0.5	V	1, 2, 3
V_T	Differential Output Voltage	R_L = 100Ω, V_{CC} = 4.5V	(1)	2.0		V	1, 2, 3
$\lvert V_T\rvert - \lvert\overline{V_T}\rvert$	Difference in Differential Output	R_L = 100Ω, V_{CC} = 4.5V	(1)		0.4	V	1, 2, 3
V_{OS}	Common Mode Output Voltage	R_L = 100Ω, V_{CC} = 5.5V	(1)		3.0	V	1, 2, 3
$\lvert V_{OS}-\overline{V_{OS}}\rvert$	Diff in Common Mode Output	R_L = 100Ω, V_{CC} = 5.5V	(1)		0.4	V	1, 2, 3
I_I	Input Current	$V_I = V_{CC}$, Gnd, V_{IH}, or V_{IL}, V_{CC} = 5.5V			±1.0	µA	1, 2, 3
I_{CC}	Quiescent Power Supply Current	I_O = 0µA, $V_I = V_{CC}$ or Gnd, V_{CC} = 5.5V	(2)		500	µA	1, 2, 3
		I_O = 0µA, V_I = 2.4V or 0.5V, V_{CC} = 5.5V	(2)		2.1	mA	1, 2, 3
I_{OZ}	TRI-STATE Output Leakage Current	$V_O = V_{CC}$ or Gnd, Enable = V_{IL}, V_{CC} = 5.5V, $\overline{\text{Enable}}$ = V_{IH}			±5.0	µA	1, 2, 3
I_{SC}	Output Short Circuit Current	$V_I = V_{CC}$ or Gnd, V_{CC} = 5.5V	(1), (3)	-30	-150	mA	1, 2, 3
I_{Off}	Output Leakage Current "Power Off"	V_{CC} = 0V, V_O = 6V			100	µA	1, 2, 3
		V_{CC} = 0V, V_O = 0V			-100	µA	1, 2, 3

(1) See EIA Specification RS-422 for exact test conditions.
(2) Measured per input. All other inputs at V_{CC} or GND.
(3) This is the current sourced when a high output is shorted to ground. Only one output at a time should be shorted.

DS26C31M Electrical Characteristics AC Parameters - Propagation Delay Time (see Figure 26)

The following conditions apply, unless otherwise specified. V_{CC} = 5V, $t_R \le$ 6ns, $t_F \le$ 6ns

Parameter		Test Conditions	Notes	Min	Max	Unit	Sub-groups
t_{PLH}	Input to Output Prop Delay	Figure 27			14	ns	9, 10, 11
t_{PHL}	Input to Output Prop Dalay	Figure 27			14	ns	9, 10, 11
	Skew		(1)		3.0	ns	9, 10, 11
t_{TLH}	Output Rise Time	Figure 29			14	ns	9, 10, 11
t_{THL}	Output Fall Time	Figure 29			14	ns	9, 10, 11
t_{PZH}	Output Enable Time	Figure 28			22	ns	9, 10, 11
t_{PZL}	Output Enable Time	Figure 28			28	ns	9, 10, 11
t_{PHZ}	Output Disable Time	Figure 28	(2)		12	ns	9, 10, 11
t_{PLZ}	Output Disable Time	Figure 28	(2)		14	ns	9, 10, 11

(1) Skew is defined as the difference in propagation delays between complimentary outputs at the 50% point.
(2) Output disable time is the delay from ENABLE or $\overline{\text{ENABLE}}$ being switched to the output transistors turning off.

Copyright © 2010–2013, Texas Instruments Incorporated

Typical Performance Characteristics

Differential Propagation Delay vs Temperature




Figure 3.

Differential Propagation Delay vs Power Supply Voltage




Figure 4.

Differential Skew vs Temperature




Figure 5.

Differential Skew vs Power Supply Voltage




Figure 6.

Differential Transition Time vs Temperature




Figure 7.

Differential Transition Time vs Power Supply Voltage




Figure 8.

Typical Performance Characteristics (continued)

Complementary Skew vs Temperature




Figure 9.

Complementary Skew vs Power Supply Voltage




Figure 10.

Differential Output Voltage vs Output Current




Figure 11.

Differential Output Voltage vs Output Current




Figure 12.

Output High Voltage vs Output High Current




Figure 13.

Output High Voltage vs Output High Current




Figure 14.

Copyright © 2010–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Output Low Voltage vs Output Low Current




Figure 15.

Output Low Voltage vs Output Low Current




Figure 16.

Supply Current vs Temperature




Figure 17.

Output Low Voltage vs Output Low Current




Figure 18.

Output Low Voltage vs Output Low Current




Figure 19.

Supply Current vs Temperature




Figure 20.

Copyright © 2010–2013, Texas Instruments Incorporated

Typical Performance Characteristics (continued)

Supply Current vs Power Supply Voltage




Figure 21.

No Load Supply Current vs Data Rate




Figure 22.

Loaded Supply Current vs Data Rate




Figure 23.

Output Short Circuit Current vs Temperature




Figure 24.

Output Short Circuit Current vs Power Supply Voltage





Figure 25.

Copyright © 2010–2013, Texas Instruments Incorporated

AC TEST CIRCUIT AND SWITCHING TIME WAVEFORMS



Note: C1 = C2 = C3 = 40 pF (Including Probe and Jig Capacitance), R1 = R2 = 50Ω, R3 = 500Ω.

Figure 26. AC Test Circuit




Figure 27. Propagation Delays





Figure 28. Enable and Disable Times


Copyright © 2010–2013, Texas Instruments Incorporated



Input pulse; f = 1 MHz, 50%; $t_r \leq 6$ ns, $t_f \leq 6$ ns

Figure 29. Differential Rise and Fall Times

TYPICAL APPLICATIONS



*R_T is optional although highly recommended to reduce reflection.

Figure 30. Two-Wire Balanced System, RS-422

Copyright © 2010–2013, Texas Instruments Incorporated

REVISION HISTORY

Table 2. Revision History

Released	Revision	Section	Changes
10/26/2010	A	New Release, Corporate format	1 MDS data sheets converted into one Corp. data sheet format. MNDS26C31M-X Rev 0B0 will be archived.

Changes from Original (April 2013) to Revision A **Page**

- Changed layout of National Data Sheet to TI format 10

Copyright © 2010–2013, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
DS26C31ME/883	Active	Production	LCCC (NAJ) | 20	50 | TUBE	Yes	Call TI	Level-1-NA-UNLIM	-55 to 125	DS26C31ME/ 883 Q 5962-91639 01M2A ACO 01M2A >T
DS26C31ME/883.A	Active	Production	LCCC (NAJ) | 20	50 | TUBE	Yes	Call TI	Level-1-NA-UNLIM	-55 to 125	DS26C31ME/ 883 Q 5962-91639 01M2A ACO 01M2A >T
DS26C31MJ/883	Active	Production	CDIP (NFE) | 16	25 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	DS26C31MJ/883 5962-9163901MEA Q
DS26C31MJ/883.A	Active	Production	CDIP (NFE) | 16	25 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	DS26C31MJ/883 5962-9163901MEA Q
DS26C31MW/883	Active	Production	CFP (NAD) | 16	19 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	DS26C31MW /883 Q 5962-91639 01MFA ACO 01MFA >T
DS26C31MW/883.A	Active	Production	CFP (NAD) | 16	19 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	DS26C31MW /883 Q 5962-91639 01MFA ACO 01MFA >T

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.


(6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
DS26C31ME/883	NAJ	LCCC	20	50	470	11	3810	0
DS26C31ME/883.A	NAJ	LCCC	20	50	470	11	3810	0
DS26C31MJ/883	NFE	CDIP	16	25	506.98	15.24	13440	NA
DS26C31MJ/883	NFE	CDIP	16	25	506.98	15.24	13440	NA
DS26C31MJ/883.A	NFE	CDIP	16	25	506.98	15.24	13440	NA
DS26C31MJ/883.A	NFE	CDIP	16	25	506.98	15.24	13440	NA
DS26C31MW/883	NAD	CFP	16	19	502	23	9398	9.78
DS26C31MW/883.A	NAD	CFP	16	19	502	23	9398	9.78


NAJ0020A



CONTROLLING DIMENSION IS INCH
VALUES IN [ ] ARE MILLIMETERS

E20A (Rev F)


NFE0016A



CONTROLLING DIMENSION IS INCH
VALUES IN [ ] ARE MILLIMETERS

J16A (REV L)

NAD0016A



DIMENSIONS ARE IN INCHES

W16A (Rev T)

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025