

Programmer's Guide

LMK3H2108A19 Configuration Guide



ABSTRACT

This document provides the configuration information for the LMK3H2108A19 device. For the default configuration of the LMK3H2108 device, refer to the [LMK3H2108 data sheet](#).

Table of Contents

1 Configuration Overview	1
1.1 LMK3H2108A19 Configuration Information.....	1
2 Revision History	6

Trademarks

All trademarks are the property of their respective owners.

1 Configuration Overview

This section provides an overview of the critical device settings of the configurations.

1.1 LMK3H2108A19 Configuration Information

Table 1-1. LMK3H2108A19 Frequency Configuration

OTP Page	OUT0 (MHz)	OUT1 (MHz)	OUT2 (MHz)	OUT3 (MHz)	OUT4 (MHz)	OUT5 (MHz)	OUT6 (MHz)	OUT7 (MHz)
OTP Page 0	100	100	100	100	100	100	100	100
OTP Page 1	100	100	100	100	100	100	100	100
OTP Page 2	100	100	100	100	100	100	100	100
OTP Page 3	100	100	100	100	100	100	100	100

Table 1-2. LMK3H2108A19 I2C Configuration

OTP Page	I2C Configuration
OTP Page 0	I2C Address: 0x09 I Byte Register Addressing
OTP Page 1	I2C Address: 0x09 I Byte Register Addressing
OTP Page 2	I2C Address: 0x09 I Byte Register Addressing
OTP Page 3	I2C Address: 0x09 I Byte Register Addressing

OTP Page 0

Table 1-3. LMK3H2108A19 GPI Settings, OTP Page 0

GPI Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPI0	GPI	Normal	Enabled	Disabled
GPI1	GPI	Normal	Enabled	Disabled
GPI2	GPI	Normal	Enabled	Disabled
GPI3	GPI	Normal	Enabled	Disabled
GPI4	GPI	Normal	Enabled	Disabled
GPI5	GPI	Normal	Enabled	Disabled

Table 1-4. LMK3H2108A19 GPIO Settings, OTP Page 0

GPIO Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPIO0	Dynamic OTP	Normal	Enabled	Disabled
GPIO1	Dynamic OTP	Normal	Enabled	Disabled
GPIO2	GPI	Normal	Enabled	Disabled
GPIO3	Status Output	Inverted	Disabled	Enabled
GPIO4	Global OE	Inverted	Disabled	Enabled

Table 1-5. LMK3H2108A19 Input Settings, OTP Page 0

Input	Powered Up/Down	Input Format	Input Termination
IN_0	Powered Down	N/A (IN0 Unused)	None, DC
IN_1	Powered Down	N/A (IN0 Unused)	None, DC
IN_2	Powered Down	N/A (IN0 Unused)	None, DC

Table 1-6. LMK3H2108A19 Output Settings, OTP Page 0

Output	Frequency (MHz)	Format	Clock Source	Output State	OE Group	SSC Behavior
OUT0	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT1	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT2	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT3	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT4	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT5	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT6	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled
OUT7	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Disabled

OTP Page 1

Table 1-7. LMK3H2108A19 GPI Settings, OTP Page 1

GPI Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPI0	GPI	Normal	Enabled	Disabled
GPI1	GPI	Normal	Enabled	Disabled
GPI2	GPI	Normal	Enabled	Disabled
GPI3	GPI	Normal	Enabled	Disabled
GPI4	GPI	Normal	Enabled	Disabled
GPI5	GPI	Normal	Enabled	Disabled

Table 1-8. LMK3H2108A19 GPIO Settings, OTP Page 1

GPIO Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPIO0	Dynamic OTP	Normal	Enabled	Disabled
GPIO1	Dynamic OTP	Normal	Enabled	Disabled
GPIO2	GPI	Normal	Enabled	Disabled
GPIO3	Status Output	Inverted	Disabled	Enabled
GPIO4	Global OE	Inverted	Disabled	Enabled

Table 1-9. LMK3H2108A19 Input Settings, OTP Page 1

Input	Powered Up/Down	Input Format	Input Termination
IN_0	Powered Down	N/A (IN0 Unused)	None, DC
IN_1	Powered Down	N/A (IN0 Unused)	None, DC
IN_2	Powered Down	N/A (IN0 Unused)	None, DC

Table 1-10. LMK3H2108A19 Output Settings, OTP Page 1

Output	Frequency (MHz)	Format	Clock Source	Output State	OE Group	SSC Behavior
OUT0	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT1	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT2	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT3	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT4	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT5	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT6	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread
OUT7	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.25% Down-spread

OTP Page 2

Table 1-11. LMK3H2108A19 GPI Settings, OTP Page 2

GPI Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPI0	GPI	Normal	Enabled	Disabled
GPI1	GPI	Normal	Enabled	Disabled
GPI2	GPI	Normal	Enabled	Disabled
GPI3	GPI	Normal	Enabled	Disabled
GPI4	GPI	Normal	Enabled	Disabled
GPI5	GPI	Normal	Enabled	Disabled

Table 1-12. LMK3H2108A19 GPIO Settings, OTP Page 2

GPIO Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPIO0	Dynamic OTP	Normal	Enabled	Disabled
GPIO1	Dynamic OTP	Normal	Enabled	Disabled
GPIO2	GPI	Normal	Enabled	Disabled
GPIO3	Status Output	Inverted	Disabled	Enabled
GPIO4	Global OE	Inverted	Disabled	Enabled

Table 1-13. LMK3H2108A19 Input Settings, OTP Page 2

Input	Powered Up/Down	Input Format	Input Termination
IN_0	Powered Down	N/A (IN0 Unused)	None, DC
IN_1	Powered Down	N/A (IN0 Unused)	None, DC
IN_2	Powered Down	N/A (IN0 Unused)	None, DC

Table 1-14. LMK3H2108A19 Output Settings, OTP Page 2

Output	Frequency (MHz)	Format	Clock Source	Output State	OE Group	SSC Behavior
OUT0	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT1	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT2	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT3	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT4	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT5	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT6	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread
OUT7	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.3% Down-spread

OTP Page 3

Table 1-15. LMK3H2108A19 GPI Settings, OTP Page 3

GPI Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPI0	GPI	Normal	Enabled	Disabled
GPI1	GPI	Normal	Enabled	Disabled
GPI2	GPI	Normal	Enabled	Disabled
GPI3	GPI	Normal	Enabled	Disabled
GPI4	GPI	Normal	Enabled	Disabled
GPI5	GPI	Normal	Enabled	Disabled

Table 1-16. LMK3H2108A19 GPIO Settings, OTP Page 3

GPIO Pin	Pin Behavior	Polarity	Internal Pull-Down	Internal Pull-Up
GPIO0	Dynamic OTP	Normal	Enabled	Disabled
GPIO1	Dynamic OTP	Normal	Enabled	Disabled
GPIO2	GPI	Normal	Enabled	Disabled
GPIO3	Status Output	Inverted	Disabled	Enabled
GPIO4	Global OE	Inverted	Disabled	Enabled

Table 1-17. LMK3H2108A19 Input Settings, OTP Page 3

Input	Powered Up/Down	Input Format	Input Termination
IN_0	Powered Down	N/A (IN0 Unused)	None, DC
IN_1	Powered Down	N/A (IN0 Unused)	None, DC
IN_2	Powered Down	N/A (IN0 Unused)	None, DC

Table 1-18. LMK3H2108A19 Output Settings, OTP Page 3

Output	Frequency (MHz)	Format	Clock Source	Output State	OE Group	SSC Behavior
OUT0	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT1	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT2	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT3	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT4	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT5	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT6	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread
OUT7	100	85 Ω LP-HCSL	PATH1	Enabled	Global OE Only	Enabled, -0.5% Down-spread

2 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from January 22, 2026 to July 29, 2026 (from Revision * (January 2026) to Revision A (July 2026))

Page

- Updated I2C Address value in the *LMK3H2108A19 I2C Configuration* table.....[1](#)
-

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025