

Table of Contents:

Page 1:	EVM history / discussion
Page 2:	Proposed improved layout
Page 3:	Vout vs. Load (load line) and conversion eff. off 12Vin before and after snubber / gate slowing
Page 4:	Ripple out and Enable at 48A load
Page 5:	Load dynamics on EVM
Page 6:	Major waveforms before snubbers added
Page 7:	Major waveforms after snubbers added
Page 8:	Major waveforms after gate drive slowed
Page 9:	Thermal picture at max thermal load rating of 32A

History:

The HPA470 / HPA602 EVMs were developed before we had a full understanding of the CPU / GPU Core current requirements and before the high speed NextFet switches were available. Based upon earlier available FETs and our understanding of the Core current requirements provisions for 2 hi side and 2 low side FETs per phase were made and the larger IHLP5050FD chokes were designed in.

Based upon the latest requirements of 48A peak electrical and 32A for thermal purposes and the availability of these new higher speed NextFets:


- a) Only one hi side and low side MOSFET per phase is needed.
- b) Smaller IHLP4040DZ chokes can be used.
- c) The layout needs to be updated to accommodate the higher speed MOSFETs by having the input caps extremely closely coupled to the MOSFETs to reduce voltage overshoot and ringing noise. Also, a snubber needs to be added to reduce ~100Mhz ringing in noise sensitive applications.

A new layout PMP5783 is in the works to accommodate all the concerns listed in c) above. For now testing on the existing HPA-470 was done to demonstrate that the single set of FETs (per phase) and smaller chokes can meet the thermal requirements and all the electrical requirements. On the existing EVM I was able to demonstrate the elimination of ringing with the snubbers and the reduction of the peak Vds on the low side FETs by increasing R17 & R19 from zero to 5.6 ohms to slow turn on of high side MOSFETs. This came at a cost of increased losses as will be shown on Page 3. With the improved layout less snubbing and less slowing of gate drive will be needed allowing a higher efficiency.

See next page for best approach for layout which will be done in PMP5783.

For the choke the best part to use per the Vishay loss simulator is the IHLP4040DZ-01 0.56uHy choke. However, the closest part we had in our lab was IHLP4040DZ-11 0.47uHy choke. Based upon my simulations on Vishay's loss calculator the preferred part will save at 32A output an additional 350mW per phase or 700mW in all compared with the part I tested with. This will correspond to about a 2% increase in efficiency at the 32A load.

Proposed improved layout approach:



Q1 is the high side FET; Q2 is the low side FET; C1 and C2 are the input caps (ceramic size 1210); C8 and R6 is the snubber. Key is rotating Q1 and Q2 such that drain of high side FET and source of low side FET face same side where the input caps are to be placed. Snubber then should be placed as close to drain source of low side FET as feasible. Traces to gates are much less critical and can be on other layers and be signal trace (10 to 25 mils) width.

Output load line and conversion efficiency from the 12V input. Bias was always 5.00V and bias input power for gate drive is not included in calculations below. Based upon FETs used and 300kHz operation, 14mA will be needed off the 5V Bias for gate drive when switching at 300kHz.

Note: operation above 32A load (max thermal requirement) is with about 200 LFM airflow

**Regulation, losses and efficiency (from 12V excluding bias power):**

Vin Volts	Iin mA	Vout1 mVolts	Iout1 A	Efficiency %	Losses in mW
Before	Snubber	Added	And	Gate	slowed
12.11	1	997	0	N/A	12
12.11	99	995	1.01	83.8	194
12.08	489	987	5.01	83.7	962
12.06	920	978	10.00	88.1	1315
12.03	1359	970	15.00	89.0	1799
12.10	1793	962	20.00	88.7	2455
12.07	2338	952	26.00	87.7	3468
12.03	2908	943	32.01	86.3	4798
12.04	4438	916	48.01	82.3	9456
After	Snubber	Added	And	Gate	slowed
12.12	1	997	0	N/A	12
12.11	100.5	995	1.01	82.6	212
12.08	482	988	5.01	85.0	873
12.06	927	978	10.00	87.5	1400
12.03	1367	970	15.00	88.5	1895
12.10	1804	962	20.00	88.1	2588
12.06	2356	953	26.00	87.2	3635
12.03	2931	944	32.01	85.7	5042
12.07	3671	929.5	40.01	83.9	7120
12.04	4470	916	48.01	81.7	9842


At Thermal max of 32A the added losses due to snubbers and gate slowing are 244mW.

At the 48A peak load the added losses due to snubbers and gate slowing are 386mW.

Load line is -1.7mV per A instead of target -1.9mV per A. This is probably due to actual resistance of choke being 11% less than value that was used to calculate load line.


Output ripple at full Electrical load of 48A:

13-Jul-10  
16:35:33



Start up from CPU Enable (VR\_ON):


13-Jul-10  
18:05:36



Qq


Step load response using 'on board' dynamic load:

13-Jul-10  
16:41:53



Load dump response using same on board dynamic load:

13-Jul-10  
16:40:59




Qq

Major waveforms: Before snubber added or high side gate drive slowed:


Q3 of phase 2:

13-Jul-10  
16:22:15



Q6 of phase 1:


13-Jul-10  
16:23:25



Such waveforms will have both System EMC Engineer and Reliability Engineer screaming !!!


Now snubber was added, but not yet slowing of high side drive: First Q3

13-Jul-10 17:50:28  
Reading Floppy Disk Drive



And Q6:

13-Jul-10 17:52:13




System EMC happy, but not Reliability!!!

Finally, the gate drive to the high side FETs were slowed with R17 and R19 increased to 5.6 ohms from zero. This change only slows turn on, not turn off of hi side FETs.


**Q3:**

16-Jul-10  
13:57:20



**Q6:**

16-Jul-10  
13:56:15




Now both System EMC and Reliability happy!!!

Thermal results:

Note; Q3 & Q6 are the low side FETs and Q1 & Q8 are the high side FETs:  
All thermal runs / images are after snubbers added and gate drives to high side FETs slowed with R17 & R19 changed from zero to 5.6 ohms:

PMP5800 snu slo gate 12.05Vin 2.936Ain 944mV 32.09A  
Full Thermal load, no airflow 23-25 deg. C ambient  
Q3 hottest at 58; Q6at57; Q1at54; Q8at52; snubbers at 55&54;  
L1 top at 51; L2 top at 49



Thermal summaries for these two runs shown below at full 48A load with and without airflow. See the full Thermal Report in .pdf form for PMP5800 to see the actual images:

PMP5800 snu slo gate 12.03Vin 4.481Ain 916mV 48.09A  
Full electrical load, ~200 LFM airflow ave. 23-25 deg. C ambient  
Q3 hottest at 63; Q6at61; Q1at54; Q8at54; snubbers at 54&53;  
L1 top at 52; L2 top at 49

PMP5800 snu slo gate 12.04Vin 4.545Ain 919mV 48.09A  
Full electrical load, no airflow 10 minutes run 23-25 deg. C ambient  
Q3 hottest at 88; Q6at86; Q1at78; Q8at76; snubbers at 79&78;  
L1 top at 70; L2 top at 67

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

<b>Products</b>		<b>Applications</b>	
Amplifiers	<a href="http://amplifier.ti.com">amplifier.ti.com</a>	Audio	<a href="http://www.ti.com/audio">www.ti.com/audio</a>
Data Converters	<a href="http://dataconverter.ti.com">dataconverter.ti.com</a>	Automotive	<a href="http://www.ti.com/automotive">www.ti.com/automotive</a>
DLP® Products	<a href="http://www.dlp.com">www.dlp.com</a>	Communications and Telecom	<a href="http://www.ti.com/communications">www.ti.com/communications</a>
DSP	<a href="http://dsp.ti.com">dsp.ti.com</a>	Computers and Peripherals	<a href="http://www.ti.com/computers">www.ti.com/computers</a>
Clocks and Timers	<a href="http://www.ti.com/clocks">www.ti.com/clocks</a>	Consumer Electronics	<a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>
Interface	<a href="http://interface.ti.com">interface.ti.com</a>	Energy	<a href="http://www.ti.com/energy">www.ti.com/energy</a>
Logic	<a href="http://logic.ti.com">logic.ti.com</a>	Industrial	<a href="http://www.ti.com/industrial">www.ti.com/industrial</a>
Power Mgmt	<a href="http://power.ti.com">power.ti.com</a>	Medical	<a href="http://www.ti.com/medical">www.ti.com/medical</a>
Microcontrollers	<a href="http://microcontroller.ti.com">microcontroller.ti.com</a>	Security	<a href="http://www.ti.com/security">www.ti.com/security</a>
RFID	<a href="http://www.ti-rfid.com">www.ti-rfid.com</a>	Space, Avionics & Defense	<a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a>
RF/IF and ZigBee® Solutions	<a href="http://www.ti.com/lprf">www.ti.com/lprf</a>	Video and Imaging	<a href="http://www.ti.com/video">www.ti.com/video</a>
		Wireless	<a href="http://www.ti.com/wireless-apps">www.ti.com/wireless-apps</a>

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2010, Texas Instruments Incorporated