

Product Bulletin

AFE8406: Highly Integrated Wideband Receiver for Wireless Infrastructure

Highly Integrated Receiver

The AFE8406 wideband receiver from Texas Instruments (TI) provides two ADCs and up to 16 DDC channels for high density in a variety of wireless infrastructure equipments. Leveraging TI's advanced digital signal processing and mixed-signal technologies, this multi-channel communications signal processor offers a high level of integration that leads to lower costs and faster development times for systems supporting a range of 3G standards. The integration of multiple ADCs and DDCs into a single AFE8406 can significantly reduce board space and lower system cost.

Wireless applications that can benefit from the integration, performance and flexibility of the AFE8406 include:


- Base station receivers
- Multi-carrier digital receivers
- UMTS (4 carriers/1 sector with diversity)
- CDMA-1X (8 carriers/1 sector with diversity)
- TD-SCDMA (16 carriers/1 sector without diversity or 8 carriers/1 sector with diversity)
- Wideband receivers
- Software radios
- Wireless local loop
- Intelligent antennas

The AFE8406 receiver delivers outstanding IF performance with extremely low noise characteristics, assuring the signal integrity that enables multi-carrier systems. The high SNR and SFDR performance provided by the integrated dual channels of the 14-bit 85 MSPS ADC enable the designation of up to eight carriers for each channel. The device provides

Key Features

- Dual-channel input supports two signal chains for density receivers
- High-performance 14-bit 85 MSPS ADC enables multi-carrier base station receivers
- SNR greater than 68 dB at 140 MHz, SFDR greater than 70 dBc at 140 MHz
- SNR greater than 70 dB at 70 MHz, SFDR greater than 82 dBc at 70 MHz
- 8 or 16 DDC channels support more carriers per signal chain

a greater number of DDC channels than any previously available solution, enabling more carriers on each signal chain. The integrated DDC channels further support the channelization of each individual carrier in the receiver. The flexibility of the DDC also enables the support of narrowband or wideband carriers. This level of integration simplifies and reduces the amount of



The AFE8406 wideband receiver combines two ADCs and up to 16 DDC channels to achieve higher density and lower costs in a variety of wireless infrastructure equipments.

interfaces required between multiple ADC and DDC channels, as well as reduces the number of devices necessary to achieve high-density applications on one chip. The result is a smaller and lower-cost board.

An additional AFE8406 feature that provides flexible implementation are two 16-bit digital inputs. Each DDC channel can be programmed to accept data from any of the four inputs, and each channel can operate with real or complex inputs. The ADC and DDC functions are clocked independently, with built-in FIFO support for each. The device provides received total wideband power (RTWP) measurement for the composite power across carriers, with a programmable time window for

measurement. The AGC in this block detects signal power, generates 6-bits control word going outside to the digitally controlled variable gain amplifier (DVGA) connected before the ADCs, thereby creating a front end composite AGC loop that maximizes full use of the ADCs dynamic range achieving better sensitivity.

The AFE8406 wideband receiver is available in a small-footprint, 23 mm x 23 mm BGA package that keeps board requirements to a minimum.

Development Support

The AFE8406 is backed by TI's worldwide design support and manufacturing capacity. An evaluation module with the GC Studio software suite is available

for analysis, providing a fast start in development. Application notes and reference designs are also available. TI's in-depth support and manufacturing strength help speed time to market and volume ramp up for wireless infrastructure products.

For More Information

To learn more about the AFE8406 wideband receiver please visit our Web site at www.ti.com/afe8406. For more information about any of TI's extensive line of wireless infrastructure products, call your TI sales office or visit our Web site at www.ti.com/wi to find out how TI can help you cost-efficiently enhance your next generation of wireless products.

TI Worldwide Technical Support

Internet

TI Semiconductor Product Information Center Home Page

support.ti.com

TI Semiconductor KnowledgeBase Home Page

support.ti.com/sc/knowledgebase

Product Information Centers

Americas

Phone +1(972) 644-5580
 Fax +1(972) 927-6377
 Internet/Email support.ti.com/sc/pic/americas.htm

Europe, Middle East, and Africa

Phone
 Belgium (English) +32 (0) 27 45 54 32
 Finland (English) +358 (0) 9 25173948
 France +33 (0) 1 30 70 11 64
 Germany +49 (0) 8161 80 33 11
 Israel (English) 1800 949 0107
 Italy 800 79 11 37
 Netherlands (English) +31 (0) 546 87 95 45
 Russia +7 (0) 95 363 4824
 Spain +34 902 35 40 28
 Sweden (English) +46 (0) 8587 555 22
 United Kingdom +44 (0) 1604 66 33 99
 Fax +49 (0) 8161 80 2045
 Internet support.ti.com/sc/pic/euro.htm

Japan

Fax International +81-3-3344-5317
 Domestic 0120-81-0036
 Internet/Email International support.ti.com/sc/pic/japan.htm
 Domestic www.tij.co.jp/pic

Asia

Phone
 International +886-2-23786800
 Domestic Toll-Free Number
 Australia 1-800-999-084
 China 800-820-8682
 Hong Kong 800-96-5941
 India +91-80-51381665 (Toll)
 Indonesia 001-803-8861-1006
 Korea 080-551-2804
 Malaysia 1-800-80-3973
 New Zealand 0800-446-934
 Philippines 1-800-765-7404
 Singapore 800-886-1028
 Taiwan 0800-006800
 Thailand 001-800-886-0010
 Fax 886-2-2378-6808
 Email tiasia@ti.com
ti-china@ti.com
 Internet support.ti.com/sc/pic/asia.htm

Important Notice: The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

Technology for Innovators and the black/red banner are trademarks of Texas Instruments.

All other trademarks are the property of their respective owners.

B091905

© 2005 Texas Instruments Incorporated

Printed in U.S.A. by (Printer, City, State)

♻️ Printed on recycled paper



SLYT220