

MPEG Surround Audio Coding on TI Floating-Point DSPs



Fraunhofer Institut
Integrierte Schaltungen

Matthias Neusinger
Fraunhofer IIS
ner@iis.fraunhofer.de



Agenda

- The Fraunhofer Institute for Integrated Circuits
- The MPEG Surround Coding Algorithm
- Audio Coding for TI Floating-Point Processors
- Conclusions

Minds in Motion

The “Fraunhofer Gesellschaft” - FhG



- Largest private research organization in Europe
- Non-profit organization, founded in 1949
- 56 Institutes in 40 locations in Germany
- Offices in Europe, USA and Asia
- Permanent staff 12,500, mainly scientists and engineers

Minds in Motion

Fraunhofer IIS Institute for Integrated Circuits

***“Home
of mp3”***



- Founded in 1985, staff ~450 in 4 locations
- Audio and Multimedia Cluster:
 - More than 100 engineers in Erlangen
 - MPEG Audio encoders and decoders
 - MPEG-4 Advanced Audio Coding (AAC, HE-AAC v2)
 - MPEG Layer-3 (mp3)
 - MPEG-4 Video Coding, AV Streaming, Virtual Acoustics
 - Digital Rights Management

Minds in Motion

Agenda

- The Fraunhofer Institute for Integrated Circuits
- **The MPEG Surround Coding Algorithm**
- Audio Coding for TI Floating-Point Processors
- Conclusions

Minds in Motion


The MPEG Surround Coding Algorithm

- Overview
- MPEG Standardization
- Applications
- Technical Description
- Features and Modes
- Profiles and Levels
- Summary

Minds in Motion

MPEG Surround Overview


- Efficient high-quality multichannel audio coding
- Backwards compatible with existing mono/stereo systems
- Significantly better quality than matrixed surround systems
- Highly scalable from lowest bitrates to highest quality



Minds in Motion

Spatial Audio Coding

- Efficient and backwards compatible coding of multichannel audio
- Transmission of downmix and compact side information



Minds in Motion

MPEG Standardization

- ISO/MPEG Call for Proposals on 'Spatial Audio Coding' (March 2004)
- Proposals of **Fraunhofer/Agere** and **Coding Technologies/Philips** showed best and complementary performance
- Reference Model Zero: Combination of both systems (verification of merge April 2005)
- International Standard January 2007

Minds in Motion

Applications

Attractive for upgrading existing mono/stereo distribution systems to surround

- Digital Audio Broadcasting
 - DAB Surround, HD Radio
- Digital Video Broadcasting
 - ISDB, DVB-T, DVB-H, DMB
- Internet Streaming/Download
 - IPTV / Video-on-Demand

Minds in Motion



The MPEG Surround Coding Algorithm

- Overview
- MPEG Standardization
- Applications
- **Technical Description**
- Features and Modes
- Profiles and Levels
- Summary

Minds in Motion

Encoder Structure



- Processing in subband domain
- Hierarchical tree structure
- Two-to-one (TTO) and three-to-two (TTT) boxes
 - Downmixing
 - Parameter extraction
- Quantization and coding



Minds in Motion

Spatial Parameters



- Channel Level Difference (CLD)
- Inter-Channel Correlation/Coherence (ICC)
- Channel Prediction Coefficients (CPC)
- Quantization of parameters according to psychoacoustic criteria



Minds in Motion


Decoding Principle

- Processing in subband domain
- One-to-two (OTT) and two-to-three (TTT) boxes
 - Decorrelation
 - Mixing according to parameters



Minds in Motion

Decoder Structure




Minds in Motion

Filterbank

Hybrid filterbank:


- Complex-modulated 64 band QMF bank
 - Nyquist filtering of lowest 3 QMF bands
- 71 hybrid subbands
1 timeslot = 64 samples



Minds in Motion

Time/Frequency Resolution

- Customizable frame length
- Parameter sets
 - One or more per frame
 - Linear interpolation
- Grouping of hybrid subbands to parameter bands according to perceptual criteria



Minds in Motion

Decorrelation

- Recreates diffuse sound fields
- Improves spaciousness

Decorrelators:

- Create output signals with correlation close to zero
- Reverberation filters in subband domain
 - All-pass filters
 - Spectral and temporal envelope shaping

Minds in Motion

Temporal Shaping Tools



Improve temporal structure of output signals

- Subband Temporal Processing (STP)
 - Temporal shaping of decorrelated signals in the subband domain
- Guided Envelope Shaping (GES)
 - Temporal shaping of direct part of output channel signals according to transmitted envelope data

Minds in Motion

Residual Coding

- Extraction and AAC encoding of residual signals on encoder side
- Residuals replace decorrelated signals on decoder side
- Improved quality for high-bitrate scenarios (up to transparency)
- Scalable residual bandwidth



Minds in Motion


The MPEG Surround Coding Algorithm

- Overview
- MPEG Standardization
- Applications
- Technical Description
- **Features and Modes**
- Profiles and Levels
- Summary

Minds in Motion

External Downmix



- Transmission of external 'artistic' downmix
- Downmix compensation on decoder side



Minds in Motion

Binaural Processing


- Virtual headphone surround
- Binaural decoding
 - Binaural processing on decoder side
- 3D stereo mode
 - Binaural processing on encoder side for direct headphone listening
 - Inversion for MPEG surround decoding



Minds in Motion

Matrix Compatible Mode


- Encoder creates matrix compatible downmix
- Matrix inversion in MPEG Surround decoder



Minds in Motion

Enhanced Matrix Mode

- No side information
- Extraction of parameters from matrix compatible downmix
- Significantly better quality than legacy matrixed systems



Minds in Motion

Low Power Decoder

- Reduced decoding complexity/power consumption at slightly lower quality
- Partially complex processing
 - Real-valued QMF bank
 - Real to complex converters for lower QMF bands
 - Aliasing reduction
 - Low power decorrelators

Minds in Motion

Profiles and Levels

Level	Configurations	Max. output channels	Max. sampling rate	Residual coding
1	515, 525	2.0	48	-
2	515, 525	5.1	48	-
3	515, 525	5.1	48	X
4	515, 525, 727, 757	7.1	48	X
5	515, 525, 727, 757, arbitrary extension	32	96	X

Minds in Motion

MPEG Surround Summary

- High scalability from lowest bitrates to transparency
- Backwards compatible
- Support for external (artistic) downmix
- Matrix compatible encoding, enhanced matrix decoding mode
- Binaural processing
- Low power decoder profile

Minds in Motion

MPEG-Surround-Demo

- Software-Decoder + 5.1 Soundcard
- Demo Items:
 - Money
 - Five voices
 - Effects

Minds in Motion

Agenda

- The Fraunhofer Institute for Integrated Circuits
- The MPEG Surround Coding Algorithm
- **Audio Coding for TI Floating-Point Processors**
- Conclusions


Minds in Motion

Audio Coding on TI Floating-point Processors

- **TMS320C672x Processor Platform**
- Floating-point Audio Coding Basics
- MPEG-Surround Implementation
- Available Audio Codecs
- Prototype Realization

Minds in Motion

TI Floating-Point DSP Platforms



C67x+™ Floating-Point DSP Platform

	C6722B 200/250 MHz	C6726B 225/266 MHz	C6727B 250/300 MHz
MFLOPS	1200/1500	1500	1500/1800
Memory	128 K Bytes SRAM 32 K Bytes Instr. Cache	256 K Bytes SRAM 32 K Bytes Instr. Cache	256 K Bytes SRAM 32 K Bytes Instr. Cache
McASP	2	3	3
I²C	2	2	2
SPI	2	2	2
HPI	N/A	N/A	Yes
EMIF	16-bit/100MHz	16-bit/133MHz	32-bit/133MHz
dMax	Yes	Yes	Yes
Package	RFP	RFP	GDH/ZDH
Availability	NOW	NOW	NOW

← **Software Compatible** →

Typical Applications

Musical Instruments and effects



Sound and musical modification and generation



Pro-audio, synthesizers



Audio broadcast, encoding and studio applications



Minds in Motion

TMS320C672x: Features

- 200/250/300 MHz CPU clock
 - Enhanced C67x+ core
 - Memory Organization
 - 32 KByte L1 program cache
 - Up to 256 KByte internal RAM
 - dMAX DMA engine
 - Up to four floating-point additions/cycle
- ➔ Very cheap and powerful 32-bit floating-point DSP

Minds in Motion

TMS320C672x: Memory Performance

Cycles for memory transfer (1K word)

DSP, transfer memory type src→dest	C6727 (copy loop)	C6727 (DMA burst transfer)	C6713 (copy loop, L2 data cache valid/not valid)
int.→int.	1100	(7600)	2100 / 2400
int.→ext.	12300	7700	2300 / 7700
ext.→int.	55500	11000	2600 / 8200
ext.→ext.	68000	13000	2100 / 13700

C672x has no data cache

- Avoid direct SDRAM access
- Operate on internal RAM
- Use DMA for data movement

Performance of DMA: 6 cycles/word

Conclusion:

- Best performance if all data internal
- Performance problems for memory-intensive applications
- Memory optimizations


Minds in Motion

Audio Coding on TI Floating-point Processors

- TMS320C672x Processor Platform
- **Floating-point Audio Coding Basics**
- MPEG-Surround Implementation
- Available Audio Codecs
- Prototype Realization

Minds in Motion

Advantages of Real-Time DSP Systems



- Cost-effective
- Reliable
- Power-efficient
- Powerful interfaces on chip
- Low data delay between input/output

Minds in Motion

Preparation of Audio Reference Code

- Using single precision
 - Standard math functions use double precision by default
 - Single precision → final resolution of 19 bits
→ enough for 16 bit output resolution
- Avoid long integer types
 - Long (40 bit) data types to integer (32 bit)

Minds in Motion

Optimization of Audio Reference Code

- High Level
 - Powerful C-Compiler → most parts optimized in “C”
 - Algorithmic simplifications
 - Using vector functions for pipeline benefits
 - Sequential data processing
 - Advantage of L1/L2 cache strategy (671x)
 - Memory optimizations (internal memory, DMA)
- Low Level
 - Rewritten in assembler:
 - t/f-mapping (MDCT, FFT)
 - Math functions

Minds in Motion

Audio Coding on TI Floating-point Processors

- TMS320C672x Processor Platform
- Floating-point Audio Coding Basics
- **MPEG-Surround Implementation**
- Available Audio Codecs
- Prototype Realization


Minds in Motion

MPEG Surround Optimization Steps

- Reduce memory demand
- ‘Slot based’ processing
- Avoid redundant copying and math operations
- Reorganize nested loops and multidimensional arrays
- Use of vector functions

Minds in Motion

MPEG-Surround Decoder Workload



High-quality decoder
525 configuration (C6727)

- Filterbanks: 28%
- Decorrelation: 26%
- Matrix operations: 21%
- STP: 16%

Minds in Motion

Audio Coding on TI Floating-point Processors

- TMS320C672x Processor Platform
- Floating-point Audio Coding Basics
- MPEG-Surround Implementation
- Available Audio Codecs
- Prototype Realization

Minds in Motion

Available Audio Codecs for TI DSPs

All figures in MIPS for 44.1kHz sampling rate	Encoder	Decoder
	TI-C6713	TI-C6713
mp3 (stereo)	70*	35
MPEG-4 AAC-LC (stereo)	60	30
5.1 MPEG-4 HE AAC	300	-
5.1 MPEG-4 HE AAC 96kHz	-	225
mp3 Surround Decoder	-	90
MPEG-Surround	TBD	TBD

* Preliminary results, C-level optimization not completely finished

Minds in Motion

Audio Coding on TI Floating-point Processors

- TMS320C672x Processor Platform
- Floating-point Audio Coding Basics
- MPEG-Surround Implementation
- Available Audio Codecs
- **Prototype Realization**

Minds in Motion

Prototype Realization

- Hardware
 - TMS320C6713 DSK
 - Lyrtech PADK
 - DSP-Weuffen C6727 EVM
- Tools
 - CodeComposer Studio 3.1
 - CodeComposer Simulator C67xx

Minds in Motion


Lyrtech Professional Audio Development Kit (PADK)



- TMS320C6727 DSP at 300 MHz
- 128 MB SDRAM
- 16 MB Flash
- Coaxial and optical S/PDIF inputs and outputs
- 8-channel analog inputs and outputs
- 24bit 192kHz D/A and A/D converters
- LED and DIP switches
- Hi-speed USB port

Minds in Motion

DSP-Weuffen C6727 EVM



- TMS320C6727 DSP at 300 MHz
- AIC23 stereo codec
- 128 MB SDRAM
- 512 kB Flash
- 4 pushbuttons, 4 LEDs
- JTAG connector
- Connectors for memory interface expansion
- Connectors for UHPI or expansion for low cost USB-connector-card via UHPI

Minds in Motion

Agenda

- The Fraunhofer Institute for Integrated Circuits
- The MPEG Surround Coding Algorithm
- Audio Coding for TI Floating-Point Processors
- **Conclusions**

Minds in Motion

Final Conclusion

- MPEG-Surround Audio Coding algorithm is the key for exciting new products
 - Soon available on TMS320C6713/27
- Texas Instruments DSPs are a perfect platform for cost-efficient low resource implementations and rapid prototyping
- Fraunhofer IIS offers implementations for all TI floating-point platforms

Minds in Motion

MPEG Surround Audio Coding on TI Floating-Point DSPs



Fraunhofer Institut
Integrierte Schaltungen

Matthias Neusinger

Fraunhofer IIS

ner@iis.fraunhofer.de

Minds in Motion