

MPEG-2 Main Profile Decoder

CAPABILITY SUPPORTED (V1.00) FEATURES

- **MPEG-2 (MP@HL) of ISO/IEC 13818-2**
- **Compliant Per ISO/IEC 13818-4, Based on Inverse Discrete Cosine Transform (IDCT)**
- **YUV 420 Planar and YUV 422 Interleaved Output Formats**
- **Supports a Maximum of Three Quantization Tables**
- **Supports Interlaced and Progressive Decoding**
- **Tested for 720P (60 Frames Per Second) and 1080I (60 Fields Per Second) Decoding in File-To-File Tests. Actual HD Decode Performance in Real Systems Will Require System Level Optimization of Drivers and Codec Execution Framework to Achieve These Resolutions in Practice.**
- **Supports Only Elementary Video Stream Input Formats**
- **Supports MPEG-1 Constrained Parameters Bit-Streams (CPB)**

BACKGROUND

The MPEG-2 standard was initially developed by the Moving Picture Experts Group (MPEG). The standard allows text and other data to be added to video and audio data streams. It is widely used to specify the format of the digital television signals that are broadcast by terrestrial, cable, and direct broadcast satellite TV systems. It also specifies the format of movies and other programs that are distributed on DVD and other similar disks..

DESCRIPTION

TTexas Instruments MPEG-2 decoder software is a proven module that allows for digital video decoding. The ready-to-implement MPEG-2 decoder reduces time-to-market because it can be easily integrated into a design without writing or debugging software. It conforms to the MPEG-2 standards approved by the International Standards Organization (ISO) and the International Electrotechnical Commission (IEC).

The MPEG-2 Main Profile (MP) D1 decoder is xDM compliant for video decoding applications. It is available in system tested codec combinations with a codec engine, DSP/BIOS, DSPLink and Framework components. The MPEG-2 combination includes MP3 decode in audio/video example applications and other example combinations are planned for the future..



PRODUCT PREVIEW



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

is a trademark of ~ Texas Instruments.

Software Architecture

2 WWW.TI.COM/DIGITALMEDIASOFTWARE DSKT MEM, TSK API The overall software architecture for the DaVinci Technology-based TMS320DM644x processor is shown in Figure 1. TI digital media encoders and decoders seamlessly plug into the signal processing layer architecture; the right side of the above diagram. The codec engine framework includes code for different classes of TI eXpressDSP digital media software. It connects to the application layer and exposes user control through the VISA API; a high level interface that allows developers to control and operate the software from a high level Operating System (OS) environment. TI digital media codecs, such as the MPEG-2 decoder, allow developers to focus design efforts on differentiating features at the application layer, while DaVinci's open software environment allows developers to include differentiating IP on any of the DSP, application, or IO layers shown above. For more information on TI software architecture, please reference the following technical documents:

- MPEG-2 Video Decoder: TMS320C62x™ DSP Implementation




Figure 1. Software Architecture

need some text here...

Commonly Used Terms:

API – Application Programming Interface

DMAN – Direct Memory Access Manager


EPSI – Easy Peripheral Software Interface

MEM - Memory

TSK – Task

VISA – Video Imaging Speech Audio

xDM – eXpressDSP Algorithm Interoperability Standard for Digital Media



A. Available via a secure website to which registered DVEVM users are granted access

For Protection:



Figure 2. Required Tools

Performance Summary

need some text here too...

Table 1. Performance Summary

Criteria	PERFORMANCE
MIPS	<ul style="list-style-type: none"> • 170 MHz Typical (v1.00) • 220 MHz @ D1
Memory	<ul style="list-style-type: none"> • 2360 kB External • 62 kB Internal Data • 130 kB Program
Memory IO	<ul style="list-style-type: none"> • MP D1 218 megabytes/second

Availability and Pricing

- Available stand alone or in codec combinations
- Available now, v1.00
- Price: Up front fee \$10,000 + \$.50 per unit royalty @ 10 KU – for further pricing information, contact your TI representative or visit www.ti.com/digitalmediasoftware.

Future Features

- Error resiliency - bounds checking/robustness
- Trick play and reverse play support
- Bottom field reordering in case of non-progressive sequences where bottom field is sent ahead of top field for frame pictures
- Display Width feature
- Streams which are non-multiples of 16
- Feature XDM_PARSE_HEADER, allows parsing of only headers, skipping picture data decoding

PRODUCT PREVIEW

GET STARTED TODAY

Request an evaluation from your TI representative or a TI Authorized Software Provider www.ti.com/asp. To receive future updates or more information, complete the contact me information form at www.ti.com/digitalmediasoftware .

PRODUCT PREVIEW

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
RF/IF and ZigBee® Solutions	www.ti.com/lprf

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Medical	www.ti.com/medical
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2008, Texas Instruments Incorporated