## ANALOG DESIGN JOURNAL article archive

| Title   | Author(s)  | Issue Date |
|---|--|------------|
| Implementing an isolated USB2.0 On-the-go (OTG) port  | Manasa Gadiyar and Anant<br>Kamath                         | 2023 Q1    |
| Achieving high converter efficiency with an active clamp in a PSFB converter                                  | Sheng-Yang Yu, Benjamin Lough<br>and LiehChung Yin         | 2023 Q1    |
| Building a multipatient contactless vital signs sensor for at-home use with mmWave                            | Greg Peake and Matthieu<br>Chevrier                        | 2023 Q1    |
| Using a second stage filter to reduce voltage ripple  | Rich Nowakowski and Sarmad<br>Abedin                       | 2022 Q4    |
| Power factor correction using peak current-mode control   | Bosheng Sun  | 2022 Q4    |
| Addressing EMI conducted emissions challenges in electric vehicles with GaN-<br>based OBCs                    | Brent McDonald   | 2022 Q3    |
| Extending the holdup time for a wide-input DC/DC converter  | Tiger Zhou   | 2022 Q3    |
| Designing for high common-mode voltages in analog input modules   | Ahmed Noeman   | 2022 Q3    |
| Isolated voltage sensing in AC motor drives   | Alex Smith, Roland Bucksch and<br>Martin Staebler          | 2022 Q2    |
| Improve power density with a baby boost converter in a PFC circuit  | Sheng-Yang Yu, Benjamin<br>Genereaux and LiehChung Yin     | 2022 Q2    |
| Using Hall-effect sensors for contactless linear movement sensing   | Mekre Mesganaw   | 2022 Q2    |
| Protect against high-current faults using hybrid hot-swap architecture  | Rakesh Panguloori and Durga<br>Praveen G                   | 2022 Q1    |
| How to ensure the stability and performance of an active EMI filter   | Yongbin Chu and Yogesh<br>Ramadass                         | 2022 Q1    |
| How to implement an isolated USB 2.0 high-speed, Type-C® DRP  | Anant Kamath and Manasa<br>Gadiyar                         | 2022 Q1    |
| Selecting a multichannel, ultra-low current measurement IC  | Eduardo Bartolome, Shriram<br>Devi and Nagesh Surendranath | 2022 Q1    |
| Using isolated comparators for faulted detection in electric motor drives                                     | Krunal Maniar  | 2022 Q1    |
| Going TVS-less in reverse-battery protection design   | Abhijeet Godbole and Dilip Jain                            | 2021 Q4    |
| Ultra-fast USB battery charging with power dense switched-cap converters                                      | Jing Ye and Xiaohu Qin                                     | 2021 Q4    |
| Designing with small DC/DC converters: HotRod <sup>™</sup> QFN vs. enhanced HotRod <sup>™</sup> QFN packaging | Rich Nowakowski and Simon<br>Zhao                          | 2021 Q4    |
| Optimizing input and output transient settling times in amplifier circuits                                    | Timothy Claycomb   | 2021 Q4    |
| Active EMI filters to reduce size and cost of EMI filters in automotive systems                               | Yongbin Chu and Yogesh<br>Ramadass                         | 2021 Q3    |
| How to prevent transformer saturation in push-pull converters   | Anant Kamath   | 2021 Q3    |
| Using voltage supervisors for rail monitoring in functional safety applications                               | Mathew Jacob   | 2021 Q3    |
| Clutter-free power supplies for RF converters in radar applications (Part 2)                                  | Rob Reeder and Neeraj Gill                                 | 2021 Q3    |
| The pros and cons of spread-spectrum implementation methods in buck regulators                                | Sam Jaffe  | 2021 Q2    |
| Design considerations for isolated current sensing  | Alex Smith   | 2021 Q2    |
| Clutter-free power supplies for RF converters in radar applications (Part 1)                                  | Rob Reeder, Neeraj Gill                                    | 2021 Q2    |
| Current sensing in high-power USB Type-C® applications  | Damkroger, Ben   | 2021 1Q    |
| Low-noise electrification using 48-V automotive systems   | Beck, Marshall   | 2021 1Q    |

| Title  | Author(s)   | Issue Date |
|--|---|------------|
| Maximize power density with three-level buck-switching chargers                                      | Falin, Jeff   | 2021 1Q    |
| High-power, low-cost, discrete linear pre-regulator for automotive rear lights                       | Helmlinger, Michael; Zamora,<br>Marcoo; Mellin, Olivier | 2021 1Q    |
| How to simplify AFE filtering via high-speed ADCs with internal digital filters                      | Neu, Thomas   | 2020 4Q    |
| Selecting output caps to optimize ripple and stability in PSR flyback converters                     | Hegarty, Timothy  | 2020 4Q    |
| Wide-bandgap semiconductors: Performance and benefits of GaN versus SiC                              | Beheshti, Masoud  | 2020 4Q    |
| Automotive EMC-compliant reverse-battery protection with ideal-diode controllers                     | Jain, Dilip; Godbole,Abhijeet                           | 2020 4Q    |
| Multibattery management in medical ultrasound systems  | Pithadia, Sanjay; Saxena, Neeraj                        | 2020 4Q    |
| Transformer structures that achieve low EMI with low- and high-side rectifiers                       | Keogh, Bernard; Wang, Max<br>(Jun)                      | 2020 4Q    |
| Comparing two-wire microphone circuits for automotive applications                                   | Semig, Peter; Manandhar,<br>Sanjeev                     | 2020 3Q    |
| Designing high-performance PWM DACs for field transmitters   | Noeman, Ahmed   | 2020 3Q    |
| Selecting capacitors to minimize distortion in audio applications                                    | Kaye, Zak   | 2020 3Q    |
| Design considerations for USB Type-C <sup>™</sup> Power Delivery AC adapters                         | Broiles, Jim  | 2020 3Q    |
| Breaking down accuracy errors in precision high-speed signal chain designs                           | Reeder, Rob   | 2020 3Q    |
| Why use PSR-flyback isolated converters in dual-battery mHEV systems                                 | Hegarty, Timothy  | 2020 2Q    |
| Enabling precision delta-sigma ADCs in functional safety applications                                | Lotzenburger, Lars                                      | 2020 2Q    |
| Thermal design concerns for buck converters in high-power automotive<br>applications                 | Beck, Marshall  | 2020 2Q    |
| How to improve PFC light-load efficiency   | Sun, Bosheng  | 2020 1Q    |
| Error analysis for ratiometric and absolute methods of temperature sensing                           | Ebrahimi-Darkhaneh, Hadi                                | 2020 1Q    |
| Designing PoE switching supplies for input power sharing and with power limiting                     | Picard, Jean; Fernandez, Darwin                         | 2020 1Q    |
| Advanced EMI mitigation techniques for automotive converters   | Tripathi, Ambreesh; Ramadass,<br>Yogesh                 | 2020 1Q    |
| Push-pull converter simplifies isolated power supply in automotive HEV/EV system                     | Kamath, Anant   | 2020 1Q    |
| How an auxless PSR flyback converter increases PLC reliability and density                           | Hegarty, Timothy  | 2019 4Q    |
| mplementing STO functionality with diagnostic and monitoring for industrial motor<br>drives          | Bhatnagar, Aishwarya                                    | 2019 4Q    |
| Challenges and solutions for PoE systems in Ethernet switches  | Xu, Penny   | 2019 4Q    |
| EMI filter components and their nonidealities for automotive DC/DC regulators                        | Beck, Marshall  | 2019 4Q    |
| A small-footprint PoE solution for machine-vision cameras and sensors                                | Oberhuber, Ralph  | 2019 4Q    |
| mplementing a small-footprint power over Ethernet solution for machine vision<br>cameras and sensors | Graf, Steffen   | 2019 4Q    |
| Methods of output-voltage adjustment for DC/DC converters  | Chris Glaser  | 2019 3Q    |
| Maximizing the dynamic range of analog fronts ends having a transimpedance<br>amp                    | Samir Cherian   | 2019 3Q    |
| Precision signal-conditioning solutions for motor-control position feedback                          | Ralph Oberhuber   | 2019 3Q    |
| Measurement error caused by self-heating in NTC and PTC thermistors                                  | Hadi Ebrahimi-Darkhaneh                                 | 2019 3Q    |
| Select inductors for buck converters to get optimum efficiency and reliability                       | Mathew Jacob  | 2019 3Q    |
| Selecting output caps for buck converters based on Zout and load slew rates                          | Cheng, Brian; Neidorff, Bob                             | 2019 2Q    |
| Easily improve the performance of analog circuits with decompensated amplifiers                      | Freet, Jacob  | 2019 2Q    |
| High-side current sources for industrial applications  | Noeman, Ahmed   | 2019 2Q    |
| A comparison of battery-charger topologies for portable applications                                 | Aguilar, Alvaro   | 2019 2Q    |
| How to debug I2C through waveform analysis   | Nguyen, Duy   | 2019 1Q    |
| Maximizing power density and thermal performance in power- module designs                            | Frazor, Josh; Jacob, Mathew                             | 2019 1Q    |
| Selecting amplifiers for shunt-based current sensing in 3- phase motor drives                        | Staebler,Martin   | 2019 1Q    |
| mproving battery life in wearable patient monitors and medical patches                               | Pithadia, Sanjay  | 2019 1Q    |
| The impact of a balun on the second harmonic of an RF DAC  | Li, Fanlong   | 2019 1Q    |

| Title   | Author(s)  | Issue Date |
|---|--|------------|
| Multimode control for a four-switch buck-boost converter  | Sun, Bosheng   | 2018 4Q    |
| How to implement wire-break detection and diagnostics in isolated digital inputs                                | Anant, Kamath S  | 2018 4Q    |
| t's about time: How TDR enables predictive maintenance for industrial Ethernet                                  | Matthieu Chevrier, Mattieu;<br>Mauer, Thomas                                       | 2018 4Q    |
| How to use power scaling to maximize power savings in a SAR ADC system  | Sosa, Cynthia  | 2018 4Q    |
| Using a high-frequency switching regulator without a linear regulator to power a data-converter system          | Rich Nowakowski, Rich; Abedin,<br>Sarmad   | 2018 4Q    |
| Stretching a single-phase design with a buck controller to support high currents                                | Jacob, Mathew  | 2018 4Q    |
| Does adaptive pre-boost control in automotive-lighting applications boost<br>efficiency?                        | Helmlinger, Michael; Vemuri,<br>Arun   | 2018 4Q    |
| Op amps with complementary-pair input stages: What are the design trade-offs?                                   | Semig, Peter; Claycomb,<br>Timothy   | 2018 3Q    |
| Understanding 100% mode in low-power DC/DC converters   | Glaser, Chris  | 2018 3Q    |
| How to parallel two DC/DC converters with digital controllers   | Sun, Bosheng   | 2018 3Q    |
| Designing a front-end interface for vibration sensors that monitor machine performance                          | Noeman, Ahmed  | 2018 3Q    |
| A comparative analysis of bridgeless boost PFC circuit  | Chellappan, Salil  | 2018 3Q    |
| Analyzing the impact of clock noise on an RF sampling DAC system  | Li, Lanlong  | 2018 2Q    |
| How to reduce radiated emissions of digital isolators for systems with RF modules                               | Rao, Koteshwar   | 2018 2Q    |
| The architecture of a switched-capacitor charger with fast charging and high efficiency                         | Schnier, Steven; Cui, Yutian   | 2018 2Q    |
| Second-sourcing options for small-package amplifiers  | Claycomb, Tim  | 2018 2Q    |
| Common mistakes made in controller designs for power converters   | Jacob, Mathew  | 2018 1Q    |
| Design tips for linear and switched-mode power supplies   | Long, Billy  | 2018 1Q    |
| Designing for high common-mode rejection in balanced audio inputs   | Caldwell, John   | 2018 1Q    |
| RF-sampling tool kit for system designers   | Neu, Tommy   | 2018 1Q    |
| Understanding the thermal-resistance specification of DC/DC converters with<br>ntegrated power MOSFETs          | Miller, Peter; Nowakowski, Rich  | 2018 1Q    |
| Achieving a clean startup by using a DC/DC converter's precise enable pin                                       | Chris Glaser   | 2017 4Q    |
| Using interleaving with SAR ADCs for lower power, smaller siz e and lower cost                                  | Liska, Peggy   | 2017 4Q    |
| Comparing internally-compensated advanced current mode (A CM) with D-CAP3™ control                              | Nowakowski, Rich; Manack,<br>Ryan  | 2017 4Q    |
| Jsing noise-gain shaping to stabilize fully- differential amplifiers  | Freet, Jacob   | 2017 4Q    |
| Managing pixel-clock input jitter for more robust serial-link communications                                    | Syu, Jason   | 2017 4Q    |
| Reducing noise on the output of a switching regulator   | Hubbard, Dylan   | 2017 3Q    |
| mproving the thermal performance of a MicroSiPTM power module   | Glaser, Chris; Horton, Sandra  | 2017 3Q    |
| How to use isolation to improve ESD, EFT and surge immunity in industrial systems                               | Kamath, Anant  | 2017 3Q    |
| What you need to know about high-speed cables for FPD-Link III SerDes   | Chin, T.K.   | 2017 3Q    |
| Designing high-efficiency isolated bidirectional power converter for a UPS                                      | Sivakumar, Ramkumar  | 2017 2Q    |
| Control challenges in a totem pole PFC  | Sun, Bosheng   | 2017 2Q    |
| An EMC/EMI system-design and testing methodology for FPD- Link III SerDes                                       | Verma, Ankur   | 2017 2Q    |
| Designing a modern power supply for RF sampling converters  | Neu, Thomas  | 2017 2Q    |
| Design and analysis of a time-gain control (TGC) circuit to drive the control voltage<br>or TI's ultrasound AFE | Udupa, Anand; Amjhera Wala,<br>Shabbir; Nagabhushana, Karthik;<br>Pithadia, Sanjay | 2017 1Q    |
| How to design remotely powered cameras for automotive applications  | Chin, T.K.   | 2017 1Q    |
| Automating circuit designs for photodiode amplifiers  | Baker, Bonnie  | 2017 1Q    |
| Signal-to-noise ratio of an LVDT amplitude demodulator  | Vemuri, Arun; Torres, Hector   | 2017 1Q    |
| Clocking the RF ADC: Should you worry about jitter or phase noise?  | Neu, Thomas  | 2017 1Q    |

| Title   | Author(s)                                   | Issue Date |
|---|---|------------|
| How to build a LIDAR system with a time-to-digital converter  | Chevrier, Matthieu; Campanella,<br>Giovanni | 2017 1Q    |
| Designing the front-end DC/DC conversion stage to withstand automotive<br>transients                                    | Choudhary, Vijay                            | 2016 4Q    |
| System modeling in MATLAB Simulink® for PLL-based resolver-to-digital<br>converters                                     | Verma, Ankur                                | 2016 4Q    |
| Testing tips for applying external power to supply outputs without an input voltage                                     | Glaser, Chris                               | 2016 4Q    |
| Measuring the linear operating region of instrumentation amplifiers   | Semig, Pete; Wells, Collin                  | 2016 4Q    |
| Saving board space with a low-profile series-capacitor buck converter   | Shenoy, Pradeep                             | 2016 4Q    |
| Notor-control considerations for electronic speed control in drones   | Mogensen, Kristen                           | 2016 4Q    |
| Low-EMI buck converter powers a multivariable sensor transmitter with BLE connectivity                                  | Hegarty, Tim                                | 2016 3Q    |
| Modeling the output impedance of an op amp for stability analysis   | Wells, Collin; Oljaca, Miro                 | 2016 3Q    |
| Green box testing: A method for optimizing high-speed serial links  | Morrison, Casey                             | 2016 3Q    |
| How unmatched impedance at the clock input of an RF ADC affects SNR and jitter  | Tommy Neu                                   | 2016 3Q    |
| Ratiometric measurement in the context of LVDT-sensor signal conditioning   | Vemuri, Arun T; Sullivan, Matthew           | 2016 3Q    |
| low to compare your circuit requirements to active-filter approximations  | Baker, Baker                                | 2016 3Q    |
| Reduce buck converter EMI and voltage stress by minimizing inductive parasitics   | Hegarty, Timothy                            | 2016 3Q    |
| inear operating region of two-op-amp instrumentation amplifiers with gain stages  | Semig, Pete                                 | 2016 2Q    |
| Adjusting the soft-start time of an integrated power module   | Glaser, Chris                               | 2016 2Q    |
| low to select input capacitors for a buck converter   | Xie, Manjing                                | 2016 2Q    |
| ow-IQ synchronous buck converter enables intelligent field- sensor applications   | Hegarty, Timothy                            | 2016 2Q    |
| The intricacies of signal integrity in high-speed communications  | Zarr, Rick                                  | 2016 2Q    |
| ncrease power factor by digitally compensating PFC EMI- capacitor reactive<br>current                                   | Sun, Bosheng                                | 2016 2Q    |
| Battery-charging considerations for low-power applications  | Allag, Tahar                                | 2016 1Q    |
| Jsing op amps to reduce near-field EMI on PCBs  | Toporski, Todd                              | 2016 1Q    |
| Design considerations for resolver-to-digital converters in electric vehicles   | Ankur Verma, Ankur;<br>Chellamuthu, Anand   | 2016 1Q    |
| Automating amplifier circuit design   | Baker, Bonnie                               | 2016 1Q    |
| JESD204B over optical fiber enables new architecture for phased-array radar   | Guibord, Matt                               | 2016 1Q    |
| NOSFET power losses and how they affect power-supply efficiency   | Lakkas, George                              | 2016 1Q    |
| Agency requirements for stand-by power consumption with offline and PoL converters for consumer electronic applications | Nowakowski, Rich; King, Brian               | 2015 4Q    |
| Inderstanding frequency variation in the DCS-Control™ topology  | Chris Glaser                                | 2015 4Q    |
| /CM vs. VOUT plots for instrumentation amplifiers with two op amps  | Pete Semig                                  | 2015 4Q    |
| Common-mode transient immunity for isolated gate drivers  | Shailendra Baranwal                         | 2015 4Q    |
| Pushing the envelope with high-performance digital-isolation technology   | Anant Kamath                                | 2015 4Q    |
| How to reduce current spikes at AC zero-crossing for totem- pole PFC  | Bosheng Sun                                 | 2015 4Q    |
| Faster, cooler charging with dual chargers  | Jeff Falin                                  | 2015 4Q    |
| Ten tips for successfully designing with automotive EMC/EMI requirements  | Mark Sauerwald                              | 2015 3Q    |
| Transient-testing platforms and automation techniques for LDOs and buck<br>regulators                                   | Kern Wong                                   | 2015 3Q    |
| Debugging power-supply startup issues   | Robert Taylor and Ryan Manack               | 2015 3Q    |
| Ceramic or electrolytic output capacitors in DC/DC converters—Why not both?   | Michael Score                               | 2015 3Q    |
| Design tips for a resistive-bridge pressure sensor in industrial process-control<br>systems                             | Peter Semig, Collin Wells, Miro<br>Oljaca   | 2015 3Q    |
| Fast input-voltage transient response with digitally-controlled isolated DC/DC  | Frank Tang                                  | 2015 2Q    |

| Title   | Author(s)  | Issue Date |
|---|--|------------|
| Two-step calibration of sensor signal conditioners                            | Arun T Vemuri and Javier Valle-<br>Mayorga           | 2015 2Q    |
| Designing an anti-aliasing filter for ADCs in the frequency doma              | Bonnie Baker   | 2015 2Q    |
| Tips and tricks for high-speed, high-voltage measurement                      | Grant Smith  | 2015 2Q    |
| ESD204B multi-device synchronization: Breaking down the requirements          | Matt Guibord   | 2015 2Q    |
| Advanced linear equalization in multi-gigabit systems                         | Lee Sledjeski  | 2015 2Q    |
| Stabilizing difference amplifiers for headphone applications                  | John Caldwell  | 2015 1Q    |
| Reducing distortion from CMOS analog switches                                 | John Caldwell  | 2015 1Q    |
| Bandstop filters and the Bainter topology                                     | Bonnie Baker   | 2015 1Q    |
| Five steps to a great step-down converter PCB layout                          | Chris Glaser   | 2015 1Q    |
| Fly-Buck™ converter provides EMC and isolation in PLC applications            | Timothy Hegarty                                      | 2015 1Q    |
| Optimal operating point of an LED   | Donald Schelle                                       | 2015 1Q    |
| tacked-FETs enable high-efficiency, high-density solutions                    | Tiger Zhou   | 2015 1Q    |
| Distortion and source impedance in JFET-input op amps                         | Caldwell, John                                       | 2014 4Q    |
| PICE models for Precision DACs  | Prakash, Rahul                                       | 2014 4Q    |
| solated sensing systems with low power consumption                            | Duena, Jose; Hendrick, Tom                           | 2014 4Q    |
| Power-supply sequencing for FPGAs   | Sirhan, Sami; Gupta, Sureena                         | 2014 4Q    |
| Design a transient-mode bridgeless PFC with a standard PFC controller         | Yu, Sheng-Yang                                       | 2014 4Q    |
| How to set up a knock-sensor signal-conditioning system                       | Tran, Yvette   | 2014 3Q    |
| PD-Link III – doing more with less  | Sauerwald, Mark                                      | 2014 3Q    |
| Dealing with nonlinearity in LVDT position sensors                            | Vemuri, Arun T                                       | 2014 3Q    |
| Decrease testing time for quality control of op amp noise                     | Tabris, Mohamed; Barthel,<br>Richard                 | 2014 3Q    |
| Design tips for an efficient non-inverting buck-boost converter               | Fan, Haifeng   | 2014 3Q    |
| AC cycle skipping improves PFC light-load efficiency                          | Sun, Bosheng   | 2014 3Q    |
| ndustrial-strength design considerations to prevent thermal and EMI damage    | Zarr, Rick   | 2014 2Q    |
| Battery-charging considerations for high-power portable devices               | Allag, Tahar; Liu, Wenjia                            | 2014 2Q    |
| Systems telemetry: What, why and how?   | Gupta, Sureena; Sirhan, Sami                         | 2014 2Q    |
| Adapting Qi-compliant wireless-power solutions to low-power wearable products | Johns, Bill; Sengupta, Upal;<br>Siddabattula, Kalyan | 2014 2Q    |
| Extract maximum power from the supply when charging a battery                 | Falin, Jeff; Rushil, KK; Ye, Jing                    | 2014 2Q    |
| Closed-loop motor control: An Introduction to rotary resolvers                | Byrd, Dwight   | 2014 1Q    |
| ow-cost flyback solutions for 10-mW standby power                             | Lokhandwala, Adnaan                                  | 2014 1Q    |
| Split-rail approaches extend boost-converter input-voltage ranges             | Fan, Haifeng   | 2014 1Q    |
| Accurately measuring efficiency of ultralow-IQ devices                        | Glaser, Chris  | 2014 1Q    |
| New-generation ESD-protection devices need no VCC connection                  | Liang, Roger   | 2014 1Q    |
| CAN bus, Ethernet, or FPD-Link: Which is best for automotive communications?  | Sauerwald, Mark                                      | 2014 1Q    |
| When is the JESD204B interface the right choice?                              | Gupta, Sureena                                       | 2014 1Q    |
| ow-cost solution for measuring input power and RMS current                    | Sun, Bosheng   | 2013 4Q    |
| Dynamic power management for faster, more efficient battery charging          | Wong, Samuel   | 2013 4Q    |
| Fechniques for accurate PSRR measurements                                     | Rice, John; Sandler, Steve<br>(Picotest)             | 2013 4Q    |
| Correcting cross-wire faults in modern e-metering networks                    | Kugelstadt, Thomas                                   | 2013 4Q    |
| Designing active analog filters in minutes                                    | Baker, Bonnie C.                                     | 2013 4Q    |
| Driving solenoid coils efficiently in switchgear applications                 | Pithadia, Sanjay                                     | 2013 4Q    |
| High-efficiency, low-ripple DCS-Control™ offers seamless PWM/power-save       | Glaser, Chris  | 2013 3Q    |

| Title   | Author(s)                              | Issue Date |
|---|--|------------|
| Linear versus switching regulators in industrial applications with a 24-V bus                           | Nowakowski, Richard; Taylor,<br>Robert | 2013 3Q    |
| Basics of debugging the controller area network (CAN) physical layer                                    | Monroe, Scott                          | 2013 3Q    |
| Exploring anti-aliasing filters in signal conditioners for mixed- signal, multimodal sensory processing | Vemuri, Arun T.                        | 2013 3Q    |
| Improved LiFePO4 cell balancing in battery-backup systems with an Impedance<br>Track™ fuel gauge        | Keller, Keith                          | 2013 3Q    |
| Grounding in mixed-signal systems demystified, Part 2   | Pithadia, Sanjay; More, Shridhar       | 2013 2Q    |
| ntroduction to capacitive touch-screen controllers  | Siegel, Eric                           | 2013 2Q    |
| RS-485 failsafe biasing: Old versus new transceivers  | Kugelstadt, Thomas                     | 2013 2Q    |
| Synchronous rectification boosts efficiency by reducing power loss                                      | Fagnani, Anthony                       | 2013 2Q    |
| Designing a negative boost converter from a standard positive buck converter                            | Pieper, Mark                           | 2013 2Q    |
| Digital current balancing for an interleaved boost PFC  | Sun, Bosheng                           | 2013 2Q    |
| Grounding in mixed-signal systems demystified, Part 1   | Pithadia, Sanjay; More, Shridhar       | 2013 1Q    |
| Add a digitally controlled PGA with noise filter to an ADC  | Gossner, Kai                           | 2013 1Q    |
| Design of a 60-A interleaved active-clamp forward converter   | King, Brian                            | 2013 1Q    |
| Power MOSFET failures in mobile PMUs: Causes and design precautions                                     | Wong, Kern                             | 2013 1Q    |
| 35-V single-channel gate drivers for IGBT and MOSFET renewable energy applications                      | Stevens, John                          | 2013 1Q    |
| How to pick a linear regulator for noise-sensitive applications   | Gupta, Sureena                         | 2013 1Q    |
| arnessing wasted energy in 4- to 20-mA current-loop systems   | Glaser, Chris                          | 2012 4Q    |
| VEBENCH® tools and the photodetector's stability  | Baker, Bonnie C.                       | 2012 4Q    |
| DO noise examined in detail   | Nogowa, Masashi                        | 2012 4Q    |
| Design considerations for system-level ESD circuit protection   | Liang, Roger                           | 2012 4Q    |
| Simple open-circuit protection for boost converters in LED driver applications                          | Caldwell, John; Amidon, Gregory        | 2012 4Q    |
| Jsing a fixed threshold in ultrasonic distance-ranging automotive applications                          | Vemuri, Arun T.                        | 2012 3Q    |
| Data-rate independent half-duplex repeater design for RS-485  | Kugelstadt, Thomas                     | 2012 3Q    |
| Easy solar-panel maximum-power-point tracking for pulsed- load applications                             | Glaser, Chris                          | 2012 3Q    |
| ligh-definition haptics: Feel the difference!   | Rao, ShreHarsha                        | 2012 3Q    |
| Applying acceleration and deceleration profiles to bipolar stepper motors                               | Quinones, Jose                         | 2012 3Q    |
| Controlling switch-node ringing in synchronous buck converters  | Taylor, Robert; Manack, Ryan           | 2012 2Q    |
| A solar-powered buck/boost battery charger  | Falin, Jeff; Li, Wang                  | 2012 2Q    |
| Remote sensing for power supplies   | Zhou, Tiger                            | 2012 2Q    |
| Design considerations for a resistive feedback divider in a DC/DC converter                             | Fernandez, Darwin                      | 2012 2Q    |
| ndustrial flow meters/flow transmitters   | Kalyanaraman, Deepa                    | 2012 2Q    |
| Source resistance and noise considerations in amplifiers  | Vega, Jorge                            | 2012 2Q    |
| Turbo-boost charger supports CPU turbo mode   | Qian, Jinrong; Chen, Suheng            | 2012 1Q    |
| Benefits of a multiphase buck converter   | David, Baba                            | 2012 1Q    |
| Downslope compensation for buck converters when the duty cycle exceeds 50%                              | John, Bottrill                         | 2012 1Q    |
| High-efficiency AC adapters for USB charging  | Lokhandwala, Adnaan                    | 2012 1Q    |
| Measuring op-amp settling time by using sample-and-hold technique                                       | Vega, Jorge; Ramus, Xavier             | 2012 1Q    |
| Solar charging solution delivers narrow voltage DC/DC system bus for multicell<br>pattery applications  | Li, Wang; Day, Michael                 | 2011 4Q    |
| Solar lantern with dimming achieves 92% efficiency  | Glaser, Chris                          | 2011 4Q    |
| Analog linearization of resistance temperature detectors  | Trump, Bruce                           | 2011 4Q    |
| How delta-sigma ADCs work, Part 2   | Baker, Bonnie C.                       | 2011 4Q    |
| A boost-topology battery charger powered from a solar panel   | Falin, Jeff; Li, Wang                  | 2011 3Q    |

| Title  | Author(s)                             | Issue Date |
|--|---------------------------------------|------------|
| Isolated RS-485 transceivers support DMX512 stage lighting and special-effects applications                  | Kugelstadt, Thomas                    | 2011 3Q    |
| Industrial data-acquisition interfaces with digital isolators  | Kugelstadt, Thomas                    | 2011 3Q    |
| Clock jitter analyzed in the time domain, Part 3   | Neu, Thomas                           | 2011 3Q    |
| How delta-sigma ADCs work, Part 1  | Baker, Bonnie C.                      | 2011 3Q    |
| Converting single-ended video to differential video in single- supply systems                                | Karki, James                          | 2011 3Q    |
| Implementation of microprocessor-controlled, wide-input- voltage, SMBus smart battery charger                | Keller, Keith                         | 2011 2Q    |
| Benefits of a coupled-inductor SEPIC converter   | John, Betten                          | 2011 2Q    |
| IQ: What it is, what it isn't, and how to use it   | Glaser, Chris                         | 2011 2Q    |
| Backlighting the tablet PC   | Falin, Jeff; Meng, Xianghao           | 2011 2Q    |
| Challenges of designing high-frequency, high-input-voltage DC/DC converters                                  | Nowakowski, Richard; King,<br>Brian   | 2011 2Q    |
| The IBIS model, Part 3: Using IBIS models to investigate signal-integrity issues                             | Baker, Bonnie C.                      | 2011 2Q    |
| Fine tuning TI's Impedance Track™ battery fuel gauge with LiFePO4 cells in<br>shallow-discharge applications | Keller, Keith                         | 2011 1Q    |
| Designing an isolated I <sup>2</sup> C Bus interface by using digital isolators                              | Kugelstadt, Thomas                    | 2011 1Q    |
| The IBIS model, Part 2: Determining the total quality of an IBIS model                                       | Baker, Bonnie C.                      | 2011 1Q    |
| A low-cost, non-isolated AC/DC buck converter with no transformer  | Falin, Jeff; Parks, Dave              | 2010 4Q    |
| Save power with a soft Zener clamp   | John, Betten                          | 2010 4Q    |
| Clock jitter analyzed in the time domain, Part 2   | Neu, Thomas                           | 2010 4Q    |
| The IBIS model, Part 1: A conduit into signal-integrity analysis   | Baker, Bonnie C.                      | 2010 4Q    |
| Interfacing high-voltage applications to low-power controllers   | Kugelstadt, Thomas                    | 2010 4Q    |
| Coupled inductors broaden DC/DC converter usage  | Falin, Jeff                           | 2010 3Q    |
| Computing power going "Platinum"   | O'Loughlin, Michael                   | 2010 3Q    |
| Magnetic-field immunity of digital capacitive isolators  | Kugelstadt, Thomas                    | 2010 3Q    |
| Clock jitter analyzed in the time domain, Part 1   | Neu, Thomas                           | 2010 3Q    |
| Operational amplifier gain stability, Part 3: AC gain-error analysis   | Oljaca, Miroslav; Surtihadi, Henry    | 2010 3Q    |
| Discrete design of a low-cost isolated 3.3- to 5-V DC/DC converter   | Kugelstadt, Thomas                    | 2010 2Q    |
| Designing DC/DC converters based on ZETA topology  | Falin, Jeff                           | 2010 2Q    |
| How digital filters affect analog audio signal levels  | Jorge, Arbona; Supriyo, Palit         | 2010 2Q    |
| Precautions for connecting APA outputs to other devices  | Crump, Stephen                        | 2010 2Q    |
| Operational amplifier gain stability, Part 2: DC gain-error analysis   | Oljaca, Miroslav; Surtihadi, Henry    | 2010 1Q    |
| Fuel-gauging considerations in battery backup storage systems  | Karki, James                          | 2010 1Q    |
| Li-ion battery charger solutions for meeting JEITA compliance  | Qian, Jinrong                         | 2010 1Q    |
| Operational amplifier gain stability, Part 1: General system analysis  | Oljaca, Miroslav; Surtihadi, Henry    | 2010 1Q    |
| Interfacing op amps to high-speed DACs, Part 3: Current- sourcing DACs simplified                            | Karki, James                          | 2010 1Q    |
| Signal conditioning for piezoelectric sensors  | Eduardo, Bartolome                    | 2009 4Q    |
| Using power solutions to extend battery life in MSP430 applications  | Day, Michael                          | 2009 4Q    |
| Efficiency of synchronous versus nonsynchronous buck converters  | Nowakowski, Richard; Tang,<br>Ning    | 2009 4Q    |
| How the voltage reference affects ADC performance, Part 3  | Baker, Bonnie C.; Miroslav,<br>Oljaca | 2009 4Q    |
| Using fully differential op amps as attenuators, Part 3: Single- ended unipolar input signals                | Karki, James                          | 2009 4Q    |
| Interfacing op amps to high-speed DACs, Part 2: Current- sourcing DACs                                       | Karki, James                          | 2009 3Q    |
| Impact of sampling-clock spurs on ADC performance  | Neu, Thomas                           | 2009 3Q    |

| Title  | Author(s)                             | Issue Date |
|--|---------------------------------------|------------|
| How the voltage reference affects ADC performance, Part 2                                    | Baker, Bonnie C.; Miroslav,<br>Oljaca | 2009 3Q    |
| Using fully differential op amps as attenuators, Part 2: Single- ended bipolar input signals | Karki, James                          | 2009 3Q    |
| Using the infinite-gain, MFB filter topology in fully differential active filters            | Kuehl, Thomas                         | 2009 2Q    |
| Taming linear-regulator inrush currents  | Falin, Jeff                           | 2009 2Q    |
| Designing a linear Li-lon battery charger with power-path control                            | Mauney, Charles                       | 2009 2Q    |
| Selecting the right charge-management solution   | Masoud, Beheshti                      | 2009 2Q    |
| Designing with digital isolators   | Kugelstadt, Thomas                    | 2009 2Q    |
| How the voltage reference affects ADC performance, Part 1                                    | Baker, Bonnie C.; Miroslav,<br>Oljaca | 2009 2Q    |
| Using fully differential op amps as attenuators, Part 1: Differential bipolar input signals  | Karki, James                          | 2009 1Q    |
| Cell balancing buys extra run time and battery life  | Wen, Sihua                            | 2009 1Q    |
| Improving battery safety, charging, and fuel gauging in portable media applications          | Qian, Jinrong                         | 2009 1Q    |
| Paralleling power modules for high-current applications                                      | Jason, Arrigo                         | 2009 1Q    |
| Using a portable-power boost converter in an isolated flyback application                    | Falin, Jeff; King, Brian              | 2009 1Q    |
| Message priority inversion on a CAN Bus  | Crump, Stephen                        | 2009 1Q    |
| RS-485: Passive failsafe for an idle bus   | Kugelstadt, Thomas                    | 2009 1Q    |
| Output impedance matching with fully differential operational amplifiers                     | Karki, James                          | 2008 4Q    |
| Compensating and measuring the DC/DC converter loop that powers a high-<br>power LED driver  | Falin, Jeff                           | 2008 4Q    |
| Designing DC/DC converters based on SEPIC topology   | Falin, Jeff                           | 2008 4Q    |
| Getting the most battery life from portable systems  | Keller, Keith; Banak, M.A.            | 2008 4Q    |
| Stop-band limitations of the Sallen-Key, low-pass filter                                     | Baker, Bonnie C.                      | 2008 4Q    |
| Input impedance matching with fully differential amplifiers                                  | Karki, James                          | 2008 4Q    |
| A dual-polarity, bidirectional current-shunt monitor   | Kuehl, Thomas                         | 2008 3Q    |
| New current-mode PWM controllers support boost, flyback, SEPIC and LED-driver applications   | Schneider, Jürgen                     | 2008 3Q    |
| Cascading of input serializers boosts channel density for digital inputs                     | Dehmelt, Frank                        | 2008 3Q    |
| When good grounds turn bad—isolate!  | Kugelstadt, Thomas                    | 2008 3Q    |
| A DAC for all precision occasions  | Baker, Bonnie C.                      | 2008 3Q    |
| A new filter topology for analog high-pass filters   | Fortunato, Mark                       | 2008 2Q    |
| Selecting antennas for low-power wireless application  | Audun, Andersen                       | 2008 2Q    |
| Understanding output voltage limitations of DC/DC buck converters                            | Tucker, John                          | 2008 2Q    |
| Battery-charger front-end IC improves charging-system safety                                 | Ye, Mao                               | 2008 2Q    |
| Understanding the pen-interrupt (PENIRQ) operation of touch- screen controllers              | Fang, Wendy; Wang, Ing-Yih<br>James   | 2007 4Q    |
| Driving a WLED does not always require 4 V   | Hadden, William                       | 2007 4Q    |
| Host-side gas-gauge-system design considerations for single- cell handheld<br>applications   | Qian, Jinrong; Vega, Michael          | 2007 4Q    |
| Using a buck converter in an inverting buck-boost topology                                   | Tucker, John                          | 2007 4Q    |
| Using touch-screen controller's auxiliary inputs   | Fang, Wendy; Wang, Ing-Yih<br>James   | 2007 3Q    |
| Power-management solutions for telecom systems improve performance, cost,<br>and size        | Narveson, Brian C.; Harris,<br>Adrian | 2007 3Q    |
| TPS6108x: A boost converter with extreme versatility   | Falin, Jeff                           | 2007 3Q    |
| Get low-noise, low-ripple, high-PSRR power with the TPS717xx                                 | Falin, Jeff                           | 2007 3Q    |
| Simultaneous power-down sequencing with the TPS74x01 family of linear<br>regulators          | Falin, Jeff                           | 2007 3Q    |

| Title   | Author(s)   | Issue Date |
|---|---|------------|
| Calibration in touch-screen systems   | Fang, Wendy; Chang, Tony  | 2007 2Q    |
| Current balancing in four-pair, high-power PoE applications   | Tom, Steven R.  | 2007 2Q    |
| Enabling high-speed USB OTG functionality on TI DSPs  | Harmon, Dan   | 2007 2Q    |
| Spreadsheet modeling tool helps analyze power- and ground- plane voltage drops to keep core voltages within tolerance | Widener, Steve  | 2007 2Q    |
| Conversion latency in delta-sigma converters  | Baker, Bonnie C.  | 2007 2Q    |
| New zero-drift amplifier has an IQ of 17 µA   | Kugelstadt, Thomas  | 2007 1Q    |
| LDO white-LED driver TPS7510x provides incredibly small solution size   | Hadden, William   | 2007 1Q    |
| Power management for processor core voltage requirements  | Harris, Adrian  | 2007 1Q    |
| A 3 A, 1.2 Vout linear regulator with 80% efficiency and Plost < 1 W  | Falin, Jeff   | 2006 4Q    |
| Fully integrated TPS6300x buck-boost converter extends Li- ion battery life   | Johns, Bill   | 2006 4Q    |
| Detection of RS-485 signal loss   | Gingerich, Kevin  | 2006 4Q    |
| Clamp function of high-speed ADC THS4041  | Liu, Hui-Qing   | 2006 3Q    |
| TPS61059 powers white-light LED as photoflash or movie light  | Lester, Scot  | 2006 3Q    |
| TPS65552A powers portable photoflash  | Lester, Scot  | 2006 3Q    |
| Using the ADS8361 with the MSP430 USI port  | Hendrick, Tom   | 2006 3Q    |
| Complete battery-pack design for one- or two-cell portable applications   | Vega, Michael   | 2006 3Q    |
| mproved CAN network security with TI's SN65HVD1050 transceiver  | Crump, Stephen  | 2006 2Q    |
| Low-cost current-shunt monitor IC revives moving-coil meter design  | Kugelstadt, Thomas  | 2006 2Q    |
| TLC5940 PWM dimming provides superior color quality in LED video displays   | Day, Michael  | 2006 2Q    |
| Wide-input dc/dc modules offer maximum design flexibility   | Jones, Geoff  | 2006 2Q    |
| Powering today's multi-rail FPGAs and DSPs, Part 2  | Falin, Jeff   | 2006 2Q    |
| Device spacing on RS-485 buses  | Gingerich, Kevin  | 2006 2Q    |
| Matching the noise performance of the operational amplifier to the ADC  | Baker, Bonnie C.  | 2006 1Q    |
| Powering today's multi-rail FPGAs and DSPs, Part 1  | Falin, Jeff   | 2006 1Q    |
| TPS79918 RF LDO supports migration to StrataFlash® Embedded Memory (P30)  | Day, Michael  | 2006 1Q    |
| Practical considerations when designing a power supply with the TPS6211x  | Falin, Jeff; Johns, Bill  | 2006 1Q    |
| High-speed notch filters  | Carter, Bruce   | 2006 1Q    |
| Understanding and comparing data sheets for high-speed ADCs   | Eduardo, Bartolome  | 2005 4Q    |
| Getting the most out of your instrumentation amplifier design   | Kugelstadt, Thomas  | 2005 4Q    |
| TLC5940 dot correction compensates for variations in LED brightness   | Day, Michael; Saab, Tarek   | 2005 4Q    |
| Low-power, high-intercept interface to the ADS5424 14-bit, 105-MSPS converter for undersampling applications          | Steffes, Michael; Ramus, Xavier                                       | 2005 3Q    |
| Miniature solutions for voltage isolation   | Jones, Geoff  | 2005 3Q    |
| New power modules improve surface-mount manufacturability   | Thornton, Chris   | 2005 3Q    |
| So many amplifiers to choose from: Matching amplifiers to applications  | Mancini, Ron  | 2005 3Q    |
| Using resistive touch screens for human-machine interface   | Downs, Rick   | 2005 3Q    |
| Simple DSP interface for ADS784x/834x ADCs  | Hendrick, Tom   | 2005 2Q    |
| Auto-zero amplifiers ease the design of high-precision circuits   | Kugelstadt, Thomas  | 2005 2Q    |
| Understanding noise in LDO linear regulators  | Teel, John C.   | 2005 2Q    |
| Understanding power supply ripple rejection in linear regulators  | Teel, John C.   | 2005 2Q    |
| Maximizing signal integrity with M-LVDS backplanes  | McCormick, Michael; Graham,<br>David                                  | 2005 1Q    |
| A better bootstrap/bias supply circuit  | O'Loughlin, Michael   | 2005 1Q    |
| Implementation of 12-bit delta-sigma DAC with MSC12xx controller  | Cheung, Hugo; Raj, Sreeja   | 2005 1Q    |
| Clocking high-speed data converters   | Eduardo, Bartolome; Vineet,<br>Mishra; Goutam, Dutta; David,<br>Smith | 2005 1Q    |

| Title  | Author(s)                     | Issue Date         |
|--|-------------------------------|--------------------|
| 14-bit, 125-MSPS ADS5500 evaluation  | Liu, Hui-Qing                 | 2004 3Q            |
| Active filters using current-feedback amplifiers   | Stephens, Randy               | 2004 3Q            |
| Tips for successful power-up of today's high-performance FPGAs                             | Falin, Jeff; Pham, Landa      | 2004 3Q            |
| -ailsafe in RS-485 data buses  | Gingerich, Kevin              | 2004 3Q            |
| ntegrated logarithmic amplifiers for industrial applications                               | Kugelstadt, Thomas            | 2004 1Q            |
| Dp amp stability and input capacitance   | Mancini, Ron                  | 2004 1Q            |
| ED-driver considerations   | Day, Michael                  | 2004 1Q            |
| The RS-485 unit load and maximum number of bus connections                                 | Gingerich, Kevin              | 2004 1Q            |
| Estimating available application power for Power-over- Ethernet applications               | Patoka, Martin                | 2004 1Q            |
| ADS809 analog-to-digital converter with large input pulse signal                           | Liu, Hui-Qing                 | 2004 1Q            |
| wo-channel, 500-kSPS operation of the ADS8361  | Hendrick, Tom                 | 2003 4Q            |
| Calculating noise figure in op amps  | Karki, James                  | 2003 4Q            |
| JCC28517 100-W PFC power converter with 12-V, 8-W bias supply, Part 2                      | O'Loughlin, Michael           | 2003 4Q            |
| Evaluation criteria for ADSL analog front end  | Wu, John Z. ; Teeple, C.R.    | 2003 4Q            |
| Calculating noise figure and third-order intercept in ADCs                                 | Karki, James                  | 2003 4Q<br>2003 4Q |
| ADS82x ADC with non-uniform sampling clock   | Liu, Hui-Qing                 | 2003 4Q            |
| Expanding the usability of current-feedback amplifiers                                     | Stephens, Randy               | 2003 3Q<br>2003 3Q |
| /ideo switcher using high-speed op amps  | Carter. Bruce                 | 2003 3Q<br>2003 3Q |
| JCC28517 100-W PFC power converter with 12-V, 8-W bias supply, Part 1                      | O'Loughlin, Michael           | 2003 3Q            |
| Soft-start circuits for LDO linear regulators  | Falin, Jeff                   | 2003 3Q<br>2003 3Q |
|  |                               |                    |
| Auto-Track™ voltage sequencing simplifies simultaneous power-up and power-<br>lown         | Thornton, Chris               | 2003 1Q            |
| Jsing the TPS61042 white-light LED driver as a boost converter                             | Falin, Jeff                   | 2003 1Q            |
| oad-sharing techniques: Paralleling power modules with overcurrent protection              | Dinwoodie, Lisa               | 2003 1Q            |
| Analyzing feedback loops containing secondary amplifiers                                   | Mancini, Ron                  | 2003 1Q            |
| Inderstanding piezoelectric transformers in CCFL backlight applications                    | Day, Michael; Lee, Bang S.    | 2002 4Q            |
| Power conservation options with dynamic voltage scaling in portable DSP designs            | Falin, Jeff                   | 2002 4Q            |
| Jsing the UCC3580-1 controller for highly efficient 3.3-V/100- W isolated supply<br>design | King, Brian                   | 2002 4Q            |
| Active output impedance for ADSL line drivers  | Stephens, Randy               | 2002 4Q            |
| nterfacing op amps and analog-to-digital converters  | Carter, Bruce                 | 2002 4Q            |
| FilterPro™ low-pass design tool  | John, Bishop                  | 2002 3Q            |
| Jsing high-speed op amps for high-performance RF design, Part 2                            | Carter, Bruce                 | 2002 3Q            |
| Jsing direct data transfer to maximize data acquisition throughput                         | Mark, Buccini                 | 2002 3Q            |
| MSC1210 debugging strategies for high-precision smart sensors                              | Cheung, Hugo                  | 2002 3Q            |
| Adjusting the A/D voltage reference to provide gain  | Russell, Anderson             | 2002 2Q            |
| Jsing high-speed op amps for high-performance RF design, Part 1                            | Carter, Bruce                 | 2002 2Q            |
| Vorst-case design of op amp circuits   | Mancini, Ron                  | 2002 2Q            |
| Fully differential amplifier design in high-speed data acquisition systems                 | Karki, James                  | 2002 2Q            |
| Powering electronics from the USB port   | Kollman, Robert; Betten, John | 2002 2Q            |
| Dptimizing the switching frequency of ADSL power supplies                                  | John, Betten; Michael, Day    | 2002 2Q            |
| SWIFT™ Designer power supply design program  | Rogers, Philip; John, Bishop  | 2002 2Q            |
| Synchronizing non-FIFO variations of the THS1206   | Hendrick, Tom                 | 2002 2Q            |
| SHDSL AFE1230 application  | Liu, Hui-Qing                 | 2002 1Q            |
| Why use a wall adapter for ac input power?   | Kollman, Robert; Betten, John | 2002 1Q            |
| Audio power amplifier measurements, Part 2   | Palmer, Richard               | 2002 1Q            |
| Power control design key to realizing InfiniBand(SM) benefits                              | Jonathan, Bearfield           | 2002 1Q            |

| Title   | Author(s)                                      | Issue Date |
|---|--|------------|
| Power consumption of LVPECL and LVDS  | Sterzik, Chris                                 | 2002 1Q    |
| Comparing magnetic and piezoelectric transformer approaches in CCFL applications  | Wells, Eddy                                    | 2002 1Q    |
| Intelligent sensor system maximizes battery life: Interfacing the MSP430F123 Flash<br>MCU, ADS7822, and TPS60311          | Mark, Buccini                                  | 2001 3Q    |
| Audio power amplifier measurements  | Palmer, Richard                                | 2001 3Q    |
| An audio circuit collection, Part 3   | Carter, Bruce                                  | 2001 3Q    |
| Designing for low distortion with high-speed op amps  | Karki, James                                   | 2001 3Q    |
| Runtime power control for DSPs using the TPS62000 buck converter  | Matzberger, Markus                             | 2001 3Q    |
| Power supply solution for DDR bus termination   | Kollman, Robert; Betten, John;<br>Lee, Bang S. | 2001 3Q    |
| The SN65LVDS33/34 as an ECL-to-LVTTL converter  | Sterzik, Chris                                 | 2001 3Q    |
| A/D and D/A conversion of PC graphics and component video signals, Part 2:<br>Software and control                        | Bart De, Canne                                 | 2001 3Q    |
| -48-V/+48-V hot-swap applications   | Dai, Heping                                    | 2001 1Q    |
| Frequency response errors in voltage feedback op amps   | Mancini, Ron                                   | 2001 1Q    |
| An audio circuit collection, Part 2   | Carter, Bruce                                  | 2001 1Q    |
| Pressure transducer-to-ADC application  | John, Bishop                                   | 2001 1Q    |
| Notebook computer upgrade path for audio power amplifiers   | Palmer, Richard                                | 2001 1Q    |
| Optimal design for an interleaved synchronous buck converter under high-slew-<br>rate, load-current transient conditions  | Miftakhutdinov, Rais                           | 2001 1Q    |
| 1.6- to 3.6-volt BTL speaker driver reference design  | Kehr, Ryan                                     | 2001 1Q    |
| Synthesis and characterization of nickel manganite from different carboxylate precursors for thermistor sensors           | Kamat, R.K.; Naik, G.M.;<br>Verenkar, V.M.S.   | 2001 1Q    |
| A/D and D/A conversion of PC graphics and component video signals, Part 1:<br>Hardware                                    | Bart De, Canne                                 | 2001 1Q    |
| Using SPI synchronous communication with data converters—interfacing the MSP430F149 and TLV5616                           | Mancini, Ron                                   | 2001 1Q    |
| Building a simple data acquisition system using the TMS320C31 DSP   | Parguian, Joselito                             | 2001 1Q    |
| Comparison of different power supplies for portable DSP solutions working from a single-cell battery                      | Neuhaeusler, Juergen                           | 2000 4Q    |
| Understanding the load-transient response of LDOs   | King, Brian                                    | 2000 4Q    |
| A statistical survey of common-mode noise   | Gaboian, Jerry                                 | 2000 4Q    |
| Analysis of fully differential amplifiers   | Karki, James                                   | 2000 4Q    |
| Thermistor temperature transducer-to-ADC application  | John, Bishop                                   | 2000 4Q    |
| An audio circuit collection, Part 1   | Carter, Bruce                                  | 2000 4Q    |
| The Active Fail-Safe feature of the SN65LVDS32A   | Morgan, Mark; Smith, Bryan                     | 2000 4Q    |
| Using quad and octal ADCs in SPI mode   | Hendrick, Tom                                  | 2000 4Q    |
| Hardware auto-identification and software auto-configuration for the TLV320AIC10<br>DSP Codec-a "plug-and-play" algorithm | Fang, Wendy; Miller, Perry                     | 2000 4Q    |
| Smallest DSP-compatible ADC provides simplest DSP interface   | Purvis, Joe                                    | 2000 4Q    |
| Optimal output filter design for microprocessor or DSP power supply   | Miftakhutdinov, Rais                           | 2000 3Q    |
| Advantages of using PMOS-type low-dropout linear regulators in battery<br>applications                                    | King, Brian                                    | 2000 3Q    |
| Performance of LVDS with different cables   | Dehmelt, Frank                                 | 2000 3Q    |
| Efficiently interfacing serial data converters to high-speed DSPs   | Philipose, Lijoy                               | 2000 3Q    |
| Higher data throughput for DSP analog-to-digital converters   | Heinz-Peter, Beckemeyer                        | 2000 3Q    |
| New DSP development environment includes data converter plug-ins  | Christ, Manfred; Walzer, Frank                 | 2000 3Q    |
| Reducing PCB design costs: From schematic capture to PCB layout   | Hendrick, Tom                                  | 2000 3Q    |
| The PCB is a component of op amp design   | Carter, Bruce                                  | 2000 3Q    |

| Title   | Author(s)                               | Issue Date |
|---|---|------------|
| Fully differential amplifiers   | Karki, James                            | 2000 3Q    |
| Design of op amp sine wave oscillators  | Mancini, Ron                            | 2000 3Q    |
| Low-cost, minimum-size solution for powering future- generation Celeron <sup>™</sup> -type processors with peak currents up to 26 A | Miftakhutdinov, Rais; Rogers,<br>Philip | 2000 2Q    |
| Simple design of an ultra-low-ripple DC/DC boost converter with TPS60100 charge<br>pump   | Kormann, Brigitte; Pelfrey, Jim         | 2000 2Q    |
| LVDS: The ribbon cable connection   | Cole, Elliott                           | 2000 2Q    |
| Introduction to phase-locked loop system modeling   | Li, Wang; Meiners, Jason                | 2000 2Q    |
| The design and performance of a precision voltage reference circuit for 14-bit and 16-bit A-to-D and D-to-A converters              | Miller, Perry; Moore, Doug              | 2000 2Q    |
| Using a decompensated op amp for improved performance   | Karki, James                            | 2000 2Q    |
| Sensor to ADC-analog interface design   | Mancini, Ron                            | 2000 2Q    |
| LVDS receivers solve problems in non-LVDS applications  | Cole, Elliott                           | 2000 1Q    |
| Skew definition and jitter analysis   | Corrigan, Steve                         | 2000 1Q    |
| Powering Celeron <sup>™</sup> -type microprocessors using TI's TPS5210 and TPS5211 controllers                                      | Miftakhutdinov, Rais; Rogers,<br>Philip | 2000 1Q    |
| Power supply solutions for TI DSPs using synchronous buck converters  | Lee, Bang S.                            | 2000 1Q    |
| A methodology of interfacing serial A-to-D converters to DSPs   | Kugelstadt, Thomas                      | 2000 1Q    |
| PCB layout for the TPA005D1x and TPA032D0x Class-D APAs   | Palmer, Richard                         | 2000 1Q    |
| Matching operational amplifier bandwidth with applications  | Mancini, Ron                            | 2000 1Q    |
| Understanding the stable range of equivalent series resistance of an LDO regulator  | Lee, Bang S.                            | 1999 4Q    |
| Synchronous buck regulator design using the TI TPS5211 high-frequency hysteretic controller   | Miftakhutdinov, Rais                    | 1999 4Q    |
| TI TPS5602 for powering TI's DSP  | Lee, Bang S.                            | 1999 4Q    |
| Keep an eye on the LVDS input levels  | Cole, Elliott                           | 1999 4Q    |
| Techniques for sampling high-speed graphics with lower- speed A/D converters  | Bart De, Canne                          | 1999 4Q    |
| Precision voltage references  | Miller, Perry; Moore, Doug              | 1999 4Q    |
| Reducing crosstalk of an op amp on a PCB  | Stephens, Randy                         | 1999 4Q    |
| Single-supply op amp design   | Mancini, Ron                            | 1999 4Q    |
| Migrating from the TI TL770x to the TI TLC770x  | Benjie, Balser                          | 1999 3Q    |
| Extended output voltage adjustment (0 V to 3.5 V) using the TI TPS5210  | Lee, Bang S.                            | 1999 3Q    |
| Stability analysis of low-dropout linear regulators with a PMOS pass element  | Rogers, Everett                         | 1999 3Q    |
| TIA/EIA-568A Category 5 cables in low-voltage differential signaling (LVDS)   | Cole, Elliott                           | 1999 3Q    |
| Evaluating operational amplifiers as input amplifiers for A-to-D converters   | Karki, James                            | 1999 3Q    |
| Low-power data acquisition sub-system using the TI TLV1572  | Kugelstadt, Thomas                      | 1999 3Q    |
| Aspects of data acquisition system design   | Miller, Perry                           | 1999 3Q    |
| Power supply decoupling and audio signal filtering for the Class-D audio power<br>amplifier   | Palmer, Richard; Darling, Timothy       | 1999 3Q    |
| Reducing the output filter of a Class-D amplifier   | Score, Mike                             | 1999 3Q    |

**Important Notice:** The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

All trademarks are the property of their respective owners.

© 2023 Texas Instruments Incorporated



## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2023, Texas Instruments Incorporated