REVISIONS		
REV #	DESCRIPTION	DATE
REV E1-1	CCN #	091023

FABRICATION NOTES:

1. FABRICATE PCB IN ACCORDANCE WITH IPC-6012D, CLASS 2; PER IPC-6011. PCB SHALL BE MANUFACTURED USING ITEQ IT 180A OR EQUIVALENT
2. MATERIALS:
   1. LAMINATE AND PREPREG (8-STAGE) TO BE IN ACCORDANCE WITH IPC-4101/126. (NELCO TG 170)
   2. COPPER FOIL TO BE IN ACCORDANCE WITH IPC-MF-150. UNLESS OTHERWISE SPECIFIED, THE COPPER FOIL THICKNESS TOLERANCES SHALL BE AS PER IPC 4012B TABLE NO.3-7 AND 3-8.
3. ALL HOLES SHALL BE LOCATED WITHIN 0.150MM DIAMETER OF TRUE POSITION. LAYER TO LAYER REGISTRATION SHALL BE WITHIN 0.125MM.
4. BOW AND TWIST SHALL NOT EXCEED MORE THAN 0.75% OF THE DESIGN LENGTH.
5. CONDUCTOR WIDTH SHALL NOT BE LESS THAN 20% FROM ITS ORIGINAL DATA. INCASE FOR MATCHING IMPEDANCE MISTRAL SHALL APPROVE THE MODIFIED WIDTHS AND SPACING. TRACE WIDTH SHALL BE MEASURED ON THE SURFACE IN CONTACT WITH THE LAMINATE.
6. BOARD FINISHED SHALL BE ACCORDING TO IPC-6012D CLASS 2.
7. AUTOMATED OPTICAL INSPECTION OF ALL THE LAYERS IS REQUIRED.
8. FINISH:
   1. ALL EXPOSED CONDUCTIVE PATTERN AREAS NOT COVERED WITH SOLDER MASK OR OTHER PLATING SHALL BE ENIG, ELECTROLESS NICKEL/IMMERSION GOLD, ELECTROLESS NICKEL SHALL BE 3-6 MICRONS, TYPICAL IMMERSION GOLD THICKNESS SHALL BE 0.04-0.06 MICRONS OF SOLDERABLE IMMERSION GOLD SURFACE.
   2. APPLY LIQUID PHOTO IMAGEABLE SOLDER MASK PER IPC-SM-840, CLASS H, TO BOTH SIDES OF THE BOARD OVER BARE COPPER. VIA HOLES SHALL BE RESIN FILLED AND COVERED WITH SOLDER MASK. ONLY SOLDER MASK IMAGES THAT ARE 0.08(0.003") PER SIDE SHALL BE REDUCED IF REQUIRED. ALL OTHER SOLDER MASK IMAGES SHALL NOT BE ENLARGED. DEFAULT COLOUR OF SOLDER MASK SHALL BE GREEN.
   3. SILKSCREEN SHALL BE WHITE, PERMANENT, ORGANIC, NON-CONDUCTIVE INK. THERE SHALL BE NO SILKSCREEN ON ANY SOLDERABLE COMPONENT PAD. CLIPPING OF SILK SCREEN SHALL BE ALLOWED IF THE SILK SCREEN FALLS ON SOLDERABLE AREAS.
   4. SURFACE AND VIA HOLES FINISH SHALL NOT BE LESS THAN 250M (0.00570"). INCASE OF LASER VIA'S, BLIND VIA'S SHALL NOT BE LESS THAN 120M (0.00247") AND BURIED VIA'S SHALL NOT BE LESS THAN 150M (0.0006").
   5. ALL HOLES SURROUNDED BY LAND <=0.010" SHALL BE COMPLIANCE TO IPC6012, CLASS 2.
9. MARKING:
   1. BOARD SHALL MEET THE REQUIREMENTS OF UL-796E WITH FLAMMABILITY RATING OF MINIMUM 94V-0. UL LOGO, MANUFACTURER'S IDENTIFICATION AND DATE CODE LETTER SHALL BE RENDERED IN SILKSCREEN.
10. TEST REQUIREMENTS:
   1. 100% NET LIST ELECTRICAL VERIFICATION USING MISTRAL SUPPLIED IPC-D-356 NET LIST FOR OPENS AND SHORTS.
11. TARNISH IS ALLOWED ONLY IN THE PANEL FRAME, NOT IN THE CIRCUIT AREA.
12. TEAR DROPS SHALL BE ADDED ON VIA'S AND THROUGH HOLE PADS IN ALL INTERNAL AND OUTER LAYERS.
13. ALL UNCONNECTED VIA'S SHALL BE SUPPRESSED IF REQUIRED.
14. FINISHED PCB THICKNESS SHALL BE 0.070" +/-10%.
15. MIN TRACE WIDTH/SPACING ON BOARD IS 0.0032"/0.0031".
16. ENSURE UL REGISTERED E-FILE NUMBER SHALL BE PRINTED ON THE PCB SILKSCREEN.
17. VIA ON PAD SHALL BE RESIN FILLED AND CAP-PLATED.





DRILL CHART: TOP to BOTTOM

ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	8.0	+3.0/-3.0	PLATED	3348
•	32.0	+3.0/-3.0	PLATED	1
•	36.0	+3.0/-3.0	PLATED	66
•	40.0	+3.0/-3.0	PLATED	6
•	42.0	+3.0/-3.0	PLATED	24
•	44.0	+2.0/-2.0	PLATED	4
•	52.0	+3.0/-3.0	PLATED	4
■	66.0	+3.0/-3.0	PLATED	4
●	118.0	+3.0/-3.0	PLATED	3
•	32.0	+3.0/-3.0	NON-PLATED	4
•	34.0	+2.0/-2.0	NON-PLATED	2
•	44.0	+2.0/-2.0	NON-PLATED	1
■	48.0	+3.0/-3.0	NON-PLATED	2
■	62.0	+2.0/-2.0	NON-PLATED	1
■	66.0	+3.0/-3.0	NON-PLATED	2
■	68.0	+3.0/-3.0	NON-PLATED	4
◆	108.0	+3.0/-3.0	NON-PLATED	10
◆	126.0	+3.0/-3.0	NON-PLATED	4
•	49.0x22.0	+3.0/-3.0	PLATED	4
●	62.0x24.0	+2.0/-2.0	PLATED	4
■	68.0x34.0	+3.0/-3.0	PLATED	2
▬	82.0x24.0	+2.0/-2.0	PLATED	4
▬	118.0x28.0	+3.0/-3.0	PLATED	2

LAYER STACKUP

LAYER NAME		FINISHED Cu	X-SECTION	DIELECTRIC THICKNESS [INCHES]
PRIMARY SIDE SILKSCREEN				
PRIMARY SIDE SOLDERMASK				
L01	PRIMARY SIDE	1.35oz		0.0035
L02	GROUND-PLANE-1	1.0oz		0.0040
L03	INNER-SIGNAL-1	1.0oz		0.0057
L04	GROUND-PLANE-2	1.0oz		0.0050
L05	INNER-SIGNAL-2	1.0oz		0.0058
L06	GROUND-PLANE-3	1.0oz		0.0040
L07	POWER-PLANE-1	1.0oz		0.0058
L08	POWER-PLANE-2	1.0oz		0.0050
L09	POWER-PLANE-3	1.0oz		0.0054
L10	INNER-SIGNAL-3	1.0oz		0.0040
L11	GROUND-PLANE-4	1.0oz		0.0035
L12	SECONDARY SIDE	1.35oz		
SECONDARY SIDE SOLDERMASK				
SECONDARY SIDE SILKSCREEN				

IMPEDANCE SPECIFICATIONS

SLN	TYPE	LAYER	TRACEWIDTH(Mils)	SPACING(Mils)	IMPEDANCE(Ohms)	REF LAYER
01	EDGE COUPLED MICROSTRIP	L1, L12	4.1	6.2	100	L2, L11
02	EDGE COUPLED MICROSTRIP	L1, L12	4	4.5	90	L2, L11
03	MICROSTRIP	L1, L12	5.9	NA	50	L2, L11
04	EDGE COUPLED STRIPLINE	L3, L10	4.2	5	100	L2/L4, L9/L11
05	EDGE COUPLED STRIPLINE	L05	4.5	6.1	100	L4/L6
06	EDGE COUPLED STRIPLINE	L3, L10	3.6	5.8	90	L2/L4, L9/L11
07	EDGE COUPLED STRIPLINE	L5	4	4.7	90	L4/L6
08	EDGE COUPLED STRIPLINE	L3, L10	4.3	4.5	80	L2/L4, L9/L11
09	EDGE COUPLED STRIPLINE	L5	5.2	4.2	80	L5/L6
10	EDGE COUPLED STRIPLINE	L10	4.5	4.5	85	L9/L11
11	EDGE COUPLED STRIPLINE	L3	3	6.5	133	L2/L4
12	STRIPLINE	L3, L10	4.5	NA	50	L2/L4, L9/L11
13	STRIPLINE	L5	4.05	NA	50	L4/L6
14	STRIPLINE	L5	8.2	NA	80	L5/L6
15	STRIPLINE	L3	3	NA	50	L2/L4
16	STRIPLINE	L10	8	NA	33	L9/L11
17	MICROSTRIP	L1	8	NA	50	L2
18	STRIPLINE	L3	3	NA	66	L2/L4
19	MICROSTRIP	L1	17.5	NA	33	L2

SIGNATURES		DATE
LAYOUT BY	KK	091023
REVIEWED BY	ZA	091023
APPROVED BY	AMB	091023

TEXAS INSTRUMENTS

PROC1664E1-1

AM62P EVM BOARD

SIZE	REV
D	E1-1
SCALE:NONE	SHEET 1 OF 19