AC INPUT
90~264VAC
50/60 Hz

## Assembly Notes

1.

12V/1.5A

5V/0.2A

BSC074N15NS5ATMA1

IPB048N15N5LF

RLTI-1457

T1

Lm = 300uH

P:S1:S2:A = 33:5:5:7

IPD70R1K4P7S

CPC3982TTR

TPS629203DRLR

UCC28781QRTWRQ1

UCC5304DWV

TLP383(GR-TPL,E

ATL431AIDBZR

| | | | |
|---|---|---|---|
| Orderable: UCC28781EVM-053 | | Designed for: Public Release | Mod. Date: 2/8/2023 |
| TID #: N/A | | Project Title: ZVS Aux Flyback | |
| Number: PMP23195 | Rev: C | Sheet Title: | |
| SVN Rev: Not in version control | | Assembly Variant: 001 | Sheet: 1 of 2 |
| Drawn By: U. Goerke | | File: PMP23331.schdoc | Size: B |
| Engineer: Ben Lough | | Contact: http://www.ti.com/support | |

Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

http://www.ti.com

© Texas Instruments 2022