REVISIONS		
REV #	DESCRIPTION	DATE
REV E2	CCN #	270225

FABRICATION NOTES:

1. FABRICATE PCB IN ACCORDANCE WITH IPC-6012B, CLASS 2; PER IPC-6011. PCB SHALL BE MANUFACTURED USING ITEQ IT 180A OR EQUIVALENT
2. MATERIALS:
   1. LAMINATE AND PREPREG (B-STAGE) TO BE IN ACCORDANCE WITH IPC-4101/126. (MIN.TG 170)
   2. COPPER FOIL TO BE IN ACCORDANCE WITH IPC-MF-150. UNLESS OTHERWISE SPECIFIED, THE COPPER FOIL THICKNESS TOLERANCES SHALL BE AS PER IPC 6012B TABLE NO.3-7 AND 3-8.
3. ALL HOLES SHALL BE LOCATED WITHIN 0.15MM DIAMETER OF TRUE POSITION. LAYER TO LAYER REGISTRATION SHALL BE WITHIN 0.125MM.
4. BOW AND TWIST SHALL NOT EXCEED MORE THAN 0.75% OF THE DESIGN LENGTH.
5. CONDUCTOR WIDTH SHALL NOT BE LESS THAN 20% FROM ITS ORIGINAL DATA. INCASE FOR MATCHING IMPEDANCE MISTRAL SHALL APPROVE THE MODIFIED WIDTHS AND SPACING. TRACE WIDTH SHALL BE MEASURED ON THE SURFACE IN CONTACT WITH THE LAMINATE.
6. BOARD FINISHED SHALL BE ACCORDING TO IPC-6012D CLASS 2.
7. AUTOMATED OPTICAL INSPECTION OF ALL THE LAYERS IS REQUIRED.
8. FINISH:
   1. ALL EXPOSED CONDUCTIVE PATTERN AREAS NOT COVERED WITH SOLDER MASK OR OTHER PLATING SHALL BE ENIG, ELECTROLESS NICKEL/IMMERSION GOLD, ELECTROLESS NICKEL SHALL BE 3-6 MICRONS, TYPICAL IMMERSION GOLD THICKNESS SHALL BE 0.04-0.06 MICRONS OF SOLDERABLE IMMERSION GOLD SURFACE.
   2. APPLY LIQUID PHOTO IMAGEABLE SOLDER MASK PER IPC-SM-840, CLASS H, TO BOTH SIDES OF THE BOARD OVER BARE COPPER. VIA HOLES SHALL BE RESIN FILLED AND COVERED WITH SOLDER MASK. ONLY SOLDER MASK IMAGES THAT ARE 0.08(0.003") PER SIDE SHALL BE REDUCED IF REQUIRED. ALL OTHER SOLDER MASK IMAGES SHALL NOT BE ENLARGED. DEFAULT COLOUR OF SOLDER MASK SHALL BE GREEN.
   3. SILKSCREEN SHALL BE WHITE, PERMANENT, ORGANIC, NON-CONDUCTIVE INK. THERE SHALL BE NO SILKSCREEN ON ANY SOLDERABLE COMPONENT PAD. CLIPPING OF SILK SCREEN SHALL BE ALLOWED IF THE SILK SCREEN FALLS ON SOLDERABLE AREAS.
   4. SURFACE AND VIA HOLES FINISH SHALL NOT BE LESS THAN 200M [0.00079"], INCASE OF LASER VIA'S, BLIND VIA'S SHALL NOT BE LESS THAN 12UM [0.00047"] AND BURIED VIA'S SHALL NOT BE LESS THAN 15UM [0.0006"].
   5. ALL HOLES SURROUNDED BY LAND <=0.010" SHALL BE COMPLIANCE TO IPC6012, CLASS 2.
9. MARKING:
   1. BOARD SHALL MEET THE REQUIREMENTS OF UL-796E WITH FLAMMABILITY RATING OF MINIMUM 94V-0. UL LOGO, MANUFACTURER'S IDENTIFICATION AND DATE CODE LETTER SHALL BE RENDERED IN SILKSCREEN.
10. TEST REQUIREMENTS:
   1. 100% NET LIST ELECTRICAL VERIFICATION USING MISTRAL SUPPLIED IPC-D-356 NET LIST FOR OPENS AND SHORTS.
11. THIEVING IS ALLOWED ONLY IN THE PANEL FRAME, NOT IN THE CIRCUIT AREA.
12. TEAR DROPS SHALL BE ADDED ON VIA'S AND THROUGH HOLE PADS IN ALL INTERNAL AND OUTER LAYERS.
13. ALL UNCONNECTED VIA'S SHALL BE SUPPRESSED IF REQUIRED.
14. FINISHED PCB THICKNESS SHALL BE 0.070" +/-10%.
15. MIN TRACE WIDTH/SPACING ON BOARD IS 0.0032"/0.0031".
16. ENSURE UL REGISTERED E-FILE NUMBER SHALL BE PRINTED ON THE PCB SILKSCREEN.
17. VIA ON PAD SHALL BE RESIN FILLED AND CAP-PLATED.

DETAIL-A

DETAIL-A(V-GROOVE DETAILS)
SCALE:NTS

DRILL CHART: TOP to BOTTOM

ALL UNITS ARE IN MILS

FIGURE	FINISHED SIZE	TOLERANCE DRILL	TOLERANCE TRAVEL	PLATED	QTY
•	8.0	+3.0/-3.0	-	PLATED	3408
•	30.0	+3.0/-3.0	-	PLATED	1
•	36.0	+3.0/-3.0	-	PLATED	48
•	40.0	+3.0/-2.0	-	PLATED	6
•	40.0	+3.0/-3.0	-	PLATED	86
•	44.0	+2.0/-2.0	-	PLATED	4
■	66.0	+3.0/-3.0	-	PLATED	4
◎	118.0	+3.0/-3.0	-	PLATED	1
▪	32.0	+3.0/-3.0	-	NON-PLATED	4
▪	34.0	+2.0/-2.0	-	NON-PLATED	2
▪	44.0	+2.0/-2.0	-	NON-PLATED	1
▪	48.0	+3.0/-3.0	-	NON-PLATED	2
▪	62.0	+2.0/-2.0	-	NON-PLATED	1
▪	66.0	+3.0/-3.0	-	NON-PLATED	2
▪	68.0	+3.0/-3.0	-	NON-PLATED	4
▪	108.0	+3.0/-3.0	-	NON-PLATED	10
◎	126.0	+3.0/-3.0	-	NON-PLATED	4
▬	46.0x26.0	+3.0/-3.0	+3.0/-3.0	PLATED	4
▬	48.0x22.0	+3.0/-3.0	+3.0/-3.0	PLATED	4
▬	62.0x24.0	+2.0/-2.0	+2.0/-2.0	PLATED	4
▬	68.0x34.0	+3.0/-3.0	+3.0/-3.0	PLATED	4
▬	82.0x24.0	+2.0/-2.0	+2.0/-2.0	PLATED	4
▬	118.0x28.0	+3.0/-3.0	+3.0/-3.0	PLATED	2

LAYER STACKUP



IMPEDANCE SPECIFICATIONS

SL#	TYPE	LAYER	TRACEWIDTH(Mils)	SPACING(Mils)	IMPEDANCE(Ohms)	REF LAYER
01	EDGE COUPLED MICROSTRIP	L1, L12	4.1	6.2	100	L2, L11
02	EDGE COUPLED MICROSTRIP	L1, L12	4	4.3	90	L2, L11
03	MICROSTRIP	L1, L12	5.9	NA	50	L2, L11
04	EDGE COUPLED STRIPLINE	L3, L10	3.2	8	100	L2/L4, L9/L11
05	EDGE COUPLED STRIPLINE	L05	3.5	6.3	100	L4/L6
06	EDGE COUPLED STRIPLINE	L3, L10	3.6	5.8	90	L2/L4, L9/L11
07	EDGE COUPLED STRIPLINE	L5	4	4.7	90	L4/L6
08	EDGE COUPLED STRIPLINE	L3, L10	4.3	4.5	80	L2/L4, L9/L11
08	EDGE COUPLED STRIPLINE	L5	5.2	4.5	80	L2/L4
09	EDGE COUPLED STRIPLINE	L10	6.6	4.5	66	L9/L11
10	EDGE COUPLED STRIPLINE	L3	3	6.5	133	L2/L4
11	STRIPLINE	L3, L10	3.5	NA	50	L2/L4, L9/L11
12	STRIPLINE	L5	4.25	NA	50	L4/L6
13	STRIPLINE	L3	5.7	NA	40	L2/L4
14	STRIPLINE	L5	6.6	NA	40	L4/L6
15	STRIPLINE	L10	8	NA	33	L9/L11
16	MICROSTRIP	L1	9	NA	40	L2
17	STRIPLINE	L3	3	NA	66	L2/L4
18	MICROSTRIP	L1	12.5	NA	33	L2

SIGNATURES		DATE
LAYOUT BY	UD	270225
REVIEWED BY	ZA	270225
APPROVED BY	AMB	270225

TEXAS INSTRUMENTS

PROC164E2

AM62P EVM BOARD

SIZE D | Rev E2

SCALE:NONE | SHEET 1 OF 19