



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	Production Release Version	2020-02-12	2020-02-12



DESIGN CROSS SECTION CHART  
TOTAL THICKNESS 1.6 MM

# PANEL DRAWING



DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILLIMETERS				
FIGURE	FINISHED SIZE	ROTATION	PLATED	QTY
•	0.2	-	PLATED	1357
◉	0.201	-	PLATED	25
•	1.05	-	PLATED	75
•	1.1	-	PLATED	1
⊕	3.2	-	PLATED	4
•	0.899	-	NON-PLATED	6
•	1.0	-	NON-PLATED	3
•	3.2	-	NON-PLATED	2
◉	1.3x0.6	90.000	PLATED	2

	TEXAS INSTRUMENTS	
	DRILL	LAUNCHXL-CC1310 A
	DATE: 2020-02-17	

FAB NOTES:

1. ALL DIMENSIONS ARE IN MM, UNLESS OTHERWISE NOTED.
2. THE PWB SHALL BE FABRICATED TO IPC-6012, CLASS 2 AND WORKMANSHIP SHALL CONFORM TO IPC-A-600, CLASS 2. CURRENT REVISIONS.
3. BOARD MATERIAL SHALL BE 180 Tg/340 Td ISOLA FR-370HR OR EQUIVALENT, RoHS COMPLIANT AND LEAD FREE ASSEMBLY CAPABLE. BOARD MATERIAL SHALL MEET OR EXCEED IPC-4101B. RoHS/REACH CERTIFICATE OF CONFORMANCE SHALL BE DELIVERED WITH EACH LOT
4. BOARD MATERIAL & CONSTRUCTION TO BE U.L. 94V-0 APPROVED AND MARKED ON THE FINISHED BOARD. UL GUIDE NUMBER SHOULD BE MARKED ON THE FINISHED BOARD.
5. OVERALL BOARD THICKNESS TO BE 1.6 MM AND APPLIES AFTER ALL LAMINATION AND PLATING PROCESSES, MEASURED FROM COPPER TO COPPER.
6. MAX. WARP & TWIST TO BE .0075 PER INCH.
7. BOARD MUST BE ELECTRICALLY TESTED USING SUPPLIED IPC-D-356 NETLIST.
8. 0.32MM TRACES ON LAYER 1 ARE 50 OHMS +/-10%. THEY ARE REFERENCE TO LAYER 2 GROUND
9. MANUFACTURER MARKING: TWO LETTER + YEAR + WEEK  
THE LETTER CODE SHALL IDENTIFY THE MANUFACTURER AND IS DECIDED BY MFR. NO LOGOS OR OTHER IDENTIFIERS ARE ALLOWED  
THE MARKING SHALL BE IN BOTTOM SILK SCREEN PRINT

**PROCESS NOTES:**

1. APPLY LPI SOLDERMASK OVER BARE COPPER (SMOBC). SOLDERMASK SHALL CONFORM TO IPC-SM-840, CLASS H. CURRENT REV. COLOR OF MASK TO BE RED.
2. PLATE ALL EXPOSED AREAS WITH ELECTROLESS NICKEL IMMERSION GOLD. NICKEL:100 MICRO-INCHES MIN. GOLD:2-8 MICROINCHES MIN.
3. SOLDERMASK ARTWORK HAS ZERO (0) OVERSIZED PADS.FABRICATION VENDOR IS ALLOWED TO ADJUST THE COMPONENT SOLDERMASK PADS TO MEET THEIR TOOLING REQUIREMENTS.
4. APPLY NON-CONDUCTIVE LPI SILKSCREEN OR EQUIVALENT PER THE ARTWORK.COLOR: WHITE.
5. ALL VIAS ARE TENTED.

UNLESS OTHERWISE SPECIFIED	SIGNATURES		DATE		TEXAS INSTRUMENTS		
DIMENSIONS ARE IN MM	DRAWN	TER	2020-02-17				
	CHECKED	SJO	2020-02-17				
					FABRICATION DRAWING LAUNCHXL-CC1310 CC1310 LaunchPad		
					SIZE	FSCM NO	DWG NO
					SCALE	NONE	SHEET 1 OF 1