

# SNx4LVC74A Dual Positive-Edge-Triggered D-Type Flip-Flops With Clear and Preset

## 1 Features

- Operate from 1.65V to 3.6V
- Inputs accept voltages to 5.5V
- Maximum  $t_{pd}$  of 5.2ns at 3.3V
- Typical  $V_{OLP}$  (output ground bounce)  $<0.8V$  at  $V_{CC} = 3.3V$ ,  $T_A = 25^\circ C$
- Typical  $V_{OHV}$  (output  $V_{OH}$  undershoot)  $>2V$  at  $V_{CC} = 3.3V$ ,  $T_A = 25^\circ C$
- Latch-up performance exceeds 250mA per JESD 17
- ESD protection exceeds JESD 22
  - 2000V human-body model (A114-A)
  - 1000V charged-device model (C101)

## 2 Applications

- Servers
- Medical, Healthcare, and Fitness
- Telecom Infrastructures
- TVs, Set-Top Boxes, and Audio
- Test and Measurement
- Industrial Transport
- Wireless Infrastructure
- Enterprise Switching
- Motor Drives
- Factory Automation and Control

## 3 Description


The SNx4LVC74A devices integrate two positive-edge triggered D-type flip-flops in one convenient device.

The SN54LVC74A is designed for 2.7V to 3.6V  $V_{CC}$  operation, and the SN74LVC74A is designed for 1.65V to 3.6V  $V_{CC}$  operation.

### Device Information

| PART NUMBER | PACKAGE <sup>(1)</sup> | PACKAGE SIZE <sup>(2)</sup> | BODY SIZE <sup>(3)</sup> |
|-------------|------------------------|-----------------------------|--------------------------|
| SNx4LVC74A  | BQA (WQFN, 14)         | 3mm × 2.5mm                 | 3mm × 2.5mm              |
|             | D (SOIC, 14)           | 8.65mm × 6mm                | 8.65mm × 3.91mm          |
|             | DB (SSOP, 14)          | 6.2mm × 7.8mm               | 6.20mm × 5.30mm          |
|             | NS (SOP, 14)           | 10.2mm × 7.8mm              | 10.20mm × 5.30mm         |
|             | PW (TSSOP, 14)         | 5mm × 6.4mm                 | 5.00mm × 4.40mm          |
|             | RGY (VQFN, 14)         | 3.50mm × 3.50mm             | 3.50mm × 3.50mm          |
|             | J (CDIP, 14)           | 19.55mm × 7.9mm             | 19.56 mm × 6.67 mm       |
|             | W (CFP, 14)            | 9.21mm × 9 mm               | 9.21 mm × 5.97 mm        |
|             | FK (LCCC, 20)          | 8.9mm × 8.9mm               | 8.89 mm × 8.89 mm        |

- (1) For more information, see [Mechanical, Packaging, and Orderable Information](#).
- (2) The package size (length × width) is a nominal value and includes pins, where applicable.
- (3) The body size (length × width) is a nominal value and does not include pins.



Copyright © 2016, Texas Instruments Incorporated


**Logic Diagram, Each Flip-Flop (Positive Logic)**




## Table of Contents

|                                                                                       |          |                                                                      |           |
|---------------------------------------------------------------------------------------|----------|----------------------------------------------------------------------|-----------|
| <b>1 Features</b> .....                                                               | <b>1</b> | <b>7 Detailed Description</b> .....                                  | <b>10</b> |
| <b>2 Applications</b> .....                                                           | <b>1</b> | 7.1 Overview.....                                                    | 10        |
| <b>3 Description</b> .....                                                            | <b>1</b> | 7.2 Functional Block Diagram.....                                    | 10        |
| <b>4 Pin Configuration and Functions</b> .....                                        | <b>3</b> | 7.3 Feature Description.....                                         | 10        |
| <b>5 Specifications</b> .....                                                         | <b>4</b> | 7.4 Device Functional Modes.....                                     | 10        |
| 5.1 Absolute Maximum Ratings.....                                                     | 4        | <b>8 Application and Implementation</b> .....                        | <b>11</b> |
| 5.2 ESD Ratings.....                                                                  | 4        | 8.1 Application Information.....                                     | 11        |
| 5.3 Recommended Operating Conditions.....                                             | 4        | 8.2 Typical Application.....                                         | 11        |
| 5.4 Thermal Information: SN74LVC74A.....                                              | 5        | 8.3 Power Supply Recommendations.....                                | 12        |
| 5.5 Electrical Characteristics.....                                                   | 5        | 8.4 Layout.....                                                      | 12        |
| 5.6 Timing Requirements: SN54LVC74A.....                                              | 6        | <b>9 Device and Documentation Support</b> .....                      | <b>14</b> |
| 5.7 Timing Requirements: SN74LVC74A.....                                              | 6        | 9.1 Documentation Support.....                                       | 14        |
| 5.8 Timing Requirements: SN74LVC74A, –40°C to<br>125°C and –40°C to 85°C.....         | 7        | 9.2 Receiving Notification of Documentation Updates....              | 14        |
| 5.9 Switching Characteristics: SN54LVC74A.....                                        | 7        | 9.3 Support Resources.....                                           | 14        |
| 5.10 Switching Characteristics: SN74LVC74A.....                                       | 7        | 9.4 Trademarks.....                                                  | 14        |
| 5.11 Switching Characteristics: SN74LVC74A, –<br>40°C to 125°C and –40°C to 85°C..... | 8        | 9.5 Electrostatic Discharge Caution.....                             | 14        |
| 5.12 Operating Characteristics.....                                                   | 8        | 9.6 Glossary.....                                                    | 14        |
| 5.13 Typical Characteristics.....                                                     | 8        | <b>10 Revision History</b> .....                                     | <b>14</b> |
| <b>6 Parameter Measurement Information</b> .....                                      | <b>9</b> | <b>11 Mechanical, Packaging, and Orderable<br/>Information</b> ..... | <b>15</b> |


## 4 Pin Configuration and Functions



**Figure 4-1. D, DB, J, PW, NS, or W Package 14-Pin SOIC, SSOP, CDIP, TSSOP, SO, or CFP (Top View)**



**Figure 4-2. BQA or RGY Package 14-Pin WQFN or VQFN With Exposed Thermal Pad (Top View)**



**Figure 4-3. FK Package 20-Pin LCCC (Top View)**

**Table 4-1. Pin Functions**

| NAME    | PIN                                          |                     | I/O | DESCRIPTION                                            |
|---------|----------------------------------------------|---------------------|-----|--------------------------------------------------------|
|         | CDIP, CFP, PDIP, SO, SOIC, SSOP, TSSOP, VQFN | LCCC                |     |                                                        |
| 1CLK    | 3                                            | 4                   | I   | Channel 1 clock input                                  |
| 1 CLR   | 1                                            | 2                   | I   | Channel 1 clear input. Pull low to set Q output low.   |
| 1D      | 2                                            | 3                   | I   | Channel 1 data input                                   |
| 1 PRE   | 4                                            | 6                   | I   | Channel 1 preset input. Pull low to set Q output high. |
| 1Q      | 5                                            | 8                   | O   | Channel 1 output                                       |
| 1 Q-bar | 6                                            | 9                   | O   | Channel 1 inverted output                              |
| 2CLK    | 11                                           | 16                  | I   | Channel 2 clock input                                  |
| 2 CLR   | 13                                           | 19                  | I   | Channel 2 clear input. Pull low to set Q output low.   |
| 2D      | 12                                           | 18                  | I   | Channel 2 data input                                   |
| 2 PRE   | 10                                           | 14                  | I   | Channel 2 preset input. Pull low to set Q output high. |
| 2Q      | 9                                            | 13                  | O   | Channel 2 output                                       |
| 2 Q-bar | 8                                            | 12                  | O   | Channel 2 Inverted output                              |
| GND     | 7                                            | 10                  | —   | Ground                                                 |
| NC      | —                                            | 1, 5, 7, 11, 15, 17 | —   | No connect                                             |
| VCC     | 14                                           | 20                  | —   | Supply                                                 |

## 5 Specifications

### 5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                                            | MIN       | MAX            | UNIT |
|--------------------------------------------|-----------|----------------|------|
| Supply voltage, $V_{CC}$                   | –0.5      | 6.5            | V    |
| Input voltage, $V_I$ <sup>(2)</sup>        | –0.5      | 6.5            | V    |
| Output voltage, $V_O$ <sup>(2) (3)</sup>   | –0.5      | $V_{CC} + 0.5$ | V    |
| Input clamp current, $I_{IK}$              | $V_I < 0$ | –50            | mA   |
| Output clamp current, $I_{OK}$             | $V_O < 0$ | –50            | mA   |
| Continuous output current, $I_O$           |           | ±50            | mA   |
| Continuous current through $V_{CC}$ or GND |           | ±100           | mA   |
| Storage temperature, $T_{stg}$             | –65       | 150            | °C   |

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.

(3) The value of  $V_{CC}$  is provided in *Recommended Operating Conditions*.

### 5.2 ESD Ratings

|                                     | VALUE                                                                          | UNIT  |
|-------------------------------------|--------------------------------------------------------------------------------|-------|
| $V_{(ESD)}$ Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 |
|                                     | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1000 |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 5.3 Recommended Operating Conditions

see<sup>(1)</sup>

|                                                        |                                           |            | MIN                  | MAX                  | UNIT |
|--------------------------------------------------------|-------------------------------------------|------------|----------------------|----------------------|------|
| $V_{CC}$ Supply voltage                                | Operating                                 | SN54LVC74A | 2                    | 3.6                  | V    |
|                                                        |                                           | SN74LVC74A | 1.65                 | 3.6                  |      |
|                                                        | Data retention only                       |            | 1.5                  |                      |      |
| $V_{IH}$ High-level input voltage                      | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | SN74LVC74A | $0.65 \times V_{CC}$ |                      | V    |
|                                                        | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$   | SN74LVC74A | 1.7                  |                      |      |
|                                                        | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$   |            | 2                    |                      |      |
| $V_{IL}$ Low-level input voltage                       | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | SN74LVC74A |                      | $0.35 \times V_{CC}$ | V    |
|                                                        | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$   | SN74LVC74A |                      | 0.7                  |      |
|                                                        | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$   |            |                      | 0.8                  |      |
| $V_I$ Input voltage                                    |                                           |            | 0                    | 5.5                  | V    |
| $V_O$ Output voltage                                   |                                           |            | 0                    | $V_{CC}$             | V    |
| $I_{OH}$ High-level output current                     | $V_{CC} = 1.65\text{ V}$                  | SN74LVC74A |                      | –4                   | mA   |
|                                                        | $V_{CC} = 2.3\text{ V}$                   | SN74LVC74A |                      | –8                   |      |
|                                                        | $V_{CC} = 2.7\text{ V}$                   |            |                      | –12                  |      |
|                                                        | $V_{CC} = 3\text{ V}$                     |            |                      | –24                  |      |
| $I_{OL}$ Low-level output current                      | $V_{CC} = 1.65\text{ V}$                  | SN74LVC74A |                      | 4                    | mA   |
|                                                        | $V_{CC} = 2.3\text{ V}$                   | SN74LVC74A |                      | 8                    |      |
|                                                        | $V_{CC} = 2.7\text{ V}$                   |            |                      | 12                   |      |
|                                                        | $V_{CC} = 3\text{ V}$                     |            |                      | 24                   |      |
| $\Delta t/\Delta v$ Input transition rise or fall rate |                                           |            |                      | 10                   | ns/V |

### 5.3 Recommended Operating Conditions (continued)

see<sup>(1)</sup>

|                |                                | MIN        | MAX | UNIT |    |
|----------------|--------------------------------|------------|-----|------|----|
| T <sub>A</sub> | Operating free-air temperature | SN54LVC74A | –55 | 125  | °C |
|                |                                | SN74LVC74A | –40 | 125  |    |

- (1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation. See the TI application report, [Implications of Slow or Floating CMOS Inputs](#) (SCBA004).

### 5.4 Thermal Information: SN74LVC74A

| THERMAL METRIC <sup>(1)</sup> |                                              | SN74LVC74A    |             |              |            |               |               | UNIT |
|-------------------------------|----------------------------------------------|---------------|-------------|--------------|------------|---------------|---------------|------|
|                               |                                              | BQA<br>(WQFN) | D<br>(SOIC) | DB<br>(SSOP) | NS<br>(SO) | PW<br>(TSSOP) | RGY<br>(VQFN) |      |
|                               |                                              | 14 PINS       | 14 PINS     | 14 PINS      | 14 PINS    | 14 PINS       | 14 PINS       |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 102.3         | 127.8       | 140.4        | 123.8      | 150.8         | 92.1          | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | 96.8          | 54.8        | 59.2         | 48.1       | 50.3          | 52.2          | °C/W |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | 70.9          | 48          | 54.6         | 49.1       | 63.4          | 30.8          | °C/W |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | 16.6          | 20.3        | 24.1         | 17.9       | 6.2           | 2.4           | °C/W |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | 70.9          | 47.7        | 54.1         | 48.8       | 62.8          | 30.9          | °C/W |
| R <sub>θJC(bot)</sub>         | Junction-to-case (bottom) thermal resistance | 50.1          | —           | —            | —          | —             | 12.5          | °C/W |

- (1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

### 5.5 Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER        |                           | TEST CONDITIONS                                                                                                    |                                                                                          | MIN                   | TYP | MAX | UNIT |
|------------------|---------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------|-----|-----|------|
| V <sub>OH</sub>  | High-level output voltage | I <sub>OH</sub> = −100 μA                                                                                          | V <sub>CC</sub> = 1.65 V to 3.6 V and T <sub>A</sub> = −55°C to 125°C (SN54LVC74A only)  | V <sub>CC</sub> − 0.2 |     | V   |      |
|                  |                           |                                                                                                                    | V <sub>CC</sub> = 2.7 V to 3.6 V and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only)   | V <sub>CC</sub> − 0.2 |     |     |      |
|                  |                           | I <sub>OH</sub> = −4 mA, V <sub>CC</sub> = 1.65 V, and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only)           |                                                                                          | 1.2                   |     |     |      |
|                  |                           | I <sub>OH</sub> = −8 mA, V <sub>CC</sub> = 2.3 V, and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only)            |                                                                                          | 1.7                   |     |     |      |
|                  |                           | I <sub>OH</sub> = −12 mA                                                                                           | V <sub>CC</sub> = 2.7 V                                                                  | 2.2                   |     |     |      |
|                  |                           |                                                                                                                    | V <sub>CC</sub> = 3 V                                                                    | 2.4                   |     |     |      |
|                  |                           | I <sub>OH</sub> = −24 mA, V <sub>CC</sub> = 3 V                                                                    |                                                                                          | 2.2                   |     |     |      |
| V <sub>OL</sub>  | Low-level output voltage  | I <sub>OL</sub> = 100 μA                                                                                           | V <sub>CC</sub> = 1.65 V to 3.6 V, and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only) | 0.2                   |     | V   |      |
|                  |                           |                                                                                                                    | V <sub>CC</sub> = 2.7 V to 3.6 V and T <sub>A</sub> = −55°C to 125°C (SN54LVC74A only)   | 0.2                   |     |     |      |
|                  |                           | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 1.65 V, and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only)            |                                                                                          | 0.45                  |     |     |      |
|                  |                           | I <sub>OL</sub> = 8 mA, V <sub>CC</sub> = 2.3 V, and T <sub>A</sub> = −40°C to 125°C (SN74LVC74A only)             |                                                                                          | 0.7                   |     |     |      |
|                  |                           | I <sub>OL</sub> = 12 mA, V <sub>CC</sub> = 2.7 V                                                                   |                                                                                          | 0.4                   |     |     |      |
|                  |                           | I <sub>OL</sub> = 24 mA, V <sub>CC</sub> = 3 V                                                                     |                                                                                          | 0.55                  |     |     |      |
|                  |                           |                                                                                                                    |                                                                                          |                       |     |     |      |
| I <sub>I</sub>   | Input current             | V <sub>I</sub> = 5.5 V or GND, V <sub>CC</sub> = 3.6 V                                                             |                                                                                          |                       | ±5  | μA  |      |
| I <sub>CC</sub>  | Supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND, I <sub>O</sub> = 0, V <sub>CC</sub> = 3.6 V                               |                                                                                          |                       | 10  | μA  |      |
| ΔI <sub>CC</sub> | Change in supply current  | One input at V <sub>CC</sub> − 0.6 V, other inputs at V <sub>CC</sub> or GND, and V <sub>CC</sub> = 2.7 V to 3.6 V |                                                                                          |                       | 500 | μA  |      |

**SN54LVC74A, SN74LVC74A**

SCAS287W – JANUARY 1993 – REVISED DECEMBER 2024

**5.5 Electrical Characteristics (continued)**

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER |                   | TEST CONDITIONS                                                           | MIN | TYP | MAX | UNIT |
|-----------|-------------------|---------------------------------------------------------------------------|-----|-----|-----|------|
| $C_i$     | Input capacitance | $V_i = V_{CC}$ or GND, $V_{CC} = 3.3\text{ V}$ , $T_A = 25^\circ\text{C}$ |     | 5   |     | pF   |

**5.6 Timing Requirements: SN54LVC74A**

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))

|                    |                                      |                                                             | MIN                                      | MAX | UNIT |
|--------------------|--------------------------------------|-------------------------------------------------------------|------------------------------------------|-----|------|
| $f_{\text{clock}}$ | Clock frequency                      | $V_{CC} = 2.7\text{ V}$                                     |                                          | 83  | MHz  |
|                    |                                      | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$                    |                                          | 100 |      |
| $t_w$              | Pulse duration                       | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ low      | 3.3                                      |     | ns   |
|                    |                                      | CLK high or low                                             | 3.3                                      |     |      |
| $t_{\text{su}}$    | Setup time before CLK $\uparrow$     | Data                                                        | $V_{CC} = 2.7\text{ V}$                  | 3.4 | ns   |
|                    |                                      |                                                             | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ | 3   |      |
|                    |                                      | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ inactive | $V_{CC} = 2.7\text{ V}$                  | 2.2 |      |
|                    |                                      |                                                             | $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ | 2   |      |
| $t_h$              | Hold time, data after CLK $\uparrow$ |                                                             | 1                                        |     | ns   |

**5.7 Timing Requirements: SN74LVC74A**

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))

|                    |                                      |                                                             | MIN                                       | MAX | UNIT |
|--------------------|--------------------------------------|-------------------------------------------------------------|-------------------------------------------|-----|------|
| $f_{\text{clock}}$ | Clock frequency                      | $V_{CC} = 1.8\text{ V}$ or $2.5\text{ V}$                   |                                           | 83  | MHz  |
| $t_w$              | Pulse duration                       | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ low      | $V_{CC} = 1.8\text{ V} \pm 0.15\text{ V}$ | 4.1 | ns   |
|                    |                                      |                                                             | $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$  | 3.3 |      |
|                    |                                      | CLK high or low                                             | $V_{CC} = 1.8\text{ V} \pm 0.15\text{ V}$ | 4.1 |      |
|                    |                                      |                                                             | $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$  | 3.3 |      |
| $t_{\text{su}}$    | Setup time before CLK $\uparrow$     | Data                                                        | $V_{CC} = 1.8\text{ V} \pm 0.15\text{ V}$ | 3.6 | ns   |
|                    |                                      |                                                             | $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$  | 2.3 |      |
|                    |                                      | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ inactive | $V_{CC} = 1.8\text{ V} \pm 0.15\text{ V}$ | 2.7 |      |
|                    |                                      |                                                             | $V_{CC} = 2.5\text{ V} \pm 0.2\text{ V}$  | 1.9 |      |
| $t_h$              | Hold time, data after CLK $\uparrow$ | $V_{CC} = 1.8\text{ V}$ or $2.5\text{ V}$                   | 1                                         |     | ns   |

## 5.8 Timing Requirements: SN74LVC74A, –40°C to 125°C and –40°C to 85°C

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))

|                    |                                                             |                                                                                                     |                                                  | MIN                                             | MAX | UNIT |
|--------------------|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------------------------------|-------------------------------------------------|-----|------|
| $f_{\text{clock}}$ | Clock frequency                                             | $T_A = -40^\circ\text{C}$ to $125^\circ\text{C}$                                                    | $V_{\text{CC}} = 2.7\text{ V}$                   |                                                 | 83  | MHz  |
|                    |                                                             |                                                                                                     | $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$  |                                                 | 100 |      |
|                    |                                                             | $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$ and $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$ |                                                  |                                                 | 150 |      |
| $t_w$              | Pulse duration                                              | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ low                                              | $V_{\text{CC}} = 2.7\text{ V}$ or $3.3\text{ V}$ | 3.3                                             |     | ns   |
|                    |                                                             | CLK high or low                                                                                     | $V_{\text{CC}} = 2.7\text{ V}$ or $3.3\text{ V}$ | 3.3                                             |     |      |
| $t_{\text{su}}$    | Setup time before CLK $\uparrow$                            | Data                                                                                                | $T_A = -40^\circ\text{C}$ to $125^\circ\text{C}$ | $V_{\text{CC}} = 2.7\text{ V}$                  | 3.4 | ns   |
|                    |                                                             |                                                                                                     |                                                  | $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$ | 3   |      |
|                    |                                                             | $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$ and $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$ |                                                  |                                                 | 3   |      |
|                    | $\overline{\text{PRE}}$ or $\overline{\text{CLR}}$ inactive | $T_A = -40^\circ\text{C}$ to $125^\circ\text{C}$                                                    | $V_{\text{CC}} = 2.7\text{ V}$                   | 2.2                                             |     |      |
|                    |                                                             |                                                                                                     | $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$  | 2                                               |     |      |
|                    |                                                             | $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$ and $V_{\text{CC}} = 3.3\text{ V} \pm 0.3\text{ V}$ |                                                  |                                                 | 2   |      |
| $t_h$              | Hold time, data after CLK $\uparrow$                        | $V_{\text{CC}} = 2.7\text{ V}$ or $3.3\text{ V}$                                                    |                                                  | 1                                               |     | ns   |

## 5.9 Switching Characteristics: SN54LVC74A

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))

| PARAMETER        |                          | FROM<br>(INPUT)                | TO<br>(OUTPUT)      | TEST CONDITIONS                 | MIN | MAX | UNIT |
|------------------|--------------------------|--------------------------------|---------------------|---------------------------------|-----|-----|------|
| f <sub>max</sub> | Maximum clock frequency  | —                              | —                   | V <sub>CC</sub> = 2.7 V         | 83  |     | MHz  |
|                  |                          |                                |                     | V <sub>CC</sub> = 3.3 V ± 0.3 V | 100 |     |      |
| t <sub>pd</sub>  | Propagation (delay) time | CLK                            | Q or $\overline{Q}$ | V <sub>CC</sub> = 2.7 V         |     | 6   | ns   |
|                  |                          |                                |                     | V <sub>CC</sub> = 2.7 V         | 1   | 5.2 |      |
|                  |                          | PRE or $\overline{\text{CLR}}$ |                     | V <sub>CC</sub> = 3.3 V ± 0.3 V |     | 6.4 |      |
|                  |                          |                                |                     | V <sub>CC</sub> = 3.3 V ± 0.3 V | 1   | 5.4 |      |

## 5.10 Switching Characteristics: SN74LVC74A

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))

| PARAMETER        |                          | FROM<br>(INPUT)            | TO<br>(OUTPUT)      | TEST CONDITIONS                  | MIN | MAX | UNIT |
|------------------|--------------------------|----------------------------|---------------------|----------------------------------|-----|-----|------|
| f <sub>max</sub> | Maximum clock frequency  | —                          | —                   |                                  | 83  |     | MHz  |
| t <sub>pd</sub>  | Propagation (delay) time | CLK PRE                    | Q or $\overline{Q}$ | V <sub>CC</sub> = 1.8 V ± 0.15 V | 1   | 7.1 | ns   |
|                  |                          |                            |                     | V <sub>CC</sub> = 2.5 V ± 0.2 V  | 1   | 4.4 |      |
|                  |                          | or $\overline{\text{CLR}}$ |                     | V <sub>CC</sub> = 1.8 V ± 0.15 V | 1   | 6.9 |      |
|                  |                          |                            |                     | V <sub>CC</sub> = 2.5 V ± 0.2 V  | 1   | 4.6 |      |

## 5.11 Switching Characteristics: SN74LVC74A, –40°C to 125°C and –40°C to 85°C

over recommended operating free-air temperature range (unless otherwise noted; see [Parameter Measurement Information](#))



| PARAMETER                                | FROM (INPUT)            | TO (OUTPUT)         | TEST CONDITIONS                                                    |                                 | MIN | MAX | UNIT |
|------------------------------------------|-------------------------|---------------------|--------------------------------------------------------------------|---------------------------------|-----|-----|------|
| f <sub>max</sub> Maximum clock frequency | —                       | —                   | T <sub>A</sub> = −40°C to 125°C                                    | V <sub>CC</sub> = 2.7 V         | 83  |     | MHz  |
|                                          |                         |                     |                                                                    | V <sub>CC</sub> = 3.3 V ± 0.3 V | 100 |     |      |
|                                          |                         |                     | T <sub>A</sub> = −40°C to 85°C and V <sub>CC</sub> = 3.3 V ± 0.3 V |                                 | 150 |     |      |
| t <sub>pd</sub> Propagation (delay) time | CLK                     | Q or $\overline{Q}$ | T <sub>A</sub> = −40°C to 125°C                                    | V <sub>CC</sub> = 2.7 V         | 1   | 6   | ns   |
|                                          |                         |                     |                                                                    | V <sub>CC</sub> = 3.3 V ± 0.3 V | 5.2 |     |      |
|                                          |                         |                     | T <sub>A</sub> = −40°C to 85°C and V <sub>CC</sub> = 3.3 V ± 0.3 V |                                 | 1   | 5.2 |      |
|                                          | PRE or $\overline{CLR}$ |                     | T <sub>A</sub> = −40°C to 125°C                                    | V <sub>CC</sub> = 2.7 V         | 1   | 6.4 |      |
|                                          |                         |                     |                                                                    | V <sub>CC</sub> = 3.3 V ± 0.3 V | 5.4 |     |      |
|                                          |                         |                     | T <sub>A</sub> = −40°C to 85°C and V <sub>CC</sub> = 3.3 V ± 0.3 V |                                 | 1   | 5.4 |      |
| t <sub>sk(o)</sub> Skew (time), output   | —                       | —                   | T <sub>A</sub> = −40°C to 85°C and V <sub>CC</sub> = 3.3 V ± 0.3 V |                                 | 1   |     | ns   |

## 5.12 Operating Characteristics

$T_A = 25^\circ\text{C}$

| PARAMETER                                            | TEST CONDITIONS     | TYP                     | UNIT |
|------------------------------------------------------|---------------------|-------------------------|------|
| $C_{pd}$ Power dissipation capacitance per flip-flop | $f = 10\text{ MHz}$ | $V_{CC} = 1.8\text{ V}$ | 24   |
|                                                      |                     | $V_{CC} = 2.5\text{ V}$ | 24   |
|                                                      |                     | $V_{CC} = 3.3\text{ V}$ | 26   |

## 5.13 Typical Characteristics




## 6 Parameter Measurement Information

Phase relationships between waveforms were chosen arbitrarily for the examples listed in the following table. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1\text{MHz}$ ,  $Z_O = 50\Omega$ ,  $t_f \leq 2.5\text{ns}$ .


The outputs are measured individually with one input transition per measurement.

| $V_{CC}$                       | $V_t$         | $R_L$             | $C_L$         | $\Delta V$     |
|--------------------------------|---------------|-------------------|---------------|----------------|
| $1.8\text{V} \pm 0.15\text{V}$ | $V_{CC}/2$    | $1\text{k}\Omega$ | $30\text{pF}$ | $0.15\text{V}$ |
| $2.5\text{V} \pm 0.2\text{V}$  | $V_{CC}/2$    | $500\Omega$       | $30\text{pF}$ | $0.15\text{V}$ |
| $2.7\text{V}$                  | $1.5\text{V}$ | $500\Omega$       | $50\text{pF}$ | $0.3\text{V}$  |
| $3.3\text{V} \pm 0.3\text{V}$  | $1.5\text{V}$ | $500\Omega$       | $50\text{pF}$ | $0.3\text{V}$  |




(1)  $C_L$  includes probe and test-fixture capacitance.

**Figure 6-1. Load Circuit for Push-Pull Outputs**



(1) The greater between  $t_{PLH}$  and  $t_{PHL}$  is the same as  $t_{pd}$ .

**Figure 6-2. Voltage Waveforms Propagation Delays**



(1) The greater between  $t_r$  and  $t_f$  is the same as  $t_t$ .

**Figure 6-3. Voltage Waveforms, Input and Output Transition Times**

## 7 Detailed Description

### 7.1 Overview


The SNx4LVC74A devices feature two independent positive-edge triggered D flip-flops. Integrated preset ( $\overline{\text{PRE}}$ ) and clear ( $\overline{\text{CLR}}$ ) functions allow for easy setup and control during operation.

The SN54LVC74A device is specified from  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ , and the SN74LVC74A device is specified from  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ .

A low level at the preset ( $\overline{\text{PRE}}$ ) or clear ( $\overline{\text{CLR}}$ ) inputs sets or resets the outputs, regardless of the levels of the other inputs. When  $\overline{\text{PRE}}$  and  $\overline{\text{CLR}}$  are inactive (high), data at the data (D) input meeting the setup time requirements is transferred to the outputs on the positive-going edge of the clock pulse. Clock triggering occurs at a voltage level and is not directly related to the rise time of the clock pulse. Following the hold-time interval, data at the D input can be changed without affecting the levels at the outputs.

The data I/Os and control inputs are overvoltage tolerant. This feature allows the use of these devices for down-translation in a mixed-voltage environment.

### 7.2 Functional Block Diagram



Copyright © 2016, Texas Instruments Incorporated

### 7.3 Feature Description

A low level at the preset ( $\overline{\text{PRE}}$ ) or clear ( $\overline{\text{CLR}}$ ) inputs sets or resets the outputs, regardless of the levels of the other inputs. When  $\overline{\text{PRE}}$  and  $\overline{\text{CLR}}$  are inactive (high), data at the data (D) input meeting the setup time requirements is transferred to the outputs on the positive-going edge of the clock pulse. Clock triggering occurs at a voltage level and is not directly related to the rise time of the clock pulse. Following the hold-time interval, data at the D input can be changed without affecting the levels at the outputs.

### 7.4 Device Functional Modes

Table 7-1 describes the SNx4LVC74A functionality and interactions between the  $\overline{\text{PRE}}$ ,  $\overline{\text{CLR}}$ , CLK, and D inputs.

**Table 7-1. Function Table**

| INPUTS |     |     |   | OUTPUTS          |                       |
|--------|-----|-----|---|------------------|-----------------------|
| PRE    | CLR | CLK | D | Q                | $\overline{\text{Q}}$ |
| L      | H   | X   | X | H                | L                     |
| H      | L   | X   | X | L                | H                     |
| L      | L   | X   | X | H <sup>(1)</sup> | H <sup>(1)</sup>      |
| H      | H   | ↑   | H | H                | L                     |

**Table 7-1. Function Table (continued)**

| INPUTS |     |            |   | OUTPUTS |             |
|--------|-----|------------|---|---------|-------------|
| PRE    | CLR | CLK        | D | Q       | $\bar{Q}$   |
| H      | H   | $\uparrow$ | L | L       | H           |
| H      | H   | L          | X | $Q_0$   | $\bar{Q}_0$ |

(1) This configuration is nonstable; that is, it does not persist when PRE or CLR returns to its inactive (high) level.

## 8 Application and Implementation


### Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 8.1 Application Information

A common application for the SN74LVC74A is a frequency divider. By connecting the  $\bar{Q}$  output to the D input, the Q output toggles states on each positive edge of the incoming clock signal. Because it takes two positive edges, or two clock pulses, to complete one complete pulse on the output (one pulse to toggle from low to high, another to toggle from high to low), the incoming clock frequency is effectively divided by two.

### 8.2 Typical Application



**Figure 8-1. Frequency Divider**

#### 8.2.1 Design Requirements



This device uses CMOS technology and has balanced output drive. Avoid bus contention because it can drive currents in excess of maximum limits. The high drive also creates fast edges into light loads, so consider routing and load conditions to prevent ringing.

#### 8.2.2 Detailed Design Procedure

- Recommended input conditions:
  - For rise time and fall time specification, see  $(\Delta t/\Delta V)$  in [Recommended Operating Conditions](#).
  - For specified high and low levels, see  $(V_{IH}$  and  $V_{IL})$  in [Recommended Operating Conditions](#).
  - Inputs are overvoltage tolerant allowing them to go as high as  $(V_I \text{ max})$  in [Recommended Operating Conditions](#) at any valid  $V_{CC}$ .
- Recommended maximum output conditions:

- Load currents must not exceed ( $I_O$  max) per output and must not exceed (Continuous current through  $V_{CC}$  or GND) total current for the part. These limits are located in [Absolute Maximum Ratings](#).
- Outputs must not be pulled above  $V_{CC}$ .

### 8.2.3 Application Curves



### 8.3 Power Supply Recommendations

The power supply may be any voltage between the minimum and maximum supply voltage rating located in [Recommended Operating Conditions](#).

Each  $V_{CC}$  terminal must have a good bypass capacitor to prevent power disturbance. A 0.1- $\mu$ F capacitor is recommended for devices with a single supply. If there are multiple  $V_{CC}$  terminals, then 0.01- $\mu$ F or 0.022- $\mu$ F capacitors are recommended for each power terminal. It is permissible to parallel multiple bypass capacitors to reject different frequencies of noise. Multiple bypass capacitors may be paralleled to reject different frequencies of noise. The bypass capacitor must be installed as close to the power terminal as possible for the best results.


### 8.4 Layout

#### 8.4.1 Layout Guidelines

Inputs must not float when using multiple bit logic devices. In many cases, functions or parts of functions of digital logic devices are unused. Some examples include situations when only two inputs of a triple-input AND gate are used, or when only 3 of the 4-buffer gates are used. Such input pins must not be left unconnected because the undefined voltages at the outside connections result in undefined operational states.

Specified in [Figure 8-4](#) are rules that must be observed under all circumstances. All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating. The logic level that must be applied to any particular unused input depends on the function of the device. Generally, they are tied to GND or  $V_{CC}$ , whichever makes more sense or is more convenient.

## 8.4.2 Layout Example



**Figure 8-4. Layout Diagram**

## 9 Device and Documentation Support

### 9.1 Documentation Support

#### 9.1.1 Related Documentation

For related documentation see the following:

[Implications of Slow or Floating CMOS Inputs](#) (SCBA004)

### 9.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on [ti.com](http://ti.com). Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 9.3 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

### 9.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

### 9.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 9.6 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

## 10 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Revision V (May 2024) to Revision W (December 2024)                                                                                                                                                                                                                                                                                                                   | Page        |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| <ul style="list-style-type: none"> <li>Updated R0JA values: D = 93.7 to 127.8, DB = 107.3 to 140.4, NS = 90.3 to 123.8, PW = 121.7 to 150.8, RGY = 54.9 to 92.1; Updated D, DB, NS, PW, and RGY packages for R0JC(top), R0JB, ΨJT, ΨJB, and R0JC(bot), all values in °C/W.....</li> </ul>                                                                                          | 5           |
| Changes from Revision U (January 2017) to Revision V (May 2024)                                                                                                                                                                                                                                                                                                                    | Page        |
| <ul style="list-style-type: none"> <li>Updated the numbering format for tables, figures, and cross-references throughout the document.....</li> <li>Added BQA package to <i>Device Information</i> table, <i>Pin Configuration and Functions</i> section, and <i>Thermal Information</i> table.....</li> <li>Added package size to <i>Device Information</i> table.....</li> </ul> | 1<br>1<br>1 |

## 11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable part number           | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                      |
|---------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|------------------------------------------|
| <a href="#">5962-9761601Q2A</a> | Active        | Production           | LCCC (FK)   20  | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>9761601Q2A<br>SNJ54LVC<br>74AFK |
| <a href="#">5962-9761601QCA</a> | Active        | Production           | CDIP (J)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-9761601QC<br>A<br>SNJ54LVC74AJ      |
| <a href="#">5962-9761601QDA</a> | Active        | Production           | CFP (W)   14    | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-9761601QD<br>A<br>SNJ54LVC74AW      |
| <a href="#">5962-9761601VDA</a> | Active        | Production           | CFP (W)   14    | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-9761601VD<br>A<br>SNV54LVC74AW      |
| <a href="#">SN74LVC74ABQAR</a>  | Active        | Production           | WQFN (BQA)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ABQAR.A                | Active        | Production           | WQFN (BQA)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| <a href="#">SN74LVC74AD</a>     | Active        | Production           | SOIC (D)   14   | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74AD.B                   | Active        | Production           | SOIC (D)   14   | 50   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| <a href="#">SN74LVC74ADBR</a>   | Active        | Production           | SSOP (DB)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74ADBR.A                 | Active        | Production           | SSOP (DB)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74ADBR.B                 | Active        | Production           | SSOP (DB)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74ADBRG4                 | Active        | Production           | SSOP (DB)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| <a href="#">SN74LVC74ADR</a>    | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ADR.A                  | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ADR.B                  | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ADRE4                  | Active        | Production           | SOIC (D)   14   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| <a href="#">SN74LVC74ADT</a>    | Active        | Production           | SOIC (D)   14   | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ADT.B                  | Active        | Production           | SOIC (D)   14   | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| <a href="#">SN74LVC74ANSR</a>   | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ANSR.A                 | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ANSR.B                 | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ANSR1G4                | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |

| Orderable part number           | Status<br>(1) | Material type<br>(2) | Package   Pins  | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                      |
|---------------------------------|---------------|----------------------|-----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|------------------------------------------|
| SN74LVC74ANSR1G4.A              | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| SN74LVC74ANSR1G4.B              | Active        | Production           | SOP (NS)   14   | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LVC74A                                   |
| <a href="#">SN74LVC74APW</a>    | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APW.B                  | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWG4                  | Active        | Production           | TSSOP (PW)   14 | 90   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| <a href="#">SN74LVC74APWR</a>   | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWR.A                 | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWR.B                 | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWRE4                 | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| <a href="#">SN74LVC74APWRG4</a> | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWRG4.B               | Active        | Production           | TSSOP (PW)   14 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| <a href="#">SN74LVC74APWT</a>   | Active        | Production           | TSSOP (PW)   14 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWT.B                 | Active        | Production           | TSSOP (PW)   14 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| SN74LVC74APWTG4                 | Active        | Production           | TSSOP (PW)   14 | 250   SMALL T&R       | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LC74A                                    |
| <a href="#">SN74LVC74ARGYR</a>  | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| SN74LVC74ARGYR.A                | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| SN74LVC74ARGYR.B                | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| SN74LVC74ARGYRG4                | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| SN74LVC74ARGYRG4.A              | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| SN74LVC74ARGYRG4.B              | Active        | Production           | VQFN (RGY)   14 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-2-260C-1 YEAR               | -40 to 125   | LC74A                                    |
| <a href="#">SNJ54LVC74AFK</a>   | Active        | Production           | LCCC (FK)   20  | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>9761601Q2A<br>SNJ54LVC<br>74AFK |
| <a href="#">SNJ54LVC74AJ</a>    | Active        | Production           | CDIP (J)   14   | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-9761601QC<br>A<br>SNJ54LVC74AJ      |
| <a href="#">SNJ54LVC74AW</a>    | Active        | Production           | CFP (W)   14    | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-9761601QD<br>A<br>SNJ54LVC74AW      |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

**(2) Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

**(3) RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

**(4) Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**(5) MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

**(6) Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54LVC74A, SN54LVC74A-SP, SN74LVC74A :**

- Catalog : [SN74LVC74A](#), [SN54LVC74A](#)
- Automotive : [SN74LVC74A-Q1](#), [SN74LVC74A-Q1](#)
- Enhanced Product : [SN74LVC74A-EP](#), [SN74LVC74A-EP](#)
- Military : [SN54LVC74A](#)
- Space : [SN54LVC74A-SP](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
- Military - QML certified for Military and Defense Applications
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74LVC74ABQAR   | WQFN         | BQA             | 14   | 3000 | 180.0              | 12.4               | 2.8     | 3.3     | 1.1     | 4.0     | 12.0   | Q1            |
| SN74LVC74ADBR    | SSOP         | DB              | 14   | 2000 | 330.0              | 16.4               | 8.35    | 6.6     | 2.4     | 12.0    | 16.0   | Q1            |
| SN74LVC74ADR     | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LVC74ADT     | SOIC         | D               | 14   | 250  | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| SN74LVC74ANSR    | SOP          | NS              | 14   | 2000 | 330.0              | 16.4               | 8.1     | 10.4    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LVC74ANSR1G4 | SOP          | NS              | 14   | 2000 | 330.0              | 16.4               | 8.1     | 10.4    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74LVC74APWR    | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC74APWRG4  | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC74APWT    | TSSOP        | PW              | 14   | 250  | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74LVC74ARGYR   | VQFN         | RGY             | 14   | 3000 | 330.0              | 12.4               | 3.75    | 3.75    | 1.15    | 8.0     | 12.0   | Q1            |
| SN74LVC74ARGYRG4 | VQFN         | RGY             | 14   | 3000 | 330.0              | 12.4               | 3.75    | 3.75    | 1.15    | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74LVC74ABQAR   | WQFN         | BQA             | 14   | 3000 | 210.0       | 185.0      | 35.0        |
| SN74LVC74ADBR    | SSOP         | DB              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| SN74LVC74ADR     | SOIC         | D               | 14   | 2500 | 333.2       | 345.9      | 28.6        |
| SN74LVC74ADT     | SOIC         | D               | 14   | 250  | 213.0       | 191.0      | 35.0        |
| SN74LVC74ANSR    | SOP          | NS              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| SN74LVC74ANSR1G4 | SOP          | NS              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| SN74LVC74APWR    | TSSOP        | PW              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| SN74LVC74APWRG4  | TSSOP        | PW              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| SN74LVC74APWT    | TSSOP        | PW              | 14   | 250  | 353.0       | 353.0      | 32.0        |
| SN74LVC74ARGYR   | VQFN         | RGY             | 14   | 3000 | 360.0       | 360.0      | 36.0        |
| SN74LVC74ARGYRG4 | VQFN         | RGY             | 14   | 3000 | 353.0       | 353.0      | 32.0        |

**TUBE**


\*All dimensions are nominal

| Device          | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-9761601Q2A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| 5962-9761601VDA | W            | CFP          | 14   | 25  | 506.98 | 26.16  | 6220   | NA     |
| SN74LVC74AD     | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LVC74AD.B   | D            | SOIC         | 14   | 50  | 506.6  | 8      | 3940   | 4.32   |
| SN74LVC74APW    | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74LVC74APW.B  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SN74LVC74APWG4  | PW           | TSSOP        | 14   | 90  | 530    | 10.2   | 3600   | 3.5    |
| SNJ54LVC74AFK   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |

## GENERIC PACKAGE VIEW

**FK 20**

**LCCC - 2.03 mm max height**

8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4229370VA\

**J 14**

## GENERIC PACKAGE VIEW

**CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4040083-5/G



**J0014A**

## PACKAGE OUTLINE

**CDIP - 5.08 mm max height**

CERAMIC DUAL IN LINE PACKAGE



4214771/A 05/2017

### NOTES:

1. All controlling linear dimensions are in inches. Dimensions in brackets are in millimeters. Any dimension in brackets or parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This package is hermetically sealed with a ceramic lid using glass frit.
4. Index point is provided on cap for terminal identification only and on press ceramic glass frit seal only.
5. Falls within MIL-STD-1835 and GDIP1-T14.

# EXAMPLE BOARD LAYOUT

J0014A

CDIP - 5.08 mm max height

CERAMIC DUAL IN LINE PACKAGE



LAND PATTERN EXAMPLE  
NON-SOLDER MASK DEFINED  
SCALE: 5X



4214771/A 05/2017

**PW0014A**

## PACKAGE OUTLINE

**TSSOP - 1.2 mm max height**

SMALL OUTLINE PACKAGE



4220202/B 12/2023

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT

PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4220202/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220202/B 12/2023

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW


**RGY 14**

**VQFN - 1 mm max height**

3.5 x 3.5, 0.5 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4231541/A



### VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD




1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for thermal and mechanical performance.


**RGY0014A**

### VQFN - 1 mm max height


PLASTIC QUAD FLATPACK - NO LEAD



LAND PATTERN EXAMPLE  
SCALE:20X



NON SOLDER MASK  
DEFINED  
(PREFERRED)



SOLDER MASK  
DEFINED

## SOLDER MASK DETAILS

4219040/A 09/2015

NOTES: (continued)


4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/slua271](http://www.ti.com/lit/slua271)).

# EXAMPLE STENCIL DESIGN

RGY0014A

VQFN - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



**SOLDER PASTE EXAMPLE**  
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD  
80% PRINTED SOLDER COVERAGE BY AREA  
SCALE:20X

4219040/A 09/2015

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

**D0014A****PACKAGE OUTLINE****SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4220718/A 09/2016

**NOTES:**

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm, per side.
5. Reference JEDEC registration MS-012, variation AB.

# EXAMPLE BOARD LAYOUT

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
SCALE:8X



SOLDER MASK DETAILS

4220718/A 09/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:8X

4220718/A 09/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW


**BQA 14**


**WQFN - 0.8 mm max height**

2.5 x 3, 0.5 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.






4224636/A 11/2018

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pad must be soldered to the printed circuit board for optimal thermal and mechanical performance.



## LAND PATTERN EXAMPLE

EXPOSED METAL SHOWN

SCALE: 20X



4224636/A 11/2018

## NOTES: (continued)


4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 ([www.ti.com/lit/sluea271](http://www.ti.com/lit/sluea271)).
5. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.

# EXAMPLE STENCIL DESIGN

BQA0014A

WQFN - 0.8 mm max height

PLASTIC QUAD FLAT PACK-NO LEAD



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD  
88% PRINTED COVERAGE BY AREA  
SCALE: 20X

4224636/A 11/2018

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE


14-PINS SHOWN





- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

W (R-GDFP-F14)

CERAMIC DUAL FLATPACK



- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification only.
  - Falls within MIL STD 1835 GDFP1-F14



4220762/A 05/2024

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. Reference JEDEC registration MO-150.

# EXAMPLE BOARD LAYOUT



DB0014A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4220762/A 05/2024

NOTES: (continued)


- Publication IPC-7351 may have alternate designs.
- Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

DB0014A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220762/A 05/2024

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025