

**PACKAGING INFORMATION**

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
AM5716AABCD	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	0 to 90	AM5716AABCD SITARATM 784 784 ABC	<a href="#">Samples</a>
AM5716AABCDA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5716AABCDA 784 784 ABC	<a href="#">Samples</a>
AM5716AABCDEA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5716AABCDEA 784 784 ABC	<a href="#">Samples</a>
AM5716AABCX	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	0 to 90	AM5716AABCX 784 784 ABC	<a href="#">Samples</a>
AM5716AABCXA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5716AABCXA 784 784 ABC	<a href="#">Samples</a>
AM5716AABCXEA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5716AABCXEA 784 784 ABC	<a href="#">Samples</a>
AM5716AABCXEQ1	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 125	AM5716AABCXEQ1 784 784 ABC	<a href="#">Samples</a>
AM5716AABCXQ1	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 125	AM5716AABCXQ1 784 784 ABC	<a href="#">Samples</a>
AM5718AABCX	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	0 to 90	AM5718AABCX 784 784 ABC	<a href="#">Samples</a>
AM5718AABCXA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5718AABCXA 784 784 ABC	<a href="#">Samples</a>
AM5718AABCXEA	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 105	AM5718AABCXEA 784 784 ABC	<a href="#">Samples</a>
AM5718AABCXEQ1	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 125	AM5718AABCXEQ1	<a href="#">Samples</a>

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
										784 784 ABC	
AM5718AABCXQ1	ACTIVE	FCBGA	ABC	760	60	RoHS & Green	Call TI   SNAGCU	Level-3-250C-168 HR	-40 to 125	AM5718AABCXQ1 784 784 ABC	<b>Samples</b>

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.