

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

- Low Jitter Clock Multiplier by x4, x6, x8. Input Frequency Range (19 MHz to 125 MHz). Supports Output Frequency From 150 MHz to 500 MHz
- Fail-Safe Power Up Initialization
- Low Jitter Clock Divider by /2, /3, /4. Input Frequency Range (50 MHz to 125 MHz). Supports Ranges of Output Frequency From 12.5 MHz to 62.5 MHz
- 2.6 mUI Programmable Bidirectional Delay Steps
- Typical 8-ps Phase Jitter (12 kHz to 20 MHz) at 500 MHz
- Typical 2.1-ps RMS Period Jitter (Entire Frequency Band) at 500 MHz
- One Single-Ended Input and One Differential Output Pair
- Output Can Drive LVPECL, LVDS, and LVTTTL
- Three Power Operating Modes to Minimize Power
- Low Power Consumption (Typical 200 mW at 500 MHz)
- Packaged in a Shrink Small-Outline Package (DBQ)
- No External Components Required for PLL
- Spread Spectrum Clock Tracking Ability to Reduce EMI
- Applications: Video Graphics, Gaming Products, Datacom, Telecom
- Accepts LVCMOS, LVTTTL Inputs for REFCLK Terminal
- Accepts Other Single-Ended Signal Levels at REFCLK Terminal by Programming Proper  $V_{DDREF}$  Voltage Level (For Example, HSTL 1.5 if  $V_{DDREF} = 1.6$  V)
- Supports Industrial Temperature Range of  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$

DBQ PACKAGE  
(TOP VIEW)

$V_{DDREF}$	1	24	P0
REFCLK	2	23	P1
$V_{DDP}$	3	22	$V_{DDO}$
GNDP	4	21	GNDO
GND	5	20	CLKOUT
LEADLAG	6	19	NC
DLYCTRL	7	18	CLKOUTB
GNDPA	8	17	GNDO
$V_{DDPA}$	9	16	$V_{DDO}$
$V_{DDPD}$	10	15	MULT0/DIV0
STOPB	11	14	MULT1/DIV1
PWRDNB	12	13	P2

NC – No internal connection

### description

The CDC5801A device provides clock multiplication and division from a single-ended reference clock (REFCLK) to a differential output pair (CLKOUT/CLKOUTB). The multiply and divide terminals (MULT/DIV0:1) provide selection for frequency multiplication and division ratios, generating CLKOUT/CLKOUTB frequencies ranging from 12.5 MHz to 500 MHz with a clock input reference (REFCLK) ranging from 19 MHz to 125 MHz. See Table 1 and Table 2 for detail frequency support.

The implemented phase aligner provides the possibility to phase align (zero delay) between CLKOUT/CLKOUTB and REFCLK or any other CLK in the system by feeding the clocks that need to be aligned to the DLYCTRL and the LEADLAG terminals.

The phase aligner also allows the user to delay or advance the CLKOUT/CLKOUTB with steps of 2.6 mUI (unit interval). For every rising edge on the DLYCTRL terminal, the output clocks are delayed by 2.6-mUI step size as long as there is low on the LEADLAG terminal. Similarly, for every rising edge on the DLYCTRL terminal, the output clocks are advanced by 2.6-mUI step size as long as there is high on the LEADLAG terminal. The CDC5801A has a fail-safe power up initialization state-machine which supports proper operation under all power up conditions. As the phase between REFCLK and CLKOUT/CLKOUTB is random after power up, the application may implement a self calibration routine at power up to produce a certain phase start position, before programming a fixed delay with the clock on the DLYCTRL terminal.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2005, Texas Instruments Incorporated

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT


SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

Depending on the selection of the mode terminals (P0:2), the device behaves as a multiplier (by 4, 6, or 8) with the phase aligner bypassed or as a multiplier or divider with programmable delay and phase aligner functionality. Through the select terminals (P0:2) user can also bypass the phase aligner and the PLL (test mode) and output the REFCLK directly on the CLKOUT/CLKOUTB terminals. Through P0:2 terminals the outputs could be in a high impedance state. This device has another unique capability to be able to function with a wide band of voltages on the REFCLK terminal by varying the voltage on the  $V_{DDREF}$  terminal.

The CDC5801A has a fail-safe power up initialization state-machine which supports proper operation under all power up conditions.

The CDC5801A device is characterized for operation over free-air temperatures of  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

### functional block diagram



# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

**FUNCTION TABLE†**

MODE	P0	P1	P2	CLKOUT/CLKOUTB
Multiplication with programmable delay and phase alignment active‡	0	0	0	REFCLK multiplied by ratio per Table 1 selected by MULT/DIV terminals. Outputs are delayed or advanced based on DLYCTRL and LEADLAG terminal configuration.
Division with programmable delay and phase alignment active ‡	0	0	1	REFCLK divided by ratio per Table 2 selected by MULT/DIV terminals. Outputs are delayed or advanced based on DLYCTRL and LEADLAG terminal configuration.
Multiplication only mode (phase aligner bypassed) §	1	0	0	In this mode one can only multiply as per Table 1. Programmable delay capability and divider capability is deactivated. PLL is running.
Test mode	1	1	0	PLL and phase aligner both bypassed. REFCLK is directly channeled to output.
Hi-Z mode	0	1	X	Hi-Z

† X = don't care, Hi-Z = high impedance

‡ Please see Table 4 and Table 5 for explanation for the programmability and phase alignment functions.

§ In this mode the DLYCTRL and LEADLAG terminals must be strapped high or low. Lowest possible jitter is achieved in this mode, but a delay of 200 ps to 2 ns expected typically from REFCLK to CLKOUT depending on the output frequency.

### Terminal Functions

TERMINAL NAME	NO.	I/O	DESCRIPTION
CLKOUT	20	O	Output clock
CLKOUTB	18	O	Output clock (complement)
DLYCTRL	7	I	Every rising edge on this terminal delays/advances the CLKOUT/CLKOUTB signal by 1/384th of the CLKOUT/CLKOUTB period. (e.g., for a 90 degree delay or advancement one needs to provide 96 rising edges). See Table 4.
GND	5		GND for V <sub>DDREF</sub> and V <sub>DDPD</sub>
GNDO	17, 21		GND for clock output terminals (CLKOUT, CLKOUTB)
GNDP	4		GND for PLL
GNDPA	8		GND for phase aligner
LEADLAG	6	I	Decides if the output clock is delayed or advanced with respect to REFCLK. See Table 4.
MULT0/DIV0	15	I	PLL multiplier and divider select
MULT1/DIV1	14	I	PLL multiplier and divider select
NC	19		Not used
PWRDNB	12	I	Active low power down state, CLKOUT/CLKOUTB goes low
P0	24	I	Mode control, see the Function Table
P1	23	I	Mode control, see the Function Table
P2	13	I	Mode control, see the Function Table
REFCLK	2	I	Reference input clock
STOPB	11	I	Active low output disabler, PLL and PA still running, CLKOUT and CLKOUTB goes to a dc value as per Table 3
V <sub>DDPA</sub>	9	I	Supply voltage for phase aligner
V <sub>DDPD</sub>	10	I	Reference voltage for the DLYCTRL, LEADLAG terminals and STOPB function
V <sub>DDREF</sub>	1	I	Reference voltage for REFCLK
V <sub>DDO</sub>	16, 22	I	Supply voltage for the output terminals (CLKOUT, CLKOUTB)
V <sub>DDP</sub>	3	I	Supply voltage for PLL

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

### PLL divider/multiplier selection

Table 1 and Table 2 list the supported REFCLK and BUSCLK (CLKOUT/CLKOUTB) frequencies.

**Table 1. Multiplication Ratios (P0:2 = 000 or 100)**

MULT0	MULT1	REFCLK (MHZ)	MULTIPLICATION RATIO	BUSCLK (MHZ)
0	0	38–125	4	152–500
0	1	25–83.3	6	150–500
1	1	19–62.5	8	152–500

**Table 2. Divider Ratio (P0:2 = 001)**

MULT0	MULT1	REFCLK (MHZ)	DIVISION RATIO	BUSCLK <sup>(1)</sup> (MHZ)
0	0	100–125	2	50–62.5
1	0	75–93	3	25–31
1	1	50–62	4	12.5–15.5

<sup>†</sup> BUSCLK will be undefined until a valid reference clock is available at REFCLK. After applying REFCLK, the PLL requires stabilization time to achieve phase lock.

**Table 3. Clock Output Driver States**

STATE	PWRDNB	STOPB	CLKOUT	CLKOUTB
Powerdown	0	X	GND	GND
CLK stop	1	0	V <sub>O</sub> , STOP	V <sub>O</sub> , STOP
Normal	1	1	As per Function Table	As per Function Table

**Table 4. Programmable Delay and Phase Alignment**

DLYCTRL	LEADLAG	CLKOUT AND CLKOUTB
Each rising edge <sup>†</sup>	1	Will be advanced by one step size (see Table 5)
Each rising edge <sup>†</sup>	0	Will be delayed by one step size (see Table 5)

<sup>†</sup> For every 32<sup>nd</sup> edge, there are one or two edges the phase aligner does not update. Therefore, CLKOUT phase is not updated on every 32<sup>nd</sup> edge.

**Table 5. Clock Output Driver States**

FUNCTIONALITY	STEP SIZE
Multiply by 4, 6, 8	CLKOUT period/384 (for example, 6.5 ps at 400 MHz)
Divide by 2	CLKOUT period/3072 (for example, 6.5 ps at 50 MHz)
Divide by 3	CLKOUT period/6144 (for example, 6.5 ps at 25 MHz)
Divide by 4	CLKOUT period/12288 (for example, 6.5 ps at 12.5 MHz)

NOTE: The frequency of the DLYCTRL terminal must always be equal or less than the frequency of the LEADLAG terminal.

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

### absolute maximum ratings over operating free-air temperature (unless otherwise noted)<sup>†</sup>

Supply voltage range, $V_{DD}$ (see Note 1)	–0.5 V to 4 V
Output voltage range, $V_O$ , at any output terminal	–0.5 V to $V_{DD} + 0.5$ V
Input voltage range, $V_I$ , at any input terminal	–0.5 V to $V_{DD} + 0.5$ V
Continuous total power dissipation	see Dissipation Rating Table
Operating free-air temperature range, $T_A$	–40°C to 85°C
Storage temperature range, $T_{stg}$	–65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to the GND terminals.

**DISSIPATION RATING TABLE**

PACKAGE	$T_A \leq 25^\circ\text{C}$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$ <sup>‡</sup>	$T_A = 85^\circ\text{C}$ POWER RATING
DBQ	1400 mW	11 mW/°C	740 mW

<sup>‡</sup> This is the inverse of the junction-to-ambient thermal resistance when board-mounted and with no air flow.

### recommended operating conditions

	MIN	NOM	MAX	UNIT
Supply voltage, $V_{DD}$ ( $V_{DDP}$ , $V_{DDPA}$ , $V_{DDO}$ )	3	3.3	3.6	V
High-level input voltage, $V_{IH}$ (CMOS)	$0.7 \times V_{DD}$			V
Low-level input voltage, $V_{IL}$ (CMOS)	$0.3 \times V_{DD}$			V
REFCLK low-level input voltage, $V_{IL}$	$0.3 \times V_{DDREF}$			V
REFCLK high-level input voltage, $V_{IH}$	$0.7 \times V_{DDREF}$			V
Input signal low voltage, $V_{IL}$ (STOPB, DLYCTRL, LEADLAG)	$0.3 \times V_{DDPD}$			V
Input signal high voltage, $V_{IH}$ (STOPB, DLYCTRL, LEADLAG)	$0.7 \times V_{DDPD}$			V
Input reference voltage for (REFCLK) ( $V_{DDREF}$ )	1.235		$V_{DD}$	V
Input reference voltage for (DLYCTRL and LEADLAG) ( $V_{DDPD}$ )	1.235		$V_{DD}$	V
High-level output current, $I_{OH}$			–16	mA
Low-level output current, $I_{OL}$			16	mA
Operating free-air temperature, $T_A$	–40		85	°C

### timing requirements

	MIN	MAX	UNIT
Input frequency of modulation, $f_{mod}$ (if driven by SSC CLKIN)		33	kHz
Modulation index (nonlinear maximum 0.5%)		0.6%	
Input slew rate, SR	1	4	V/ns
Input duty cycle on REFCLK	40%	60%	
Input frequency on REFCLK	19	125	MHz
Allowable frequency on DLYCTRL		200	MHz
Allowable frequency on LEADLAG		400	MHz
Allowable duty cycle on DLYCTRL and LEADLAG	25%	75%	



**LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH  
PROGRAMMABLE DELAY AND PHASE ALIGNMENT**

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

**electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER		TEST CONDITION <sup>†</sup>	MIN	TYP <sup>‡</sup>	MAX	UNIT
V <sub>O(STOP)</sub>	Output voltage during CLK stop mode	See Figure 1	1.1		2	V
V <sub>OX</sub>	Output crossing-point voltage	See Figure 1 and Figure 4	0.5V <sub>DDO</sub> –0.2		0.5V <sub>DDO</sub> +0.2	V
V <sub>O</sub>	Output voltage swing (V <sub>OH</sub> – V <sub>OL</sub> )	See Figure 1	1.7		2.9	V
V <sub>IK</sub>	Input clamp voltage	V <sub>DD</sub> = 3 V, I <sub>I</sub> = –18 mA			–1.2	V
V <sub>OH</sub>	High-level output voltage	See Figure 1, V <sub>DD</sub> = 3 to 3.6 V	2.0	2.6		V
		V <sub>DD</sub> = 3 V, I <sub>OH</sub> = –16 mA	2.2			
V <sub>OL</sub>	Low-level output voltage	See Figure 1, V <sub>DD</sub> = 3 to 3.6 V		0.3	0.6	V
		V <sub>DD</sub> = 3 V, I <sub>OL</sub> = 16 mA			0.5	
I <sub>OH</sub>	High-level output current	V <sub>DD</sub> = 3.135 V, V <sub>O</sub> = 1 V	–32	–52		mA
		V <sub>DD</sub> = 3.3 V, V <sub>O</sub> = 1.65 V		–51		
		V <sub>DD</sub> = 3.465 V, V <sub>O</sub> = 3.135 V	–14.5		–21	
I <sub>OL</sub>	Low-level output current	V <sub>DD</sub> = 3.135 V, V <sub>O</sub> = 1.95 V	43	61.5		mA
		V <sub>DD</sub> = 3.3 V, V <sub>O</sub> = 1.65 V		65		
		V <sub>DD</sub> = 3.465 V, V <sub>O</sub> = 0.4 V	25.5		36	
I <sub>OZ</sub>	High-impedance-state output current	P0 = 0, P1 = 1			±10	μA
I <sub>OZ(STOP)</sub>	High-impedance-state output current during CLK stop	Stop = 0, V <sub>O</sub> = GND or V <sub>DD</sub>			±100	μA
I <sub>OZ(PD)</sub>	High-impedance-state output current in power-down state	PWRDNB = 0, V <sub>O</sub> = GND or V <sub>DD</sub>	–10		100	μA
I <sub>IH</sub>	High-level input current	REFCLK, STOPB V <sub>DD</sub> = 3.6 V, V <sub>I</sub> = V <sub>DD</sub>			10	μA
		PWRDNB, P0:2, MULT/ DIV0:1 V <sub>DD</sub> = 3.6 V, V <sub>I</sub> = V <sub>DD</sub>			10	
I <sub>IL</sub>	Low-level input current	REFCLK, STOPB V <sub>DD</sub> = 3.6 V, V <sub>I</sub> = 0			–10	μA
		PWRDNB, P0:2, MULT/ DIV0:1 V <sub>DD</sub> = 3.6 V, V <sub>I</sub> = 0			–10	
Z <sub>O</sub>	Output impedance (single ended)	High state R <sub>I</sub> at I <sub>O</sub> –14.5 mA to –16.5 mA	15	35	50	Ω
		Low state R <sub>I</sub> at I <sub>O</sub> 14.5 mA to 16.5 mA	11	17	35	
	Reference current	V <sub>DDREF</sub> , V <sub>DDPD</sub> V <sub>DD</sub> = 3.6 V	PWRDNB = 0		50	μA
			PWRDNB = 1		0.5	mA
C <sub>I</sub>	Input capacitance	V <sub>I</sub> = V <sub>DD</sub> or GND		2		pF
C <sub>O</sub>	Output capacitance	V <sub>O</sub> = V <sub>DD</sub> or GND		3		pF
I <sub>DD(PD)</sub>	Supply current in power-down state	REFCLK = 0 MHz to 100 MHz, PWRDNB = 0, STOPB = 1			150	μA
I <sub>DD(CLKSTOP)</sub>	Supply current in CLK stop state	BUSCLK configured for 500 MHz			40	mA
I <sub>DD(NORMAL)</sub>	Supply current in normal state	BUSCLK = 500 MHz P0:2 = 000; load see Figure 1			70	mA

<sup>†</sup> V<sub>DD</sub> refers to any of the following; V<sub>DDPA</sub>, V<sub>DDPD</sub>, V<sub>DDREF</sub>, V<sub>DDO</sub>, and V<sub>DDP</sub>
<sup>‡</sup> All typical values are at V<sub>DD</sub> = 3.3 V, T<sub>A</sub> = 25°C.

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

**jitter specification over recommended operating free-air temperature range and  $V_{CC}$  (unless otherwise noted)**

PARAMETER	CLKOUT	TEST CONDITIONS	MIN	TYP†	MAX	UNIT
t(jitter) (Multiplication only mode. Phase alignment and programmable delay features are not selected (PA bypass). See Figure 2.)	155 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		6		ps
		Period p-p		40		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		50		
		Cycle-to-cycle (+)		27		
		Cycle-to-cycle (–)		27		
	200 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		5.5		ps
		Period p-p		36		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		36		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		36		
		Cycle-to-cycle (+)		23		
		Cycle-to-cycle (–)		23		
	312 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		3		ps
		Period p-p		20		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		18		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		18		
		Cycle-to-cycle (+)		17		
		Cycle-to-cycle (–)		17		
	400 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		2.3		ps
		Period p-p		17		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		12		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		12		
		Cycle-to-cycle (+)		15		
		Cycle-to-cycle (–)		15		
	500 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		2.1		ps
		Period p-p		16		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		8		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		8		
		Cycle-to-cycle (+)		14		
		Cycle-to-cycle (–)		14		
t(jitter) (Multiplication with phase alignment and programmable delay features selected. See Figure 2.)	155 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		9		ps
		Period p-p		70		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		50		
		Cycle-to-cycle (+)		50		
		Cycle-to-cycle (–)		50		
	200 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		7		ps
		Period p-p		55		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		36		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		36		
		Cycle-to-cycle (+)		40		
		Cycle-to-cycle (–)		40		
	312 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		4		ps
		Period p-p		35		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		18		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		18		
		Cycle-to-cycle (+)		30		
		Cycle-to-cycle (–)		30		
	400 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		3.1		ps
		Period p-p		27		
		Phase jitter (accumulated, 12 kHz to 20 MHz)		13		
		Phase jitter (accumulated, 50 kHz to 80 MHz)		13		
		Cycle-to-cycle (+)		25		
		Cycle-to-cycle (–)		25		

† All typical values are at  $V_{DD} = 3.3$  V,  $T_A = 25^\circ\text{C}$ .



# LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

jitter specification over recommended operating free-air temperature range and  $V_{CC}$  (unless otherwise noted) (continued)

PARAMETER		CLKOUT	TEST CONDITIONS	MIN	TYP†	MAX	UNIT
$t_{(jitter)}$ (Multiplication with phase alignment and programmable delay features selected. See Figure 2.)		500 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		2.9		ps
			Period p-p		24		
			Phase jitter (accumulated, 12 kHz to 20 MHz)		9		
			Phase jitter (accumulated, 50 kHz to 80 MHz)		9		
			Cycle-to-cycle (+)		20		
			Cycle-to-cycle (–)		20		
$t_{(jitter)}$ (Divider mode with phase aligner not active: DLYCTRL = LEADLAG = 0 or 1. See Figure 2.)	MULT0:1 = 11 (Divider ratio = 4)	12.5 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		12		ps
			Period p-p		75		
			Cycle-to-cycle (+)		55		
			Cycle-to-cycle (–)		55		
		15.5 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		8		ps
			Period p-p		50		
			Cycle-to-cycle (+)		38		
			Cycle-to-cycle (–)		38		
	MULT0:1 = 10 (Divider ratio = 3)	25 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		7.5		ps
			Period p-p		50		
			Cycle-to-cycle (+)		35		
			Cycle-to-cycle (–)		35		
		31 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		5.5		ps
			Period p-p		30		
			Cycle-to-cycle (+)		23		
			Cycle-to-cycle (–)		23		
	MULT0:1 = 00 (Divider ratio = 2)	50 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		8		ps
			Period p-p		40		
			Phase jitter (accumulated, 12 kHz to 20 MHz)		12		
			Cycle-to-cycle (+)		30		
		62.5 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		5.5		ps
			Period p-p		28		
			Phase jitter (accumulated, 12 kHz to 20 MHz)		9		
			Cycle-to-cycle (+)		24		
			Cycle-to-cycle (–)		24		
$t_{(jitter)}$ (Divider mode with phase alignment and programmable delay features selected. See Figure 2.)	MULT0:1 = 11 (Divider ratio = 4)	12.5 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		12.5		ps
			Period p-p		80		
			Cycle-to-cycle (+)		55		
			Cycle-to-cycle (–)		55		
		15.5 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		8.5		ps
			Period p-p		55		
			Cycle-to-cycle (+)		38		
			Cycle-to-cycle (–)		38		
	MULT0:1 = 10 (Divider ratio = 3)	25 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		10		ps
			Period p-p		60		
			Cycle-to-cycle (+)		35		
			Cycle-to-cycle (–)		35		
		31 MHz	Period RMS (1 $\Sigma$ jitter, full frequency band)		7		ps
			Period p-p		40		
			Cycle-to-cycle (+)		23		
			Cycle-to-cycle (–)		23		



**CDC5801A**  
**LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH**  
**PROGRAMMABLE DELAY AND PHASE ALIGNMENT**

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

**jitter specification over recommended operating free-air temperature range and  $V_{CC}$  (unless otherwise noted) (continued)**

PARAMETER		CLKOUT	TEST CONDITIONS	MIN	TYP†	MAX	UNIT
$t_{\text{jitter}}$ (Divider mode with phase alignment and programmable delay features selected. See Figure 2.)	MULT0:1 = 00 (Divider ratio = 2)	50 MHz	Period RMS ( $1\sigma$ jitter, full frequency band)		9		ps
			Period p-p		50		
			Phase jitter (accumulated, 12 kHz to 20 MHz)		13		
			Cycle-to-cycle (+)		35		
			Cycle-to-cycle (–)		35		
	62.5 MHz		Period RMS ( $1\sigma$ jitter, full frequency band)		6.5		ps
			Period p-p		30		
			Phase jitter (accumulated, 12 kHz to 20 MHz)		10		
			Cycle-to-cycle (+)		26		
			Cycle-to-cycle (–)		26		

† All typical values are at  $V_{DD} = 3.3\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

**switching characteristics over recommended operating free-air temperature range (unless otherwise noted)**

PARAMETER		TEST CONDITIONS	MIN	TYP†	MAX	UNIT
$t_{\text{(DC)}}$	Output duty cycle	See Figure 3	45%		55%	
$t_r$ , $t_f$	Output rise and fall times (measured at 20%–80% of output voltage)	See Figure 5 and Figure 1	150		350	ps

† All typical values are at  $V_{DD} = 3.3\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

### state transition latency specifications

PARAMETER		FROM	TO	TEST CONDITIONS	MIN	TYP†	MAX	UNIT
t(powerup)	Delay time, PWRDNB↑ to CLKOUT/CLKOUTB output settled (excluding t(DISTLOCK))	Powerdown	Normal	See Figure 6			3	ms
	Delay time, PWRDNB↑ to internal PLL and clock are on and settled						3	
t(VDDpowerup)	Delay time, power up to CLKOUT/CLKOUTB output settled	VDD	Normal	See Figure 6			3	ms
	Delay time, power up to internal PLL and clock are on and settled						3	
t(MULT)	MULT0 and MULT1 change to CLKOUT/CLKOUTB output resettled (excluding t(DISTLOCK))	Normal	Normal	See Figure 7			1	ms
t(CLKON)	STOPB↑ to CLKOUT/CLKOUTB glitch-free clock edges	CLK Stop	Normal	See Figure 8			10	ns
t(CLKSETL)	STOPB↑ to CLKOUT/CLKOUTB output settled to within 50 ps of the phase before STOPB was disabled	CLK Stop	Normal	See Figure 8			20	cycles
t(CLKOFF)	STOPB↓ to CLKOUT/CLKOUTB output disabled	Normal	CLK Stop	See Figure 8			5	ns
t(powerdown)	Delay time, PWRDNB↓ to the device in the power-down mode	Normal	Power-down	See Figure 6			1	ms
t(STOP)	Maximum time in CLKSTOP (STOPB = 0) before reentering normal mode (STOPB = 1)	STOPB	Normal	See Figure 8			100	μs
t(ON)	Minimum time in normal mode (STOPB = 1) before reentering CLKSTOP (STOPB = 0)	Normal	CLK stop	See Figure 8	100			ms

† All typical values are at VDD = 3.3 V, TA = 25°C.

### PARAMETER MEASUREMENT INFORMATION




Figure 1. Test Load and Voltage Definitions (VO(STOP), VOX, VOH, VOL)

## PARAMETER MEASUREMENT INFORMATION




Figure 2. Cycle-to-Cycle Jitter




Figure 3. Output Duty Cycle




Figure 4. Crossing-Point Voltage



Figure 5. Voltage Waveforms




Figure 6. PWRDNB Transition Timings

# CDC5801A


## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005

### PARAMETER MEASUREMENT INFORMATION



Figure 7. MULT Transition Timings



NOTE A:  $V_{ref} = V_O \pm 200 \text{ mV}$

Figure 8. STOPB Transition Timings

# CDC5801A

## LOW JITTER CLOCK MULTIPLIER AND DIVIDER WITH PROGRAMMABLE DELAY AND PHASE ALIGNMENT

SCAS813A – AUGUST 2005 – REVISED DECEMBER 2005




Figure 9. Using the CDC5801A Device as a Multiplier by 8 and Aligning Two Different Clocks

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
CDC5801ADBQ	Active	Production	SSOP (DBQ)   24	50   TUBE	-	Call TI	Call TI	-40 to 85	CDC5801A
CDC5801ADBQR	Active	Production	SSOP (DBQ)   24	2500   LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 85	CDC5801A

- (1) **Status:** For more details on status, see our [product life cycle](#).
- (2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.
- (3) **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.
- (4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.
- (5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.
- (6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION



\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CDC5801ADBQR	SSOP	DBQ	24	2500	330.0	16.4	6.5	9.0	2.1	8.0	16.0	Q1

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CDC5801ADBQR	SSOP	DBQ	24	2500	353.0	353.0	32.0



DBQ (R-PDSO-G24)

PLASTIC SMALL-OUTLINE PACKAGE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15) per side.
  - D. Falls within JEDEC MO-137 variation AE.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025